Eurocode 3: Design of steel structures Part 3-2: Towers, masts and chimneys Chimneys Estonian National Annex

Eurokoodeks 3: Teraskonstruktsioonide projekteerimine Osa 3-2: Tornid, mastid ja korstnad Korstnad Eesti standardi rahvuslik lisa



FOREWORD

This document:

- is the Estonian National Annex to the European Standard EN 1993-3-2:2006 "Eurocode 3: Design of steel structures - Part 3-2: Towers, masts and chimneys - Chimneys". It includes Estonian Nationally Determined Parameters (NDP) and procedures and it must be used together with EN 1993-3-2:2006 for structural design of constructions built in Estonia;
- was ratified with order nr 272 of the Estonian Centre for Standardisation dated 17.12.2009;
- has been endorsed with a notification published in the January 2010 issue of the official bulletin of the Estonian centre for Standardisation.

The National annex of EVS-EN 1993-3-2 was prepared by Aldur Parts. This document has been approved by Technical Committee EVS/TK 13 "Ehituskonstruktsioonide projekteerimine".

The proposition to prepare a national annex was made by EVS/TK 13, it was coordinated by the Estonian Centre for Standardisation.

λ N Metal str ICS 91.010.30 Technical aspects, 91.060.40 Chimneys, shafts, ducts, 91.080.10 Metal structures Price group G

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact the Estonian Centre for Standardisation: Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone: 605 5050; e-mail: info@evs.ee

CONTENTS

Annex NA (inf	ormative) National requirements for Estonia
NA.2.3.3.1 NA.2.3.3.5 NA.2.6	Imposed loads
NA.4.2	External corrosion allowance
NA.5.1 NA.5.2.1	Modelling of the chimney for determining action effects
NA.6.1 NA.6.2.1 NA.6.4.1 NA.6.4.2 NA.6.4.3	General Strength verification General Flange bolted connections Connection of chimney to the foundation or supporting structure
NA.7.2	Deflections
NA.9.1 NA.9.5	General Partial factors for fatigue
NA.A.1 NA.A.2	Reliability differentiation for steel chimneys
NA.C.2	Enhancement of fatigue strength for special quality requirements

Annex NA

(informative)

National requirements for Estonia

According to EN 1993-3-2:2006 every country should implement a national annex that might give alternative procedures, values and recommendations for classes with Notes indicating where National choice may be made. National choice is allowed in the following clauses:

— 2.3.3.1(1)		— 6.4.3(2)
— 2.3.3.5(1)		— 7.2(1)
— 2.6(1)		— 7.2(2)
— 4.2(1)		— 9.1(3)
— 5.1(1)	3	— 9.1(4)
— 5.2.1(3)		— 9.5(1)
— 6.1(1)P	7	— A.1(1)
— 6.2.1(6)		— A.2(1) (2 places)
— 6.4.1(1)	TO .	— C.2(1)
— 6.4.2(1)	\sim	

NA.2.3.3.1 Imposed loads

(1) Imposed loads should be applied on platforms and railings.

NOTE 1 The National Annex may give information on imposed loads on platforms and railings. The following characteristic values of imposed loads are recommended:

- Imposed loads on platforms: 2,0 kN/m² (see also EN 13084-1) ... (2.1a)
- Horizontal loads on railings: 0,5 kN/m ... (2.1b)
- No additional information is given in the Estonian National Annex.

NOTE 2 These loads may be assumed to act in the absence of other climatic loads.

NA.2.3.3.5 Ice loads

- (1) For chimneys that are likely to be subject to ice loading, the appropriate ice thicknesses, densities and distributions should be determined.
- NOTE 1 The National Annex may give further information on ice loading.
- No further information is given in the Estonian National Annex.
- NOTE 2 See also 2.3.2 of EN 1993-3-1.

NA.2.6 Durability

(1) Durability should be satisfied by complying with the fatigue assessment (see section 9) and appropriate choice of the calculated shell thickness (see 4) and/or by appropriate corrosion protection. See also section 4 of EN 1993-1-1.

NOTE The National Annex may give information on the design service life of the structure. A service life of 30 years is recommended.