
**Manipulating industrial robots —
Performance criteria and related test
methods**

*Robots manipulateurs industriels — Critères de performance et méthodes
d'essai correspondantes*



Contents

	Page
1 Scope	1
2 Normative references	2
3 Definitions	2
4 Units	2
5 Abbreviations and symbols	3
5.1 Basic abbreviations.....	3
5.2 Quantities	3
5.3 Indices	4
5.4 Other symbols	4
6 Performance testing conditions	4
6.1 Robot mounting	4
6.2 Conditions prior to testing	4
6.3 Operating and environmental conditions	5
6.4 Displacement measurement principles	5
6.5 Instrumentation	6
6.6 Load to the mechanical interface	6
6.7 Test velocities	8

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet central@iso.ch
X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

6.8	Definitions of poses to be tested and paths to be followed	9
6.9	Number of cycles	15
6.10	Test procedure	15
6.11	Characteristics to be tested - Applications	16
7	Pose characteristics	16
7.1	General description	16
7.2	Pose accuracy and pose repeatability	17
7.3	Distance accuracy and repeatability	24
7.4	Position stabilization time	29
7.5	Position overshoot	30
7.6	Drift of pose characteristics	31
7.7	Exchangeability	34
8	Path characteristics	35
8.1	General	35
8.2	Path accuracy	36
8.3	Path repeatability	37
8.4	Path accuracy on reorientation	39
8.5	Cornering deviations	40
8.6	Path velocity characteristics	42
9	Minimum posing time	44
10	Static compliance	46
11	Application specific performance criteria	46
11.1	Weaving deviations	46
12	Test report	48

Annex

A (normative)	Parameters for comparison tests	49
B (informative)	Guide for selection of tests for typical applications	54
C (informative)	Example of a test report	56

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. In accordance with ISO/IEC Directives they are approved if two-thirds of the votes cast by the P-members of the technical committee or sub-committee are in favour, and not more than one-quarter of the total number of votes cast are negative.

International Standard ISO 9283 was prepared by Technical Committee ISO/TC 184, *Industrial automation systems and integration*, Subcommittee SC 2, *Robots for manufacturing environment*.

This second edition cancels and replaces the first edition (ISO 9283:1990 and Amendment 1:1991), of which it constitutes a technical revision.

Annex A forms an integral part of this International Standard. Annexes B and C are for information only.

Introduction

ISO 9283 is part of a series of International Standards dealing with manipulating industrial robots. Other International Standards cover such topics as safety, general characteristics, coordinate systems, terminology, and mechanical interfaces. It is noted that these International Standards are interrelated and also related to other International Standards.

ISO 9283 is intended to facilitate understanding between users and manufacturers of robots and robot systems. It defines the important performance characteristics, describes how they shall be specified and recommends how they should be tested. An example of how the test results should be reported is included in Annex C of this International Standard. The characteristics for which test methods are given in this International Standard are those considered to affect robot performance significantly.

It is intended that the user of this International Standard selects which performance characteristics are to be tested, in accordance with his own specific requirements.

The tests described in this International Standard may be applied in whole or in part, depending upon the robot type and requirements.

The core part of ISO 9283 deals with testing of individual characteristics. Specific parameters for comparison testing is dealt with in Annex A (normative) for pose-to-pose characteristics and path characteristics.

Annex B (informative) of this International Standard provides guidance for selection of tests for typical applications.

Annex C (informative) of this International Standard provides a recommended format of the test report including the minimum required information and the summary of the test results.

This document is a preview generated by EVS

This page intentionally left blank

Manipulating industrial robots — Performance criteria and related test methods

1 Scope

This International Standard describes methods of specifying and testing the following performance characteristics of manipulating industrial robots:

- pose accuracy and pose repeatability;
- multi-directional pose accuracy variation;
- distance accuracy and distance repeatability;
- position stabilization time;
- position overshoot;
- drift of pose characteristics;
- exchangeability;
- path accuracy and path repeatability;
- path accuracy on reorientation
- cornering deviations;
- path velocity characteristics;
- minimum posing time;
- static compliance;
- weaving deviations.

This International Standard does not specify which of the above performance characteristics are to be chosen for testing a particular robot. The tests described in this International Standard are primarily intended for developing and verifying individual robot specifications, but can also be used for such purposes as prototype testing, type testing or acceptance testing.

To compare performance characteristics between different robots, as defined in this International Standard, the following parameters have to be the same: test cube sizes, test loads, test velocities, test paths, test cycles, environmental conditions.

Annex A provides parameters specific for comparison testing of pose-to-pose characteristics and path characteristics.

This International Standard applies to all manipulating industrial robots as defined in ISO 8373. However, for the purpose of this International Standard the term "robot" means manipulating industrial robot.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All International Standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 8373:1994, *Manipulating industrial robots — Vocabulary*.

ISO 9787:1990, *Manipulating industrial robots — Coordinate systems and motions*.

ISO 9946:1991, *Manipulating industrial robots — Presentation of characteristics*.

3 Definitions

For the purpose of this International Standard, the definitions given in ISO 8373 and the following definitions apply.

3.1 cluster: Set of measured points used to calculate the accuracy and the repeatability characteristics (example shown diagrammatically in figure 8).

3.2 barycentre: For a cluster of n points, defined by their coordinates $(\bar{x}_j, \bar{y}_j, \bar{z}_j)$, the barycentre of that cluster of points is the point whose coordinates are the mean values \bar{x} , \bar{y} , and \bar{z} calculated by formulae given in 7.2.1.

3.3 measuring dwell: Delay at the measurement point prior to recording data (e.g. time between control signal "in position" and the "start measuring" of the measuring device).

3.4 measuring time: Time elapsed when measurements are recorded.

4 Units

Unless otherwise stated, all dimensions are as follows:

- length in millimetres (mm)
- angle in radians or degrees (rad) or (°)
- time in seconds (s)
- mass in kilograms (kg)
- force in newtons (N)
- velocity in metres per second (m/s),
degrees per second (°/s) or
radians per second (rad/s)