

This document is a review generated by EVS

Digital addressable lighting interface - Part 102:
General requirements - Control gear

ESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 62386-102:2015 sisaldb Euroopa standardi EN 62386-102:2014 ingliskeelset teksti.	This Estonian standard EVS-EN 62386-102:2015 consists of the English text of the European standard EN 62386-102:2014.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 19.12.2014.	Date of Availability of the European standard is 19.12.2014.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 29.140.50, 29.140.99

Standardite reproduutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Aru 10, 10317 Tallinn, Eesti; koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 62386-102

December 2014

ICS 29.140; 29.140.50

Supersedes EN 62386-102:2009

English Version

Digital addressable lighting interface -
Part 102: General requirements - Control gear
(IEC 62386-102:2014)

Interface d'éclairage adressable numérique -
Partie 102: Exigences générales - Appareillages de
commande
(CEI 62386-102:2014)

Digital adressierbare Schnittstelle für die Beleuchtung -
Teil 102: Allgemeine Anforderungen - Betriebsgeräte
(IEC 62386-102:2014)

This European Standard was approved by CENELEC on 2014-12-12. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document 34C/1099/FDIS, future edition 2 of IEC 62386-102, prepared by SC 34C "Auxiliaries for lamps" of IEC/TC 34 "Lamps and related equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62386-102:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-09-12
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-12-12

This document supersedes EN 62386-102:2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62386-102:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60598-1	NOTE	Harmonized as EN 60598-1.
IEC 60669-2-1	NOTE	Harmonized as EN 60669-2-1.
IEC 60921	NOTE	Harmonized as EN 60921.
IEC 60923	NOTE	Harmonized as EN 60923.
IEC 60925 ¹⁾	NOTE	Harmonized as EN 60925 ¹⁾ .
IEC 61547	NOTE	Harmonized as EN 61547.
IEC 62386-102:2009	NOTE	Harmonized as EN 62386-102:2009.
CISPR 15	NOTE	Harmonized as EN 55015.

¹⁾ Withdrawn publication.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here:
www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61347	Series	Lamp controlgear	EN 61347	Series
IEC 62386-101	2014	Digital addressable lighting interface - Part 101: General requirements - System Components	EN 62386-101	2014
IEC 62386-103	2014	Digital addressable lighting interface - Part 103: General requirements - Control devices	EN 62386-103	2014

CONTENTS

FOREWORD.....	12
INTRODUCTION.....	14
1 Scope	15
2 Normative references	15
3 Terms and definitions	15
4 General	18
4.1 General.....	18
4.2 Version number	18
5 Electrical specification	18
6 Interface power supply	18
7 Transmission protocol structure.....	19
7.1 General.....	19
7.2 16 bit forward frame encoding.....	19
7.2.1 General	19
7.2.2 Address byte	19
7.2.3 Opcode byte	19
8 Timing	19
9 Method of operation.....	20
9.1 General.....	20
9.2 Control gear.....	20
9.3 Dimming curve.....	20
9.4 Calculating “ <i>targetLevel</i> ”	23
9.5 Fading	23
9.5.1 General	23
9.5.2 Fade time	24
9.5.3 Fade rate.....	25
9.5.4 Extended fade time.....	26
9.5.5 Using the fade time.....	28
9.5.6 Using the fade rate	28
9.5.7 Behaviour during a fade.....	28
9.5.8 Behaviour during startup.....	28
9.5.9 Stopping a fade	28
9.6 Min and max level.....	29
9.7 Commands	29
9.7.1 General	29
9.7.2 Level instructions without fade.....	30
9.7.3 Level instructions initiating a fade.....	30
9.7.4 Configuration instructions	30
9.7.5 Queries	30
9.7.6 Special commands	31
9.7.7 Application extended commands.....	31
9.8 Command iterations	31
9.8.1 General	31
9.8.2 Command iteration of “UP” and “DOWN” commands.....	31
9.8.3 DAPC SEQUENCE (deprecated)	31

9.9	Modes of operation	32
9.9.1	General	32
9.9.2	Operating mode 0x00: standard mode	32
9.9.3	Operating mode 0x01 to 0x7F: reserved	32
9.9.4	Operating mode 0x80 to 0xFF: manufacturer specific modes	32
9.10	Memory banks	33
9.10.1	General	33
9.10.2	Memory map.....	33
9.10.3	Selecting a memory bank location	34
9.10.4	Memory bank reading	34
9.10.5	Memory bank writing.....	34
9.10.6	Memory bank 0.....	35
9.10.7	Memory bank 1	37
9.10.8	Manufacturer specific memory banks	39
9.10.9	Reserved memory banks	39
9.11	Reset.....	39
9.11.1	Reset operation	39
9.11.2	Reset memory bank operation	39
9.12	System failure.....	39
9.13	Power on	40
9.14	Assigning short addresses	41
9.14.1	General	41
9.14.2	Random address allocation.....	41
9.14.3	Identification of a device	42
9.14.4	Direct address allocation	43
9.15	Failure state behaviour	43
9.16	Status information.....	43
9.16.1	General	43
9.16.2	Bit 0: Control gear failure.....	43
9.16.3	Bit 1: Lamp failure	44
9.16.4	Bit 2: Lamp on	44
9.16.5	Bit 3: Limit error.....	44
9.16.6	Bit 4: Fade running	44
9.16.7	Bit 5: Reset state	44
9.16.8	Bit 6: Missing short address.....	44
9.16.9	Bit 7: Power cycle seen	45
9.17	Non-volatile memory	45
9.18	Device types and features.....	45
9.19	Using scenes	46
10	Declaration of variables	47
11	Definition of commands	49
11.1	General.....	49
11.2	Overview Sheets.....	49
11.3	Level instructions	55
11.3.1	DAPC (<i>level</i>)	55
11.3.2	OFF	55
11.3.3	UP	55
11.3.4	DOWN	55
11.3.5	STEP UP	55

11.3.6	STEP DOWN	56
11.3.7	RECALL MAX LEVEL	56
11.3.8	RECALL MIN LEVEL	56
11.3.9	STEP DOWN AND OFF	57
11.3.10	ON AND STEP UP	57
11.3.11	ENABLE DAPC SEQUENCE	57
11.3.12	GO TO LAST ACTIVE LEVEL	58
11.3.13	GO TO SCENE (<i>sceneNumber</i>)	58
11.4	Configuration instructions	58
11.4.1	General	58
11.4.2	RESET	58
11.4.3	STORE ACTUAL LEVEL IN DTR0	58
11.4.4	SAVE PERSISTENT VARIABLES	58
11.4.5	SET OPERATING MODE (<i>DTR0</i>)	59
11.4.6	RESET MEMORY BANK (<i>DTR0</i>)	59
11.4.7	IDENTIFY DEVICE	59
11.4.8	SET MAX LEVEL (<i>DTR0</i>)	60
11.4.9	SET MIN LEVEL (<i>DTR0</i>)	60
11.4.10	SET SYSTEM FAILURE LEVEL (<i>DTR0</i>)	60
11.4.11	SET POWER ON LEVEL (<i>DTR0</i>)	61
11.4.12	SET FADE TIME (<i>DTR0</i>)	61
11.4.13	SET FADE RATE (<i>DTR0</i>)	61
11.4.14	SET EXTENDED FADE TIME (<i>DTR0</i>)	61
11.4.15	SET SCENE (<i>DTR0, sceneX</i>)	62
11.4.16	REMOVE FROM SCENE (<i>sceneX</i>)	62
11.4.17	ADD TO GROUP (<i>group</i>)	62
11.4.18	REMOVE FROM GROUP (<i>group</i>)	62
11.4.19	SET SHORT ADDRESS (<i>DTR0</i>)	62
11.4.20	ENABLE WRITE MEMORY	63
11.5	Queries	63
11.5.1	General	63
11.5.2	QUERY STATUS	63
11.5.3	QUERY CONTROL GEAR PRESENT	63
11.5.4	QUERY CONTROL GEAR FAILURE	63
11.5.5	QUERY LAMP FAILURE	63
11.5.6	QUERY LAMP POWER ON	63
11.5.7	QUERY LIMIT ERROR	63
11.5.8	QUERY RESET STATE	63
11.5.9	QUERY MISSING SHORT ADDRESS	63
11.5.10	QUERY VERSION NUMBER	64
11.5.11	QUERY CONTENT DTR0	64
11.5.12	QUERY DEVICE TYPE	64
11.5.13	QUERY NEXT DEVICE TYPE	64
11.5.14	QUERY PHYSICAL MINIMUM	64
11.5.15	QUERY POWER FAILURE	64
11.5.16	QUERY CONTENT DTR1	64
11.5.17	QUERY CONTENT DTR2	64
11.5.18	QUERY OPERATING MODE	65
11.5.19	QUERY LIGHT SOURCE TYPE	65

11.5.20	QUERY ACTUAL LEVEL	65
11.5.21	QUERY MAX LEVEL.....	65
11.5.22	QUERY MIN LEVEL.....	66
11.5.23	QUERY POWER ON LEVEL	66
11.5.24	QUERY SYSTEM FAILURE LEVEL	66
11.5.25	QUERY FADE TIME/FADE RATE	66
11.5.26	QUERY EXTENDED FADE TIME.....	66
11.5.27	QUERY MANUFACTURER SPECIFIC MODE	66
11.5.28	QUERY SCENE LEVEL (<i>scenex</i>).....	66
11.5.29	QUERY GROUPS 0-7.....	66
11.5.30	QUERY GROUPS 8-15.....	66
11.5.31	QUERY RANDOM ADDRESS (H)	67
11.5.32	QUERY RANDOM ADDRESS (M).....	67
11.5.33	QUERY RANDOM ADDRESS (L).....	67
11.5.34	READ MEMORY LOCATION (<i>DTR1, DTR0</i>)	67
11.6	Application extended commands.....	67
11.6.1	General	67
11.6.2	QUERY EXTENDED VERSION NUMBER	67
11.7	Special commands.....	68
11.7.1	General	68
11.7.2	TERMINATE	68
11.7.3	DTR0 (<i>data</i>)	68
11.7.4	INITIALISE (<i>device</i>)	68
11.7.5	RANDOMISE	68
11.7.6	COMPARE	69
11.7.7	WITHDRAW.....	69
11.7.8	SEARCHADDRH (<i>data</i>)	69
11.7.9	SEARCHADDRM (<i>data</i>)	69
11.7.10	SEARCHADDRL (<i>data</i>)	69
11.7.11	PROGRAM SHORT ADDRESS (<i>data</i>)	70
11.7.12	VERIFY SHORT ADDRESS (<i>data</i>)	70
11.7.13	QUERY SHORT ADDRESS	70
11.7.14	ENABLE DEVICE TYPE (<i>data</i>)	70
11.7.15	DTR1 (<i>data</i>)	71
11.7.16	DTR2 (<i>data</i>)	71
11.7.17	WRITE MEMORY LOCATION (<i>DTR1, DTR0, data</i>)	71
11.7.18	WRITE MEMORY LOCATION – NO REPLY (<i>DTR1, DTR0, data</i>)	71
11.7.19	PING	72
12	Test procedures	72
12.1	General notes on test.....	72
12.1.1	Abbreviations.....	72
12.1.2	Test execution	72
12.1.3	Data transmission.....	72
12.1.4	Test setup	73
12.1.5	Test output	73
12.1.6	Fade time measurements based on light output.....	73
12.1.7	Description of test scheme for fast fade times on PWM dimmer	74
12.1.8	Test notation	75
12.1.9	Test execution limitation	75

12.1.10	Test results	75
12.1.11	Exception handling	75
12.1.12	Unexpected answer	75
12.2	Preamble	77
12.2.1	Test preamble	77
12.3	Physical operational parameters	94
12.3.1	Polarity test	94
12.3.2	Maximum and minimum system voltage	94
12.3.3	Overshoot protection test	95
12.3.4	Current rating test	96
12.3.5	Transmitter voltages	97
12.3.6	Transmitter rising and falling edges	99
12.3.7	Transmitter bit timing	101
12.3.8	Transmitter frame timing	103
12.3.9	Receiver start-up behavior	104
12.3.10	Receiver threshold	105
12.3.11	Receiver bit timing	106
12.3.12	Extended receiver bit timing	110
12.3.13	Receiver forward frame violation	112
12.3.14	Receiver settling timing	112
12.3.15	Receiver frame timing FF-FF send twice	113
12.4	Configuration instructions	115
12.4.1	RESET	115
12.4.2	RESET: timeout / command in-between	119
12.4.3	Send-twice timeout	121
12.4.4	Commands in-between	129
12.4.5	STORE ACTUAL LEVEL IN DTR0	135
12.4.6	SAVE PERSISTENT VARIABLES	136
12.4.7	SET OPERATING MODE	136
12.4.8	SET MAX LEVEL	137
12.4.9	SET MIN LEVEL	137
12.4.10	SET SYSTEM FAILURE LEVEL	138
12.4.11	SET POWER ON LEVEL	139
12.4.12	SET FADE TIME	143
12.4.13	SET FADE RATE	143
12.4.14	SET SCENE / REMOVE FROM SCENE	144
12.4.15	ADD TO GROUP / REMOVE FROM GROUP	145
12.4.16	SET SHORT ADDRESS	146
12.4.17	SET EXTENDED FADE TIME	147
12.4.18	Reset/Power-on values	148
12.4.19	DTR0 / DTR1 / DTR2	154
12.5	Memory banks	154
12.5.1	READ MEMORY LOCATION on Memory Bank 0	154
12.5.2	READ MEMORY LOCATION on Memory Bank 1	159
12.5.3	READ MEMORY LOCATION on other Memory Banks	161
12.5.4	Memory bank writing	163
12.5.5	ENABLE WRITE MEMORY: writeEnableState	168
12.5.6	ENABLE WRITE MEMORY: timeout / command in-between	171
12.5.7	RESET MEMORY BANK: timeout / command in-between	172

12.5.8	RESET MEMORY BANK.....	175
12.6	Level instructions.....	176
12.6.1	Level instructions: Basic behaviour.....	176
12.6.2	FADE TIME: possible values	181
12.6.3	FADE TIME: transitions	182
12.6.4	FADE TIME: fading to 0	184
12.6.5	FADE TIME: small steps fading	186
12.6.6	FADE TIME: extended fade time.....	189
12.6.7	FADE RATE: possible values.....	191
12.6.8	FADE RATE: transitions	194
12.6.9	FADE RATE: extended fade time.....	195
12.6.10	FADE TIME/FADE RATE: stop fading by setting MIN/MAX levels	196
12.6.11	FADE TIME/FADE RATE: stop fading	201
12.6.12	FADE TIME/FADE RATE: stop fading when a command is sent, check timing	204
12.6.13	FADE TIME/FADE RATE: stop fading during startup.....	210
12.6.14	Level instructions: combined instructions.....	211
12.6.15	Power On Level - System Failure Level combined	213
12.6.16	ENABLE DAPC SEQUENCE.....	218
12.6.17	GO TO LAST ACTIVE LEVEL.....	219
12.6.18	GO TO SCENE	221
12.6.19	Power on: level control commands.....	222
12.6.20	Logarithmic dimming curve	224
12.6.21	Dimming curve: DAPC	225
12.6.22	Dimming curve: UP / DOWN	226
12.6.23	Dimming curve: STEP UP / STEP DOWN	227
12.6.24	FADE TIME/EXTENDED FADE TIME: light output behaviour	228
12.6.25	EXTENDED FADE TIME: light output behaviour	229
12.6.26	Behaviour during a fade.....	230
12.7	Special commands.....	232
12.7.1	INITIALISE – timer.....	232
12.7.2	TERMINATE	234
12.7.3	INITIALISE - device addressing	234
12.7.4	RANDOMISE	235
12.7.5	COMPARE	236
12.7.6	WITHDRAW.....	237
12.7.7	SEARCHADDRH / SEARCHADDRM / SEARCHADDR	238
12.7.8	PROGRAM SHORT ADDRESS.....	239
12.7.9	VERIFY SHORT ADDRESS	241
12.7.10	QUERY SHORT ADDRESS	242
12.7.11	IDENTIFY DEVICE	244
12.7.12	IDENTIFY DEVICE THROUGH RECALL MIN/MAX LEVEL.....	246
12.8	Queries and reserved commands.....	250
12.8.1	QUERY STATUS - lampFailure/lampOn	250
12.8.2	QUERY STATUS - lampOn	253
12.8.3	QUERY STATUS - limitError/lampOn	254
12.8.4	QUERY STATUS - powerCycleSeen	258
12.8.5	QUERY CONTROL GEAR PRESENT	259
12.8.6	QUERY VERSION NUMBER.....	259

12.8.7	PING	260
12.8.8	Broadcast unaddressed	260
12.8.9	Reserved commands: standard commands	262
12.8.10	Reserved commands: special commands	262
12.8.11	Application extended commands.....	263
12.8.12	Not supported device types	264
12.8.13	Removed functionality	264
12.9	Cross contamination	266
12.9.1	DTR0	266
12.9.2	NVM variables	266
12.9.3	Random address generation	268
12.9.4	Addressing 1	269
12.9.5	Addressing 2	270
12.9.6	Addressing 3	272
12.10	General subsequences	273
12.10.1	GetVersionNumber	273
12.10.2	GetExtendedVersionNumber.....	273
12.10.3	GetSupportedDeviceTypes	274
12.10.4	GetSupportedLightSources	274
12.10.5	WaitForPowerOnPhaseToFinish	276
12.10.6	WaitForLampOn	276
12.10.7	WaitForLampOnAddressed	277
12.10.8	WaitForLampLevel.....	277
12.10.9	WaitForFadeToFinish	277
12.10.10	SetShortAddress	278
12.10.11	GetRandomAddress.....	278
12.10.12	GetLimitedRandomAddress	279
12.10.13	SetSearchAddress	279
12.10.14	ReadMemBankMultibyteLocation	279
12.10.15	FindImplementedMemoryBank.....	280
12.10.16	FindAllImplementedMemoryBanks	280
12.10.17	GetNumberOfLogicalUnits	280
12.10.18	GetIndexOfLogicalUnit.....	281
12.10.19	ConnectLamps	281
12.10.20	DisconnectLamps	281
12.10.21	PowerCycle	282
12.10.22	PowerCycleAndWaitForBusPower	282
12.10.23	PowerCycleAndWaitForDecoder	283
Annex A (informative)	Examples of algorithms	284
A.1	Random address allocation.....	284
A.2	One single control gear connected to the control device	284
A.3	Using application extended commands	285
Annex B (normative)	High resolution dimmer	286
Bibliography	288
Figure 1 – IEC 62386 graphical overview	14	
Figure 2 – Control gear directly operating a light source	20	
Figure 3 – Dimming curve	21	

Figure 4 – Level over time, fading up and down	24
Figure 5 – Timing and response when receiving a command iteration	31
Figure 6 – Fading from MIN LEVEL to MAX LEVEL.....	74
Figure 7 – Fading from MAX LEVEL to off.....	74
Figure 8 – Normal fading for a PWM dimmer.....	74
Figure 9 – Fading from MAX LEVEL to off for a PWM dimmer.....	75
Figure 10 – Current rating test	97
Figure B.1 – Level behaviour in cases of off-grid starting points.....	287
Table 1 – 16-bit command frame encoding.....	19
Table 2 – Dimming curve tolerance (%, rounded to two decimals).....	21
Table 3 – Dimming curve	22
Table 4 – Fade times	25
Table 5 – Fade rates	26
Table 6 – Extended fade time - base value	27
Table 7 – Extended fade time - multiplier	27
Table 8 – Basic memory map of memory banks	33
Table 9 – Memory map of memory bank 0.....	36
Table 10 – Memory map of memory bank 1.....	38
Table 11 – Power on timing	41
Table 12 – Control gear status	43
Table 13 – Scenes	46
Table 14 – Declaration of variables.....	47
Table 15 – Standard commands.....	49
Table 16 – Special commands	53
Table 17 – Light source type encoding.....	65
Table 18 – Device addressing with “INITIALISE”	68
Table 19 – Unexpected outcome.....	76
Table 20 – Parameters for test sequence CheckFactoryDefault102.....	82
Table 21 – Parameters for test sequence CheckFactoryDefault201.....	86
Table 22 – Parameters for test sequence CheckFactoryDefault202.....	87
Table 23 – Parameters for test sequence CheckFactoryDefault203.....	88
Table 24 – Parameters for test sequence CheckFactoryDefault204.....	88
Table 25 – Parameters for test sequence CheckFactoryDefault205.....	89
Table 26 – Parameters for test sequence CheckFactoryDefault206.....	89
Table 27 – Parameters for test sequence CheckFactoryDefault207.....	90
Table 28 – Parameters for test sequence CheckFactoryDefault208.....	90
Table 29 – Parameters for test sequence CheckFactoryDefault209.....	91
Table 30 – Parameters for test sequence Maximum and minimum system voltage	95
Table 31 – Parameters for test sequence Transmitter voltages	99
Table 32 – Parameters for test sequence Transmitter rising and falling edges	100
Table 33 – Parameters for test sequence Transmitter rising and falling edges	101
Table 34 – Parameters for test sequence Transmitter bit timing	102

Table 35 – Parameters for test sequence Receiver frame timing	104
Table 36 – Parameters for test sequence Receiver start-up behavior.....	105
Table 37 – Parameters for test sequence Receiver bit timing	107
Table 38 – Parameters for test sequence Extended receiver bit timing.....	111
Table 39 – Parameters for test sequence Receiver frame violation and recovering after frame size violation.....	112
Table 40 – Parameters for test sequence Receiver frame timing	113
Table 41 – Parameters for test sequence RESET	117
Table 42 – Parameters for test sequence Send twice timeout	122
Table 43 – Parameters for test sequence Commands in-between	131
Table 44 – Parameters for test sequence SET MAX LEVEL	137
Table 45 – Parameters for test sequence SET MIN LEVEL	138
Table 46 – Parameters for test sequence SET SYSTEM FAILURE LEVEL	139
Table 47 – Parameters for test sequence SET POWER ON LEVEL.....	142
Table 48 – Parameters for test sequence SET FADE TIME	143
Table 49 – Parameters for test sequence SET FADE RATE	144
Table 50 – Parameters for test sequence SET SCENE / REMOVE FROM SCENE	145
Table 51 – Parameters for test sequence ADD TO GROUP / REMOVE FROM GROUP	146
Table 52 – Parameters for test sequence SET SHORT ADDRESS.....	147
Table 53 – Parameters for test sequence SET EXTENDED FADE TIME	148
Table 54 – Parameters for test sequence Reset/Power-on values	151
Table 55 – Parameters for test sequence DTR0 / DTR1 / DTR2	154
Table 56 – Parameters for test sequence READ MEMORY LOCATION on Memory Bank 0	158
Table 57 – Parameters for test sequence READ MEMORY LOCATION on Memory Bank 1	161
Table 58 – Parameters for test sequence Memory bank writing.....	166
Table 59 – Parameters for test sequence ENABLE WRITE MEMORY: writeEnableState	169
Table 60 – Parameters for test sequence ENABLE WRITE MEMORY: timeout / command in-between.....	172
Table 61 – Parameters for test sequence RESET MEMORY BANK: timeout / command in-between	174
Table 62 – Parameters for test sequence RESET MEMORY BANK	176
Table 63 – Parameters for test sequence Level instructions: Basic behaviour	178
Table 64 – Parameters for test sequence FADE TIME: possible values.....	181
Table 65 – Parameters for test sequence FADE TIME: transitions	184
Table 66 – Parameters for test sequence FADE TIME: fading to 0	186
Table 67 – Parameters for test sequence FADE TIME: small steps fading	189
Table 68 – Parameters for test sequence FADE TIME: extended fade time	190
Table 69 – Parameters for test sequence FADE RATE: possible values.....	193
Table 70 – Parameters for test sequence FADE RATE: possible values	194
Table 71 – Parameters for test sequence FADE RATE: transitions	195
Table 72 – Parameters for test sequence FADE RATE: extended fade time	196
Table 73 – Parameters for test sequence FADE TIME/FADE RATE: stop fading by setting MIN/MAX levels	199

Table 74 – Parameters for test sequence FADE TIME/FADE RATE: stop fading	203
Table 75 – Parameters for test sequence FADE TIME/FADE RATE: stop fading when a command is sent, check timing	205
Table 76 – Parameters for test sequence FADE TIME/FADE RATE: stop fading during startup	210
Table 77 – Parameters for test sequence Level instructions: combined instructions	212
Table 78 – Parameters for test sequence PowerOnLevel and SystemFailureLevel	217
Table 79 – Parameters for test sequence ENABLE DAPC SEQUENCE.....	219
Table 80 – Parameters for test sequence GO TO LAST ACTIVE LEVEL	220
Table 81 – Parameters for test sequence GO TO SCENE	222
Table 82 – Parameters for test sequence Power on: level control commands.....	224
Table 83 – Parameters for test sequence Logarithmic dimming curve	225
Table 84 – Parameters for test sequence Dimming curve: DAPC	226
Table 85 – Parameters for test sequence FADE TIME/EXTENDED FADE TIME: light output behaviour	229
Table 86 – Parameters for test sequence Behaviour during a fade.....	232
Table 87 – Parameters for test sequence INITIALISE - device addressing	235
Table 88 – Parameters for test sequence COMPARE.....	237
Table 89 – Parameters for test sequence WITHDRAW.....	238
Table 90 – Parameters for test sequence PROGRAM SHORT ADDRESS	241
Table 91 – Parameters for test sequence VERIFY SHORT ADDRESS	242
Table 92 – Parameters for test sequence QUERY SHORT ADDRESS	243
Table 93 – Parameters for test sequence IDENTIFY DEVICE	246
Table 94 – Parameters for test sequence IDENTIFY DEVICE THROUGH RECALL MIN/MAX LEVEL.....	250
Table 95 – Parameters for test sequence QUERY STATUS - lampFailure/lampOn.....	253
Table 96 – Parameters for test sequence QUERY STATUS - lampOn	254
Table 97 – Parameters for test sequence QUERY STATUS - limitError/lampOn	256
Table 98 – Parameters for test sequence QUERY STATUS - powerCycleSeen	258
Table 99 – Parameters for test sequence QUERY CONTROL GEAR PRESENT	259
Table 100 – Parameters for test sequence Broadcast unaddressed	261
Table 101 – Parameters for test sequence Reserved commands: standard commands	262
Table 102 – Parameters for test sequence Reserved commands: special commands	263
Table 103 – Parameters for test sequence Addressing 2.....	272

INTRODUCTION

IEC 62386 contains several parts, referred to as series. The 1xx series includes the basic specifications. Part 101 contains general requirements for system components, Part 102 extends this information with general requirements for control gear and Part 103 extends it further with general requirements for control devices.

The 2xx parts extend the general requirements for control gear with lamp specific extensions (mainly for backward compatibility with Edition 1 of IEC 62386) and with control gear specific features.

The 3xx parts extend the general requirements for control devices with input device specific extensions describing the instance types as well as some common features that can be combined with multiple instance types.

This second edition of IEC 62386-102 is published in conjunction with IEC 62386-101:2014 and with the various parts that make up the IEC 62386-2xx series for control gear, together with IEC 62386-103:2014 and the various parts that make up the IEC 62386-3xx series of particular requirements for control devices. The division into separately published parts provides for ease of future amendments and revisions. Additional requirements will be added as and when a need for them is recognised.

The setup of the standard is graphically represented in Figure 1 below.




Figure 1 – IEC 62386 graphical overview

When this part of IEC 62386 refers to any of the clauses of the other two parts of the IEC 62386-1xx series, the extent to which such a clause is applicable and the order in which the tests are to be performed are specified. The other parts also include additional requirements, as necessary.

All numbers used in this International Standard are decimal numbers unless otherwise noted. Hexadecimal numbers are given in the format 0xVV, where VV is the value. Binary numbers are given in the format XXXXXXXXb or in the format XXXX XXXX, where X is 0 or 1 and "x" in binary numbers means "don't care".

The following typographic expressions are used:

Variables: *variableName* or *variableName[3:0]*, giving only bits 3 to 0 of *variableName*

Range of values: [lowest, highest]

Command: "COMMAND NAME"