

This document is a preview generated by EVS

Maritime navigation and radiocommunication equipment and systems - Shipborne radar - Performance requirements, methods of testing and required test results

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 62388:2013 sisaldab Euroopa standardi EN 62388:2013 ingliskeelset teksti.	This Estonian standard EVS-EN 62388:2013 consists of the English text of the European standard EN 62388:2013.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kätesaadavaks 04.10.2013.	Date of Availability of the European standard is 04.10.2013.
Standard on kätesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 33.060, 47.020.70

Standardite reproduutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

English version

**Maritime navigation and radiocommunication equipment and systems -
Shipborne radar -
Performance requirements, methods of testing and required test results
(IEC 62388:2013)**

Matériels et systèmes de navigation et de
radiocommunication maritimes -
Radars de bord -
Exigences de performance, méthodes
d'essai et résultats exigés
(CEI 62388:2013)

Navigations- und
Funkkommunikationsgeräte und -systeme
für die Seeschifffahrt -
Radar für Schiffe -
Leistungsanforderungen, Prüfverfahren
und geforderte Prüfergebnisse
(IEC 62388:2013)

This European Standard was approved by CENELEC on 2013-07-31. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 80/696/FDIS, future edition 2 of IEC 62388, prepared by IEC TC 80 "Maritime navigation and radiocommunication equipment and systems" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62388:2013.

The following dates are fixed:

- latest date by which the document has to be implemented at (dop) 2014-04-30 national level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2016-07-31

This document supersedes EN 62388:2008.

EN 62388:2013 includes the following significant technical changes with respect to EN 62388:2008:

- In 6.2 (Transmission and interference) reference is now made to a revised Annex B (Unwanted emissions) where the mask has been tightened from 20 dB/decade to 30 dB/decade in line with ITU requirements and a new informative Annex J has been added concerning interference from emissions in adjacent frequency bands;
- Clause 7 (Display presentation) has been simplified (and the previous Annexes J and K deleted) with reference made instead to EN 62288 with associated changes throughout the standard;
- In 9.9.2 (PI lines and positioning) the requirements for parallel index lines have been revised;
- In 10.4.4 (Display orientation) a new mode of display orientation "head-up stabilised" has been added;
- In 11.5 (Automatic Identification System) new requirements and tests have been added for types of AIS targets, AIS repeater stations and filtering of AIS targets;
- In Clause 12 (Chart radar) a new subclause 12.3 has been added for ECDIS backup requirements;
- In Clause 13 (Ergonomic criteria) a new subclause 13.5 has been added giving requirements for default control settings;
- 14.3 (Output interfacing) has been revised together with the associated Annex H to update the requirements particularly with regard to interfaces to the VDR;
- Clause 16 (Alerts and failures) has been revised to update the requirements to align with bridge alert management and new requirements added for an alert management interface with associated changes throughout the standard;
- In Clause 18 (Equipment familiarisation and documentation) a new subclause 18.3 has been added for maintenance information and equipment update.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62388:2013 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 62616	NOTE	Harmonised as EN 62616.
ISO 9000	NOTE	Harmonised as EN ISO 9000.
ISO 9241-8	NOTE	Harmonised as EN ISO 9241-8.
ISO 9241-12	NOTE	Harmonised as EN ISO 9241-12.

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60945	-	Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results	EN 60945	-
IEC 61162	series	Maritime navigation and radiocommunication equipment and systems - Digital interfaces	EN 61162	series
IEC 61174	-	Maritime navigation and radiocommunication equipment and systems - Electronic chart display and information system (ECDIS) - Operational and performance requirements, methods of testing and required test results	EN 61174	-
IEC 61924-2	2012	Maritime navigation and radiocommunication equipment and systems - Integrated navigation systems - Part 2: Modular structure for INS - Operational and performance requirements, methods of testing and required test results	EN 61924-2	2013
IEC 61996-1	2013	Maritime navigation and radiocommunication equipment and systems - Shipborne voyage data recorder (VDR) - Part 1: Performance requirements, methods of testing and required test results	EN 61996-1	2013
IEC 62288	-	Maritime navigation and radiocommunication equipment and systems - Presentation of navigation-related information on shipborne navigational displays - General requirements, methods of testing and required test results	EN 62288	-
ITU-R Recommendation M.628	-	Technical characteristics for search and rescue radar transponders	-	-
ITU-R Recommendation M.824	-	Technical parameters of radar beacons (racons)	-	-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ITU-R Recommendation M.1176	-	Technical parameters of radar target enhancers	-	-
IHO S-52	-	Specifications for chart content and display aspects of ECDIS	-	-
IHO S-52, Appendix 2, Annex A	-	IHO ECDIS Presentation Library	-	-
IMO Resolution A.424(IX)	-	Performance standards for gyrocompasses	-	-
IMO Resolution A.694(17)	-	General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids	-	-
IMO Resolution A.821(19)	-	Performance standards for gyrocompasses for high-speed craft	-	-
IMO Resolution MSC.96(72)	-	Amendments to performance standards for devices to indicate speed and distance (resolution A.824(19))	-	-
IMO Resolution MSC.116(73)	-	Performance standards for marine transmitting heading devices (THDs)	-	-
IMO Resolution MSC.191(79)	-	Performance standards for the presentation of navigation-related information on shipborne navigational displays	-	-
IMO Resolution MSC.192(79)	-	Adoption of the revised performance standards for radar equipment	-	-
IMO Resolution MSC.232(82)	-	Revised performance standards for electronic chart display and information systems (ECDIS)	-	-
IMO Resolution MSC.302(87)	-	Adoption of performance standards for Bridge Alert Management	-	-
IMO MSC.1/Circ.1389	-	Guidance on procedures for updating shipborne navigation and communication equipment	-	-
VESA-2007-5	2007	Industry Standards and Guidelines for Computer Display Monitor Timing (DMT) Standard	-	-
DDWG DVI	1999	Digital Visual Interface (DVI) Revision 1.0, Digital Display Working Group (DDWG)	-	-

CONTENTS

FOREWORD	11
1 Scope	14
2 Normative references	14
3 Terms and definitions	15
4 General	27
4.1 Overview	27
4.2 Purpose	28
4.3 Application of these standards	28
4.4 Equipment categories	28
4.5 Establishing equipment type and status	29
4.6 Conditions of measurement and related definitions	30
4.7 Quality requirements	30
5 Tests	30
5.1 Test sites and simulation	30
5.1.1 Environmental and RF testing	30
5.1.2 Over-sea radar performance tests	30
5.1.3 Test targets and target simulation for performance tests	31
5.2 Test terminology and format	31
5.2.1 General	31
5.2.2 Test requirement terminology	31
5.2.3 Testing method terminology	32
6 Radar performance	32
6.1 General	32
6.2 Transmission and interference	32
6.2.1 Transmission frequency	32
6.2.2 Interference	33
6.3 Performance optimisation and monitoring	33
6.3.1 General	33
6.3.2 Optimum performance	33
6.4 Gain and anti-clutter functions	34
6.4.1 General	34
6.4.2 Gain function	34
6.4.3 Manual and automatic sea anti-clutter	34
6.4.4 Rain anti-clutter	35
6.5 Signal processing	35
6.5.1 General	35
6.5.2 Target enhancement	35
6.5.3 Radar signal correlation	36
6.5.4 Signal processing and radar image latency	36
6.5.5 Second-time-around echoes	36
6.5.6 Transmission format	37
6.5.7 Picture update	37
6.5.8 Additional processing	37
6.5.9 Signal processing description	37
6.6 Operation with SARTs, target enhancers (RTEs) and beacons	38
6.6.1 General	38

6.6.2	Radar beacons, SARTs and enhancers	38
6.7	Minimum range and range compensation.....	38
6.7.1	General.....	38
6.7.2	Range compensation.....	39
6.7.3	Minimum range	39
6.8	Range and bearing discrimination	40
6.8.1	General.....	40
6.8.2	Measurement conditions	40
6.8.3	Range discrimination	40
6.8.4	Bearing discrimination	40
6.8.5	Fundamental radar accuracy	41
6.9	Target detection performance assessment.....	41
6.9.1	General.....	41
6.9.2	Range of first detection in minimal clutter	42
6.9.3	Assessment of target detection with clutter	44
6.9.4	Radar performance documentation.....	49
6.10	Radar antenna (including pitch and roll)	50
6.10.1	General.....	50
6.10.2	Vertical radiation pattern/pitch and roll	50
6.10.3	Antenna horizontal pattern	51
6.10.4	Antenna side lobes.....	51
6.11	Radar availability – Standby and transmit	52
6.11.1	Requirements	52
6.11.2	Methods of test and required results	52
7	Display presentation	53
7.1	General.....	53
7.1.1	Requirements	53
7.1.2	Methods of test and required results	53
7.2	Linearity and index delay	53
7.2.1	Requirements	53
7.2.2	Methods of test and required results	53
7.3	Use and discrimination of colour	53
7.3.1	Requirements	53
7.3.2	Methods of test and required results	53
8	CCRP and own ship.....	54
8.1	Consistent common reference point (CCRP)	54
8.1.1	CCRP	54
8.1.2	CCRP position	54
8.1.3	Measurements	54
8.1.4	Antenna offset	55
8.2	Own ship.....	55
8.2.1	General.....	55
8.2.2	Own ship's outline and minimised symbol	55
8.2.3	Heading line	55
8.2.4	Stern line	56
9	Navigation tools.....	56
9.1	General.....	56
9.2	Units of measurement.....	56
9.2.1	Requirements	56

9.2.2	Methods of test and required results	57
9.3	Presentation	57
9.3.1	Requirements	57
9.3.2	Methods of test and required results	57
9.4	Display range scales	57
9.4.1	Mandatory range scales.....	57
9.5	Variable range marker (VRM)	58
9.5.1	General.....	58
9.5.2	VRM measurements	58
9.6	Electronic bearing line (EBL)	59
9.6.1	General.....	59
9.6.2	EBL measurements	59
9.6.3	EBL origin position	60
9.7	Cursor	60
9.7.1	General.....	60
9.7.2	Cursor measurement	60
9.7.3	Selection by cursor.....	61
9.8	Offset measurement of range and bearing	61
9.8.1	General.....	61
9.8.2	Electronic range and bearing line (ERBL)	61
9.9	Parallel index lines (PI).....	62
9.9.1	General.....	62
9.9.2	PI lines and positioning.....	62
9.10	Bearing scale.....	63
9.10.1	General.....	63
9.10.2	Bearing scale presentation.....	63
9.11	Range rings.....	64
9.11.1	General.....	64
9.11.2	Range ring presentation and measurement.....	64
9.12	Radar maps.....	65
9.12.1	General.....	65
9.12.2	Map functions and display simple user-defined maps.....	65
9.12.3	Map memory and transfer	65
9.12.4	Map presentation properties.....	66
9.13	Navigation routes	66
9.13.1	General.....	66
9.13.2	Route display and monitoring	67
10	Orientation, motion and stabilisation	67
10.1	General.....	67
10.2	Azimuth orientation	67
10.2.1	Accuracy of alignment	67
10.2.2	Heading readout and reference.....	68
10.2.3	Azimuth stabilisation update	69
10.3	Motion and orientation modes.....	69
10.3.1	General.....	69
10.3.2	True and relative motion	69
10.4	Off-centring	70
10.4.1	General.....	70
10.4.2	Manual and automatic off-centring	70

10.4.3 Automatic reset.....	70
10.4.4 Display orientation	71
10.5 Ground and sea stabilisation.....	72
10.5.1 Mode and source	72
10.5.2 Ground stabilisation	72
10.5.3 Sea stabilisation	73
11 Aids for collision avoidance	73
11.1 General.....	73
11.2 Target trails and past positions.....	73
11.2.1 General.....	73
11.2.2 Time and plot requirements.....	74
11.2.3 Trails/past position availability	74
11.3 Target tracking (TT)	75
11.3.1 General.....	75
11.3.2 Presentation of targets	75
11.3.3 Tracking calculations.....	76
11.3.4 Target tracking availability	76
11.3.5 Classification and tracked target capacity	77
11.3.6 Manual acquisition	78
11.3.7 Automatic acquisition	78
11.3.8 Motion trend	78
11.3.9 Visibility of 50 %	79
11.3.10 Tracking algorithm	79
11.3.11 Target swap	79
11.3.12 Cease tracking.....	79
11.3.13 Target tracking scenarios.....	79
11.3.14 Target motion and tracking accuracy.....	80
11.3.15 Tracker range and bearing accuracy	88
11.3.16 Reference target.....	89
11.4 Tracking limitations	89
11.4.1 Tracking warnings	89
11.4.2 Documentation.....	90
11.4.3 Requirements	90
11.4.4 Methods of test and required results	90
11.5 Automatic identification system.....	90
11.5.1 General.....	90
11.5.2 AIS targets and data report capacity	90
11.5.3 AIS target filtering	92
11.5.4 Activation and deactivation of AIS targets	92
11.5.5 AIS functionality and presentation	93
11.6 Radar and AIS target data.....	95
11.6.1 Requirements	95
11.6.2 Methods of test and required results	95
11.6.3 Bow crossing range and time (BCR/BCT).....	96
11.7 Operational target alerts	96
11.7.1 CPA and TCPA.....	96
11.7.2 New target warning	97
11.7.3 Lost tracked radar target.....	97
11.7.4 Lost AIS target criteria	98

11.8	Target association	99
11.8.1	General.....	99
11.8.2	Association and priority.....	99
11.9	Trial manoeuvre.....	103
11.9.1	General.....	103
11.9.2	Trial functions.....	103
12	Chart radar (optional classification)	104
12.1	General requirements	104
12.1.1	General.....	104
12.1.2	Chart operation and source.....	104
12.1.3	Chart elements and availability.....	105
12.1.4	Chart reference.....	106
12.1.5	Primary chart information set.....	106
12.1.6	Chart stabilisation and chart redraw.....	107
12.1.7	Chart position and latency.....	108
12.1.8	Matching and adjustment.....	108
12.1.9	Chart symbols, colours, and size	109
12.1.10	Chart display size	110
12.1.11	Chart alerts and indications.....	110
12.1.12	Chart malfunction.....	111
12.1.13	Chart radar malfunction	111
12.2	Additional requirements for standalone radar with chart facilities.....	111
12.2.1	General.....	111
12.2.2	Provision and updating of chart information	111
12.2.3	Content and structure of chart data	112
12.3	Additional requirements for ECDIS back-up (optional)	112
12.3.1	General.....	112
12.3.2	Requirements	112
12.3.3	Test Methods and required results	112
13	Ergonomic criteria (control functions and display)	112
13.1	General.....	112
13.2	Operational controls	112
13.2.1	Requirements	112
13.2.2	Methods of test and required results	113
13.3	Primary controls.....	113
13.3.1	Requirements	113
13.3.2	Methods of test and required results	113
13.4	Control properties	114
13.4.1	Requirements	114
13.4.2	Methods of test and required results	114
13.5	Default control setting and saved user control settings.....	114
13.5.1	Requirements	114
13.5.2	Test methods and required results	115
14	Interfacing	116
14.1	General.....	116
14.2	Input interfacing.....	116
14.2.1	Input data.....	116
14.2.2	Input quality, integrity and latency.....	117
14.3	Output interfacing	117

14.3.1	Output format	117
14.3.2	Output target data	117
14.3.3	VDR interface	118
15	Design, servicing and installation	119
15.1	General.....	119
15.2	Fault diagnosis and servicing	119
15.2.1	Requirements	119
15.2.2	Methods of test and required results	120
15.3	Display design	120
15.3.1	Requirements	120
15.3.2	Methods of test and required results	120
15.4	Transceiver design.....	120
15.4.1	General.....	120
15.4.2	Sector blanking.....	121
15.5	Antenna design.....	121
15.5.1	Requirements	121
15.5.2	Methods of test and required results	121
15.6	Inter-switched and multiple radars	122
15.6.1	General.....	122
15.6.2	System safeguards.....	122
15.6.3	Combining radar	122
15.6.4	Multiple radar system status.....	123
15.7	Multiple operational displays	123
15.7.1	Additional information and conformity.....	123
15.7.2	Requirements	123
15.7.3	Methods of test and required results	124
15.8	Safety – antenna and radiation	124
15.8.1	General.....	124
15.8.2	Antenna radiation and rotation.....	124
15.8.3	Microwave radiation levels	124
16	Alerts and failures.....	125
16.1	General.....	125
16.1.1	Priority of alerts	125
16.1.2	Alerts and indications	125
16.1.3	Alarm contact outputs	125
16.1.4	Alert management interface.....	125
16.1.5	Unacknowledged warnings	126
16.1.6	Unacknowledged alarms	127
16.1.7	Remote acknowledgement and silencing of alerts.....	127
16.1.8	Picture freeze	128
16.1.9	Sensor failure alert.....	128
16.2	Backup and fallback arrangements	128
16.2.1	Requirements	128
16.2.2	Failure of heading information (azimuth stabilisation).....	128
16.2.3	Failure of speed through the water information.....	129
16.2.4	Failure of course and speed over ground information	129
16.2.5	Failure of position input information	129
16.2.6	Failure of radar video input information	130
16.2.7	Failure of AIS input information.....	130

16.2.8 Failure of an integrated or networked system	130
17 Environmental testing	130
17.1 General.....	130
17.2 Testing to IEC 60945.....	131
17.2.1 Requirements	131
17.2.2 Methods of test and required results	131
17.3 Additional environmental tests	131
17.3.1 General.....	131
17.3.2 Antenna shock test.....	132
18 Equipment familiarisation and documentation	132
18.1 Familiarisation simulator	132
18.1.1 General.....	132
18.1.2 Requirements	132
18.1.3 Methods of test and required results	132
18.2 Instructions and documentation	133
18.2.1 General.....	133
18.2.2 Documentation.....	133
18.2.3 Operating instructions.....	133
18.3 Radar system installation.....	134
18.3.1 Requirements	134
18.3.2 Methods of test and required results	134
18.4 Maintenance information for equipment update	135
18.4.1 Requirements	135
18.4.2 Methods of test and required results	135
Annex A (informative) Guidelines for radar functionality on navigation displays.....	136
Annex B (normative) Unwanted emissions of radar systems.....	137
Annex C (informative) Radar target size (RCS) and detection range calculations	142
Annex D (informative) Factors that influence target detection.....	146
Annex E (normative) Sensor errors.....	155
Annex F (informative) Target scenario simulator/reported target simulator.....	157
Annex G (informative) Tracked and reported target states	158
Annex H (normative) IEC 61162 sentence formats	159
Annex I (normative) Radar control function/indication grouping	168
Annex J (informative) Interference to shipborne radar from emissions in adjacent frequency bands.....	172
Bibliography.....	175
 Figure 1 – Reduction of range to first detection due to rain at S-band	45
Figure 2 – Reduction of range to first detection due to rain at X-band	45
Figure 3 – TT scenario 1	82
Figure 4 – TT scenario 2	83
Figure 5 – TT scenario 3	84
Figure 6 – TT scenario 4	85
Figure 7 – TT scenario 5	86
Figure B.1 – B ₋₄₀ falls within the allocated band	140
Figure B.2 – B ₋₄₀ falls outside the allocated band.....	141

Figure C.1 – Enhancement by reflection (dB) over free-space (9,41 GHz)	145
Figure C.2 – Enhancement by reflection (dB) over free-space (3,05 GHz)	145
Figure D.1 – Effect of sea spikes on target detection.....	148
Figure D.2 – Multi-path plots for S-band.....	150
Figure D.3 – Multi-path plot for X-band	150
Figure G.1 – Tracked target states	158
Figure G.2 – AIS target state	158
Table 1 – Performance requirements for categories of ship/craft for SOLAS V	29
Table 2 – Range of first detection in clutter-free conditions	42
Table 3 – X-band pass/fail assessment criteria	48
Table 4 – S-band pass/fail assessment criteria	48
Table 5 – Pass/fail assessment.....	49
Table 6 – Douglas sea state parameters	49
Table 7 – Main horizontal beam pattern	51
Table 8 – Effective side-lobes.....	52
Table 9 – Features and colours to be used for radar maps.....	66
Table 10 – Tracked target capacity (subset of Table 1).....	77
Table 11 – Typical tracked target accuracy (95 % probability figures)	80
Table 12 – TT scenario 1, with sensor errors applied	81
Table 13 – TT scenario 1, times of measurement task	81
Table 14 – TT scenario 1, accuracies after 1 min and 3 min (all values)	82
Table 15 – TT scenario 2, own ship turning through 180°	83
Table 16 – TT scenario 3, initial target data.....	84
Table 17 – TT scenario 4, initial target data for fast targets (standard speed ships).....	84
Table 18 – TT scenario 4, initial target data for fast targets (HSC).....	85
Table 19 – TT scenario 5: initial target data for standard craft.....	86
Table 20 – TT scenario 5: initial target data for collision scenario for HSC.....	86
Table 21 – Measurement points and results at 3 min and 6 min for HSC	87
Table 22 – Measurement points and results at 11 min and 14 min for HSC	87
Table 23 – Measurement points and results at 3 min and 6 min for standard craft	87
Table 24 – Measurement points and results at 11 min and 14 min for standard craft.....	88
Table 25 – Measurement of tracked target accuracy.....	88
Table 26 – AIS display capacity (subset of Table 1)	91
Table 27 – AIS reporting rates	98
Table 28 – Association scenario 1, initial TT and AIS target position and data	100
Table 29 – Association scenario 1, AIS target data for diverging and converging tracks	101
Table 30 – Association scenario 2, initial TT and AIS target position and data	101
Table 31 – Association scenario 2, AIS target data for changing speed.....	102
Table 32 – Association scenario 3, TT and AIS target start position and data.....	102
Table 33 – Association scenario 4, initial TT and AIS target position and data	103
Table 34 – Association scenario 4, TT and AIS target with the same course and speed	103
Table 35 – Control settings configured in response to ‘Default’ selection.....	115

Table 36 – Antenna shock test severity (half sine pulse).....	132
Table B.1 – Measurement frequency ranges.....	138
Table D.1 – Spread of RCS values for typical ships.....	147
Table D.2 – S-band performance predictions for ranges of 0,2, 0,4, 0,7 NM.....	149
Table D.3 – X-band performance predictions for ranges of 0,2, 0,7 NM	149
Table D.4 – Parameters for attenuation in uniform rain conditions	151
Table D.5 – Typical values for attenuation and backscatter in uniform rain conditions.....	151
Table D.6 – Additional radar system parameters (X/S-band)	151
Table D.7 – Target size, height and RCS values	152
Table D.8 – S-band radar parameters (LP).....	153
Table D.9 – X-band radar parameters (LP).....	154
Table H.1 – Mandatory IEC 61162-1 sentences	159
Table H.2 – Optional IEC 61162-3 messges	160
Table H.3 – Description of terms	161
Table H.4 – Header format (1 of 2).....	162
Table H.5 – Package data format	164
Table I.1 – Top-level grouping of data and control functions for radar applications	168
Table I.2 – Icons for common function controls (1 of 2).....	169

MARITIME NAVIGATION AND RADIOTRANSFER EQUIPMENT AND SYSTEMS –

Shipborne radar – Performance requirements, methods of testing and required test results

1 Scope

This International Standard specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards not inferior to those adopted by the IMO in Resolution MSC.192(79).

(MSC.192/2) *The radar installation, in addition to meeting the general requirements as set out in resolution A.694(17) and the related standard IEC 60945, should comply with the performance standards of MSC.192(79). When a requirement of this standard is different from IEC 60945, the requirement in this standard takes precedence.*

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IEC 61174, *Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information systems (ECDIS) – Operational and performance requirements, methods of testing and required test results*

IEC 61924-2:2012, *Maritime navigation and radiocommunication equipment and systems – Part 2 Modular Structure for INS - Operational and performance requirements, methods of testing and required test results*

IEC 61996-1:2012, *Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR) – Part 1: Voyage data recorder (VDR) - Performance requirements – Methods of testing and required test results*

IEC 62288, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements, methods of testing and required results*

ITU-R Recommendation M.628, *Technical characteristics for search and rescue radar transponders*

ITU-R Recomendation M.824, *Technical parameters of radar beacons (racons)*

ITU-R Recommendation M.1176, *Technical parameters of radar target enhancers*

IHO S-52, *Specifications for chart content and display aspects of ECDIS*

IHO S-52 Annex A, *IHO ECDIS Presentation Library*

IMO Resolution A.424(XI), *Performance standards for Gyro-compasses*

IMO Resolution A.694(17), *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A.821(19), *Performance standards for Gyro-compasses for High-Speed Craft*

IMO Resolution MSC.96(72), *Amendments to IMO Resolution A.824(19), Performance standards for devices to indicate speed and distance*

IMO Resolution MSC.116(73), *Performance standards for marine transmitting heading devices (THDs)*

IMO Resolution MSC.191(79), *Performance standards for the presentation of navigation-related information on shipborne navigational displays*

IMO Resolution MSC.192(79), *Revised performance standards for radar equipment*

IMO Resolution MSC.232(82), *Revised performance standards for electronic chart display and information systems (ECDIS)*

IMO Resolution MSC.302(87), *Performance standards for bridge alert management*

IMO MSC.1/Circ.1389, *Guidance on procedures for updating shipborne navigation and communication equipment*

VESA-2007-5:2007, *Industry standards and guidelines for computer display monitor timing (DMT)*

DDWG DVI:1999, *Digital Visual Interface (DVI) Revision 1.0, Digital Display Working Group (DDWG)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

activated AIS target

target representing the automatic or manual activation of a sleeping target for the display of additional graphically presented information

Note 1 to entry: *The target is displayed by an “activated target” symbol including a vector; the heading; and the ROT or direction of turn indication (if available) to indicate initiated course changes.*

[SOURCE: IMO Resolution MSC.192(79):2004, Appendix 2, modified – added Note 1 to entry]

3.2

acquisition of a radar target

process of acquiring a target and initiating its tracking

[SOURCE: IMO Resolution MSC.192(79):2004, Appendix 2]