

PLAHVATUSOHTLIKUD KESKKONNAD. OSA 36:
MITTEELEKTRILISED SEADMED
PLAHVATUSOHTLIKELE KESKKONDADELE.
PÕHIMEETOD JA NÕUDED

Explosive atmospheres - Part 36: Non-electrical
equipment for explosive atmospheres - Basic method
and requirements (ISO 80079-36:2016)

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN ISO 80079-36:2016 sisaldab Euroopa standardi EN ISO 80079-36:2016 ingliskeelset teksti.	This Estonian standard EVS-EN ISO 80079-36:2016 consists of the English text of the European standard EN ISO 80079-36:2016.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 06.04.2016.	Date of Availability of the European standard is 06.04.2016.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 13.230

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:

Aru 10, 10317 Tallinn, Eesti; koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Aru 10, 10317 Tallinn, Estonia; homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

**Explosive atmospheres - Part 36: Non-electrical equipment
for explosive atmospheres - Basic method and
requirements (ISO 80079-36:2016)**

Atmosphères explosives - Partie 36: Appareils non
électriques destinés à être utilisés en atmosphères
explosives - Méthodologie et exigences (ISO 80079-
36:2016)

Explosionsfähige Atmosphären - Teil 36: Nicht-
elektrische Geräte für den Einsatz in explosionsfähigen
Atmosphären - Grundlagen und Anforderungen (ISO
80079-36:2016)

This European Standard was approved by CEN on 18 February 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

European Foreword

This document (EN ISO 80079-36:2016) has been prepared by Technical Committee ISO/TMBG "Technical Management Board - groups" in collaboration with Technical Committee CEN/TC 305 "Potentially explosive atmospheres - Explosion prevention and protection" the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2016, and conflicting national standards shall be withdrawn at the latest by October 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

The significant changes with respect to EN 13463-1:2009 are included in Annex ZB "*Significant changes between this European Standard and EN 13463-1:2009*".

This document supersedes EN 13463-1:2009.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of 2014/34/EU.

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

Extensions to the marking scheme described in the Directive are found in the ATEX Guidelines published by the European Commission. These are particularly useful for equipment that conforms to more than one category.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 80079-36:2016 has been approved by CEN as EN ISO 80079-36:2016 without any modification.

Annex ZA (informative)

Relationship between this European Standard and the Essential Requirements of EU Directive 2014/34/EU

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association to provide a means of conforming to Essential Requirements of the New Approach Directive 2014/34/EU.

Once this standard is cited in the Official Journal of the European Union under that Directive and has been implemented as a national standard in at least one Member State, compliance with the clauses of this standard given in Table ZA.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding Essential Requirements of that Directive and associated EFTA regulations.

Table ZA.1 — Correspondence between this European Standard and Directive 2014/34/EU

Clauses/sub-clauses of this EN	Essential Requirements (ERs) of EU Directive 2014/34/EU	Qualifying remarks/Notes
4	1.0.1 1.0.2	
5.1	1.0.1 1.0.2 1.0.3	
5.2	1.0.2 1.3	
6.1	1.3	
6.2.1, 6.2.2, 6.2.3	1.2.8 1.3.1 1.4.1	
6.2.4	2.0.1 2.0.2	
6.2.5, 6.2.6	2.1.1 2.2.1 2.3.1	
6.2.7	2.1.2 2.2.2 2.3.2	
6.3	1.3.1	reference to EN 1127-1

Table ZA.1 (continued)

Clauses/sub-clauses of this EN	Essential Requirements (ERs) of EU Directive 2014/34/EU	Qualifying remarks/Notes
6.4	1.3.4	
6.5	1.0.1 1.3.1	reference to EN 60079 series
6.6	1.3.3	
6.7	1.3.2	
6.8 - 6.9	1.3.1	
7.1, 7.2	1.3.4	
7.3	1.2.6	
7.4	1.1.3 1.4.1 1.4.2	
7.5	1.2.2 1.2.6	
7.6	1.1.3 1.4.2	
7.7	1.1.3 1.4.1 1.4.2	
8	1.1.3 1.2.1 1.2.2 1.2.5	
9.1	1.0.1 1.0.3 1.0.4	
9.5	1.0.6	
10	1.0.5	
Annexes A - G	1.0.2 1.3.1	

WARNING — Other requirements and other EU Directives may be applicable to the product(s) falling within the scope of this standard.

Annex ZB (informative)

Correspondence of equipment groups

In all cases Equipment Protection Levels (EPL) as defined by EN 60079-0 are related to the corresponding Equipment Groups and Equipment Categories according to the following table. The same applies if a standard makes reference to the intended use of equipment in Zones according to the definitions in EN 60079-10.

Table ZB.1 — Correspondence of equipment groups

EN 60079-0		Directive 2014/34/EU		EN 60079-10-1 and EN 60079-10-2
EPL	Group	Equipment Group	Equipment Category	Zones
Ma	I	I	M1	NA
Mb			M2	
Ga	II	II	1G	0
Gb			2G	1
Gc			3G	2
Da	III		1D	20
Db			2D	21
Dc			3D	22

Instructions

The manufacturer or his authorized representative in the Community is to draw up the instructions for use in the required Community languages.


Marking


The marking according to this standard is to be supplemented by the marking according to Directive 2014/34/EU. Examples are given below.

European marking examples

Directive part

 I M2

 II 2 G

 II 1 D

Standard part

Ex h I Mb

Ex h IIB T4 Gb

Ex h IIIC 120°C Da

Equipment example

Non-electrical equipment for Mining Industry,

Non-electrical equipment intended to be used in Surface Industry classified as Gas Explosive Atmosphere - Zone1

Non-electrical equipment intended to be used in Surface Industry classified as Explosive Atmosphere of Combustible Dust - Zone 20

Annex ZC (informative)

Significant changes between this European Standard and EN 13463-1:2009

This European Standard supersedes EN 13463-1:2009

Table ZC.1 — Significant changes between this European Standard and EN 13463-1:2009

Modifications significatives	Clause	Minor and formal changes	Extensions	Extensions
Introduction of new definitions and slight redefinitions concerning ignition sources to improve ignition hazard assessment	Clause 3	X		
Introduction of Equipment Protection Level instead of Category relating to ATEX Directive	Clause 4.1		X	
Introduction of Dust groups defined as Group IIIA, IIIB, & IIIC	Clause 4.4		X	
Introduction in the instructions for safe use and required maintenance for the equipment shall be specified by the manufacturer	Clause 5.1		X	
Change of wording regarding the formal Ignition hazard identification and assessment	Clause 5.2.1	X		
Introduction of what the assessment shall show	Clause 5.2.2.1		X	
Change of wording regarding EPL Mb equipment requirement	Clause 5.2.2.2	X		
Introduction of a new note regarding the risk of ignition due to other ignition source	Clause 6.1		X	
Change of wording regarding the ambient temperature	Clause 6.2.2	X		
Introduction of a new note regarding the option to calculate maximum temperatures	Clause 6.2.3		X	
Introduction of a new note regarding the layers of coal dust	Clause 6.2.3		X	
Introduction of a new note regarding the instructions	Clause 6.2.5		X	

Table ZC.1 (continued)

Modifications significatives	Article	Minor and formal changes	Extensions	Extensions
Introduction of a new column regarding requirement for T5 classification	Clause 6.2.6.1		X	
Introduction of two new notes regarding the enclosed volume	Clause 6.2.6.2		X	
Introduction of requirement regarding External hot surfaces	Clause 6.2.6.3		X	

NOTE 1 The technical changes referred to include the significant technical changes from the revised EN but this is not an exhaustive list of all modifications from the previous version.

Explanations:

A) Definitions

Minor and editorial changes

clarification
decrease of technical requirements
minor technical change
editorial corrections

Changes in a standard classified as 'Minor and editorial changes' refer to changes regarding the previous standard, which modify requirements in an editorial or a minor technical way. Also changes of the wording to clarify technical requirements without any technical change are classified as 'Minor and editorial changes'.

A reduction in level of existing requirement is also classified as 'Minor and editorial changes'

Extension

addition of technical options

Changes in a standard classified as 'extension' refers to changes regarding the previous standard, which add new or modify existing technical requirements, in a way that new options are given, but without increasing requirements for equipment that was fully compliant with the previous standard. Therefore these 'extensions' will not have to be considered for products in conformity with the preceding edition.

Major technical changes

addition of technical requirements

increase of technical requirements

Changes in a standard classified as 'Major technical change' refer to changes regarding the previous standard, which add new or increase the level of existing technical requirements, in a way that a product in conformity with the preceding standard will not always be able to fulfil the requirements given in the standard. 'Major technical changes' have to be considered for products in conformity with the preceding edition. For every change classified as 'Major Technical Change' additional information is provided in clause B) of the Annex ZB.

NOTE 2 These changes represent current technological knowledge¹. However, these changes should not normally have an influence on equipment already placed on the market.

B) Information about the background of 'Major Technical Changes'

None

¹ see also ATEX Guideline 10.3 and Annex ZA

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references.....	14
3 Terms and definitions	15
4 EPL and equipment groups	18
4.1 EPL	18
4.2 Group I	18
4.3 Group II	18
4.4 Group III	19
4.5 Equipment for specific explosive gas atmospheres	19
5 Ignition hazard assessment.....	19
5.1 General requirements.....	19
5.2 Procedure of ignition hazard assessment.....	20
5.2.1 Formal Ignition hazard identification and assessment.....	20
5.2.2 Group I equipment assessment	21
5.2.3 Group II and III equipment assessment.....	21
5.2.4 Assessment with malfunctions	22
5.2.5 Basic information necessary for the ignition hazard assessments	22
5.2.6 Ignition hazard assessment report	22
6 Assessment of possible ignition sources and control means	23
6.1 General.....	23
6.2 Hot surfaces	23
6.2.1 General	23
6.2.2 Ambient temperatures	23
6.2.3 Establishing the maximum surface temperature	23
6.2.4 Group I equipment	24
6.2.5 Group II equipment	24
6.2.6 Special cases for Group I and Group II equipment	25
6.2.7 Group III equipment	26
6.3 Flames and hot gases (including hot particles).....	26
6.4 Mechanically generated sparks and hot surfaces	26
6.4.1 General	26
6.4.2 Assessment of sparks generated by single impacts.....	26
6.4.3 Assessment of sparks and hot surfaces generated by friction.....	28
6.4.4 External equipment parts containing light metals.....	29
6.5 Electrical ignition sources except stray current.....	29
6.6 Stray electric currents, cathodic corrosion protection	29
6.6.1 Internal sources	29
6.6.2 External sources	29
6.7 Static electricity.....	29
6.7.1 General	29
6.7.2 Connection facilities for earthing conducting parts	30
6.7.3 Prevention of highly efficient charge generating mechanisms (leading to propagating brush discharges on non-conductive layers and coatings)	30
6.7.4 Equipment group I.....	30

6.7.5	Equipment group II.....	31
6.7.6	Equipment group III.....	31
6.8	Adiabatic compression and shock waves	32
6.9	Exothermic reactions, including self-ignition of dusts.....	32
7	Additional considerations	32
7.1	Dust deposits and other material in the gap of moving parts	32
7.2	Dust deposits and other material in the flame arresters incorporated in the equipment.....	33
7.3	Opening times of enclosures	33
7.4	Non-metallic enclosures and non-metallic parts of the equipment	33
7.4.1	General	33
7.4.2	Specification of the materials.....	33
7.4.3	Thermal endurance	33
7.5	Removable parts	33
7.6	Materials used for cementing	33
7.7	Light transmitting parts	34
7.8	Stored energy	34
8	Verification and tests	34
8.1	General.....	34
8.2	Determination of the maximum surface temperature.....	34
8.2.1	General	34
8.2.2	Hot Surface Ignition Test.....	36
8.3	Mechanical tests	37
8.3.1	Test for resistance to impact	37
8.3.2	Drop test.....	37
8.3.3	Required results.....	37
8.4	Additional tests of non-metallic parts of the equipment relevant for explosion protection.....	37
8.4.1	Test temperatures	37
8.4.2	Tests for Group I equipment	37
8.4.3	Tests for Group II and III equipment	38
8.4.4	Thermal endurance to heat.....	38
8.4.5	Thermal endurance to cold	39
8.4.6	Resistance to chemical substances for Group I equipment	39
8.4.7	Mechanical resistance tests	39
8.4.8	Surface resistance test of non-conductive parts of the equipment relevant for explosion prevention and protection	39
8.4.9	Thermal shock test.....	39
9	Documentation	39
9.1	Technical documentation.....	39
9.2	Conformity with the documentation	40
9.3	Certificate	40
9.4	Responsibility for marking	40
10	Instructions.....	40
11	Marking	41
11.1	Location.....	41
11.2	General.....	41
11.3	Warning markings	42
11.4	Marking on very small equipment.....	43

11.5	Examples of marking	43
Annex A	(informative) Methodology for confirming the EPL	44
A.1	Methodology for confirming the EPL of Group I	44
A.1.1	EPL Ma	44
A.1.2	EPL Mb	44
A.2	Methodology for confirming the EPL of Group II and III	44
A.2.1	EPL Ga and Da	44
A.2.2	EPL Gb and Db	44
A.2.3	EPL Gc and Dc	44
Annex B	(informative) Explanation of the ignition hazard assessment procedure	45
B.1	Overview	45
B.1.1	General	45
B.1.2	Reporting with the help of a table	45
B.2	Assessment Procedure	45
B.3	Assessment Steps	46
B.3.1	Identification of Ignition Hazards	46
B.3.2	Determination of measures	47
B.3.3	Concluding ignition hazard estimation and categorisation	48
B.3.4	Determination of the EPL	48
Annex C	(informative) Examples of ignition hazard assessment	49
C.1	General remarks	49
C.2	Examples for common cases demonstrating the use of the scheme	49
C.3	Example of an ignition hazard assessment for a pump	56
C.4	Example of an ignition hazard assessment for an agitator	60
Annex D	(normative) Charging tests with non-conductive materials	71
D.1	General	71
D.2	Principle of the test	71
D.3	Samples and apparatus	72
D.4	Procedure	72
D.4.1	Conditioning	72
D.4.2	Determination of the most efficient charging method	72
Annex E	(informative) Consideration of misuse which can reasonably be anticipated during ignition hazard assessment procedure	76
E.1	General	76
E.2	Identification and analysis of the ignition hazards	76
E.3	First assessment of the ignition hazards	76
E.4	Determination of safety measures	76
E.5	Final assessment of the ignition hazards	77
Annex F	(informative) Development of different types of incendive electrostatic discharges	78
Annex G	(normative) Protection concepts of types of protection "d", "p" and "t" acceptable for non-electrical equipment	79
Annex H	(informative) Volume dependence of auto-ignition temperature	80
Annex I	(informative) Relationship between Equipment protection levels (EPLs) and zones	82
	Bibliography	83
	Figure 1 – Relationship between ignition source definitions	20

Figure D.1 – Rubbing with a pure polyamide cloth	74
Figure D.2 – Discharging the charged surface of the test piece with a probe connected to earth via a 0,1 μ F capacitor	74
Figure D.3 – Charging by the influence of a DC high voltage power	75
Figure F.1 – Different types of incensive electrostatic discharges	78
Figure H.1 – Volume dependence of auto-ignition temperature	81
Table 1 – Applicability of specific clauses of IEC 60079-0	10
Table 2 – Classification of maximum surface temperatures for Group II equipment	24
Table 3 – Assessment for temperature classification for small surface areas	25
Table 4 – Single impact energy limits for EPL Ga	28
Table 5 – Single impact energy limits for EPL Gb	28
Table 6 – Single impact energy limits for EPL Gc	28
Table 7 – Single impact energy limits for EPL Da, Db and Dc	28
Table 8 – Permitted maximum projected areas for non-conductive parts of equipment liable to become electrostatically charged	31
Table 9 – Thermal endurance test	38
Table 10 – Ambient temperature marking	42
Table 11 – Text of warning markings	42
Table B.1 – Table showing recommended documentation of an example of initial assessment of equipment related ignition sources	46
Table B.2 – Example for reporting of the identification of ignition hazards (step 1) and the first assessment (step 2)	47
Table B.3 – Example for reporting of the determination of protective measures (step 3) and the concluding estimation and categorisation (step 4)	48
Table C.1 – List of examples	49
Table C.2 – Common cases demonstrating the use of the scheme – Electrostatic discharge	50
Table C.3 – Common cases demonstrating the use of the scheme – Hot surface	52
Table C.4 – Common cases demonstrating the use of the scheme – Mechanical spark	54
Table C.5 – Ignition hazard assessment report for a pump	57
Table C.6 – Ignition hazard assessment report for an agitator	61
Table H.1 – AITs of combustibles taken from IEC 60079-20-1 as contained in Figure H.1	80
Table I.1 – Relationship between Equipment protection levels (EPLs) and zones	82

INTRODUCTION

This part of ISO/IEC 80079 addresses for the first time basic requirements and protection concepts for mechanical explosion protected equipment on an international level. Up to now, with some exceptions, only the design, manufacture, installation and operation of electrical equipment in explosive atmospheres have been addressed in ISO and IEC standards. Examples of non-electrical equipment are: couplings, pumps, gearboxes, brakes, hydraulic and pneumatic motors and any combination of devices to realise a machine, fan, engine, compressor, assemblies, etc.

Although many but not all of such machines use an explosion protected electric motor for motive power the measures needed to reduce the risk of ignition in mechanical equipment as part of the machine may be different to those applied to electrical equipment.

Whereas electrical equipment working within design parameters often contains effective ignition sources such as sparking parts, this is not necessarily true for mechanical equipment which is designed to operate without break-down between predetermined maintenance operations.

Generally there are two mechanical ignition scenarios that need to be considered. These are, ignition resulting from a failure in the machine such as a bearing over-heating or ignition created by the normal functioning of the machine such as a hot brake surface.

Experience has shown that it is essential to perform a comprehensive ignition hazard assessment on the complete mechanical equipment to identify all potential ignition sources and determine if they can become effective ignition sources during the expected lifetime of the mechanical equipment. Once these ignition risks are understood and documented it is then possible to assign protective measures, depending on the required Equipment Protection Level (EPL), to minimise the probability that these ignition sources will become effective.

This standard addresses mechanical equipment and assemblies intended for the generation, transfer, storage, measurement, control and conversion of energy and/or the processing of material and which are capable of causing an explosion through their own potential sources of ignition.

Potential ignition sources are not limited to those created by the equipment but include any ignition sources created by the operation of the equipment; for example hot surfaces when pumping hot fluids or electrostatic charging when handling plastics.

If the only source of ignition of an item comes from the external process such items are not considered to have their own source of ignition, and they are not in the scope of this part of ISO/IEC 80079.

NOTE Examples are items made from plastics (polymers) like plastic pipes and containers that can become charged due to an external process (and not by the operation of the equipment), or items that can become hot due to an external process (like a pipe). These are not considered to be "non-electrical equipment" on their own. If on the other hand such items are incorporated into non-electrical equipment, and could become an ignition source by the intended operation of the equipment, they need to be assessed together with the equipment under consideration (for example a plastic pipe as part of a petrol dispenser could become charged due to the operation of this dispenser).

EXPLOSIVE ATMOSPHERES –

Part 36: Non-electrical equipment for explosive atmospheres – Basic method and requirements

1 Scope

This part of ISO/IEC 80079 specifies the basic method and requirements for design, construction, testing and marking of non-electrical Ex equipment, Ex Components, protective systems, devices and assemblies of these products that have their own potential ignition sources and are intended for use in explosive atmospheres.

Hand tools and manually operated equipment without energy storage are excluded from the scope of this standard. This standard does not address the safety of static autonomous process equipment when it is not part of equipment referred to in this standard.

NOTE 1 Static autonomous process equipment includes items such as tanks, vessels, fixed pipework and hand operated valves which do not have their own source of energy that could create a potential ignition source during operation.

This standard does not specify requirements for safety, other than those directly related to the risk of ignition which may then lead to an explosion. The standard atmospheric conditions (relating to the explosion characteristics of the atmosphere) under which it may be assumed that equipment can be operated are:

- temperature -20 °C to +60 °C;
- pressure 80 kPa (0,8 bar) to 110 kPa (1,1 bar); and
- air with normal oxygen content, typically 21 % v/v.

Such atmospheres can also exist inside the equipment. In addition, the external atmosphere can be drawn inside the equipment by natural breathing produced as a result of fluctuations in the equipment's internal operating pressure, and/or temperature.

NOTE 2 Although the standard atmospheric conditions above give a temperature range for the atmosphere of -20 °C to +60 °C, the normal ambient temperature range for the equipment is -20 °C to +40 °C, unless otherwise specified and marked. It is considered that -20 °C to +40 °C is appropriate for most equipment and that to manufacture all equipment to be suitable for a standard atmosphere upper ambient temperature of +60 °C would place unnecessary design constraints.

NOTE 3 The requirements of this standard can also be helpful for the design, construction, testing and marking of equipment intended for use in atmospheres outside the validity range stated above. In this case however, the ignition hazard assessment, ignition protection provided, additional testing (if necessary), manufacturer's technical documentation and instructions to the user, clearly demonstrate and indicate the equipment's suitability for the conditions it may encounter. It is also recognized that changes in temperature and pressure can have a significant influence on characteristics of the explosive atmosphere, such as ignitability.

This part of ISO/IEC 80079 specifies the requirements for the design and construction of equipment, intended for explosive atmospheres in conformity with all Equipment Protection Levels (EPLs) of Group I, II and III.

NOTE 4 It is not unusual for equipment designed and constructed in accordance with this standard for a particular EPL to be used in areas requiring an EPL with a higher level of safety by including the application of additional measures. Such measures include for example inerting, suppression, venting or containment or for example by dilution, drainage, monitoring and shut-down. Such measures are outside the scope of this standard.

This standard supplements and modifies the general requirements of IEC 60079-0, as shown in Table 1. Where a requirement of this standard conflicts with a requirement of IEC 60079-0, as far as applicable for non-electrical equipment, the requirement of this standard takes precedence.