

English Version

**Fixed capacitors for use in electronic equipment - Part 26:
Sectional specification - Fixed aluminium electrolytic capacitors
with conductive polymer solid electrolyte
(IEC 60384-26:2018/COR1:2020)**

Condensateurs fixes utilisés dans les équipements
électroniques - Partie 26: Spécification intermédiaire -
Condensateurs fixes électrolytiques en aluminium à
électrolyte solide en polymère conducteur
(IEC 60384-26:2018/COR1:2020)

To be completed
(IEC 60384-26:2018/COR1:2020)

This corrigendum becomes effective on 15 May 2020 for incorporation in the English language version of the EN.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Endorsement notice

The text of the corrigendum IEC 60384-26:2018/COR1:2020 was approved by CENELEC as EN IEC 60384-26:2018/AC:2020-05 without any modification.

INTERNATIONAL ELECTROTECHNICAL COMMISSION
COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

IEC 60384-26
Edition 2.0 2018-05

IEC 60384-26
Edition 2.0 2018-05

**FIXED CAPACITORS FOR USE IN ELECTRONIC
EQUIPMENT –**

**Part 26: Sectional specification –
Fixed aluminium electrolytic
capacitors with conductive polymer solid
electrolyte**

**CONDENSATEURS FIXES UTILISÉS
DANS LES ÉQUIPEMENTS ÉLECTRONIQUES –**

**Partie 26: Spécification intermédiaire –
Condensateurs fixes
électrolytiques en aluminium à électrolyte solide
en polymère conducteur**

CORRIGENDUM 1

Corrections to the French version appear after the English text.

Les corrections à la version française sont données après le texte anglais.

In Table 3, Group 0, 4.3 Dimension (detail), in the column "Conditions of test and measurements", replace the text "See 4.3.2" with "See 4.3.1".

Group 0	ND		See Table 2	
4.22 High surge current ^e		See 4.22.1		
4.3 Visual examination		See 4.3.1		No visible damage Legible marking and as specified in the detail specification
4.3 Dimension (detail)		See 4.3.1		See detail specification

In Table 3, Group 2, 4.13.5 Final inspections, Leakage current, in the column "Performance requirements", replace the text "≤ 5 times of the limit in 4.4.3.1" with "≤ 5 times the limit in 4.4.1.3".

Group 2	D		See Table 2	
4.13 Damp heat, steady state		See 4.13.1		
4.13.2 Initial inspection				
Capacitance		See 4.4.2		
4.13.4 Recovery		See 4.13.4		
4.13.5 Final inspections				
Visual examination		See 4.3.1		No visible damage Legible marking
Leakage current		See 4.4.1		≤ 5 times the limit in 4.4.1.3