



INTERNATIONAL STANDARD ISO 1798:1997
TECHNICAL CORRIGENDUM 1

Published 2003-03-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Flexible cellular polymeric materials — Determination of tensile strength and elongation at break —

TECHNICAL CORRIGENDUM 1

Matériaux polymères alvéolaires souples — Détermination de la résistance à la traction et de l'allongement à la rupture

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO 1798:1997 was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 4, *Products (other than hoses)*

Page 1, Clause 2

Replace ISO 5893:1993 by ISO 5893:2002, *Rubber and plastics test equipment — Tensile, flexural and compression types (constant rate of traverse) — Specification*.

Page 3, Clause 6

Insert the following note after the third paragraph:

NOTE The probability of test pieces being rejected can be minimized by selecting a gauge length close to the permitted maximum of 50 mm.

Page 5, Clause 8, item g)

Replace

the tensile strength in megapascals

by

the tensile strength in kilopascals.