

English version
Version Française
Deutsche Fassung

Crane safety - General design - Part 2: Load actions

Sécurité des appareils de levage à charge
suspendue - Conception générale - Partie
2: Effets de charge

Kransicherheit - Konstruktion allgemein -
Teil 2: Lasteinwirkungen

This corrigendum becomes effective on 7 March 2012 for incorporation in the official English version of the EN.

Ce corrigendum prendra effet le 7 mars 2012 pour incorporation dans la version anglaise officielle de la EN.

Die Berichtigung tritt am 7. März 2012 zur Einarbeitung in die offizielle Englische Fassung der EN in Kraft.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

1 Modifications to 4.2.3.4

In the key to formula (11), replace "l" with "1", to read:

$$f = 0,3 \cdot \left[1 - e^{(250\alpha)} \right]$$

Replace Table 5 with the following:

"

Combinations of wheel pairs (see figure 8)	$\xi_{1i} = \xi_{2i}$	V_{1i}	V_{2i}
CFF	$\mu\mu' l/nh$	$\frac{\mu'}{n} \left(1 - \frac{d_i}{h} \right)$	$\frac{\mu}{n} \left(1 - \frac{d_i}{h} \right)$
IFF	0		0
CFM	$\mu\mu' l/nh$		
IFM	0		

".

2 Modification to Figure A.3

Replace the Key with the following:

"

Key

1 ropes

2 pipes, rods

".