

**EUROPEAN STANDARD**  
**NORME EUROPÉENNE**  
**EUROPÄISCHE NORM**

**EN 1998-2:2005/AC**

February 2010  
Février 2010  
Februar 2010

---

**ICS** 91.120.25; 93.040

English version  
Version Française  
Deutsche Fassung

**Eurocode 8 - Design of structures for earthquake resistance - Part 2:  
Bridges**

**Eurocode 8 - Calcul des structures pour  
leur résistance aux séismes - Partie 2:  
Ponts**

**Eurocode 8 - Auslegung von Bauwerken  
gegen Erdbeben - Teil 2: Brücken**

This corrigendum becomes effective on 10 February 2010 for incorporation in the three official language versions of the EN.

Ce corrigendum prendra effet le 10 février 2010 pour incorporation dans les trois versions linguistiques officielles de la EN.

Die Berichtigung tritt am 10. Februar 2010 zur Einarbeitung in die drei offiziellen Sprachfassungen der EN in Kraft.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: Avenue Marnix 17, B-1000 Brussels**

---

© 2010 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.  
Tous droits d'exploitation sous quelque forme et de quelque manière que ce soit réservés dans le monde entier aux membres nationaux du CEN.  
Alle Rechte der Verwertung, gleich in welcher Form und in welchem Verfahren, sind weltweit den nationalen Mitgliedern von CEN vorbehalten.

Ref. No.:EN 1998-2:2005/AC:2010 D/E/F

**1) Modifications to "National annex for EN 1998-2"**

*In second paragraph, grid lines, 2nd column, 2nd line (for the Item related to the reference 1.1.1(8)), replace "Informative Annexes A, B, C, D, E, F, H and JJ" with "Informative Annexes A, B, C, D, E, F, H, JJ and K".*

*In second paragraph, grid lines, 2nd column, 2nd line (for the Item related to the reference 7.7.1(2)), replace "Values of factors  $\delta_w$  and  $\delta_b$  for the lateral restoring capability of the isolation system" with "Value of the ratio  $\delta$  for the evaluation of the lateral restoring capability".*

*In second paragraph, grid lines, just after the row dedicated to reference 7.7.1(2), add the following row:*

"

7.7.1(4)	Value of $\gamma_{du}$ reflecting uncertainties in the estimation of design displacements
.	

**2) Modification to 4.2.4.4**

*Paragraph (2), subparagraph (a), replace "Such an identification should be based" with "Such identification should be based".*

**3) Modification to 5.6.2**

*Paragraph (2)P, list entry b), NOTE, replace "ascribed to  $\gamma_{bd1}$  fro use in a country" with "ascribed to  $\gamma_{bd1}$  for use in a country".*

**4) Modifications to 6.2.2**

*Paragraph (3), replace "acheived in either one" with "achieved in either one".*

*Paragraph (4)P, Equation (6.10), replace "min*
$$\left(\frac{A_t}{s_T}\right) = \frac{\sum A_s f_{ys}}{1,6 f_{yt}} (mm^2/m)" with  
"min$$
$$\left(\frac{A_t}{s_L}\right) = \frac{\sum A_s f_{ys}}{1,6 f_{yt}} (mm^2/m)".$$

*Paragraph (4)P, after Equation (6.10), replace:*

*" $s_T$  is the transverse distance between tie legs, in m;"*

*with:*

*" $s_L$  is the spacing of the legs along the axis of the member, in m;".*