



INTERNATIONAL STANDARD ISO 12917-1:2002 TECHNICAL CORRIGENDUM 1

Published 2009-10-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Petroleum and liquid petroleum products — Calibration of horizontal cylindrical tanks —

Part 1: Manual methods

TECHNICAL CORRIGENDUM 1

Pétrole et produits pétroliers liquides — Jaugeage des réservoirs cylindriques horizontaux —

Partie 1: Méthodes manuelles

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO 12917-1:2002 was prepared by Technical Committee ISO/TC 28, *Petroleum products and lubricants*, Subcommittee SC 2, *Measurement of petroleum and related products*.

Page 8, Clause 15

At the end of the first sentence, replace “can be neglected” with “can be neglected if E/D is less than 0,012”. At the end of the paragraph, replace “normative annex A” with “Annex A”.

Page 14, Figure A.1:

Replace items 1 and 2 in the key with the following:

Key

Value of H/D : 0,5 to 0,999 — subtract volume correction when the tank is more than half full

Value of H/D : 0,001 to 0,5 — add volume correction when the tank is less than half full