



INTERNATIONAL STANDARD ISO/IEC 14496-4:2004/Amd.11:2006
TECHNICAL CORRIGENDUM 2

Published 2007-02-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Coding of audio-visual objects —
Part 4:
Conformance testing

AMENDMENT 11: Parametric stereo conformance

TECHNICAL CORRIGENDUM 2

Technologies de l'information — Codage des objets audiovisuels —

Partie 4: Essai de conformité

AMENDEMENT 11: Conformité stéréo paramétrique

RECTIFICATIF TECHNIQUE 2

Technical Corrigendum 2 to ISO/IEC 14496-4:2004/Amd.11:2006 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

In subclause 6.6.18.2.4, replace Table AMD11.1:

| file base name | content | bitrate (kbit/s) | iid_data | icc_data | ipd_data | opd_data | mixing procedure | iid-/icc-mode | Diff max | RMS max (linear) | test procedure |
|----------------|---------|------------------|----------|----------|----------|----------|------------------|---------------|----------|------------------|----------------|
| al_sbr_ps_00 | sweep | 32 | - | - | - | - | - | - | 8 | 1.7 | RMS |
| al_sbr_ps_01 | sweep | 32 | y | - | - | - | - | - | 12 | 1.8 | RMS |
| al_sbr_ps_02 | sweep | 32 | - | y | - | - | Ra | - | - | - | - |
| al_sbr_ps_03 | sweep | 32 | y | y | - | - | Rb | - | - | - | - |
| al_sbr_ps_04 | sweep | 32 | y | - | y | y | - | - | - | - | - |
| al_sbr_ps_05 | sweep | 32 | y | y | - | - | Ra | - | - | - | - |
| al_sbr_ps_06 | sweep | 32 | y | y | - | - | Ra | y | - | - | - |

with the following (changes highlighted):

| file base name | content | bitrate (kbit/s) | iid_data | icc_data | ipd_data | opd_data | mixing procedure | iid-/icc-mode switching | Diff max baseline decoding | RMS max (linear value) baseline decoding | Diff max unrestricted decoding | RMS max (linear value) unrestricted decoding | test procedure |
|----------------|---------|------------------|----------|----------|----------|----------|------------------|-------------------------|----------------------------|--|--------------------------------|--|----------------|
| al_sbr_ps_00 | sweep | 32 | - | - | - | - | - | - | 8 | 1.7 | 8 | 1.7 | RMS |
| al_sbr_ps_01 | sweep | 32 | y | - | - | - | - | - | 12 | 1.8 | 12 | 1.8 | RMS |
| al_sbr_ps_02 | sweep | 32 | - | y | - | - | R _a | - | 30 | 3.6 | 30 | 3.6 | RMS |
| al_sbr_ps_03 | sweep | 32 | y | y | - | - | R _b | - | 45 | 3.7 | - | - | RMS |
| al_sbr_ps_04 | sweep | 32 | y | - | y | y | - | - | 12 | 1.8 | - | - | RMS |
| al_sbr_ps_05 | sweep | 32 | y | y | - | - | R _a | - | 40 | 3.6 | - | - | RMS |
| al_sbr_ps_06 | sweep | 32 | y | y | - | - | R _a | y | 40 | 3.7 | - | - | RMS |