



INTERNATIONAL STANDARD ISO 3601-1:2008
TECHNICAL CORRIGENDUM 1

Published 2009-07-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Fluid power systems — O-rings —

Part 1:

Inside diameters, cross-sections, tolerances and designation codes

TECHNICAL CORRIGENDUM 1

Transmissions hydrauliques et pneumatiques — Joints toriques — Partie 1: Diamètres intérieurs, sections, tolérances et codes d'identification dimensionnelle

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO 3601-1:2008 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 7, *Sealing devices*.

Page 5, Table 2, size code 026/027:

Delete the line between the cells for inside diameter inch tolerance class B (eighth column from the left) to show that $\pm 0,014$ is valid for both sizes, such that the two rows read as follows:

026	31,47 × 1,78	31,47	± 0,28	± 0,35	1,239	± 0,011	± 0,014	0,259	0,015 8
027	33,05 × 1,78	33,05		± 0,36	1,301			0,272	0,016 6

Page 17, Table 6, Size code 473:

Replace the nominal inside diameter inch value $d_1 = 23,490$ with $d_1 = 23,940$, such that the row reads as follows:

473	608,08 × 6,99	608,08	± 2,79	± 4,08	23,940	± 0,110	± 0,161	74,043	4,518 4
-----	---------------	--------	--------	--------	--------	---------	---------	--------	---------

ICS 23.100.60, 83.140.50

Ref. No. ISO 3601-1:2008/Cor.1:2009(E)