
**Information technology — Digitally
recorded media for information
interchange and storage — Data
migration method for optical disks for
long-term data storage**

*Technologies de l'information — Supports enregistrés
numériquement pour échange et stockage d'information — Méthode
de migration de données pour disques optiques pour le stockage à
long terme*



This document is a preview generated by ERS



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Test method	4
4.1 Test parameters	4
4.2 Test area	4
4.3 Test drive	5
4.3.1 General	5
4.3.2 Test drive calibration	5
4.4 Disk preparation	5
4.5 Test execution	5
5 Test interval for periodic performance test	5
6 Test result evaluation	6
6.1 General	6
6.2 Initial performance test	6
6.3 Periodic performance test	6
7 Prevention of deterioration	7
Annex A (informative) Causes of deterioration for optical disks for long-term data storage	8
Annex B (informative) Recommendations on handling, storage and cleaning conditions for optical disks for long-term data storage	10
Annex C (informative) Relation between BER and PI SUM 8	12
Annex D (informative) Guideline for adjustment of the estimated lifetime to higher stress conditions	13
Annex E (informative) Calculation for B_{mig} Life using B_{50} Life and B_5 Life	15
Annex F (informative) Guideline of test interval and migration	17
Annex G (informative) Test area	20
Annex H (informative) Max RSER criteria for BD Recordable and BD Rewritable disks	21
Annex I (informative) Guideline for treatment of defects	22
Bibliography	23

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Digitally Recorded Media for Information Interchange and Storage*.

This third edition cancels and replaces the second edition (ISO/IEC 29121:2013), which has been technically revised.

The main changes compared to the previous edition are as follows:

- CD-R, CD-RW, BD-Recordable and BD Rewritable disks have been added as the optical disks for long-term data storage applicable in this document, and accordingly, the title of this document has been changed.
- Terminologies have been harmonized with those used in ISO/IEC 16963 and relevant updates in the latest version of ISO/IEC 16963 have been reflected.
- ISO/IEC 16963 has been moved from the Normative references clause to the Bibliography at publication stage in order to conform to the requirements from the ISO/IEC Directives Part 2.
- Minor editorial changes have been made to conform to the latest version of ISO/IEC Directives Part 2.

Introduction

Many organizations now use optical disks for long-term storage of information. It is assumed that a disk selected for recording has already been qualified for that purpose. It is therefore important to be able to verify that data have been recorded correctly and remains readable for the required amount of time. Previous International Standards clearly defined requirements for interchange, but did not contain requirements for longevity.

Longevity is limited both by disk degradation and by technology obsolescence. Interchange is regularly verified to assure that information on existing recorded disks will continue to be recoverable. Users can have a maintenance policy that protects disks against unanticipated failure or use, such as by making one copy, another to function as a backup or master and another for routine access. Hardware-support life cycles typically vary between five to ten years, and technology life cycles usually end after 20 years. Consequently, recordings that require a longer life cycle may have to be transferred to upgraded platforms every 10 to 30 years.

Optical disks for long-term storage should be evaluated. Significant longevity differences can exist for disks from different manufacturers and even between disks from the same manufacturer. It is preferable that disks selected for long-term preservation should have a long estimated lifetime, which can be estimated according to ISO/IEC 16963.

Disks with initially poor quality do not offer sufficient headroom and can reach the unrecoverable-error threshold before the next scheduled inspection, which is to be avoided for long-term data storage. This means that a disk of high initial recorded quality that maintains this condition for life is expected to have superior longevity.

Because read data are corrected by an error-correction decoder, it is impossible to detect degradation without detecting the raw error rate or raw error number. The raw error can be detected with a standard test drive. The quality of the disk can be specified as the number of erroneous inner-parity detections with DVD-R, DVD-RW, +R and +RW disks. The quality of a DVD-RAM disk is defined instead by its byte error rate. Deterioration can be monitored by checking the raw error numbers and continues to be monitored. Methods described in this document define a quality-control policy that can non-destructively identify degradation, and thereby support timely and effective corrective action.

DVD-R, DVD-RW, DVD-RAM, +R and +RW disks are based on the technology now widely known as DVD in the market. This entails the use of red laser diodes, two 0,6-mm thick substrates bonded together by an adhesive layer to protect the recording layer from dust, write-once (DVD-R, +R) or phase-change recording layers (DVD-RW, DVD-RAM, +RW) and a 0,60 or 0,65 NA objective lens to ensure good spatial margins required for a professional data preservation. Disks having dual recording layers with a spacer between them are used in addition to those with a conventional single recording layer.

After the issuance of the previous edition of this document, ISO/IEC standards for the physical format of BD Recordable and Rewritable disks were published in 2013. ISO/IEC 16963 was also updated to include testing of BD Recordable and Rewritable disks in 2015. Accordingly, ISO/IEC JTC 1/SC 23 started work to include BD Recordable and Rewritable disks in this document and held joint discussions with Ecma International TC31. The BD data migration part of this work was standardized separately by Ecma International as ECMA-413, along with contributions from the Japanese national committee of SC 23. CD-R and CD-RW disks included in ISO/IEC 16963 are also incorporated.

ISO/IEC 16963 was initially listed as a normative reference in this document to introduce the lifetime estimation method. However, as the application of this method is strongly recommended as opposed to required, ISO/IEC 16963 was moved from the Normative references clause to the Bibliography for conformance with the ISO/IEC Directives Part 2.

Information technology — Digitally recorded media for information interchange and storage — Data migration method for optical disks for long-term data storage

1 Scope

This document specifies the data migration method for DVD-R, DVD-RW, DVD-RAM, +R, +RW, CD-R, CD-RW, BD Recordable and BD Rewritable disks for long-term data storage. By applying this document for information storage, digital data can be migrated to a next new disk without loss from the present disk as long as data errors are completely corrected before and during the migration and provided copying of the data is allowed.

This document specifies:

- a data migration method for long-term data storage;
- test methods including test parameters, test area, test drive, disk preparation and test execution;
- an initial performance test and a periodic performance test that check a readability of the data recorded on the disks with categorized Maximum Data Error tables; and
- a necessity of precaution to reduce the possibility of deterioration in order to assure the integrity of the disks during their use, storage, handling or transportation.

This document offers guidelines to use disks with estimated lifetime of B_{mig} ($B_{0,000\ 1}$) Life which is introduced using B_5 Life and B_{50} Life specified in ISO/IEC 16963.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 12862, *Information technology — 120 mm (8,54 Gbytes per side) and 80 mm (2,66 Gbytes per side) DVD recordable disk for dual layer (DVD-R for DL)*

ISO/IEC 13170, *Information technology — 120 mm (8,54 Gbytes per side) and 80 mm (2,66 Gbytes per side) DVD re-recordable disk for dual layer (DVD-RW for DL)*

ISO/IEC 17341, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +RW format — Capacity: 4,7 Gbytes and 1,46 Gbytes per side (recording speed up to 4X)*

ISO/IEC 17342, *Information technology — 80 mm (1,46 Gbytes per side) and 120 mm (4,70 Gbytes per side) DVD re-recordable disk (DVD-RW)*

ISO/IEC 17344, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +R format — Capacity: 4,7 Gbytes and 1,46 Gbytes per side (recording speed up to 16X)*

ISO/IEC 17592, *Information technology — 120 mm (4,7 Gbytes per side) and 80 mm (1,46 Gbytes per side) DVD rewritable disk (DVD-RAM)*

ISO/IEC 23912, *Information technology — 80 mm (1,46 Gbytes per side) and 120 mm (4,70 Gbytes per side) DVD Recordable Disk (DVD-R)*

ISO/IEC 25434, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +R DL format — Capacity: 8,55 Gbytes and 2,66 Gbytes per side (recording speed up to 16X)*

ISO/IEC 26925, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +RW HS format — Capacity: 4,7 Gbytes and 1,46 Gbytes per side (recording speed 8X)*

ISO/IEC 29642, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +RW DL format — Capacity: 8,55 Gbytes and 2,66 Gbytes per side (recording speed 2,4X)*

ISO/IEC 30190:2016, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Recordable disk*

ISO/IEC 30191:2015, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes single sided disk and 200,0 Gbytes double sided disk) and Quadruple Layer (128,0 Gbytes single sided disk) BD Recordable disk*

ISO/IEC 30192, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Rewritable disk*

ISO/IEC 30193, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes per disk) BD Rewritable disk*

ECMA-394, *Recordable Compact Disc Systems CD-R Multi-Speed*

ECMA-395, *Recordable Compact Disc Systems CD-RW Ultra-Speed*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

B_{mig} Life

B_{mig}

lifetime (3.9) for use of *data migration* (3.5) and identical to $B_{0,000\ 1}$ Life which is 0,000 001 quantile of the lifetime distribution (i.e. 0,000 1 % failure time) or 99,999 9 % survival lifetime

Note 1 to entry: See [Annex E](#).

3.2

B_5 Life

5 percentile of the *lifetime* (3.9) distribution (i.e. 5 % failure time) or 95 % survival lifetime

[SOURCE: ISO/IEC 16963:2017, 3.4]

3.3

$(B_5 \text{ Life})_L$

95 % lower confidence bound of B_5 Life

[SOURCE: ISO/IEC 16963:2017, 3.5]

3.4

B_{50} Life

50 percentile of the *lifetime* (3.9) distribution (i.e. 50 % failure time) or 50 % survival lifetime

[SOURCE: ISO/IEC 16963:2017, 3.6]