# TECHNICAL SPECIFICATION

ISO/TS 17165-2

Second edition 2018-04

# Hydraulic fluid power — Hose assemblies —

Part 2:

# Practices for hydraulic hose assemblies

Transmissions hydrauliques — Flexibles de raccordement — Partie 2: Pratiques pour les flexibles de raccordement hydrauliques





© ISO 2018

Nementation, no par hanical, includin requested fir All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Co	ntent	S	Page
Fore	eword		<b>v</b>
Intr	oductio	n	vi
1	Scop	e	1
2	<.O	native references	
3		s and definitions	
4		y considerations	
•	4.1	General	
	4.2	Fluid injections	
	4.3	Whipping hoses	
	4.4	Burns from conveyed fluids	
	4.5	Fire and explosions from conveyed fluids	2
	4.6	Fire and explosions from static-electric discharge	
	4.7	Electrical shock	
	4.8	Mechanisms controlled by fluid power	3
5	Hose	selection and routing	3
	5.1	General	
	5.2	System pressures	3
	5.3	Suction	
	5.4	External pressure	
	5.5	Temperature	3
	5.6	Permeation	4
	5.7	Compatibility between hose materials and system fluids	
	5.8	Environment	
	5.9	Static-electric discharge	5
	5.10	Sizing	5
	5.11	Unintended uses	5
	5.12	Specifications and standards	
	5.13	Unusual applications	5
	5.14	Hose assembly cleanliness	5
	5.15	Hose fittingsVibration	
	5.16		
	5.17	Hose cover protection	5
	5.18	External physical abuse Swivel hose fittings and connectors	6
	5.19 5.20	Rotary connectors	6
	5.21	Slings and clamps	
	5.22	Minimum bend radius	
	5.23	Elbows and connectors	
	5.24	Lengths	
	5.21	5.24.1 General	
		5.24.2 Motion absorption	
		5.24.3 Tolerances and machine motion	
		5.24.4 Change in hose length due to changes in pressure	
	5.25	Hose movement and bending	
6	Hose	assembly fabrication	10
	6.1	General	10
	6.2	Component inspection	
	6.3	Hose fitting parts	
	6.4	Compatibility between hose and hose fittings	
	6.5	Hose assembly equipment	
	6.6	Safety equipment	
	6.7	Condition of hose assembly parts	11

# ISO/TS 17165-2:2018(E)

	6.8 Cleanliness of hoses and hose assemblies	
	6.10 Assembly inspection	
	6.11 Marking	12
7	Hose installation and replacement	12
	7.1 General	12
	7.2 Pre-installation inspection	12
	7.3 Handling during installation	
	7.4 Twist angle and orientation	
	7.5 Securing and protection	
	7.6 Routing	
	7.7 Assembly torque	
	7.8 System checkouts	13
8	Maintenance inspection	
	8.1 General	13
	8.2 Inspection frequency	
	8.3 Visual inspection (hose and hose fittings)	
	8.4 Visual inspection (all other components in the system)	14
	8.5 Functional tests	
9	Storage	15
	9.1 General	15
	9.2 Age control	15
	9.2.1 Shelf life	
	9.2.2 Storage period	15
	9.3 Storage conditions	15
10	Identification statement (reference to this document)	17
Ann	ex A (informative) Examples of actual failure resulting from improper u	
Ribli	liography	20
	7	
		· ·
		CV
		0,
		`/_

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 4, *Connectors and similar products and components*.

This edition cancels and replaces the first edition (ISO/TS 17165-2:2013), which has been technically revised.

The main changes to the previous edition are:

— in 9.2.2, the shelf life of rubber hose in bulk form or hose assembly has been changed.

A list of all the parts in the ISO 17165 series can be found on the ISO website.

# Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit.

sit.

stween cc.
) and flexibic. To allow fluid flow between components, components are interconnected by piping, both rigid (tubes and tube connectors) and flexible (hose assemblies, which consist of hose and hose fittings).

# Hydraulic fluid power — Hose assemblies —

# Part 2:

# Practices for hydraulic hose assemblies

# 1 Scope

This document provides guidelines for selection, routing, fabrication, installation, replacement, maintenance and storage of hose and hose assemblies for hydraulic fluid power systems which are manufactured from hoses conforming to ISO 1436, ISO 3862, ISO 3949, ISO 4079 and ISO 11237, and hose fittings conforming to the ISO 12151 series.

NOTE 1 Many of these practices also can be suitable for use with other types of hoses and systems.

NOTE 2 Annex A lists examples of actual failure resulting from improper use of hydraulic hose and hose assemblies.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5598, Fluid power systems and components — Vocabulary

ISO 6605, Hydraulic fluid power — Test methods for hoses and hose assemblies

ISO 8330, Rubber and plastics hoses and hose assemblies — Vocabulary

ISO 8331, Rubber and plastics hoses and hose assemblies — Guidelines for selection, storage, use and maintenance

ISO 17165-1, Hydraulic fluid power — Hose assemblies — Part 1: Dimensions and requirements

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598, ISO 8330 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>
- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>

### 3.1

#### manufacturing date of the hose assembly

date when hose and hose fittings were assembled into a hose assembly