

INTERNATIONAL STANDARD

IEC
62271-102

First edition
2001-12

High-voltage switchgear and controlgear –

Part 102:
Alternating current disconnectors
and earthing switches

Appareillage à haute tension –

Partie 102:
Sectionneurs et sectionneurs de terre
à courant alternatif



Reference number
IEC 62271-102:2001(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (http://www.iec.ch/searchpub/cur_fut.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (http://www.iec.ch/online_news/justpub/jp_entry.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC
62271-102

First edition
2001-12

High-voltage switchgear and controlgear –

Part 102: **Alternating current disconnectors** **and earthing switches**

Appareillage à haute tension –

Partie 102:
Sectionneurs et sectionneurs de terre
à courant alternatif

© IEC 2001 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

CONTENTS

FOREWORD	7
1 General	10
1.1 Scope	10
1.2 Normative references	10
2 Normal and special service conditions	11
3 Definitions	11
3.1 General terms	11
3.2 Assemblies of switchgear and controlgear	11
3.3 Parts of assemblies	11
3.4 Switching devices	11
3.5 Parts of switching devices	13
3.6 Operation	14
3.7 Characteristic quantities	15
4 Ratings	18
4.1 Rated voltage (U_r)	18
4.2 Rated insulation level	18
4.3 Rated frequency (f_r)	18
4.4 Rated normal current and temperature rise	18
4.5 Rated short-time withstand current (I_k)	19
4.6 Rated peak withstand current (I_p)	19
4.7 Rated duration of short-circuit (t_k)	19
4.8 Rated supply voltage of closing and opening devices and of auxiliary and control circuits (U_a)	19
4.9 Rated supply frequency of closing and opening devices and of auxiliary circuits	19
4.10 Rated pressure of compressed gas supply for insulation and/or operation	19
4.101 Rated short-circuit making current	19
4.102 Rated contact zone	19
4.103 Rated mechanical terminal load	20
4.104 Rated values of the bus-transfer current switching capability of disconnectors	21
4.105 Rated values of the induced current switching capability of earthing switches	21
4.106 Rated values of mechanical endurance for disconnectors and earthing switches	22
4.107 Rated values of electrical endurance for earthing switches	22
5 Design and construction	22
5.1 Requirements for liquids in disconnectors and earthing switches	22
5.2 Requirements for gases in disconnectors and earthing switches	22
5.3 Earthing of disconnectors and earthing switches	22
5.4 Auxiliary and control equipment	22
5.5 Dependent power operation	23
5.6 Stored energy operation	23

5.7	Independent manual operation.....	23
5.8	Operation of releases	23
5.9	Low- and high-pressure interlocking and monitoring devices.....	23
5.10	Nameplates	23
5.11	Interlocking devices	24
5.12	Position indication	24
5.13	Degree of protection by enclosures.....	24
5.14	Creepage distances	25
5.15	Gas and vacuum tightness.....	25
5.16	Liquid tightness	25
5.17	Flammability	25
5.18	Electromagnetic compatibility (EMC).....	25
5.101	Special requirements for earthing switches	25
5.102	Requirements in respect of the isolating distance of disconnectors	25
5.103	Mechanical strength.....	26
5.104	Operation of disconnectors and earthing switches– Position of the movable contact system and its indicating and signalling devices	26
5.105	Maximum force required for manual operation	27
5.106	Dimensional tolerances.....	27
6	Type tests	27
6.1	General	27
6.2	Dielectric tests.....	28
6.3	Radio interference voltage (riv) test.....	30
6.4	Measurement of the resistance of circuits	30
6.5	Temperature-rise tests.....	31
6.6	Short-time withstand current and peak withstand current tests	31
6.7	Verification of the protection	33
6.8	Tightness tests	33
6.9	Electromagnetic compatibility tests (EMC).....	33
6.101	Test to prove the short-circuit making performance of earthing switches.....	33
6.102	Operating and mechanical endurance tests	34
6.103	Operation under severe ice conditions	37
6.104	Operation at the temperature limits.....	39
6.105	Test to verify the proper functioning of the position indicating device	40
6.106	Bus-transfer current switching tests	40
6.107	Induced current switching tests.....	40
6.108	Bus-charging switching tests	41
7	Routine tests	41
7.1	Dielectric test on the main circuit	41
7.2	Dielectric test on auxiliary and control circuits	41
7.3	Measurement of the resistance of the main circuit	42
7.4	Tightness test.....	42
7.5	Design and visual checks	42
7.101	Mechanical operating tests	42

8	Guide to the selection of disconnectors and earthing switches.....	42
8.101	General	42
8.102	Selection of rated values for normal service conditions	43
9	Information to be given with enquiries, tenders and orders	46
9.101	Information to be given with enquiries and orders	46
9.102	Information to be given with tenders	47
10	Rules for transport, storage, installation, operation and maintenance	48
10.1	Conditions during transport, storage and installation.....	48
10.2	Installation.....	49
10.3	Operation	49
10.4	Maintenance.....	49
11	Safety.....	49
11.1	Electrical aspects	49
11.2	Mechanical aspects	49
11.3	Thermal aspects.....	49
11.4	Operation aspects	49
Annex A (normative)	Design and testing of position indicating devices.....	56
A.1	General	56
A.2	Normal and special service conditions	56
A.3	Definitions	56
A.4	Ratings	57
A.5	Design and construction	57
A.6	Type tests.....	57
A.7	Routine tests	60
Annex B (normative)	Bus-transfer current switching by disconnectors.....	61
B.1	General	61
B.2	Normal and special service conditions	61
B.3	Definitions	61
B.4	Ratings	61
B.5	Design and construction	62
B.6	Type tests.....	62
Annex C (normative)	Induced current switching by earthing switches.....	67
C.1	General	67
C.2	Normal and special service conditions	67
C.3	Definitions	67
C.4	Ratings	68
C.5	Design and construction	69
C.6	Type tests.....	70

Annex D (informative) Test voltage for the most disadvantageous dielectric position of an earthing switch during operation (temporary approach)	77
Annex E (normative) Special requirements for disconnectors and earthing switches used in gas-insulated and/or metal-enclosed switchgear	78
E.1 General	78
E.2 Normal and special service conditions	78
E.3 Definitions	78
E.4 Ratings	79
E.5 Design and construction	79
E.6 Type tests	80
E.7 Routine tests	81
E.8 Guide to the selection of disconnectors and earthing switches	82
E.9 Information to be given with enquiries, tenders and orders	82
E.10 Rules for transport, storage, installation, operation and maintenance	82
Annex F (normative) Gas-insulated metal-enclosed switchgear for rated voltages 72,5 kV and above – Requirements for switching of bus-charging currents by disconnectors	83
F.1 General	83
F.2 Normal and special service conditions	83
F.3 Definitions	83
Figure 1 – Fixed contact parallel to support	50
Figure 2 – Fixed contact (as indicated in figure 8) perpendicular to support	50
Figure 3 – Three-phase test arrangement for disconnectors and earthing switches with rated voltages below 52 kV	51
Figure 4 – Single-phase test arrangement for disconnectors with a horizontal isolating distance and for earthing switches with rated voltage of 52 kV and above	52
Figure 5 – Single-phase test arrangement for divided support disconnectors (earthing switches) with a vertical isolating distance with rated voltages of 52 kV and above to be used with flexible conductors	53
Figure 6 – Single-phase test arrangement for divided support disconnectors (earthing switches) with a vertical isolating distance with rated voltages of 52 kV and above to be used with rigid conductors	54
Figure 7 – Example of the application of rated mechanical terminal loads to a two-column disconnector	55
Figure 8 – Example of the application of rated mechanical terminal loads to a pantograph disconnector	55
Figure A.1 – Position indicating device	60
Figure B.1 – Test circuits for bus-transfer current making and breaking tests	66
Figure C.1 – Test circuit for electromagnetically induced current making and breaking tests	75
Figure C.2 – Test circuits for electrostatically induced current making and breaking tests	76

Figure F.1 – Test circuit for test duty 1.....	85
Figure F.2 – Typical voltage waveform (Including VFT and FT components)	86
Figure F.3 – Test circuit for test duty 2.....	87
Figure F.4 –Test circuit for test duty 3.....	88
Table 1 – Recommended contact zones for "fixed" contacts supported by flexible conductors.....	20
Table 2 – Recommended contact zones for "fixed" contacts supported by rigid conductors.....	20
Table 3 – Recommended static mechanical terminal loads.....	21
Table 3a – Classification of disconnectors for mechanical endurance	22
Table 4 – Nameplate information	24
Table 5 – Power frequency 1 min withstand voltages	30
Table 6 – Power frequency voltage tests.....	41
Table B.1 – Rated bus-transfer voltages for disconnectors.....	62
Table C.1 – Standardized values of rated induced currents and voltages for earthing switches.....	69
Table C.2 – Standardized values of recovery voltages for electromagnetically induced current breaking tests	72
Table C.3 – Test circuit capacitances (C_1 values) for electrostatically induced current making and breaking tests	73
Table F.1 – Test voltages for making and breaking tests.....	85
Table F.2 – Specified bus-charging currents	88
Table F.3 – Specified number of tests.....	89

This document is a preview generated by EVS

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –**Part 102: Alternating current disconnectors
and earthing switches**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organisation for standardisation comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardisation in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organisations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organisation for Standardisation (ISO) in accordance with conditions determined by agreement between the two organisations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this international standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62271-102 has been prepared by subcommittee 17A: High-voltage switchgear and controlgear, of IEC technical committee 17: Switchgear and controlgear.

This first edition cancels and replaces the third edition of IEC 60129 published in 1984, amendment 1 (1992) and amendment 2 (1996) and constitutes a technical revision. In addition, it replaces IEC 61128, IEC 61129 and IEC 61259, which are hereby withdrawn and cancelled. A reference table is provided at the end of this foreword.

The text of this standard is based on the following documents:

FDIS	Report on voting
17A/617/FDIS	17A/619/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

Annexes A, B, C, E and F form an integral part of this standard.

Annex D is for information only.

This standard should be read in conjunction with IEC 60694, second edition, published in 1996, to which it refers and which is applicable, unless otherwise specified. In order to simplify the indication of corresponding requirements, the same numbering of clauses and subclauses is used as in IEC 60694. Additional subclauses are numbered from 101.

The committee has decided that this publication remains valid until 2013. At this date, in accordance with the committee's decision, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

The contents of the corrigendum of April 2002 and May 2003 have been included in this copy.

New numbering

COMMON NUMBERING OF IEC 62271 PUBLICATIONS FALLING UNDER THE RESPONSIBILITY OF SUBCOMMITTEES SC 17A AND SC 17C

In accordance with the decision taken at the joint SC 17A/SC 17C meeting in Frankfurt, June 1998 (item 20.7 of 17A/535/RM), a common numbering system has been established for the publications falling under the responsibility of SC 17A and SC 17C. IEC 62271 - *High-voltage switchgear and controlgear* is the publication number and main title element for the common publications.

Numbering of these publications will apply the following principle:

- a) Common standards prepared by SC 17A and SC 17C will start with IEC 62271-1;
- b) Standards of SC 17A will start with IEC 62271-100;
- c) Standards of SC 17C will start with number IEC 62271-200;
- d) Publications prepared by SC 17A and SC 17C will start with number IEC 62271-300.

The table below relates the new numbers to the old numbers. The parts numbered (xxx) will be given a final number pending the decision to publish the revised publication as standard or technical report.

generated by EVS

**Common numbering of IEC 62271 publications falling under
the responsibility of subcommittees SC 17A and SC 17C**

IEC 62271	HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR -	Old IEC number, if any
Part	Title	
1	Common specifications	IEC 60694
2	Seismic qualification for rated voltages of 72,5 kV and above	-
100	High-voltage alternating current circuit-breakers	IEC 60056
101	Synthetic testing	IEC 60427
102	Alternating current disconnectors and earthing switches	IEC 60129
103	Switches for rated voltages above 1 kV and less than 52 kV	IEC 60265-1
104	Switches for rated voltages of 52 kV and above	IEC 60265-2
105	Alternating current switch-fuse combinations	IEC 60420
106	Alternating current contactors and contactor based motor-starters	IEC 60470
107	Alternating current switchgear-fuse combinations	-
108	Switchgear having combined functions	-
109	Series capacitor by-pass switches	-
200	Metal enclosed switchgear and controlgear for rated voltages up to and including 52 kV	IEC 60298
201	Insulation-enclosed switchgear and controlgear for rated voltages up to and including 52 kV	IEC 60466
202	High-voltage/low voltage prefabricated substations	IEC 61330
203	Gas-insulated metal enclosed switchgear for rated voltages above 52 kV	IEC 60517
204	High-voltage gas-insulated transmission lines for rated voltages of 72,5 kV and above	IEC 61640
(300)	Guide for seismic qualification of high-voltage alternating current circuit-breakers	IEC 61166
(301)	Guide for inductive load switching	IEC 61233
(302)	Guide for short-circuit and switching test procedures for metal-enclosed and dead tank circuit-breakers	IEC 61633
(303)	Use and handling of sulphur hexafluoride (SF ₆) in high-voltage switchgear and controlgear	IEC 61634
(304)	Additional requirements for enclosed switchgear and controlgear from 1 kV to 72,5 kV to be used in severe climatic conditions	IEC 60932
(305)	Cable connections for gas-insulated metal-enclosed switchgear for rated voltages above 52 kV	IEC 60859
(306)	Direct connection between power transformers and gas-insulated metal-enclosed switchgear for rated voltages above 52 kV	IEC 61639
(307)	The use of electronic and associated technologies in auxiliary equipment of switchgear and controlgear	IEC 62063
308	Guide for asymmetrical short-circuit breaking test duty T100a	
309	TRV parameters for high-voltage switchgear and controlgear for rated voltages above 1 kV and less than 100 kV	-
310	Electrical endurance testing for circuit-breakers rated 72,5 kV and above	-

High-voltage switchgear and controlgear –

Part 102: Alternating current disconnectors and earthing switches

1 General

1.1 Scope

This part of IEC 62271 applies to alternating current disconnectors and earthing switches, designed for indoor and outdoor enclosed and open terminal installations for voltages above 1 000 V and for service frequencies up to and including 60 Hz.

It also applies to the operating devices of these disconnectors and earthing switches and their auxiliary equipment.

Additional requirements for disconnectors and earthing switches in enclosed switchgear and controlgear are given in IEC 60298, IEC 60466 and IEC 60517.

NOTE Disconnectors in which the fuse forms an integral part are not covered by this standard.

1.2 Normative references

Subclause 1.2 of IEC 60694 is applicable with the following additions:

IEC 60137:1995, *Insulating bushings for alternating voltages above 1 000 V*

IEC 60265-1:1998, *High-voltage switches – Part 1: Switches for rated voltages above 1 kV and less than 52 kV*

IEC 60265-2:1988, *High-voltage switches – Part 2: High-voltage switches for rated voltages of 52 kV and above*

IEC 60298:1990, *A.C. metal-enclosed switchgear and controlgear for rated voltages above 1 kV and up to and including 52 kV*

IEC 60466:1987, *A.C. insulation-enclosed switchgear and controlgear for rated voltages above 1 kV and up to and including 38 kV*

IEC 60517:1990, *Gas-insulated metal-enclosed switchgear for rated voltages of 72,5 kV and above*

IEC 60694:1996, *Common specifications for high-voltage switchgear and controlgear standards*

IEC 60865-1:1993, *Short-circuit currents – Calculation of effects – Part 1: Definitions and calculation methods*

ISO 2768-1:1989, *General tolerances – Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*