INTERNATIONAL STANDARD

ISO 9964-2

> First edition 1993-05-01

Water quality — Determination of sodium and potassium —

Part 2:

Determination of potassium by atomic absorption spectrometry

Qualité de l'eau — Dosage du sodium et du potassium — Partie 2: Dosage du potassium par spectrométrie d'absorption atomique



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards of Dodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 9964-2 was prepared by Technical Committee ISO/TC 147, Water quality, Sub-Committee SC 2, Physical, chemical, biochemical methods.

ISO 9964 consists of the following parts, under the general title Water quality — Determination of sodium and potassium:

- Part 1: Determination of sodium by atomic absorption spectrometry
- Part 2: Determination of potassium by atomic absorption spetrometry
- Part 3: Determination of sodium and potassium by flame emission spectrometry

© ISO 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Water quality — Determination of sodium and potassium

Part 2:

Determination oppotassium by atomic absorption spectrometry

1 Scope

1.1 Field of application

This International Standard specifies a method for the determination of dissolved potassium by flame atomic absorption spectrometry (AAS). It is intended for the analysis of raw and drinking waters.

The method is applicable to water samples with a mass concentration of potassium in the range from 5 mg/l to 50 mg/l. This range can be extended to lower or higher limits if dilution factors are chosen which are different from the factor specified in clause 8.

1.2 Interferences

The ions normally present in raw and drinking waters do not interfere with the determination of potassium by atomic absorption spectrometry.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 9964. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 9964 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 5667-1:1980, Water quality — Sampling — Part 1: Guidance on the design of sampling programmes.

ISO 5667-2:1991, Water quality — Sampling — Part 2: Guidance on sampling techniques.

Principle

Addition of caesium chloride solution to the sample as a conization suppressant. Aspiration of the sample directly into the air/acetylene flame of an atomic absorption spectrometer. Measurement of the absorbance at a wavelength of 766,5 nm.

4 Reagent

During the analysis, use only reagents of recognized analytical grade and only deionized water or water of equivalent purity.

- **4.1** Hydrochloric acid, ϵ (HGI) \approx 11 mol/l, ρ = 1,18 g/ml.
- **4.2** Nitric acid, $c(HNO_3) \approx 16 \text{ mol/l}$, $\rho = 1.41 \text{ g/ml}$.
- 4.3 Caesium chloride, (CsCl), solution.

Dissolve 25 g of caesium chloride in a solution of 50 ml of hydrochloric acid (4.1) and 450 ml of water, and dilute to 1 litre with water in a one-mark volumetric flask.

One litre of this solution contains approximately 20 g of Cs.