INTERNATIONAL STANDARD

IEC 61097-6

Second edition 2005-12

Global maritime distress and safety system (GMDSS) –

Part 6:

Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)



Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

IEC Web Site (www.iec.ch)

Catalogue of IEC publications

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

IEC Just Published

This summary of recently issued publications (www.iec.ch/online news/ justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch Tel: +41 22 919 02 11 Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 61097-6

Second edition 2005-12

Global maritime distress and safety system (GMDSS) –

Part 6:

Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



PRICE CODE



CONTENTS

FO	FOREWORD4						
INTRODUCTION7							
1	Scop	e	8				
2	Norm	ative references	8				
3		itions and abbreviations					
Ü	3.1	Definitions					
	3.2	Abbreviations					
4		rmance requirements					
7	4.1	General					
	4.1	General characteristics					
	4.2	Specific characteristics					
	4.4	Interfaces					
	4.4	Receiver					
	4.6	Display	14				
	4.7	Integral printer					
	4.7	NAVTEX message memory					
	4.9	Power supplies					
	4.10	Source of UTC					
5		conditions					
5		General					
	5.1						
	5.2	Performance test					
	5.3	Performance check					
	5.4	Normal and extreme conditions					
	5.5	Standard test signal					
	5.6	Standard test file					
	5.7	Arrangement for test signal applied to the receiver input					
	5.8	Artificial antennas					
	5.9	Measurement uncertainty					
	5.10	Interpretations of measurement results					
	5.11	Conducted and radiated RF immunity tests exclusion bands Narrow band responses on receivers	.22				
•							
6		onmental tests required					
7	Seria	I interface tests	.23				
	7.1	INS input electrical tests					
	7.2	INS input performance tests	23				
	7.3	INS output electrical tests	23				
	7.4	INS output performance tests	23				
	7.5	Printer output electrical tests	23				
	7.6	Printer output performance tests	24				
8	Gene	ral and signal processing tests	24				
	8.1	Exclusion of stations	24				
	8.2	Exclusion of message categories	24				
	8.3	Receiver test facility	25				
	8.4	Search and rescue (SAR) alarm provision and reset	25				
	8.5	Additional alarms	25				

9	Rece	iver tests	25
	9.1	Call sensitivity	26
	9.2	Interference rejection and blocking immunity	26
	9.3	Co-channel rejection	27
	9.4	Intermodulation	27
	9.5	Off-frequency transmitter	28
	9.6	Simultaneous operation on several receive frequencies	28
	9.7	Protection of input circuits	28
10	Printer tests		
	10.1	Basic requirements	29
	10.2	Paper roll end alarm and storage inhibition	29
	10.3	Automatic line feed indication and paper feed	29
	10.4	Mutilated character indication	30
		Tests of technical characteristics (ITU-R Recommendation M.540)	
11	Mem	ory tests	31
	11.1	Internal storage, message tagging and erasure of oldest message identifications	31
	11.2	Erasure of message identifications/storage time	32
	11.3	Storage of message identifications	33
	11.4	Reception of messages with character errors	33
		Unsatisfactory reception	
		Power-off check	
	11.7	Brown-out test	35
		UTC handling check	
12			
	12.1	Spurious emissions	36
		Equipment manuals – checks of the manufacturer's documentation	
	12.3	Marking and identification	36
		(informative) Block diagrams of NAVTEX systems	
		(normative) Definition of satisfactory reception of a message	
Anı	nex C	(informative) IEC 61162 sentences for NAVTEX operation	40
		(normative) Manufacturer's declarations/equipment manual	
Fig	ure A.	1 – EUT with an integral printing device	37
		2 – EUT with an integral display device	
Fig	ure A.	3 – EUT black box receiver	
Tab	le 1 -	- Alarm conditions signaled using the ALR sentence formatter	13
		- Extreme power supply variation	
		- Unwanted signal levels	
		- Intermodulation frequency pairs	
ıaı	/IC 1 -	micrimodulation nequency pairs	27

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) -

Part 6: Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international
 consensus of opinion on the relevant subjects since each technical committee has representation from all
 interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61097-6 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This second edition cancels and replaces the first edition published in 1995. This edition constitutes a technical revision. This edition includes the following significant technical changes with respect to the previous edition:

- insertion of requirements and tests for memory within the NAVTEX;
- insertion of requirements and test for interfaces;
- improved receiver performance.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/419/FDIS	80/424/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 61097 consists of the following parts under the general title *Global maritime distress and safety system (GMDSS)*:

- Part 1: Radar transponder Marine search and rescue (SART) Operational and performance requirements, methods of testing and required test results
- Part 2: COSPAS-SARSAT EPIRB Satellite emergency position indicating radio beacon operating on 406 MHz Operational and performance requirements, methods of testing and required test results
- Part 3: Digital selective calling (DSC) equipment Operational and performance requirements, methods of testing and required testing results
- Part 4: INMARSAT-C ship earth station and INMARSAT enhanced group call (EGC) equipment Operational and performance requirements, methods of testing and required test results
- Part 5: Inmarsat-E Emergency position indicating radio beacon (EPIRB) operating through the Inmarsat system Operational and performance requirements, methods of testing and required test results
- Part 6: Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)
- Part 7: Shipborne VHF radiotelephone transmitter and receiver Operational and performance requirements, methods of testing and required test results
- Part 8: Shipborne watchkeeping receivers for the reception of digital selective calling (DSC) in the maritime MF, MF/HF and VHF bands Operational and performance requirements, methods of testing and required test results
- Part 9: Shipborne transmitters and receivers for use in the MF and HF bands suitable for telephony, digital selective calling (DSC) and narrow band direct printing (NBDP) Operational and performance requirements, methods of testing and required test results
- Part 10: Inmarsat-B ship earth station equipment Operational and performance requirements, methods of testing and required test results
- Part 12: Survival craft portable two-way VHF radiotelephone apparatus Operational and performance requirements, methods of testing and required test results
- Part 13: Inmarsat F77 ship earth station equipment Operational and performance requirements, methods of testing and required test results

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be either

- reconfirmed.
- withdrawn,
- replaced by a revised edition, or
- amended.

of this allowants and the second seco A bilingual version of this standard may be issued at a later date.

INTRODUCTION

NAVTEX provides shipping with navigational and meteorological warnings and urgent information by automatic display and/or print out from a dedicated receiver.

NAVTEX is a component of the IMO/IHO World-Wide Navigational Warning Service (WWNWS) defined by IMO Assembly Resolution A.706(17), as amended, and the WMO Manual on Marine Meteorological Services, Part Ibis, Provision of warnings and weather and sea bulletins (GMDSS application). It has been included as an element of the Global Maritime Distress and Safety System (GMDSS).

The original NAVTEX specification allowed for equipment with integral printers and precluded the fitting of equipment which relied on other ways of recording and displaying NAVTEX data. The use of Liquid Crystal Displays and other Visual Display Units is now ubiquitous on ships' bridges and this revision of the specification allows for their use in displaying NAVTEX data.

As a result of the final cessation of the distresss watch on 500 kHz in 1999 the frequency 490 kHz became available for use as a national NAVTEX channel and this has now been widely implemented around the world. This NAVTEX specification therefore requires simultaneous operation on an additional channel to the international channel of 518 kHz.

IMO Resolution MSC.148(77) states that the equipment should comprise radio receivers, a signal processor and:

- a) an integrated printing device; or
- b) a dedicated display device, printer output port and a non-volatile message memory; or
- c) a connection to an integrated navigation system and a non-volatile message memory.

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) -

Part 6: Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)

1 Scope

This part of IEC 61097 specifies the minimum performance requirements, technical characteristics and type-testing requirements for narrowband telegraph equipment for the reception of navigational and meteorological information as required by Regulation IV/7.1.4 of the 1988 amendments to the 1974 International Convention for Safety of Life at Sea (SOLAS), and which is associated with IEC 60945. When a requirement in this standard is different from IEC 60945, the requirement in this standard takes precedence.

This standard incorporates the performance standards of IMO Resolution MSC.148(77), the technical characteristics of ITU-R Recommendation M.540, takes account of the IMO Resolution A.694(17) and conforms with the ITU Radio Regulations where applicable.

All text of this standard, whose meaning is identical to that in IMO Resolution MSC.148(77) and ITU-R Recommendation M.540 will be printed in *italics* and the Resolution/Recommendation and paragraph number indicated between brackets.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, Marine navigation and radio communication equipment – General requirements – Methods of testing and required test results

IEC 61162-1, Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners

IEC 61162-2; Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission

IMO Safety of Life at Sea (SOLAS) Convention (1974), as amended (GMDSS)

IMO Resolution A.694(17) (1991) General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids

IMO Resolution MSC.148(77) (2003) Revised performance standards for narrow-band direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)

IMO Publication - NAVTEX Manual

IMO Resolution MSC/Circ.1122 Adoption of the revised NAVTEX manual

ITU-R Recommendation M.540-2:1990, Operational and technical characteristics for an automated direct printing telegraph system for promulgation of navigational and meteorological warnings and urgent information to ships

ITU-R Recommendation M.625-3:1995, Direct-printing telegraph equipment employing automatic identification in the maritime mobile service

Definitions and abbreviations

For the purposes of this document, the following definitions and abbreviations apply.

3.1 **Definitions**

3.1.1

LORAN-C

long range radio-navigation system operating on an assigned frequency of 100 kHz

3.1.2

NAVTEX

system for the broadcast and automatic reception of maritime safety information by means of narrow-band telegraphy

3.1.3

Test script

text file containing a number of NAVTEX messages formatted as defined in 5.5. The STF is a particular example of a test script

Abbreviations 3.2

ASCII	American Standard Code for Information Interchange
CER	character error rate
EMC	electromagnetic compatibility
EUT	equipment under test
НМІ	human-machine interface
INS	integrated navigation system
IMO	International Maritime Organization
ITU	International Telecommunication Union
PC	performance check
PT	performance test
RTC	real time clock
SAR	search and rescue
STF	standard test file
STS	standard test signal
USB	Universal Serial Bus
UTC	Co-ordinated Universal Time
	0,