

**Fibre optic communication subsystem test procedures -
Part 2-2: Digital systems - Optical eye pattern, waveform
and extinction ratio measurement (IEC 61280-2-2:2012)**

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 61280-2-2:2012 sisaldab Euroopa standardi EN 61280-2-2:2012 ingliskeelset teksti.	This Estonian standard EVS-EN 61280-2-2:2012 consists of the English text of the European standard EN 61280-2-2:2012.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 14.12.2012.	Date of Availability of the European standard is 14.12.2012.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 33.180.01

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

English version

**Fibre optic communication subsystem test procedures -
Part 2-2: Digital systems -
Optical eye pattern, waveform and extinction ratio measurement
(IEC 61280-2-2:2012)**

Procédures d'essai des sous-systèmes
de télécommunications à fibres optiques -
Partie 2-2: Systèmes numériques -
Mesure du diagramme de l'œil optique,
de la forme d'onde et du taux d'extinction
(CEI 61280-2-2:2012)

Prüfverfahren für Lichtwellenleiter-
Kommunikationsundersysteme -
Teil 2-2: Digitale Systeme -
Messung des optischen
Augendiagramms, der Wellenform
und des Extinktionsverhältnisses
(IEC 61280-2-2:2012)

This European Standard was approved by CENELEC on 2012-11-29. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 86C/1043/CDV, future edition 4 of IEC 61280-2-2, prepared by SC 86C "Fibre optic systems and active devices" of IEC/TC 86 "Fibre optics" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61280-2-2:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2013-08-29
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-11-29

This document supersedes EN 61280-2-2:2008.

EN 61280-2-2:2012 includes the following significant technical changes with respect to EN 61280-2-2:2008:

- additional definitions;
- clarification of test procedures.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61280-2-2:2012 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60825-1	NOTE	Harmonised as EN 60825-1.
IEC 61281-1	NOTE	Harmonised as EN 61281-1.

Annex ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61280-2-3	-	Fibre optic communication subsystem test procedures - Part 2-3: Digital systems - Jitter and wander measurements	EN 61280-2-3	-

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Apparatus.....	7
4.1 General.....	7
4.2 Reference receiver definition.....	8
4.3 Time-domain optical detection system	8
4.3.1 Overview	8
4.3.2 Optical-to-electrical (O/E) converter.....	9
4.3.3 Linear-phase low-pass filter.....	9
4.3.4 Oscilloscope.....	10
4.4 Overall system response	11
4.5 Oscilloscope synchronization system.....	11
4.5.1 General	11
4.5.2 Triggering with a clean clock	12
4.5.3 Triggering using a recovered clock	12
4.5.4 Triggering directly on data	13
4.6 Pattern generator	14
4.7 Optical power meter	14
4.8 Optical attenuator.....	14
4.9 Test cord.....	14
5 Signal under test	14
6 Instrument set-up and device under test set-up	14
7 Measurement procedures	15
7.1 Overview	15
7.2 Extinction ratio measurement	15
7.2.1 Configure the test equipment.....	15
7.2.2 Measurement procedure.....	15
7.2.3 Extinction ratio calculation	16
7.3 Eye amplitude	17
7.4 Optical modulation amplitude (OMA) measurement using the square wave method.....	17
7.4.1 General	17
7.4.2 Oscilloscope triggering	17
7.4.3 Amplitude histogram, step 1	17
7.4.4 Amplitude histogram, step 2	18
7.4.5 Calculate OMA	18
7.5 Contrast ratio (for RZ signals)	18
7.6 Jitter measurements	18
7.7 Eye width	19
7.8 Duty cycle distortion (DCD)	19
7.9 Crossing percentage	20
7.10 Eye height.....	21

7.11	Q-factor/signal-to-noise ratio (SNR).....	21
7.12	Rise time.....	21
7.13	Fall time	22
8	Eye-diagram analysis using a mask.....	23
8.1	Eye mask testing using the 'no hits' technique.....	23
8.2	Eye mask testing using the 'hit-ratio' technique	24
9	Test result	26
9.1	Required information	26
9.2	Available information	26
9.3	Specification information	26
	Bibliography.....	27

Figure 1	– Optical eye pattern, waveform and extinction ratio measurement configuration.....	8
Figure 2	– Oscilloscope bandwidths commonly used in eye pattern measurements.....	10
Figure 3	– PLL jitter transfer function and resulting observed jitter transfer function.....	13
Figure 4	– Histograms centred in the central 20 % of the eye used to determine the mean logic one and 0 levels, b_1 and b_0	16
Figure 5	– OMA measurement using the square wave method	18
Figure 6	– Construction of the duty cycle distortion measurement.....	20
Figure 7	– Construction of the crossing percentage measurement	21
Figure 8	– Construction of the risetime measurement with no reference receiver filtering	22
Figure 9	– Illustrations of several RZ eye-diagram parameters.....	23
Figure 10	– Basic eye mask and coordinate system.....	24
Figure 11	– Mask margins at different sample population sizes.....	26
Table 1	– Frequency response characteristics	11

FIBRE OPTIC COMMUNICATION SUBSYSTEM TEST PROCEDURES –

Part 2-2: Digital systems – Optical eye pattern, waveform and extinction ratio measurement

1 Scope

The purpose of this part of IEC 61280 is to describe a test procedure to verify compliance with a predetermined waveform mask and to measure the eye pattern and waveform parameters such as rise time, fall time, modulation amplitude and extinction ratio.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61280-2-3, *Fibre optic communication subsystem test procedures – Part 2-3: Digital systems – Jitter and wander measurements*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

amplitude histogram

graphical means to display the power or voltage population distribution of a waveform

3.2

contrast ratio

ratio of the nominal peak amplitude to the nominal minimum amplitude of two adjacent logical '1's when using return-to-zero transmission

3.3

duty cycle distortion

DCD

measure of the balance of the time width of a logical 1 bit to the width of a logical 0 bit, indicated by the time between the eye diagram nominal rising edge at the average or 50 % level and the eye diagram nominal falling edge at the average or 50 % level

3.4

extinction ratio

ratio of the nominal 1 level to the nominal 0 level of the eye diagram

3.5

eye diagram

type of waveform display that exhibits the overall performance of a digital signal by superimposing all the acquired samples on a common time axis one unit interval in width