# INTERNATIONAL STANDARD

ISO 10791-6

First edition 1998-07-01

# Test conditions for machining centres — Part 6:

Accuracy of feeds, speeds and interpolations

Conditions d'essai pour centres d'usinage —

Partie 6: Précision des avances, vitesses et interpolations



Co	ntents	Page
4	Same 2	4
1	Scope	1
2	Normative references (n	1
3	Preliminary remarks	1
	3.1 Measuring units	1
	3.2 Reference to ISO 230-1	2
	~)	2
	3.4 Tests to be performed	2
	3.5 Measuring instruments	2
	3.6 Diagrams	2
4		2
	<b>4.1</b> Speeds (K 1) and feeds (K 2)	2
	<b>4.2</b> Linear interpolation (K 3)	2
	4.3 Circular interpolation (K 4)	2
	<ul><li>4.2 Linear interpolation (K 3)</li><li>4.3 Circular interpolation (K 4)</li><li>4.4 Angular interpolation (K 5)</li></ul>	3
	<b>4.5</b> Spherical interpolation of five axes (K 6)	3
Ann	ex A (informative) Bibliography	10
	,0	•
		0
		20
		Q <sub>X</sub>
		,0
		0,
		TO SPECIAL DE LET S
		0,

#### © ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote

International Standard ISO 10791-6 was prepared by Technical Committee ISO/TC 39, Wachine tools, Subcommittee SC 2, Test conditions for metal cutting machine tools.

ISO 10791 consists of the following parts, under the general title *Test* conditions for maching centres:

- Part 1: Geometric tests for machines with horizontal spindle and with accessory heads prizontal Z-axis)
- Part 2: Geometric tests for machines with vertical spindle or universal heads with vertical primary rotary axis (vertical Z-axis)
- Part 3: Geometric tests machines with integral indexable or continuous universal heads (vertical Z-axis)
- Part 4: Accuracy and repeatability of positioning of linear and rotary axes
- Part 5: Accuracy and repeatability of positioning of work-holding pallets
- Part 6: Accuracy of feeds, speeds and interpolations
- Part 7: Accuracy of a finished test piece
- Part 8: Evaluation of the contouring performance in the three coordinate planes
- Part 9: Evaluation of the operating times of tool change and pallet change
- Part 10: Evaluation of the thermal distortions
- Part 11: Evaluation of the noise emission
- Part 12: Evaluation of the vibration severity

Annex A of this part of ISO 10791 is for information only.

## Introduction

A machining centre is a pumerically controlled machine tool capable of performing multiple machining operations, including milling, boring, drilling and tapping, as well as automatic tool changing from a magazine or similar storage unit in accordance with a machining programme.

The object of ISO 10791 is to supply information as wide and comprehensive as possible on tests which can be carried out for comparison, acceptance, maintenance on any other purpose.

ISO 10791 specifies, with reference to the relevant parts of ISO 230, *Test code for machine tools*, several families of tests for machining centres with horizontal or vertical spindle or with universal heads of different types, standing alone or integrated in flexible manufacturing systems. ISO 10791 also establishes the tolerances or maximum acceptable values for the test results corresponding to general purpose and normal accuracy machining centres.

ISO 10791 is also applicable, totally or partially, to numerically controlled milling and boring machines, when their configuration, components and movements are compatible with the tests described herein.

## Test conditions for machining centres — Part 6:

Accuracy of feeds, speeds and interpolations

### 1 Scope

This part of ISO 10791 specifies, with reference to ISO 230-1, certain kinematic tests for machining centres, concerning the spindle speeds, the feeds of the individual NC linear axes and the accuracy of the paths described by the simultaneous movement of two or more NC linear and/or rotary axes (see clause 4).

### 2 Normative references

The following standards contain provisions which, though reference in this text, constitute provisions of this part of ISO 10791. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 10791 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid international Standards.

ISO 230-1:1996, Test code for machine tools — Part 1: Geometric accuracy of machines operating under no-load or finishing conditions.

ISO 230-4:1996, Test code for machine tools — Part 4: Circular tests for numerically controlled machine tools.

### 3 Preliminary remarks

### 3.1 Measuring units

In this part of ISO 10791, all linear dimensions, deviations and corresponding tolerances are expressed in millimetres; angular dimensions are expressed in degrees, and angular deviations and the corresponding tolerances are expressed in ratios but in some cases microradians or arc seconds may be used for clarification purposes. The equivalence of the following expressions should always be kept in mind:

$$0.010/1\ 000 = 10 \times 10^{-6} = 10\ \mu rad \approx 2''$$