
**Photography — Digital cameras —
Measuring low-light performance**

*Photographie — Caméras numériques — Mesurage des performances
dans des conditions de faible luminosité*



This document is a preview generated by ERS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions and setup	2
4.1 Test chart	2
4.1.1 Test chart and illumination	2
4.2 Camera settings	3
4.2.1 General	3
4.2.2 Test lenses	4
4.2.3 Auto focus	4
4.2.4 Quality and file type	4
4.2.5 ISO sensitivity setting	4
4.2.6 White balance	4
4.2.7 Flash	5
4.2.8 Noise reduction	5
4.2.9 Exposure mode	5
4.2.10 Scene and capture modes	5
4.3 Capturing a reference image	5
4.4 Capture of the test images	5
4.4.1 Illumination level	5
4.4.2 Best image selection	5
5 Camera performance aspects affected by low light	6
5.1 Exposure time	6
5.2 Exposure level	6
5.3 Noise	6
5.4 Texture (low-contrast fine detail)	6
5.5 Chroma decrease	7
6 Presentation of the results	8
Annex A (informative) Example for generating a single performance value from measured results	10
Annex B (normative) Test chart	12
Bibliography	19

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 42, *Photography*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The major engineering difference between a system camera, a point and shoot camera, and a camera in a mobile device is the sensor size. The sensor size is also related to the overall system size including the lens. With smaller sensors, the individual light sensitive areas are also smaller and therefore less light falls onto each of the pixels.

Smaller individual light sensitive areas require higher signal amplification that leads to higher noise levels or other problems that can occur due to denoising algorithms. These problems become more visible at low-light conditions because of the lower signal levels.

Most cameras are used without a tripod even at low-light conditions. At low light in combination with a tripod, the performance of a camera is always good because the sensitivity setting can be kept to a low value and the exposure time can be very long. For these reasons the low-light performance is measured using conditions that reflect the result of a handheld shot.

Sometimes the data sheets of a camera state a light level for the low-light performance of a camera. Prior to the creation of this document, the way to determine these values was not defined and therefore the values were unreliable to users.

Photography — Digital cameras — Measuring low-light performance

1 Scope

This document specifies a protocol to measure the low-light performance of a camera. It is applicable to the measurement of digital cameras including camera phones and other mobile devices.

The performance aspects defined in this document are intended to all be tested. Picking one or some of them by the tester is out of scope of the usage of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7589, *Photography — Illuminants for sensitometry — Specifications for daylight, incandescent tungsten and printer*

ISO 14524, *Photography — Electronic still-picture cameras — Methods for measuring opto-electronic conversion functions (OECFs)*

ISO 15739, *Photography — Electronic still-picture imaging — Noise measurements*

ISO/TS 19567-1, *Photography — Digital cameras — Texture reproduction measurements — Part 1: Frequency characteristics measurements using cyclic pattern*

IEC 61966-2-1, *Multimedia systems and equipment — Colour measurement and management — Part 2-1: Default RGB colour space — sRGB*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

handheld limit exposure time

exposure time empirically considered as an upper limit to give a reasonably sharp image with handheld shooting, which is $1/f$ s, where f is the value of the 35 mm sensor equivalent focal length of the lens

Note 1 to entry: If the camera has a mechanism for image stabilization, a longer exposure time than $1/f$ s for handheld shooting can still produce reasonably sharp images.

3.2

35 mm film equivalent focal length

focal length of a lens attached to a camera with a sensor size of 24 mm × 36 mm (originated from 35 mm film) that produces the same field of view as the camera system with a lens at a given focal length for which the 35 mm sensor equivalent focal length is specified