

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Medical electrical equipment – Part 1: General requirements for basic safety and essential performance

Appareils électromédicaux – Partie 1: Exigences générales pour la sécurité de base et les performances essentielles



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2005 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur. Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IFC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch Web: www.iec.ch

About the IFC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

IEC Just Published: www.iec.ch/online_news/justpub Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: <u>www.iec.ch/webstore/custserv</u>

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

Just Published CEI: <u>www.iec.ch/online_news/justpub</u>

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

Electropedia: <u>www.electropedia.org</u>

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.


Service Clients: <u>www.iec.ch/webstore/custserv/custserv_entry-f.htm</u>

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00





INTERNATIONAL STANDARD

NORME INTERNATIONALE

Medical electrical equipment -Part 1: General requirements for basic safety and essential performance

Appareils électromédicaux -Partie 1: Exigences générales pour la sécurité de base et les performances essentielles

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE



ICS 11.040

ISBN 2-8318-8400-4

Publication IEC 60601-1 (Third edition – 2005) I-SH 01

MEDICAL ELECTRICAL EQUIPMENT – Part 1: General requirements for basic safety and essential performance

INTERPRETATION SHEET 1

This interpretation sheet has been prepared by SC 62A: Common aspects of electrical equipment used in medical practice

The text of this interpretation sheet is based on the following documents:

ISH	Report on voting
62A/599/ISH	62A/613/RVD

Full information on the voting for the approval of this interpretation sheet can be found in the report on voting indicated in the above table.

Subclause 1.1

This subclause is clarified by the following:

IEC 60601-1 does not apply to medical gas pipeline systems covered by ISO 7396-1, *Medical gas pipeline systems — Part 1: Pipeline systems for compressed medical gases and vacuum.*

NOTE Subclause 6.3 of ISO 7396-1 applies the requirement of IEC 60601-1-8 to certain monitoring and alarm signals.

This clarification will remain valid until a new version of IEC 60601-1 is published.

April 2008

Publication IEC 60601-1 (Third edition – 2005) I-SH 02

- 1 -

MEDICAL ELECTRICAL EQUIPMENT –

Part 1: General requirements for basic safety and essential performance

INTERPRETATION SHEET 2

This interpretation sheet has been prepared by subcomittee 62A: Common aspects of electrical equipment used in medical practice, of IEC technical committee 62: Electrical equipment in medical practice.

The text of this interpretation sheet is based on the following documents:

ISH	Report on voting
62A/634/ISH	62A/640/RVD

Full information on the voting for the approval of this interpretation sheet can be found in the report on voting indicated in the above table.

Subclause 11.3

This subclause is clarified by the following:

As stated in the rationale for this subclause, fire ENCLOSURES are intended to be used only where there is a significant likelihood of fire due to the presence of a source of ignition (as described in the subclause) and a significant source of fuel. Most materials used in the construction of ME EQUIPMENT are not considered to be such a source of fuel unless they are in the presence of an OXYGEN RICH ENVIRONMENT. MANUFACTURERS should determine, through analyses documented in the RISK MANAGEMENT FILE, whether the ME EQUIPMENT contains combustible materials (fuel) in sufficient quantities to support combustion in conjunction with ignition sources (capable of releasing greater than 900 J).

Subclause 13.1.2

This subclause is clarified by the following:

As stated in subclause 4.7, it is the MANUFACTURER'S RISK ANALYSIS that determines which components are subject to failure testing based on the associated RISK. Where the associated RISK of fire exceeds the MANUFACTURER'S criteria for RISK acceptability, the MANUFACTURER'S simulation analysis (such as FMEAs) should be accepted in lieu of physical testing. As also stated in 4.7, component reliability and ratings are to be considered in such failure simulation analyses. Common electronic components that have a history of use without causing equipment fires should not be considered a likely source of ignition.

Where the subclause identifies "emission of flames, molten metal, poisonous or ignitable substance in hazardous quantities;" as a hazardous situation, this refers to emissions from *the ENCLOSURE* not from components themselves. Where it identifies "exceeding the allowable values for 'other components and materials' identified in Table 22 times 1,5 minus 12,5 °C", this applies only where doing so would result in an unacceptable RISK (as identified in the MANUFACTURER'S RISK ANALYSIS according to 4.7). Typically, this would be cases where

ESSENTIAL PERFORMANCE would not be maintained or where greater than 900 J of energy would be released in the presence of flammable materials that could sustain combustion.

The first exemption to fault analysis or testing identified in subclause 13.1.2 ("The construction or the supply circuit limits the power dissipation in SINGLE FAULT CONDITION to less than 15 W or the energy dissipation to less than 900 J.") is intended to apply where the component design itself ("The construction") or fusing (or other current limiting devices) in the supply circuit ("or the supply circuit") assure the energy released during failures will not mo, assed. exceed the limits. For most common signal level components rated for operation below 5 Watts, the energy released by short-circuiting of outputs will not exceed the 900 J limit.

This clarification will remain valid until a new version of IEC 60601-1 is published.

CONTENTS

FO	REWC)RD	.11
INT	RODU	JCTION	.13
	2.		
1	Scop	e, object and related standards	.15
	1.1	* Scope	.15
	1.2	Object	
	1.3	* Collateral standards	. 15
	1.4	* Particular standards	.16
2	* Nor	mative references	. 16
3	* Ter	minology and definitions	.20
4		ral requirements	
	4.1	* Conditions for application to ME EQUIPMENT OF ME SYSTEMS	
	4.2	* RISK MANAGEMENT PROCESS for ME EQUIPMENT OF ME SYSTEMS	
	4.3	* Essential performance	
	4.4	* Expected service life	
	4.5	* Equivalent safety for ME EQUIPMENT or ME SYSTEMS	
	4.6	* ME EQUIPMENT OF ME SYSTEM parts that contact the PATIENT	
	4.7	* SINGLE FAULT CONDITION FOR ME EQUIPMENT	
	4.8	Components of ME EQUIPMENT	.43
	4.9	* Use of COMPONENTS WITH HIGH-INTEGRITY CHARACTERISTICS in ME EQUIPMENT	
	4.10	* Power supply	.44
	4.11	Power input	.45
5	* Ger	neral requirements for testing ME EQUIPMENT	
	5.1	* TYPE TESTS	.46
	5.2	* Number of samples	.46
	5.3	Ambient temperature, humidity, atmospheric pressure	.46
	5.4	Other conditions	.46
	5.5	Supply voltages, type of current, nature of supply, frequency	.47
	5.6	Repairs and modifications	.47
	5.7	* Humidity preconditioning treatment	.47
	5.8	Sequence of tests	.48
	5.9	* Determination of APPLIED PARTS and ACCESSIBLE PARTS	.48
6	* Cla	ssification of ME EQUIPMENT and ME SYSTEMS	.50
	6.1	General	. 50
	6.2	* Protection against electric shock	.50
	6.3	* Protection against harmful ingress of water or particulate matter	51
	6.4	Method(s) of sterilization	51
	6.5	Suitability for use in an OXYGEN RICH ENVIRONMENT	51
	6.6	* Mode of operation	51
			2

7	ME E	QUIPMENT identification, marking and documents	51
	7.1	General	51
	7.2	Marking on the outside of ME EQUIPMENT or ME EQUIPMENT parts	53
	7.3	Marking on the inside of ME EQUIPMENT or ME EQUIPMENT parts	57
4	7.4	Marking of controls and instruments	59
	7.5	Safety signs	60
	7.6	Symbols	61
	7.7	Colours of the insulation of conductors	61
	7.8	* Indicator lights and controls	62
	7.9	ACCOMPANYING DOCUMENTS	62
8	* Pro	tection against electrical HAZARDS from ME EQUIPMENT	68
	8.1	Fundamental rule of protection against electric shock	68
	8.2	Requirements related to power sources	69
	8.3	Classification of APPLIED PARTS	69
	8.4	Limitation of voltage, current or energy	70
	8.5	Separation of parts	73
	8.6	* Protective earthing, functional earthing and potential equalization of	
		ME EQUIPMENT	
	8.7	LEAKAGE CURRENTS and PATIENT AUXILIARY CURRENTS	
	8.8	Insulation	
	8.9	* CREEPAGE DISTANCES and AIR CLEARANCES	
	8.10	Components and wiring	
-	8.11	MAINS PARTS, components and layout	
9		tection against MECHANICAL HAZARDS of ME EQUIPMENT and ME SYSTEMS	
	9.1	MECHANICAL HAZARDS OF ME EQUIPMENT	
	9.2	* HAZARDS associated with moving parts	
	9.3	* HAZARD associated with surfaces, corners and edges	
	9.4	* Instability HAZARDS	
	9.5	* Expelled parts HAZARD	
	9.6	Acoustic energy (including infra- and ultrasound) and vibration	
	9.7	* Pressure vessels and parts subject to pneumatic and hydraulic pressure	
	9.8	* HAZARDS associated with support systems	
10		tection against unwanted and excessive radiation HAZARDS	
		X-Radiation	
		Alpha, beta, gamma, neutron and other particle radiation	
		Microwave radiation	
		* Lasers and light emitting diodes (LEDs)	
		Other visible electromagnetic radiation	
		Infrared radiation	
		Ultraviolet radiation	
11	* Pro	tection against excessive temperatures and other HAZARDS	.153
		* Excessive temperatures in ME EQUIPMENT	
		* Fire prevention	
	11.3	* Constructional requirements for fire ENCLOSURES of ME EQUIPMENT	162

	11.4	* ME EQUIPMENT and ME SYSTEMS intended for use with flammable anaesthetics	165
	11.5	* ME EQUIPMENT and ME SYSTEMS intended for use in conjunction with flammable agents	165
	11.6	Overflow, spillage, leakage, ingress of water or particulate matter, cleaning, disinfection, sterilization and compatibility with substances used with the ME EQUIPMENT.	165
	117	Biocompatibility of ME EQUIPMENT and ME SYSTEMS	
		* Interruption of the power supply / SUPPLY MAINS to ME EQUIPMENT	
12		uracy of controls and instruments and protection against hazardous outputs	
12			
		Accuracy of controls and instruments	
		Alarm systems	
40		Protection against hazardous output	
13		ARDOUS SITUATIONS and fault conditions	
		Specific HAZARDOUS SITUATIONS	
		SINGLE FAULT CONDITIONS	
14		OGRAMMABLE ELECTRICAL MEDICAL SYSTEMS (PEMS)	
		* General	
		* Documentation	
		* RISK MANAGEMENT plan	
		* PEMS DEVELOPMENT LIFE-CYCLE	
		* Problem resolution	
		RISK MANAGEMENT PROCESS	
		* Requirement specification	
		* Architecture	
	14.9	* Design and implementation	179
		* VERIFICATION	
		* PEMS VALIDATION	
	14.12	2 * Modification	180
	14.13	⁸ * Connection of PEMS by NETWORK/DATA COUPLING to other equipment	180
15	Cons	truction of ME EQUIPMENT	180
	15.1	* Arrangements of controls and indicators of ME EQUIPMENT	180
	15.2	* Serviceability	180
	15.3	Mechanical strength	181
	15.4	ME EQUIPMENT components and general assembly	185
		* MAINS SUPPLY TRANSFORMERS of ME EQUIPMENT and transformers providing separation in accordance with 8.5	
16	* Me	SYSTEMS	
-		* General requirements for the ME SYSTEMS	
		* ACCOMPANYING DOCUMENTS OF AN ME SYSTEM	
		* Power supply	
	10.5		

16.8 Interruption of the power supply to parts of an ME SYSTEM	198
16.9 ME SYSTEM connections and wiring	
17 * Electromagnetic compatibility of ME EQUIPMENT and ME SYSTEMS	200
Annex A (informative) General guidance and rationale	201
Annex B (informative) Sequence of testing	307
Annex C (informative) Guide to marking and labelling requirements for ME EQUIPMENT and ME SYSTEMS	311
Annex D (informative) Symbols on marking	
Annex E (informative) Examples of the connection of the measuring device (MD) for	2.0.4
measurement of the PATIENT LEAKAGE CURRENT and PATIENT AUXILIARY CURRENT	
Annex F (informative) Suitable measuring supply circuits	326
Annex G (normative) Protection against HAZARDS of ignition of flammable anaesthetic mixtures	329
Annex H (informative) PEMS structure, PEMS DEVELOPMENT LIFE-CYCLE and documentation	211
Annex I (informative) ME SYSTEMS aspects	
Annex J (informative) Survey of insulation paths	
Annex K (informative) Simplified PATIENT LEAKAGE CURRENT diagrams	
Annex L (normative) Insulated winding wires for use without interleaved insulation	369
Bibliography	372
INDEX	
INDEX	375
2	
INDEX OF ABBREVIATIONS AND ACRONYMS	
Figure 1 – Detachable mains connection	2.2
Figure 2 – Example of the defined terminals and conductors	
Figure 3 – Example of a CLASS I ME EQUIPMENT.	24
Figure 4 – Example of a metal-enclosed CLASS II ME EQUIPMENT	
Figure 5 – Schematic flow chart for component qualification	
Figure 6 – Standard test finger	
Figure 7 – Test hook	
Figure 8 – Test pin	71
Figure 9 – Application of test voltage to bridged PATIENT CONNECTIONS for DEFIBRILLATION-PROOF APPLIED PARTS	78
Figure 10 – Application of test voltage to individual PATIENT CONNECTIONS for DEFIBRILLATION-PROOF APPLIED PARTS	
Figure 11 – Application of test voltage to test the delivered defibrillation energy	
	81

Figure 12 – Example of a measuring device and its frequency characteristics	85
Figure 13 – Measuring circuit for the EARTH LEAKAGE CURRENT of CLASS I ME equipment, with or without APPLIED PART	88
Figure 14 – Measuring circuit for the TOUCH CURRENT	89
Figure 15 – Measuring circuit for the PATIENT LEAKAGE CURRENT from the PATIENT CONNECTION to earth	90
Figure 16 – Measuring circuit for the PATIENT LEAKAGE CURRENT via the PATIENT CONNECTION(S) of an F-TYPE APPLIED PART to earth caused by an external voltage on the PATIENT CONNECTION(S)	91
Figure 17 – Measuring circuit for the PATIENT LEAKAGE CURRENT from PATIENT CONNECTION(S) to earth caused by an external voltage on a SIGNAL INPUT/OUTPUT PART	92
Figure 18 – Measuring circuit for the PATIENT LEAKAGE CURRENT from PATIENT CONNECTION(S) to earth caused by an external voltage on a metal ACCESSIBLE PART that is not PROTECTIVELY EARTHED	93
Figure 19 – Measuring circuit for the PATIENT AUXILIARY CURRENT	94
Figure 20 – Measuring circuit for the total PATIENT LEAKAGE CURRENT with all PATIENT CONNECTIONS of all APPLIED PARTS of the same type (TYPE B APPLIED PARTS, TYPE BF APPLIED PARTS or TYPE CF APPLIED PARTS) connected together	95
Figure 21 – Ball-pressure test apparatus	107
Figure 22 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 1	120
Figure 23 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 2	120
Figure 24 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 3	120
Figure 25 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 4	120
Figure 26 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 5	120
Figure 27 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 6	121
Figure 28 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 7	121
Figure 29 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 8	121
Figure 30 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 9	121
Figure 31 – CREEPAGE DISTANCE and AIR CLEARANCE – Example 10	122
Figure 32 – Ratio between HYDRAULIC TEST PRESSURE and MAXIMUM PERMISSIBLE WORKING PRESSURE	145
Figure 33 – Human body test mass	
Figure 34 – Spark ignition test apparatus	159
Figure 35 – Maximum allowable current <i>I</i> as a function of the maximum allowable voltage <i>U</i> measured in a purely resistive circuit in an OXYGEN RICH ENVIRONMENT	
Figure 36 – Maximum allowable voltage <i>U</i> as a function of the capacitance <i>C</i> measured in a capacitive circuit used in an OXYGEN RICH ENVIRONMENT	160
Figure 37 – Maximum allowable current <i>I</i> as a function of the inductance <i>L</i> measured in an inductive circuit in an OXYGEN RICH ENVIRONMENT	160
Figure 38 – Baffle	164
Figure 39 – Area of the bottom of an ENCLOSURE as specified in 11.3 b) 1)	164
Figure A.1 – Identification of ME EQUIPMENT, APPLIED PARTS and PATIENT CONNECTIONS in an ECG monitor	207

Figure A.2 – Example of the insulation of an F-TYPE APPLIED PART with the insulation incorporated in the ME EQUIPMENT	208
Figure A.3 – Identification of ME EQUIPMENT, APPLIED PARTS and PATIENT CONNECTIONS in a PATIENT monitor with invasive pressure monitoring facility	209
Figure A.4 – Identification of ME EQUIPMENT, APPLIED PARTS and PATIENT CONNECTIONS in a multifunction PATIENT monitor with invasive pressure monitoring facilities	210
Figure A.5 – Identification of APPLIED PARTS and PATIENT CONNECTIONS in an X-ray ME SYSTEM	211
Figure A.6 – Identification of ME EQUIPMENT, APPLIED PARTS and PATIENT CONNECTIONS in a transcutaneous electronic nerve stimulator (TENS) intended to be worn on the PATIENT'S belt and connected to electrodes applied to the PATIENT'S upper arm	211
Figure A.7 – Identification of ME EQUIPMENT or ME SYSTEM, APPLIED PARTS and PATIENT CONNECTIONS in a personal computer with an ECG module	212
Figure A.8 – Pictorial representation of the relationship of HAZARD, sequence of events, HAZARDOUS SITUATION and HARM	215
Figure A.9 – Example of PATIENT ENVIRONMENT	221
Figure A.10 – Floating circuit	
Figure A.11 – Interruption of a power-carrying conductor between ME EQUIPMENT parts in separate ENCLOSURES	
Figure A.12 – Identification of MEANS OF PATIENT PROTECTION and MEANS OF OPERATOR PROTECTION.	242
Figure A.13 – Allowable protective earth impedance where the fault current is limited	249
Figure A.14 – Probability of ventricular fibrillation	255
Figure A.15 – Example of a measuring circuit for the PATIENT LEAKAGE CURRENT from a PATIENT CONNECTION to earth for ME EQUIPMENT with multiple PATIENT CONNECTIONS	
Figure A.16 – Instability test conditions	272
Figure A.17 – Example of determining TENSILE SAFETY FACTOR using Table 21	
Figure A.18 – Example of determining design and test loads	
Figure A.19 – Example of human body mass distribution	
Figure E.1 – TYPE B APPLIED PART	
Figure E.2 – Type bf applied part	
Figure E.3 – TYPE CF APPLIED PART	
Figure E.4 – PATIENT AUXILIARY CURRENT	
Figure E.5 – Loading of the PATIENT CONNECTIONS if specified by the MANUFACTURER	
Figure F.1 – Measuring supply circuit with one side of the SUPPLY MAINS at approximately earth potential	326
Figure F.2 – Measuring supply circuit with SUPPLY MAINS approximately symmetrical to earth potential.	326
Figure F.3 – Measuring supply circuit for polyphase ME EQUIPMENT specified for connection to a polyphase SUPPLY MAINS	327
Figure F.4 – Measuring supply circuit for single-phase ME EQUIPMENT specified for connection to a polyphase SUPPLY MAINS	327
	S

Figure F.5 – Measuring supply circuit for ME EQUIPMENT having a separate power supply unit or intended to receive its power from another equipment in an ME SYSTEM	328
Figure G.1– Maximum allowable current I_{ZR} as a function of the maximum allowable voltage U_{ZR} measured in a purely resistive circuit with the most flammable mixture of ether vapour with air	335
Figure G.2 – Maximum allowable voltage U_{ZC} as a function of the capacitance C_{max} measured in a capacitive circuit with the most flammable mixture of ether vapour with ai	r.336
Figure G.3 – Maximum allowable current I_{ZL} as a function of the inductance L_{max} measured in an inductive circuit with the most flammable mixture of ether vapour with air	336
Figure G.4 – Maximum allowable current I_{ZR} as a function of the maximum allowable voltage U_{ZR} measured in a purely resistive circuit with the most flammable mixture of ether vapour with oxygen	340
Figure G.5 – Maximum allowable voltage U_{zc} as a function of the capacitance C_{max} measured in a capacitive circuit with the most flammable mixture of ether vapour with oxygen	341
Figure G.6 – Maximum allowable current I_{ZL} as a function of the inductance L_{max} measured in an inductive circuit with the most flammable mixture of ether vapour with oxygen	
Figure G.7 – Test apparatus	
Figure H.1 – Examples of PEMS/ PESS structures	
Figure H.2 – A PEMS DEVELOPMENT LIFE-CYCLE model	
Figure H.3 – PEMS documentation requirements from Clause 14 and ISO 14971:2000	
Figure H.4 – Example of potential parameters required to be specified for NETWORK/DATA COUPLING	
Figure I.1 – Example of the construction of a MULTIPLE SOCKET-OUTLET (MSO)	
Figure I.2 – Examples of application of MULTIPLE SOCKET-OUTLETS (MSO)	
Figure J.1 – Insulation example 1	363
Figure J.2 – Insulation example 2	363
Figure J.3 – Insulation example 3	
Figure J.4 – Insulation example 4	364
Figure J.5 – Insulation example 5	364
Figure J.6 – Insulation example 6	364
Figure J.7 – Insulation example 7	365
Figure K.1 – ME EQUIPMENT with an ENCLOSURE made of insulating material	366
Figure K.2 – ME EQUIPMENT with an F-TYPE APPLIED PART	366
Figure K.3 – ME EQUIPMENT with an APPLIED PART and a SIGNAL INPUT/OUTPUT PART	367
Figure K.4 – ME EQUIPMENT with a PATIENT CONNECTION of a TYPE B APPLIED PART that is not PROTECTIVELY EARTHED	367
Figure K.5 – ME EQUIPMENT with a PATIENT CONNECTION of a TYPE BF APPLIED PART that is not protectively earthed	368

Table 1 – Units outside the SI units system that may be used on ME EQUIPMENT	60
Table 2 – Colours of indicator lights and their meaning for ME EQUIPMENT	62
Table 3 – * Allowable values of PATIENT LEAKAGE CURRENTS and PATIENT AUXILIARY CURRENTS under NORMAL CONDITION and SINGLE FAULT CONDITION	.86
Table 4 – * Allowable values of PATIENT LEAKAGE CURRENTS under the special test conditions identified in 8.7.4.7	.87
Table 5 – Legends of symbols for Figure 9 to Figure 11, Figure 13 to Figure 20, Figure A.15, Annex E and Annex F	.96
Table 6 – Test voltages for solid insulation forming a MEANS OF PROTECTION	104
Table 7 – Test voltages for MEANS OF OPERATOR PROTECTION	105
Table 8 – Multiplication factors for AIR CLEARANCES for altitudes up to 5 000 m	108
Table 9 – Material group classification	109
Table 10 – Mains transient voltage	.110
Table 11 – Minimum CREEPAGE DISTANCES and AIR CLEARANCES between parts of opposite polarity of the MAINS PART	.112
Table 12 – Minimum CREEPAGE DISTANCES and AIR CLEARANCES providing MEANS OF PATIENT PROTECTION	.113
Table 13 – Minimum AIR CLEARANCES providing MEANS OF OPERATOR PROTECTION from the MAINS PART	.114
Table 14 – Additional AIR CLEARANCES for insulation in MAINS PARTS with PEAK WORKING VOLTAGES exceeding the peak value of the NOMINAL MAINS VOLTAGE ^a	.115
Table 15 – Minimum AIR CLEARANCES for MEANS OF OPERATOR PROTECTION in SECONDARY CIRCUITS	.116
Table 16 – Minimum CREEPAGE DISTANCES providing MEANS OF OPERATOR PROTECTION	.117
Table 17 – NOMINAL cross-sectional area of conductors of a POWER SUPPLY CORD	126
Table 18 – Testing of cord anchorages	.127
Table 19 – MECHANICAL HAZARDS covered by this clause	131
Table 19 – MECHANICAL HAZARDS covered by this clause Table 20 – Acceptable gaps	
Table 20 – Acceptable gaps	.133
Table 20 – Acceptable gaps Table 21 – Determination of TENSILE SAFETY FACTOR	.133 .147
Table 20 – Acceptable gaps	.133 .147 .153
Table 20 – Acceptable gaps Table 21 – Determination of TENSILE SAFETY FACTOR Table 22 – Allowable maximum temperatures of parts Table 23 – Allowable maximum temperatures for ME EQUIPMENT parts that are likely to	.133 .147 .153 .154
Table 20 – Acceptable gaps Table 21 – Determination of TENSILE SAFETY FACTOR Table 22 – Allowable maximum temperatures of parts Table 23 – Allowable maximum temperatures for ME EQUIPMENT parts that are likely to be touched Table 24 – Allowable maximum temperatures for skin contact with ME EQUIPMENT APPLIED PARTS Table 25 – Acceptable perforation of the bottom of an ENCLOSURE	.133 .147 .153 .154 .154 .154
Table 20 – Acceptable gaps Table 21 – Determination of TENSILE SAFETY FACTOR Table 22 – Allowable maximum temperatures of parts Table 23 – Allowable maximum temperatures for ME EQUIPMENT parts that are likely to be touched Table 24 – Allowable maximum temperatures for skin contact with ME EQUIPMENT APPLIED PARTS	.133 .147 .153 .154 .154 .154
Table 20 – Acceptable gaps Table 21 – Determination of TENSILE SAFETY FACTOR Table 22 – Allowable maximum temperatures of parts Table 23 – Allowable maximum temperatures for ME EQUIPMENT parts that are likely to be touched Table 24 – Allowable maximum temperatures for skin contact with ME EQUIPMENT APPLIED PARTS Table 25 – Acceptable perforation of the bottom of an ENCLOSURE	.133 .147 .153 .154 .154 .163 .173
Table 20 – Acceptable gaps Table 21 – Determination of TENSILE SAFETY FACTOR Table 22 – Allowable maximum temperatures of parts Table 23 – Allowable maximum temperatures for ME EQUIPMENT parts that are likely to be touched Table 24 – Allowable maximum temperatures for skin contact with ME EQUIPMENT APPLIED PARTS Table 25 – Acceptable perforation of the bottom of an ENCLOSURE Table 26 – * Temperature limits of motor windings Table 27 – Maximum motor winding steady-state temperature	.133 .147 .153 .154 .154 .163 .173 .175
Table 20 – Acceptable gaps Table 21 – Determination of TENSILE SAFETY FACTOR Table 22 – Allowable maximum temperatures of parts Table 23 – Allowable maximum temperatures for ME EQUIPMENT parts that are likely to be touched Table 24 – Allowable maximum temperatures for skin contact with ME EQUIPMENT APPLIED PARTS Table 25 – Acceptable perforation of the bottom of an ENCLOSURE Table 26 – * Temperature limits of motor windings	.133 .147 .153 .154 .154 .163 .173 .175 .181

Table 32 – Test current for transformers 192 Table A.1 – Values of AIR CLEARANCE and CREEPAGE DISTANCE derived from Table 7 of 263 IEC 61010-1:2001 and Table 12 263 Table A.2 – CREEPAGE DISTANCES to avoid failure due to tracking from IEC 60664-1 264 Table A.3 – Instability test conditions 272 Table A.4 – Allowable time exposure for level of acceleration 274	Table 31 – Maximum allowable temperatures of transformer windings under overload and short-circuit conditions at 25 °C (± 5 °C) ambient temperature	191
Table A.1 – Values of AIR CLEARANCE and CREEPAGE DISTANCE derived from Table 7 of IEC 61010-1:2001 and Table 12 263 Table A.2 – CREEPAGE DISTANCES to avoid failure due to tracking from IEC 60664-1 264 Table A.3 – Instability test conditions 272 Table A.4 – Allowable time exposure for level of acceleration 274 Table A.5 – Guidance on surface temperatures for ME EQUIPMENT that creates low 283 Table C.1 – Marking on the outside of ME EQUIPMENT, ME SYSTEMS or their parts 311 Table C.2 – Marking of the inside of ME EQUIPMENT, ME SYSTEMS or their parts 312 Table C.3 – Marking of controls and instruments 312 Table C.4 – ACCOMPANYING DOCUMENTS, general 313 Table D.5 – ACCOMPANYING DOCUMENTS, instructions for use 313 Table D.1 – General symbols 316 Table D.2 – Safety signs 321 Table D.3 – General codes 323 Table D.1 – Some examples of Cord inlets 338 Table L.1 – NETWORK/DATA COUPLING classification 354 Table L.1 – Some examples of ME SYSTEMS for illustration 359 Table L.2 – Oven temperature 370		
Table A.3 – Instability test conditions272Table A.4 – Allowable time exposure for level of acceleration274Table A.5 – Guidance on surface temperatures for ME EQUIPMENT that creates low temperatures (cools) for therapeutic purposes or as part of its operation283Table C.1 – Marking on the outside of ME EQUIPMENT, ME SYSTEMS or their parts311Table C.2 – Marking on the inside of ME EQUIPMENT, ME SYSTEMS or their parts312Table C.3 – Marking of controls and instruments312Table C.4 – ACCOMPANYING DOCUMENTS, general313Table C.5 – ACCOMPANYING DOCUMENTS, instructions for use313Table D.1 – General symbols316Table D.2 – Safety signs321Table G.1 – Gas-tightness of cord inlets338Table G.1 – Some examples of ME SYSTEMS for illustration359Table 1.1 – Network/DATA COUPLING classification359Table L.2 – Oven temperature370	Table A.1 – Values of AIR CLEARANCE and CREEPAGE DISTANCE derived from Table 7 of	
Table A.3 – Instability test conditions272Table A.4 – Allowable time exposure for level of acceleration274Table A.5 – Guidance on surface temperatures for ME EQUIPMENT that creates low temperatures (cools) for therapeutic purposes or as part of its operation283Table C.1 – Marking on the outside of ME EQUIPMENT, ME SYSTEMS or their parts311Table C.2 – Marking on the inside of ME EQUIPMENT, ME SYSTEMS or their parts312Table C.3 – Marking of controls and instruments312Table C.4 – ACCOMPANYING DOCUMENTS, general313Table C.5 – ACCOMPANYING DOCUMENTS, instructions for use313Table D.1 – General symbols316Table D.2 – Safety signs321Table G.1 – Gas-tightness of cord inlets338Table G.1 – Some examples of ME SYSTEMS for illustration359Table 1.1 – Network/DATA COUPLING classification359Table L.2 – Oven temperature370		
Table A.5 – Guidance on surface temperatures for ME EQUIPMENT that creates low temperatures (cools) for therapeutic purposes or as part of its operation 283 Table C.1 – Marking on the outside of ME EQUIPMENT, ME SYSTEMS or their parts 311 Table C.2 – Marking on the inside of ME EQUIPMENT, ME SYSTEMS or their parts 312 Table C.3 – Marking of controls and instruments 312 Table C.4 – ACCOMPANYING DOCUMENTS, general 313 Table C.5 – ACCOMPANYING DOCUMENTS, instructions for use 313 Table D.1 – General symbols 316 Table D.2 – Safety signs 321 Table G.1 – Gas-tightness of cord inlets 338 Table G.1 – NETWORK/DATA COUPLING classification 359 Table I.1 – Network/DATA COUPLING classification 359 Table L.2 – Oven temperature 370		
temperatures (cools) for therapeutic purposes or as part of its operation		
Table C.2 – Marking on the inside of ME EQUIPMENT, ME SYSTEMS or their parts 312 Table C.3 – Marking of controls and instruments 312 Table C.4 – ACCOMPANYING DOCUMENTS, general 313 Table C.5 – ACCOMPANYING DOCUMENTS, instructions for use 313 Table D.1 – General symbols 316 Table D.2 – Safety signs 321 Table D.3 – General codes 323 Table G.1 – Gas-tightness of cord inlets 338 Table H.1 – NETWORK/DATA COUPLING classification 354 Table I.1 – Some examples of ME SYSTEMS for illustration 359 Table L.2 – Oven temperature 370	Table A.5 – Guidance on surface temperatures for ME EQUIPMENT that creates low temperatures (cools) for therapeutic purposes or as part of its operation	283
Table C.3 – Marking of controls and instruments.312Table C.4 – ACCOMPANYING DOCUMENTS, general.313Table C.5 – ACCOMPANYING DOCUMENTS, instructions for use.313Table D.1 – General symbols316Table D.2 – Safety signs.321Table D.3 – General codes323Table G.1 – Gas-tightness of cord inlets338Table H.1 – NETWORK/DATA COUPLING classification354Table I.1 – Some examples of ME SYSTEMS for illustration359Table L.2 – Oven temperature370	Table C.1– Marking on the outside of ME EQUIPMENT, ME SYSTEMS or their parts	311
Table C.4 – ACCOMPANYING DOCUMENTS, general. 313 Table C.5 – ACCOMPANYING DOCUMENTS, instructions for use. 313 Table D.1 – General symbols. 316 Table D.2 – Safety signs 321 Table D.3 – General codes 323 Table G.1 – Gas-tightness of cord inlets 338 Table H.1 – NETWORK/DATA COUPLING classification 354 Table I.1 – Some examples of ME SYSTEMS for illustration 359 Table L.2 – Oven temperature 370	Table C.2 – Marking on the inside of ME EQUIPMENT, ME SYSTEMS or their parts	312
Table C.5 – ACCOMPANYING DOCUMENTS, instructions for use.313Table D.1 – General symbols316Table D.2 – Safety signs321Table D.3 – General codes323Table G.1 – Gas-tightness of cord inlets338Table H.1 – NETWORK/DATA COUPLING classification354Table I.1 – Some examples of ME SYSTEMS for illustration359Table L.2 – Oven temperature370	Table C.3 – Marking of controls and instruments	312
Table D.1 – General symbols316Table D.2 – Safety signs321Table D.3 – General codes323Table G.1 – Gas-tightness of cord inlets338Table H.1 – NETWORK/DATA COUPLING classification354Table I.1 – Some examples of ME SYSTEMS for illustration359Table L.1 – Mandrel diameter370Table L.2 – Oven temperature370	Table C.4 – Accompanying documents, general	313
Table D.2 – Safety signs321Table D.3 – General codes323Table G.1 – Gas-tightness of cord inlets338Table H.1 – NETWORK/DATA COUPLING classification354Table I.1 – Some examples of ME SYSTEMS for illustration359Table L.1 – Mandrel diameter370Table L.2 – Oven temperature370	Table C.5 – ACCOMPANYING DOCUMENTS, instructions for use	313
Table D.3 – General codes 323 Table G.1 – Gas-tightness of cord inlets 338 Table H.1 – NETWORK/DATA COUPLING classification 354 Table I.1 – Some examples of ME SYSTEMS for illustration 359 Table L.1 – Mandrel diameter 370 Table L.2 – Oven temperature 370	Table D.1 – General symbols	316
Table G.1 – Gas-tightness of cord inlets 338 Table H.1 – NETWORK/DATA COUPLING classification 354 Table I.1 – Some examples of ME SYSTEMS for illustration 359 Table L.1 – Mandrel diameter 370 Table L.2 – Oven temperature 370	Table D.2 – Safety signs	321
Table H.1 – NETWORK/DATA COUPLING classification 354 Table I.1 – Some examples of ME SYSTEMS for illustration 359 Table L.1 – Mandrel diameter 370 Table L.2 – Oven temperature 370	Table D.3 – General codes	323
Table I.1 – Some examples of ME SYSTEMS for illustration 359 Table L.1 – Mandrel diameter 370 Table L.2 – Oven temperature 370	Table G.1 – Gas-tightness of cord inlets	338
Table L.1– Mandrel diameter	Table H.1 – NETWORK/DATA COUPLING classification	354
Table L.2 – Oven temperature		
	Table L.1– Mandrel diameter	370
	Table L.2 – Oven temperature	370

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MEDICAL ELECTRICAL EQUIPMENT – Part 1: General requirements for basic safety and essential performance FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.

- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60601-1 has been prepared by subcommittee 62A: Common aspects of electrical equipment used in medical practice, of IEC technical committee 62: Electrical equipment in medical practice.

This third edition cancels and replaces the second edition published in 1988, its Amendment 1 (1991) and Amendment 2 (1995). This edition constitutes a technical revision. This edition has been significantly restructured. Requirements in the electrical section have been further aligned with those for information technology equipment covered by IEC 60950-1 and a requirement for including a RISK MANAGEMENT PROCESS has been added. For an expanded description of this revision, see Clause A.3.

The text of this standard is based on the following documents:

FDIS	Report on voting
62A/505A/FDIS	62A/512/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this standard the following print types are used:

- Requirements and definitions: in roman type.
- Test specifications: in italic type.
- Informative material appearing outside of tables, such as notes, examples and references: in smaller type.
 Normative text of tables is also in a smaller type.
- TERMS USED THROUGHOUT THIS STANDARD THAT HAVE BEEN DEFINED IN CLAUSE 3 AND ALSO GIVEN IN THE INDEX: IN SMALL CAPITALS.

In referring to the structure of this standard, the term

- "clause" means one of the seventeen numbered divisions within the table of contents, inclusive of all subdivisions (e.g. Clause 7 includes subclauses 7.1, 7.2, etc.);
- "subclause" means a numbered subdivision of a clause (e.g. 7.1, 7.2 and 7.2.1 are all subclauses of Clause 7).

References to clauses within this standard are preceded by the term "Clause" followed by the clause number. References to subclauses within this standard are by number only.

In this standard, the conjunctive "or" is used as an "inclusive or" so a statement is true if any combination of the conditions is true.

The verbal forms used in this standard conform to usage described in Annex G of the ISO/IEC Directives, Part 2. For the purposes of this standard, the auxiliary verb:

- "shall" means that compliance with a requirement or a test is mandatory for compliance with this standard;
- "should" means that compliance with a requirement or a test is recommended but is not mandatory for compliance with this standard;
- "may" is used to describe a permissible way to achieve compliance with a requirement or test.

An asterisk (*) as the first character of a title or at the beginning of a paragraph or table title indicates that there is guidance or rationale related to that item in Annex A.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

The contents of the corrigenda of December 2006 and 2007 and the Interpretations sheets of April 2008 and January 2009 have been included in this copy.

INTRODUCTION

In 1976, IEC subcommittee 62A published the first edition of IEC/TR 60513, *Basic aspects of the safety philosophy for electrical equipment used in medical practice*. The first edition of IEC/TR 60513 provided the basis for developing:

- the first edition of IEC 60601-1 (the parent safety standard for MEDICAL ELECTRICAL EQUIPMENT);
- the IEC 60601-1-xx series of collateral standards for MEDICAL ELECTRICAL EQUIPMENT;
- the IEC 60601-2-xx series of particular standards for particular types of MEDICAL ELECTRICAL EQUIPMENT; and
- the IEC 60601-3-xx series of performance standards for particular types of MEDICAL ELECTRICAL EQUIPMENT.

Aware of the need and the urgency for a standard covering electrical equipment used in medical practice, the majority of National Committees voted in 1977 in favour of the first edition of IEC 60601-1, based on a draft that at the time represented a first approach to the problem. The extent of the scope, the complexity of the equipment concerned, and the specific nature of some of the protective measures and the corresponding tests for verifying them, required years of effort in order to prepare this first standard, which can now be said to have served as a universal reference since its publication.

However, the frequent application of the first edition revealed room for improvement. These improvements were all the more desirable in view of the considerable success that this standard has enjoyed since its publication.

The careful work of revision subsequently undertaken and continued over a number of years resulted in the publication of the second edition in 1988. This edition incorporated all the improvements that could be reasonably expected up to that time. Further developments remained under constant study. The second edition was amended in 1991 and then again in 1995.

The original IEC approach was to prepare separate BASIC SAFETY and performance standards for MEDICAL ELECTRICAL EQUIPMENT. This was a natural extension of the historical approach taken at the national and international level with other electrical equipment standards (e.g. those for domestic equipment), where BASIC SAFETY is regulated through mandatory standards but other performance specifications are regulated by market pressure. In this context, it has been said that, "The ability of an electric kettle to boil water is not critical to its safe use!"

It is now recognized that this is not the situation with many items of MEDICAL ELECTRICAL EQUIPMENT, and RESPONSIBLE ORGANIZATIONS have to depend on standards to ensure ESSENTIAL PERFORMANCE as well as BASIC SAFETY. Such areas include the accuracy with which the equipment controls the delivery of energy or therapeutic substances to the PATIENT, or processes and displays physiological data that will affect PATIENT management.

This recognition means that separating BASIC SAFETY and performance is somewhat inappropriate in addressing the HAZARDS that result from inadequate design of MEDICAL ELECTRICAL EQUIPMENT. Many particular standards in the IEC 60601-2-xx series address a range of ESSENTIAL PERFORMANCE requirements that cannot be directly evaluated by the RESPONSIBLE ORGANIZATION without applying such standards. (However, the current IEC 60601 series includes fewer requirements for ESSENTIAL PERFORMANCE than for BASIC SAFETY).

In anticipation of a third edition of IEC 60601-1, IEC subcommittee 62A prepared a second edition of IEC/TR 60513 [12]¹) in 1994. It was intended that the second edition of IEC/TR 60513 would provide guidance for developing this edition of IEC 60601-1, and for the further development of the IEC 60601-1-xx and IEC 60601-2-xx series.

In order to achieve consistency in international standards, address present expectations in the health care community and align with developments in IEC 60601-2-xx, the second edition of IEC/TR 60513 includes two major new principles:

- the first change is that the concept of "SAFETY" has been broadened from the BASIC SAFETY considerations in the first and second editions of IEC 60601-1 to include ESSENTIAL PERFORMANCE matters, (e.g. the accuracy of physiological monitoring equipment). Application of this principle leads to the change of the title of this publication from "Medical electrical equipment, Part 1: General requirements for safety" in the second edition, to "Medical electrical equipment, Part 1: General requirements for basic safety and essential performance";
- the second change is that, in specifying minimum safety requirements, provision is made for assessing the adequacy of the design PROCESS when this is the only practical method of assessing the safety of certain technologies such as programmable electronic systems. Application of this principle is one of the factors leading to introduction of a general requirement to carry out a RISK MANAGEMENT PROCESS. In parallel with the development of the third edition of IEC 60601-1, a joint project with ISO/TC 210 resulted in the publication of a general standard for RISK MANAGEMENT of medical devices. Compliance with this edition of IEC 60601-1 requires that the MANUFACTURER have a RISK MANAGEMENT PROCESS complying with ISO 14971 in place (see 4.2).

This standard contains requirements concerning BASIC SAFETY and ESSENTIAL PERFORMANCE that are generally applicable to MEDICAL ELECTRICAL EQUIPMENT. For certain types of MEDICAL ELECTRICAL EQUIPMENT, these requirements are either supplemented or modified by the special requirements of a collateral or particular standard. Where particular standards exist, this standard should not be used alone.

1) Figures in square brackets refer to the Bibliography.

MEDICAL ELECTRICAL EQUIPMENT –

Part 1: General requirements for basic safety and essential performance

1 Scope, object and related standards

1.1 * Scope

This International Standard applies to the BASIC SAFETY and ESSENTIAL PERFORMANCE of MEDICAL ELECTRICAL EQUIPMENT and MEDICAL ELECTRICAL SYSTEMS, hereafter referred to as ME EQUIPMENT and ME SYSTEMS.

If a clause or subclause is specifically intended to be applicable to ME EQUIPMENT only, or to ME SYSTEMS only, the title and content of that clause or subclause will say so. If that is not the case, the clause or subclause applies both to ME EQUIPMENT and to ME SYSTEMS, as relevant.

HAZARDS inherent in the intended physiological function of ME EQUIPMENT or ME SYSTEMS within the scope of this standard are not covered by specific requirements in this standard except in 7.2.13 and 8.4.1.

NOTE See also 4.2.

This standard can also be applied to equipment used for compensation or alleviation of disease, injury or disability.

In vitro diagnostic equipment that does not fall within the definition of ME EQUIPMENT is covered by the IEC 61010 series ²). This standard does not apply to the implantable parts of active implantable medical devices covered by ISO 14708-1 ³).

1.2 Object

The object of this standard is to specify general requirements and to serve as the basis for particular standards.

1.3 * Collateral standards

In the IEC 60601 series, collateral standards specify general requirements for BASIC SAFETY and ESSENTIAL PERFORMANCE applicable to:

- a subgroup of ME EQUIPMENT (e.g. radiological equipment);
- a specific characteristic of all ME EQUIPMENT not fully addressed in this standard.

Applicable collateral standards become normative at the date of their publication and shall apply together with this standard.

NOTE 1 When evaluating compliance with IEC 60601-1, it is permissible to independently assess compliance with the collateral standards.

²⁾ IEC 61010 (all parts), Safety requirements for electrical equipment for measurement, control, and laboratory use

³⁾ ISO 14708-1, Implants for surgery – Active implantable medical devices – Part 1: General requirements for safety, marking and for information to be provided by the manufacturer

2

NOTE 2 When declaring compliance with IEC 60601-1, the declarer should specifically list the collateral standards that have been applied. This allows the reader of the declaration to understand which collateral standards were part of the evaluation.

NOTE 3 Members of IEC maintain a register of valid International Standards. Users of this standard should consult this register to determine which collateral standards have been published.

If a collateral standard applies to ME EQUIPMENT for which a particular standard exists, then the particular standard takes priority over the collateral standard.

1.4 * Particular standards

In the IEC 60601 series, particular standards may modify, replace or delete requirements contained in this standard as appropriate for the particular ME EQUIPMENT under consideration, and may add other BASIC SAFETY and ESSENTIAL PERFORMANCE requirements.

NOTE Members of IEC and ISO maintain registers of valid International Standards. Users of this standard should consult these registers to determine which particular standards have been published.

A requirement of a particular standard takes priority over this standard.

2 * Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ATTENTION: Additional collateral standards of the IEC 60601 series, which are issued subsequent to publication of this standard, become normative at the date of their publication and shall be considered as being included among the normative references below. See 1.3.

NOTE Informative references are listed in the Bibliography on page 372.

IEC 60065:2001, Audio, video and similar electronic apparatus – Safety requirements

IEC 60068-2-2:1974, Environmental testing – Part 2: Tests. Tests B: Dry heat Amendment 1 (1993) Amendment 2 (1994)

IEC 60079-0, *Electrical apparatus for explosive gas atmospheres – Part 0: General requirements*

IEC 60079-2, *Electrical apparatus for explosive gas atmospheres – Part 2: Pressurized enclosures "p"*

IEC 60079-5, Electrical apparatus for explosive gas atmospheres – Part 5: Powder filling "q"

IEC 60079-6, Electrical apparatus for explosive gas atmospheres – Part 6: Oil-immersion "o"