

---

---

**Acoustics — Hearing protectors —**  
**Part 2:**  
**Estimation of effective A-weighted**  
**sound pressure levels when hearing**  
**protectors are worn**

*Acoustique — Protecteurs individuels contre le bruit —*

*Partie 2: Estimation des niveaux de pression acoustique pondérés A en*  
*cas d'utilisation de protecteurs individuels contre le bruit*



This document is a preview generated by EMS



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword.....	iv
Introduction.....	v
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Measurement of sound attenuation of hearing protectors</b> .....	<b>2</b>
<b>5 Calculation of the assumed protection value, <math>APV_{fx}</math> of a hearing protector for a selected protection performance</b> .....	<b>2</b>
<b>6 Octave-band method</b> .....	<b>3</b>
<b>7 HML method</b> .....	<b>4</b>
7.1 General.....	4
7.2 Calculation of $H$ , $M$ and $L$ values.....	4
7.3 Application of <b>HML</b> method for estimation of the effective A-weighted sound pressure level.....	6
<b>8 SNR method</b> .....	<b>6</b>
8.1 General.....	6
8.2 Calculation of <b>SNR</b> values.....	6
8.3 Application of <b>SNR</b> method for estimation of the effective A-weighted sound pressure level.....	7
<b>Annex A (informative) Example of the calculation of the assumed protection values, <math>APV_{fx}</math></b> .....	<b>9</b>
<b>Annex B (informative) Example of the calculation of <math>L'_{p,Ax}</math> according to the octave-band method</b> .....	<b>10</b>
<b>Annex C (informative) Example of the calculation and use of <math>H</math>, <math>M</math> and <math>L</math> values</b> .....	<b>11</b>
<b>Annex D (informative) Example of the calculation and use of <math>SNR</math> values</b> .....	<b>14</b>
<b>Annex E (informative) Uncertainty of attenuation values and ratings</b> .....	<b>16</b>
<b>Bibliography</b> .....	<b>18</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This second edition cancels and replaces the first edition (ISO 4869-2:1994) which has been technically revised. It also incorporates the corrected version ISO 4869-2:1994/Cor.1:2006.

The main technical changes are:

In the prior edition of the standard the *H*, *M*, *L*, and *SNR* values were computed from the group average data by frequency. In this edition, the values are computed subject by subject and then combined to provide both a mean value and a standard deviation value so that population distribution can be estimated. The sound attenuation values for the frequency 63 Hz have been excluded from the *H*, *M*, *L* and *SNR* calculation methods since this test frequency is optional in ISO 4869-1. Prior to rounding to the nearest integer, values derived using this edition deviate from those derived using the previous edition by less than 1 dB.

A list of all parts in the ISO 4869 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

This document estimates an “effective” level, i.e. the A-weighted sound pressure level at the head centre with the listener absent, minus the attenuation of the hearing protection devices. Effective values are estimated since those are required to assess noise hazard with respect to permissible noise exposure limits. An effective level differs from that in the ear canal since it has been converted to a sound-field value via the transfer function of the open ear. Effective levels are typically 5 dB to 10 dB less than ear canal levels depending on the spectrum of the incident noise.

Ideally, the A-weighted sound pressure level effective when a hearing protector is worn should be estimated on the basis of both the octave-band sound attenuation data of the hearing protector (measured in accordance with ISO 4869-1) and the octave-band sound pressure levels of the noise. It is recognized, however, that in many situations information on the octave-band sound pressure levels of the noise might not be available. Therefore, for many practical purposes, there is a need for simpler methods to determine the effective A-weighted sound pressure levels which are only based on the A- and C-weighted sound pressure levels of the noise. This document addresses both of these situations by specifying an octave-band calculation method as well as two alternative simplified procedures, the *HML* method and the *SNR* method.

The octave-band method is a calculation method involving the workplace octave-band sound pressure levels and the octave-band sound attenuation data for the hearing protector that is being assessed. Although it can be thought of as an “exact” reference method, it has its own inherent inaccuracies, since it is based upon mean sound attenuation values and standard deviations for a group of test subjects, and not the specific sound attenuation values for the individual person in question.

The *HML* method specifies three attenuation values, *H*, *M* and *L*, determined from the octave-band sound attenuation data of a hearing protector. These values, when combined with the C- and A-weighted sound pressure levels of the noise, are used to calculate the effective A-weighted sound pressure level when the hearing protector is worn.

The *SNR* method specifies a single attenuation value, the single number rating, determined from the octave-band sound attenuation data of a hearing protector. This value is subtracted from the C-weighted sound pressure level of the noise to calculate the effective A-weighted sound pressure level when the hearing protector is worn.

Due to the large spread of the sound attenuation provided by hearing protectors when worn by individual persons, all three methods are nearly equivalent in their accuracy in the majority of noise situations. Even the simplest method, the *SNR* method, will provide a reasonably accurate estimate of the effective A-weighted sound pressure level to aid in the selection and specification of hearing protectors. In special situations, for example especially high- or low-frequency noises, it is necessary to use either the *HML* or the octave-band method.

Depending on the choice of a certain parameter in the calculation process, various protection performances can be obtained. It should be noted that the protection performance values for all three methods are only valid when:

- the hearing protectors are worn correctly and in the same manner as they were worn by subjects when carrying out the ISO 4869-1 test;
- the hearing protectors are properly maintained;
- the anatomical characteristics of the subjects involved in the ISO 4869-1 test are a reasonable match for the population of actual wearers.

Thus, the principal source of potential inaccuracy in use of the three methods described in this document is the basic ISO 4869-1 input data. If the input data do not accurately describe the degree of protection achieved by the target population, then no calculation method will provide sufficient accuracy.

The uncertainty of the attenuation values and ratings is described in [Annex E](#).

NOTE Differences of 3 dB or less in the determination of the effective sound pressure level for comparable hearing protectors are generally insignificant.

This document is a preview generated by EVS

# Acoustics — Hearing protectors —

## Part 2:

# Estimation of effective A-weighted sound pressure levels when hearing protectors are worn

## 1 Scope

This document specifies three methods (the octave-band, *HML* and *SNR* methods) of estimating the A-weighted sound pressure levels effective when hearing protectors are worn. The methods are applicable to either the sound pressure level or the equivalent continuous sound pressure level of the noise. Although primarily intended for steady noise exposures, the methods are also applicable to noises containing impulsive components. It is possible that these methods could not be suitable for use with peak sound pressure level measurements.

The octave-band, *H*, *M*, *L* or *SNR* values are suitable for establishing sound attenuation criteria for selecting or comparing hearing protectors, and/or setting minimum acceptable sound attenuation requirements.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4869-1, *Acoustics — Hearing protectors — Part 1: Subjective method for the measurement of sound attenuation*

ISO 9612:2009, *Acoustics — Determination of occupational noise exposure — Engineering method*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4869-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

### 3.1

#### protection performance

$x$

percentage of individuals for which the achieved protection is equal to or greater than the designated value, where the percentage is indicated by adding a subscript to the symbols representing the different methods, e.g.  $APV_{fx}$ ,  $H_x$ ,  $M_x$ ,  $L_x$ ,  $SNR_x$

Note 1 to entry: The value of protection performance is often chosen to be 84 % [corresponding to the constant  $\alpha = 1$  (see [Clause 5](#))].