

Edition 1.0 2018-10

## INTERNATIONAL





#### THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either JEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11

info@iec.ch www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and

#### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### JEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch. 



Edition 1.0 2018-10

# INTERNATIONAL

Radio data system (RDS) - VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz -Vinitic Control Contro

Part 2: Message format: Coding and definitions of RDS features

**INTERNATIONAL ELECTROTECHNICAL** COMMISSION

ICS 33.160.40 ISBN 978-2-8322-6067-8

Warning! Make sure that you obtained this publication from an authorized distributor.

### CONTENTS

F	DREWC	DRD	5
IŊ	TRODU	JCTION	7
1	Scop	ge	8
2	Norm	ative references	8
3	- ( )	ns, definitions, abbreviated terms and conventions	
J	3.1	Terms and definitions	
	3.1	Abbreviated terms	
	3.3	Notation and conventions	
4		sage format	
4		4	
	4.1 4.2	Design principles  Group structure	
	4.2 4.2.1		
	4.2.1		
	4.2.2		
	4.2.3	Group type O structure	
	4.4	Group type C usage	
	4.4.1		
	4.4.2		
	4.4.3		
5	-	cription of the RDS features	
Ū	5.1	Alternative Erequencies list (AEs	17
	5.2	Alternative Frequencies list (AFs)	17
	5.3	Dynamic PTY Indicator (PTYI) using DI.	17
	5.4	Extended Country Code (ECC)	17
	5.5	Enhanced Other Networks information (EON)	17
	5.6		
	5.7	Unkage information  Open Data Applications (ODAs)	18
	5.8	Programme Identification (PI)	18
	5.9	Programme Service name – (PS)	19
	5.10	Programme Identification (PI)  Programme Service name – (PS)  Long Programme Service name – (LPS)	19
	5.11	Programme Type (PTY)	19
	5.12	Programme Type (PTY)	19
	5.13	RadioText (RT)	20
	5.14	enhanced RadioText (eRT)	
	5.15	RadioText Plus (RT+ and eRT+)	
	5.16	Traffic Programme identification (TP)	
	5.17	Traffic Announcement identification (TA)	20
	5.18	Traffic Message Channel (TMC)	21
6	Codi	ng of the group types	
	6.1	Groups of type 0A and 0B: Basic tuning and switching information with PS name	
	6.2	Group type 1A: Slow labelling codes	
	6.3	Group type 2A and 2B: RadioText	
	6.4	Group type 3A: Application identification for any specific ODA using groups	∠3
	J.→	of type A or B	24
	6.5	Group type 4A: Clock-Time and date	
	6.6	Group type 10A: Programme Type Name PTYN	

Annex A (normative) Method for linking RDS programme services — Linkage nformation — Group type 1A and 14A		6.7	Group type 14A and B: Enhanced Other Networks information (EON)	26
7.1 Programme Identification (PI) codes and Extended Country Codes (ECC) 28 7.1 PI structure 26 7.1.1 Structure 26 7.1.2 Country Identifier (CI) codes: 'Nibble 1' 26 7.1.3 Extended Country Codes (ECC) 26 7.1.4 Programme service in terms of area coverage (codes for fixed location tarfsmitters only): 'Nibble 2' 25 7.1.5 Programme reference number: 'Nibbles 3 and 4' 25 7.1.6 PI codes for low-power short range transmitting devices 25 7.1.7 Programme (PTY) codes 30 7.3 Traffic Programme (PTY) codes 30 7.3 Traffic Programme (TP) and Traffic Announcement (TA) codes 30 7.5 Coding of Alternative Frequencies (AFs) 30 7.5.1 AF code tables 30 7.5.2 Use of Alternative Frequencies in group type 0A. 32 7.5.3 Use of AF codes in group type 14A. 34 7.6 Coding of Iternative Frequencies in group type 0A. 33 7.6.1 General 38 7.6.2 Coding of frequencies for cross-referenced programme services in EON 36 7.6.3 Use of PTY with EON 36 7.6.4 Use of PTY with EON 36 7.6.5 Required main RDS feature repetition rates on distance and services in EON 36 7.6.6 Use of PTY with EON 37 7.6.7 Codes and Seature services - Linkage information - Group type 1A and 1AA 1 7.6 Coder of PTY with EON 37 7.6 Seature repetition rates on distance - Linkage information - Group type 1A and 1AA 1 7.6 Coder of PTY with EON 37 7.6 Seature repetition rates on distance - Linkage information - Group type 1A and 1AA 1 7.6 Coder of PTY with EON 37 7.6 Seature repetition rates on distance - Linkage information - Group type 1A and 1AA 1 7.6 Coder of PTY with EON 37 7.6 Seature repetition rates on distance - Linkage information - Group type 1A and 1AA 1 7.6 Coder of PTY with EON 37 7.6 Seature repetition rates on distance - Linkage information - Group type 1A 34 7.6 Coder of PTY with EON 37 7.6 Seature repetition rates on distance - Linkage - Linka		6.8		26
7.1 Programme Identification (PI) codes and Extended Country Codes (ECC) 7.1 PI structure		6.9	Group type 15B: Fast basic tuning and switching information	27
7.1.2         Country Identifier (CI) codes: Nibble 1"	7	Codi	ng of RDS features for control	28
7.1.2         Country Identifier (CI) codes: Nibble 1'				
7.1.3 Extended Country Codes (ECC) 7.1.4 Programme service in terms of area coverage (codes for fixed location transmitters only): Nibble 2' 7.1.5 Programme reference number: Nibbles 3 and 4' 7.2 Programme reference number: Nibbles 3 and 4' 7.2 Programme rype (PTY) codes 7.3 Traffic Programme (TP) and Traffic Announcement (TA) codes 7.3 Traffic Programme (TP) and Traffic Announcement (TA) codes 30 7.4 Decoder Identification (DI) and dynamic PTY Indicator (PTYI) codes 30 7.5 Coding of Alternative Frequencies (AFs) 31 7.5.1 AF code tables 32 7.5.2 Use of Alternative Frequencies in group type 0A 33 7.5.3 Use of AF codes in group type 14A 34 7.6 Coding of Enhanced Other Networks information (EON) 35 7.6.1 General 36 7.6.2 Coding of frequencies for cross-referenced programme services in EON 36 7.6.3 Use of the TP and TA features with EON 36 7.6.4 Use of PTY with EON 36 8 Required main RDS feature repetition rates 0h data-stream 0 37 8 Annex A (normative) Method for linking RDS programme services — Linkage normative) Method for linking RDS programme services — Linkage normative) Method for linking RDS programme services — Linkage normative) Method for linking RDS programme services — Linkage normative) Method for linking RDS programme services — Linkage normative) Method for linking RDS programme services — Linkage normative) Method for linking RDS programme services — Linkage normative) Method for linking RDS programme services — Linkage normative) Conversion between time and date conventions 44 A.1 General 4.2 LA – Linkage Actuator 4.3 EG – Extended Generic indicator 4.4 A.5 LSN – Linkage Set Number 4.5 LSN – Linkage Set Number 4.6 LSN – Linkage Set Number 4.7 LSN – Linkage Set Number 4.8 LS – International Linkage Set indicator 4.9 LS – Linkage Set Number 4.9 LS – International Linkage Set indicator 4.1 LS – International Linkage Set indicator 4.2 LS – Linkage Set Number 4.3 LS – Linkage Set Number 4.4 LS – Linkage Set Number 4.5 LSN – Linkage Set Number 4.6 LSN – Linkage Set Number 4.7 LSN – Linkage Set Number 4.				
7.1.4 Pregramme service in terms of area coverage (codes for fixed location transmitters only): Nibble 2'				
Tarismitters only : 'Nibble 2'				28
7.1.6 Pl códes for low-power short range transmitting devices			transmitters only): 'Nibble 2'	
7.2         Programme Type (PTY) codes         30           7.3         Traffic Programme (TP) and Traffic Announcement (TA) codes         30           7.4         Decoder Identification (DI) and dynamic PTY Indicator (PTYI) codes         30           7.5         Coding of Alternative Frequencies (AFs)         30           7.5.1         AF code tables         30           7.5.2         Use of Alternative Frequencies in group type 0A         32           7.5.3         Use of AF codes in group type 14A         34           7.6         Coding of Enhanced Other Networks information (EON)         35           7.6.1         General         35           7.6.2         Coding of frequencies for cryst referenced programme services in EON         36           7.6.3         Use of the TP and TA features with EON         36           7.6.4         Use of PTY with EON         36           8         Required main RDS feature repetition rates 0n data-stream 0         37           Annex A (normative)         Method for linking RDS programme services – Linkage normative programme services – Linkage for material programme services – Linkage for mate				
7.3 Traffic Programme (TP) and Traffic Announcement (TA) codes				
7.4         Decoder Identification (DI) and dynamic PTY Indicator (PTYI) codes         30           7.5         Coding of Alternative Frequencies (AFs)         30           7.5.1         AF code tables         30           7.5.2         Use of Alternative Frequencies in group type 0A         32           7.5.3         Use of AF codes in group type 14A         34           7.6         Coding of Enhanced Other Networks information (EON)         35           7.6.1         General         35           7.6.2         Coding of frequencies for cress-referenced programme services in EON         36           7.6.3         Use of the TP and TA features with EON         36           7.6.4         Use of PTY with EON         36           3         Required main RDS feature repetition rates on data-stream 0         37           Annex A (normative)         Method for linking RDS programme services – Linkage           nformation – Group type 1A and 14A         41           A.1         General         42           A.2         LA – Linkage Actuator         42           A.3         EG – Extended Generic indicator         42           A.4         ILS – International Linkage Set indicator         42           A.5         LSN – Linkage Set Number         42				
7.5       Coding of Alternative Frequencies (AFs)       30         7.5.1       AF code tables       30         7.5.2       Use of Alternative Frequencies in group type 0A       32         7.5.3       Use of AF codes in group type 14A       34         7.6       Coding of Enhanced Other Networks information (EON)       35         7.6.1       General       35         7.6.2       Coding of frequencies for cross-referenced programme services in EON       36         7.6.3       Use of PTY with EON       36         7.6.4       Use of PTY with EON       36         8       Required main RDS feature repetition rates by data-stream 0       37         Annex A (normative)       Method for linking RDS programme services – Linkage information – Group type 1A and 14A       41         A.1       General       41         A.2       LA – Linkage Actuator       42         A.3       EG – Extended Generic indicator       42         A.4       ILS – International Linkage Set indicator       42         A.5       LSN – Linkage Set Number       42         Annex B (informative)       Conversion between time and date conventions       44         Bibliography       45         Figure 1 – Group type A structure       12				
7.5.1 AF code tables				
7.5.2       Use of Alternative Frequencies in group type 0A				
7.5.3       Use of AF codes in group type 14A				
7.6 Coding of Enhanced Other Networks information (EON)  7.6.1 General  7.6.2 Coding of frequencies for cross-referenced programme services in EON  7.6.3 Use of the TP and TA features with EON  7.6.4 Use of PTY with EON  8 Required main RDS feature repetition rates on data-stream 0  Annex A (normative) Method for linking RDS programme services – Linkage information – Group type 1A and 14A  A.1 General  A.2 LA – Linkage Actuator  A.3 EG – Extended Generic indicator  A.4 ILS – International Linkage Set indicator  A.5 LSN – Linkage Set Number  Annex B (informative) Conversion between time and date conventions  46  Figure 1 – Group type B structure  Figure 2 – Group type B structure  Figure 3 – Group type C structure  Figure 4 – Tunnelling structure for group types A and B  Figure 5 – Basic tuning and switching information – Group type 0A  21  Figure 6 – Basic tuning and switching information – Group type 0B  22  Figure 7 – Slow labelling codes – Group type 1A  Figure 9 – RadioText – Group type 2B  Figure 10 – Application identification for any specific ODA – Group type 3A				
7.6.1       General       35         7.6.2       Coding of frequencies for cross-referenced programme services in EON       36         7.6.3       Use of the TP and TA features with EON       36         7.6.4       Use of PTY with EON       36         8       Required main RDS feature repetition rates on data-stream 0       37         Annex A (normative) Method for linking RDS programme services – Linkage information – Group type 1A and 14A       41         A.1       General       41         A.2       LA – Linkage Actuator       42         A.3       EG – Extended Generic indicator       42         A.4       ILS – International Linkage Set indicator       42         A.5       LSN – Linkage Set Number       42         Annex B (informative) Conversion between time and date conventions       44         Bibliography       46         Bigure 1 – Group type A structure       11         Figure 2 – Group type B structure       12         Figure 5 – Basic tuning and switching information – Group type 0A       21         Figure 6 – Basic tuning and switching information – Group type 0B       25         Figure 7 – Slow labelling codes – Group type 1A       22         Figure 8 – RadioText – Group type 2B       24         Figure 9 – RadioText – Group type				
7.6.2 Coding of frequencies for cross-referenced programme services in EON				
7.6.3 Use of the TP and TA features with EON				
7.6.4 Use of PTY with EON			Use of the TP and TA features with EON	36
Required main RDS feature repetition rates on data-stream 0		7.6.4	Use of PTY with EON	36
nformation – Group type 1A and 14A	8	Requ		
A.1 General				41
A.2 LA – Linkage Actuator			· · · ·	
A.3 EG - Extended Generic indicator				
A.5 LSN – Linkage Set Number		A.3	FG – Extended Generic indicator	42
A.5 LSN – Linkage Set Number		A.4	ILS – International Linkage Set indicator	42
Annex B (informative) Conversion between time and date conventions		A.5	LSN – Linkage Set Number	42
Figure 1 – Group type A structure	Ar	nnex B (	informative) Conversion between time and date conventions	44
Figure 2 – Group type B structure	Bi	bliograp	ohy	46
Figure 2 – Group type B structure				
Figure 3 – Group type C structure	Fi	gure 1 -	- Group type A structure	11
Figure 4 – Tunnelling structure for group types A and B	Fi	gure 2 -	- Group type B structure	12
Figure 5 – Basic tuning and switching information – Group type 0A	Fi	gure 3 -	- Group type C structure	12
Figure 6 – Basic tuning and switching information – Group type 0B	Fi	gure 4 -	- Tunnelling structure for group types A and B	15
Figure 7 – Slow labelling codes – Group type 1A	Fi	gure 5 -	- Basic tuning and switching information – Group type 0A	21
Figure 7 – Slow labelling codes – Group type 1A	Fi	gure 6 -	- Basic tuning and switching information – Group type 0B	22
Figure 8 – RadioText – Group type 2A	Fi	gure 7 -	- Slow labelling codes – Group type 1A	22
Figure 9 – RadioText – Group type 2B24 Figure 10 – Application identification for any specific ODA – Group type 3A24				
Figure 10 – Application identification for any specific ODA – Group type 3A24		_		
		_	Clock Time and date transmission. Group type 44	25

Figure 12 – Programme Type Name PTYN – Group type 10A	25
Figure 13 – Enhanced Other Networks information – Group type 14A	26
Figure 14 – Enhanced Other Networks information – Group type 14B	26
Figure 15 – Long PS, UTF-8 coded – Group type 15A	27
Figure 16 – Fast basic tuning and switching information – Group type 15B	27
Figure 17 - PI code structure	28
Figure A.1 Structure of group type 1A, block 3	41
Figure A.2 – Structure of group type 14A variant 12, block 3 (Linkage information) – National link	42
Figure A.3 – Structure of group type 14A variant 12, block 3 (Linkage information) – International link	43
Figure B.1 – Conversion routes between Modified Julian Date (MJD) and Coordinated Universal Time (UTC)	44
Table 1 – Group type C Function Header definition	
Table 2 – Group type A and B usage	14
Table 3 – Group type C assignment methods used to connect channel numbers with one or more AIDs	16
Table 4 – Assignment of up to three successive channel numbers to multiple AIDs	17
Table 5 – Area coverage codes	29
Table 6 – Programme service reference number codes	29
Table 7 – PI codes for short range transmitting devices	
Table 8 – Codes for TP and TA	
Table 9 – Meaning of bits d <sub>0</sub> to d <sub>3</sub>	30
Table 10 – VHF frequencies 87,6 MHz to 107,9 MHz code table	31
Table 11 – Special meanings AF code table	31
Table 12 – LF/MF code table – ITU regions 1 and 3 (9 kHz spacing)	31
Table 13 – MF code table – ITU region 2 (10 kHz spacing)	32
Table 14 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: no TMC and only 'basic' RDS features	37
Table 15 – Data-stream 0 group repetition rates: Transmitter part of a multi-programme service network: no TMC	38
Table 16 – Data-stream 0 group repetition rates: Transmitter not part of a multi- programme service network: with TMC	38
Table 17 – Data-stream 0 group repetition rates: Transmitter not part of a multi-programme service network: no TMC and with support for UTF-8 coded characters	39
Table 18 – Data-stream 0 group repetition rates: Transmitter part of a multi-programme service network: with TMC	40
Table B.1 – Symbols used for time and date calculation	44

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

Part 2: Message format: Coding and definitions of RDS features

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held esponsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62106-2 has been prepared by technical area 1. Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition, together with IEC 62106-1, IEC 62106-3, IEC 62106-4, IEC 62106-5 and IEC 62106-6, cancels and replaces IEC 62106:2015, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62106:2015:

- Provision has been made to carry RDS on multiple data-streams (RDS2).
- Data in the additional data-streams is using a newly defined group type C data structure.
- AF coding below 87,6 MHz (down to 64,1 MHz) using ODA-AID 0x6365 (see IEC 62106-6).

- Long PS (UTF-8) support has been added using group type 15A.
- Coding for the following applications is no longer detailed in the RDS standard as these can use in future the ODA concept: EWS, TDC, IH and RP.
- Obsolete and no longer part of the RDS standard are: MS (Group 0A, 0B and 15B) certain DI codes (mono/stereo, artificial head, compression), Language code, and PIN (Group 1A).

The text of this International Standard is based on the following documents:

CDV	Report on voting
100/2910/CDV	100/3056/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62106 series, published under the general title Radio data system (RDS) - VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- · replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

#### INTRODUCTION

Since the mid-1980s a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, specifically for smart phone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA  $[1, 2, 3, 4, 5]^1$ .

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved, and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard IEC 62106 for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, IEC 62106 has been restructured as follows:

Part 1: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Usage and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

The following future parts are planned:

Part 7: RBDS

Part 8: Universal Encoder Communication Protocol UECP

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

Obsolete or unused functions from the original RDS standard IEC 62106:2015 have been deleted. The presentation in Parts 1, 2 and 3 follows the OSI basic reference model for information processing systems [6].

<sup>1</sup> Numbers in square brackets refer to the Bibliography.

#### RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –

#### Part 2: Message format: Coding and definitions of RDS features

#### 1 Scope

This part of IEC 62106 defines the coding and definition of features for the Radio Data System (RDS).

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106 (all parts), Radio Data System (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz

ISO/IEC 10646, Information technology – Universal Coded Character Set (UCS)

ISO 14819 (all parts), Intelligent transport systems – Traffic and travel information messages via traffic message coding

#### 3 Terms, definitions, abbreviated terms and conventions

#### 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62106-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

#### 3.2 Abbreviated terms

For the purposes of this document, the abbreviated terms given in IEC 62106-1 and the following apply.

AF Alternative Frequency

NOTE 1 Alternative Frequencies are given in the form of lists (method A or B or mapped).

AID Application IDentification for ODAs

CI Country Identifier

CRC Cyclic Redundancy Check

CT Clock Time