
**Rubber compounding ingredients —
Sulfur — Methods of test**

Ingrédients de mélange du caoutchouc — Soufre — Méthodes d'essai



This document is a preview generated by ERS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction.....	vi
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Physical and chemical properties.....	1
5 Determination of total sulfur content.....	2
5.1 Principle.....	2
5.2 Reagents.....	2
5.3 Procedure.....	2
5.4 Expression of results.....	3
5.5 Precision.....	3
6 Determination of sieve residue.....	3
6.1 Principle.....	3
6.2 Method A.....	4
6.2.1 Apparatus.....	4
6.2.2 Procedure.....	5
6.2.3 Expression of results.....	5
6.3 Method B.....	6
6.3.1 Apparatus.....	6
6.3.2 Procedure.....	6
6.3.3 Expression of results.....	6
6.3.4 Precision.....	6
7 Determination of oil content of oil-treated sulfur.....	7
7.1 Principle.....	7
7.2 Hexane procedure.....	7
7.2.1 Reagents.....	7
7.2.2 Procedure.....	7
7.2.3 Expression of results.....	7
7.3 Sulfur-saturated hexane procedure.....	8
7.3.1 Reagents.....	8
7.3.2 Procedure.....	8
7.3.3 Expression of results.....	8
8 Determination of insoluble-sulfur content.....	8
8.1 Principle.....	8
8.2 Reference procedure using toluene.....	9
8.2.1 Reagents.....	9
8.2.2 Procedure.....	9
8.2.3 Expression of results.....	9
8.3 Alternative procedure using carbon disulfide.....	9
8.3.1 Reagents.....	9
8.3.2 Procedure.....	10
8.3.3 Expression of results.....	10
9 Determination of thermal reversion of insoluble sulfur.....	10
9.1 General.....	10
9.2 Method A.....	11
9.2.1 Principle.....	11
9.2.2 Apparatus.....	11
9.2.3 Reference procedure.....	11
9.2.4 Alternative procedure using carbon disulfide.....	13
9.2.5 Expression of results.....	13

9.3	Method B	14
9.3.1	Principle	14
9.3.2	Apparatus	14
9.3.3	Reagents	14
9.3.4	Chromatographic conditions	14
9.3.5	Preparation of calibration curve (soluble sulfur)	15
9.3.6	DSC programme	15
9.3.7	Procedure for initial soluble sulfur	15
9.3.8	Procedure for soluble sulfur after 10-min exposure time	16
9.3.9	Expression of results	16
9.4	Precision	16
10	Determination of loss in mass at 80 °C	17
10.1	Principle	17
10.2	Apparatus	17
10.3	Procedure	17
10.3.1	Method A	17
10.3.2	Method B	17
10.4	Expression of results	18
10.5	Precision	18
11	Determination of ash at 850 °C to 900 °C	18
11.1	Principle	18
11.2	Apparatus	18
11.3	Procedure	18
11.4	Expression of results	19
11.5	Precision	19
12	Determination of acidity	19
13	Determination of arsenic content	19
14	Test report	19
Annex A (informative)	Typical values of the properties of sulfur used as a rubber compounding ingredient	21
Annex B (informative)	Precision	23
Bibliography		26

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 3, *Raw materials (including latex) for use in the rubber industry*.

This fifth edition cancels and replaces the fourth edition (ISO 8332:2011), which has been technically revised. The main changes are the following:

- Change in the Scope to indicate that some of the properties can be determined by more than one test method.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Sulfur appears in three allotropic forms:

- a) rhombic;
- b) monoclinic;
- c) amorphous (insoluble in CS₂).

In rubber compounding practice, forms a) and c) are used. Both types may be used in their natural form or may be coated. The coating can be oil, or MgCO₃, or silica, or some other material that aids dispersion in the rubber compound. Sulfur is available in varying degrees of fineness.

Amorphous sulfur (insoluble sulfur) is usually produced in industry through the rapid cooling of molten sulfur and can also contain rhombic sulfur (soluble sulfur), as insoluble sulfur tends to revert back to the rhombic state on storage. Insoluble sulfur is important in the rubber industry as a vulcanizing agent since, when it is used, it can prevent rubber compounds from blooming during storage or during a production process without any adverse impact on the vulcanization process. Grades containing various amounts of insoluble sulfur are available to control blooming today (see [Annex A](#)).

Rubber compounding ingredients — Sulfur — Methods of test

WARNING — Persons using this document should be familiar with normal laboratory practice. This document does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to ensure compliance with any national regulatory conditions.

1 Scope

This document specifies methods of test for determining the main physical and chemical properties of sulfur used for compounding dry rubber.

Several of these properties can be determined by more than one test method and the user can choose the most appropriate method following the description of the test method principles provided under the corresponding clauses.

NOTE Typical levels for the relevant properties of sulfur for use as a rubber compounding ingredient are contained in [Annex A](#), for information only.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 565, *Test sieves — Metal wire cloth, perforated metal plate and electroformed sheet — Nominal sizes of openings*

ISO 3704, *Sulphur for industrial use — Determination of acidity — Titrimetric method*

ISO 3705, *Sulphur for industrial use — Determination of arsenic content — Silver diethyldithiocarbamate photometric method*

ISO 4793, *Laboratory sintered (fritted) filters — Porosity grading, classification and designation*

ISO 15528, *Paints, varnishes and raw materials for paints and varnishes — Sampling*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Physical and chemical properties

After sampling with a stainless-steel sampling tool in accordance with ISO 15528, the physical and chemical properties of sulfur used as a rubber compounding ingredient shall be determined by the following test methods.