## **INTERNATIONAL STANDARD**

Third edition 2018-11

# **Optics and photonics — Lasers and** laser-related equipment — Test methods for laser beam power (energy) density distribution

phot Add faise. Optique et photonique — Lasers et équipements associés aux lasers — Méthodes d'essai de distribution de la densité de puissance (d'énergie) du faisceau laser



Reference number ISO 13694:2018(E)



#### © ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

## Contents

| Fore  | word   |   | iv         |  |  |  |
|-------|--|---|------------|--|--|--|
| Intro | oduction   |   | <b>v</b>   |  |  |  |
| 1     | Scope  |   |            |  |  |  |
| 2     | Norma  | mative references   |            |  |  |  |
| 3     | Terms and definitions3.1Measured quantities3.2Characterizing parameters  |   |            |  |  |  |
| 4     | Coordinate system  |   |            |  |  |  |
| 5     | Characterizing parameters derived from the measured spatial distribution |   |            |  |  |  |
| 6     | Test principle   |   |            |  |  |  |
| 7     | <b>Measu</b><br>7.1<br>7.2<br>7.3<br>7.4<br>7.5                          | General<br>Preparation<br>Control of environment<br>Detector system<br>Beam-forming optics, optical attenuators, and beam splitters | 8<br>8<br> |  |  |  |
| 8     | <b>Test p</b><br>8.1<br>8.2<br>8.3                                       | <ul> <li>8.2 Detector calibration procedure</li> <li>8.2.1 Spatial calibration</li> <li>8.2.2 Power (energy) calibration</li> </ul> |            |  |  |  |
| 9     | Evalua   | Evaluation  |            |  |  |  |
| 10    | Test report  |   |            |  |  |  |
| Anne  | ex A (info   | ormative) Test report   |            |  |  |  |
|       | Bibliography   |   |            |  |  |  |
|       |  |   |            |  |  |  |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see <u>www.iso</u> .org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 172, *Optics and photonics*, Subcommittee SC 9, *Laser and electro-optical systems*.

This third edition cancels and replaces the second edition (ISO 13694:2015), which has been technically revised. The main changes compared to the previous edition are as follows:

- a) the definition of beam ellipticity has been harmonized with ISO 11145 and ISO 11146-1;
- b) the term "second linear moments" has been replaced by "second moments";
- c) the term "field of view" has been replaced by "aperture";
- d) <u>Clause 9</u> was rewritten; the paragraphs on clip-levels were corrected to reflect that they are no longer intended for noise cancelation;
- e) the entries "Fitted distribution type", "Roughness of fit R", and "Goodness of fit G" have been removed from the Test Report;
- f) the term "aspect ratio" has been removed from the test report.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

## Introduction

Many applications of lasers involve using the near-field as well as the far-field power (energy) density distribution of the beam. The power (energy) density distribution of a laser beam is characterized by the spatial distribution of irradiant power (energy) density with lateral displacement in a particular plane perpendicular to the direction of propagation. In general, the power (energy) density distribution of the beam changes along the direction of propagation. Depending on the power (energy), size, wavelength, polarization, and coherence of the beam, different methods of measurement are applicable in different situations. Five methods are commonly used: camera arrays (1D and 2D), apertures, pinholes, slits, and knife edges.

According to ISO 11145, it is possible to use two different definitions for describing and measuring the laser beam diameter. One definition is based on the measurement of the encircled power (energy); the other is based on determining the spatial moments of the power (energy) density distribution of the laser beam.

The use of spatial moments is necessary for calculating the beam propagation factor, K, and the beam propagation ratio,  $M^2$ , from measurements of the beam widths at different distances along the propagation axis. ISO 11146-1 describes this measurement procedure. For other applications, other definitions for the beam diameter can be used. For some quantities used in this document the first definition (encircled power (energy)) is more appropriate and easier to use.

| Q |       |   |    |   |
|---|-------|---|----|---|
|   | R Z O |   |    |   |
|   |       |   |    |   |
|   |       | 0 | C  |   |
|   |       |   | 0  |   |
|   |       |   | J. |   |
|   |       |   |    | S |

this document is a preview demension of the document is a preview demension of the document oc

## Optics and photonics — Lasers and laser-related equipment — Test methods for laser beam power (energy) density distribution

## 1 Scope

This document specifies methods by which the measurement of power (energy) density distribution is made and defines parameters for the characterization of the spatial properties of laser power (energy) density distribution functions at a given plane.

The methods given in this document are intended to be used for the testing and characterization of both continuous wave (cw) and pulsed laser beams used in optics and optical instruments.

This document provides definitions of terms and symbols to be used in referring to power density distribution, as well as requirements for its measurement. For pulsed lasers, the distribution of time-integrated power density (i.e. energy density) is the quantity most often measured.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11145, Optics and photonics — Laser and laser-related equipment — Vocabulary and symbols

ISO 11146-1, Lasers and laser-related equipment — Test methods for laser beam widths, divergence angles and beam propagation ratios — Part 1: Stigmatic and simple astigmatic beams

ISO 11554, Optics and photonics — Lasers and laser-related equipment — Test methods for laser beam power, energy and temporal characteristics

IEC 61040, Power and energy measuring detectors, instruments and equipment for laser radiation

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11145 and IEC 61040 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <u>http://www.iso.org/obp</u>
- IEC Electropedia: available at http://www.electropedia.org/

#### 3.1 Measured quantities

#### 3.1.1

#### power density distribution

E(x, y, z)

set of all power densities at location z of a certain cw beam with non-negative values for all transverse coordinates (x, y)