



Edition 2.0 2008-05

INTERNATIONAL STANDARD

NORME INTERNATIONALE

BASIC SAFETY PUBLICATION

PUBLICATION FONDAMENTALE DE SÉCURITÉ

Environmental testing – Part 2-31: Tests – Test Ec: Rough handling shocks, primarily for equipment-type specimens

Essais d'environnement –

Partie 2-31: Essais – Essai Ec: Choc lié à des manutentions brutales, essai destiné en premier lieu aux matériels



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur. Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

IEC Just Published: www.iec.ch/online news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: <u>www.iec.ch/webstore/custserv</u>

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: <u>csc@iec.ch</u> Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

Electropedia: <u>www.electropedia.org</u>

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

Service Clients: <u>www.iec.ch/webstore/custserv/custserv_entry-f.htm</u>

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: <u>csc@iec.ch</u> Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00





Edition 2.0 2008-05

INTERNATIONAL STANDARD

NORME INTERNATIONALE

BASIC SAFETY PUBLICATION

PUBLICATION FONDAMENTALE DE SÉCURITÉ

Environmental testing – Part 2-31: Tests – Test Ec: Rough handling shocks, primarily for equipment-type

specimens

Essais d'environnement – Partie 2-31: Essais – Essai Ec: Choc lié à des manutentions brutales, essai destiné en premier lieu aux matériels

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE



tonor of of the t

ICS 19.040

ISBN 2-8318-9794-7

CONTENTS

FO	REWO	ORD		3	
1	Scop	e		5	
2	Normative references				
3	General description of test				
4	Initial measurements				
5	Testing				
-	5.1	Drop and topple			
	0.1		Description		
		5.1.2	Test Facility		
		5.1.3	Testing procedures		
	5.2		all – Procedure 1		
		5.2.1	Description		
		5.2.2	Test Facility		
		5.2.3	Test severity	9	
		5.2.4	Testing procedures	9	
	5.3	Free fa	all repeated – Procedure 2		
		5.3.1	Description	10	
		5.3.2	Test facility		
		5.3.3	Test severity	10	
		5.3.4	Testing procedure	10	
6	Final	measu	irements	10	
7	Information to be included in the relevant specification				
	7.1	Drop a	and topple test	11	
	7.2	Free f	all and free fall repeated tests	11	
8	Infor	mation	to be given in the test report	11	
Anr	nex A	(norma	tive) Test apparatus for repeated free fall test - Procedure 2		
			ative) Selection of test severities for free fall tests - Guidance .		
Fig	ure 1	– Dropi	ping on to a face	7	
Fia	ure 2	- Dropr	ping on to a corner		
Fig		– Toppi	le (or push over)	7	
Figure A.1 – Rotating (or tumbling) barrel					
гıg	ure A.	. I – RUI		14	
Tab	ole 1 -	- Fall he	eights versus mass	9	
			mples of typical test severities	16	
, at	, io D.				
				To la	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ENVIRONMENTAL TESTING –

Part 2-31: Tests – Test Ec: Rough handling shocks, primarily for equipment-type specimens

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60068-2-31 has been prepared by IEC technical committee 104: Environmental conditions, classification and methods of test.

This second edition cancels and replaces the first edition, published in 1969 and constitutes a technical revision.

The major changes with regard to the previous edition concern the introduction of soft packaging tests, where appropriate. This new edition of IEC 60068-2-31 now incorporates the second edition of IEC 60068-2-32 (1975).

IEC 60068-2-32 will be withdrawn once this standard has been issued.

The text of this standard is based on the following documents:

FDIS	Report on voting	
104/458/FDIS	104/462/RVD	

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

It has the status of a basic safety publication in accordance with IEC Guide 104.

A list of all the parts in the IEC 60068 series, under the general title Environmental testing, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed, •
- withdrawn, •
- Orchick Concrete of the officer officer of the officer replaced by a revised edition, or
- amended.

ENVIRONMENTAL TESTING -

Part 2-31: Tests – Test Ec: Rough handling shocks, primarily for equipment-type specimens

1 Scope

This part of IEC 60068 deals with a test procedure for simulating the effects of rough handling shocks, primarily in equipment-type specimens, the effects of knocks, jolts and falls which may be received during repair work or rough handling in operational use.

This procedure does not simulate the effects of impacts received during transportation as loosely constrained cargo. Where the effects of loose cargo transportation are to be assessed, test Ee: Bounce should be used. Also this procedure does not simulate the effects of shock applied to installed equipments. Where this effect is to be assessed refer to test Ea: Shock.

Testing should only be specified for equipment likely to receive such rough handling, for example those of small to medium size and mass, and should only be applied to those faces and corners where there is a risk of such treatment being encountered.

In general, equipment which is frequently handled and serviced (for example field equipment and unit spares) can be considered at risk, whereas equipment forming an integral part of a permanent installation would not normally be considered at risk and need not be tested.

Testing may not be applicable to fragile unprotected equipment of irregular shape (for example aircraft nose radar) which, when removed from the installation would be contained in a handling frame or jig. It may however be applicable to these items of equipment when they are in their transit case or in their handling frame or jig.

For equipment which stands only on one face (for example the normal base) the test is generally only applied to that face.

Shock tests are performed on the specimen when fixed to the test machine. Drop and topple, free fall, repeated free fall and bounce tests are performed with the specimen free.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-27, Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock

IEC 60068-2-55:1987, Environmental testing – Part 2-55: Tests – Test Ee and guidance: Bounce

IEC Guide 104, *The preparation of safety publications and the use of basic safety publications and group safety publications*

ISO 48:2007, Rubber, vulcanized or thermoplastic – Determination of hardness (hardness between 10 IRHD and 100 IRHD)

ISO 4180-2:1980, Complete, filled transport packages – General rules for the compilation of performance test schedules – Part 2: Quantitative data

3 General description of test

Rough handling shocks can be simulated by one or more of the following tests:

a) Drop and topple

A simple test intended to assess the effects of knocks or jolts likely to be received primarily by equipment-type specimens during repair work or rough handling on a table or bench.

b) Free fall – Procedure 1

A simple test to assess the effects of falls likely to be experienced due to rough handling. It is also suitable to demonstrate a degree of robustness.

c) Free fall – Procedure 2

A test that additionally simulates repetitive shocks likely to be received by certain component-type specimens, for example connectors in service.

The topple test need not be applied to specimens which have dimensions which make them stable whilst being handled. Reference to points 1) and 2) below should be made for information on the "c - g ratio" and "height ratio" to establish if the test is necessary.

The falling or topple actions produced by the test procedures given in 5.1.3.1, 5.1.3.2 and 5.1.3.3 are illustrated by Figures 1, 2 and 3.

The drop and topple test includes three distinct procedures:

- i) dropping on to a face (5.1.3.1);
- ii) dropping on to an edge or a corner (5.1.3.2);
- iii) toppling (or pushover) (5.1.3.3).

The purpose of each of these procedures is basically the same, but they represent different kinds of handling.

The test is not intended to be a precise test and a tolerance of ± 10 % is allowed on the heights and angles prescribed in 5.1.2.

NOTE For a more precise shock test, test Ea: Shock (IEC 60068-2-27) should be used.

The topple test need not be applied to specimens which have dimensions which make them stable while being handled. When considering the applicability of the topple test, two dimensional ratios are important:

- 1) the ratio of the height of the centre of gravity from the base, to the smaller dimension of the base, hereinafter referred to as the c g ratio;
- 2) the ratio of the height of the specimen to the smaller dimension of the base, hereinafter referred to as the height ratio.

If the c - g ratio is small, for example less than 0,25, the specimen is unlikely to fall over due to sudden sideways displacements. If the height ratio is small, for example less than 0,5, the specimen is unlikely to topple over due to a sudden sideways force or blow at the top. In such cases the writer of the relevant specification should consider whether the topple test is applicable.