

**Fibre optic active components and devices -
Performance standards - Part 4: 1300 nm fibre optic
transceivers for Gigabit Ethernet application**

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 62149-4:2010 sisaldb Euroopa standardi EN 62149-4:2010 ingliskeelset teksti.	This Estonian standard EVS-EN 62149-4:2010 consists of the English text of the European standard EN 62149-4:2010.
Standard on kinnitatud Eesti Standardikeskuse 31.08.2010 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.	This standard is ratified with the order of Estonian Centre for Standardisation dated 31.08.2010 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.
Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kätesaadavaks tegemise kuupäev on 04.06.2010.	Date of Availability of the European standard text 04.06.2010.
Standard on kätesaadav Eesti standardiorganisatsionist.	The standard is available from Estonian standardisation organisation.

ICS 33.180.20

Võtmesõnad:

Standardite reproduutseerimis- ja levitamisõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:
Aru 10 Tallinn 10317 Estonia; www.evs.ee; Telefon: 605 5050; E-post: info@evs.ee

Right to reproduce and distribute belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact Estonian Centre for Standardisation:
Aru str 10 Tallinn 10317 Estonia; www.evs.ee; Phone: 605 5050; E-mail: info@evs.ee

English version

**Fibre optic active components and devices -
Performance standards -**

**Part 4: 1 300 nm fibre optic transceivers for Gigabit Ethernet application
(IEC 62149-4:2010)**

Composants et dispositifs actifs à fibres
optiques -
Normes de fonctionnement -
Partie 4: Emetteurs-récepteurs à fibres
optiques de 1 300 nm pour application
Gigabit Ethernet
(CEI 62149-4:2010)

Aktive Lichtwellenleiterbauelemente
und -geräte -
Betriebsverhalten -
Teil 4: 1 300-nm-Lichtwellenleiter-Sende-
und Empfangsmodule für Gigabit-
Ethernet-Anwendungen
(IEC 62149-4:2010)

This European Standard was approved by CENELEC on 2010-06-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 86C/912/CDV, future edition 2 of IEC 62149-4, prepared by SC 86C, Fibre optic systems and active devices, of IEC TC 86, Fibre optics, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62149-4 on 2010-06-01.

This European Standard supersedes EN 62149-4:2003.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2011-03-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2013-06-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 62149-4:2010 was approved by CENELEC as a European Standard without any modification.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60068-2-6	-	Environmental testing - Part 2-6: Tests - Test Fc: Vibration (sinusoidal)	EN 60068-2-6	-
IEC 60068-2-20	-	Environmental testing - Part 2-20: Tests - Test T: Test methods for solderability and resistance to soldering heat of devices with leads	EN 60068-2-20	-
IEC 60068-2-27	-	Environmental testing - Part 2-27: Tests - Test Ea and guidance: Shock	EN 60068-2-27	-
IEC 60068-2-38	-	Environmental testing - Part 2-38: Tests - Test Z/AD: Composite temperature/humidity cyclic test	EN 60068-2-38	-
IEC 60068-2-78	-	Environmental testing - Part 2-78: Tests - Test Cab: Damp heat, steady state	EN 60068-2-78	-
IEC 60749-25	-	Semiconductor devices - Mechanical and climatic test methods - Part 25: Temperature cycling	EN 60749-25	-
IEC 60749-26	-	Semiconductor devices - Mechanical and climatic test methods - Part 26: Electrostatic discharge (ESD) sensitivity testing - Human body model (HBM)	EN 60749-26	-
IEC 60825-1	-	Safety of laser products - Part 1: Equipment classification and requirements	EN 60825-1	-
IEC 60938-1	-	Fixed inductors for electromagnetic interference suppression - Part 1: Generic specification	EN 60938-1	-
IEC 60950-1 (mod)	2001	Information technology equipment - Safety - Part 1: General requirements	EN 60950-1 + corr. December + A11	2001 2007 2004
IEC 61300-2-47	-	Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-47: Tests - Thermal shocks	EN 61300-2-47	-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ISO/IEC 8802-3	2000	Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications	EN/HD	-

This document is a preview generated by EVS

CONTENTS

FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Symbols and abbreviated terms	7
3.1 Symbols	7
3.2 Abbreviated terms	7
4 Product parameters	8
4.1 Absolute limiting ratings	8
4.2 Operating environment	8
4.3 Functional specification	8
4.4 Diagrams	10
4.5 Labelling	11
5 Testing	11
5.1 General	11
5.2 Characterization testing	11
5.3 Performance testing	12
5.3.1 Sequence of testing	12
5.3.2 Sample size, sequencing and groupings	12
6 Environmental specifications	14
6.1 General safety	14
6.2 Laser safety	14
6.3 Electromagnetic emission	14
Annex A (normative) Sample size, sequencing and grouping requirements	15
 Figure 1 – Receiver section schematic	10
Figure 2 – Transmitter section schematic	11
 Table 1 – Absolute limiting ratings	8
Table 2 – Operating environment	8
Table 3 – Receiver section: functional specification	9
Table 4 – Transmitter section: functional specification	10
Table 5 – Transmitter section characterization tests	12
Table 6 – Receiver section characterization tests	12
Table 7 – Performance test plan	13

INTRODUCTION

Fibre optic transceivers are used to convert electrical signals into optical signals and vice versa. This specification covers the performance standard for 1 300 nm fibre optic transceivers for Gigabit Ethernet application. The ISO/IEC 8802-3 Gigabit Ethernet standard is used as the basis for determining the optical characteristics of the transceiver, which operates with a line rate of 1,25 Gbit/s.

FIBRE OPTIC ACTIVE COMPONENTS AND DEVICES – PERFORMANCE STANDARDS –

Part 4: 1 300 nm fibre optic transceivers for Gigabit Ethernet application

1 Scope

This part of IEC 62149 covers the performance specification for 1 300 nm fibre optic transceiver modules used for the ISO/IEC 8802-3 Gigabit Ethernet application. The performance standard contains a definition of the product performance requirements together with a series of sets of tests and measurements with clearly defined conditions, severities, and pass/fail criteria. The tests are intended to be run on a “once-off” basis to prove any product’s ability to satisfy the performance standard’s requirements.

A product that has been shown to meet all the requirements of a performance standard can be declared as complying with the performance standard, but should then be controlled by a quality assurance/quality conformance program.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-6, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-20, *Environmental testing – Part 2-20: Tests – Test T: Test methods for solderability and resistance to soldering heat of devices with leads*

IEC 60068-2-27, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*

IEC 60068-2-38, *Environmental testing – Part 2-38: Tests – Test Z/AD: Composite temperature/humidity cyclic test*

IEC 60028-2-78, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

IEC 60749-25, *Semiconductor devices – Mechanical and climatic test methods – Part 25: Temperature cycling*

IEC 60749-26, *Semiconductor devices – Mechanical and climatic test methods – Part 26: Electrostatic discharge (ESD) sensitivity testing – Human body model (HBM)*

IEC 60825-1, *Safety of laser products – Part 1: Equipment classification and requirements*

IEC 60938-1, *Fixed inductors for electromagnetic interference suppression – Part 1: Generic specification*

IEC 60950-1:2001, *Information technology equipment – Safety – Part 1: General requirements*

IEC 61300-2-47, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-47: Tests – Thermal shocks*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

3 Symbols and abbreviated terms

For the purposes of this document the following symbols and abbreviations apply.

3.1 Symbols

E_r	extinction ratio
RH	relative humidity
I_{IL}	data input current – low
I_{IH}	data input current – high
I_{out}	output current
P_o	optical output power
P_d	alarm on level
P_a	alarm off level
R_{DL}	data output load
S	receiver sensitivity
TD	transmit disable function
T_{amb}	ambient operating temperature
T_{stg}	storage temperature
T_f	data output fall time
T_r	data output rise time
V_{cc}	power supply voltage
$V_{IL} - V_{cc}$	data input voltage – low
$V_{IH} - V_{cc}$	data input voltage – high
V_{oh}	alarm output high voltage
V_{ol}	alarm output low voltage
$V_{ol} - V_{cc}$	data output voltage – low
$V_{oh} - V_{cc}$	data output voltage – high
V_{pp}	transmitter differential input voltage swing
λ_{ce}	central wavelength
$\Delta\lambda$	spectral width (r.m.s.)

3.2 Abbreviated terms

ESD	electrostatic discharge
HBM	human body model