

**Railway applications - Automated urban guided  
transport (AUGT) - Safety requirements**

This document is a preview generated by EVS

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 62267:2010 sisaldab Euroopa standardi EN 62267:2009 ingliskeelset teksti.

Standard on kinnitatud Eesti Standardikeskuse 28.02.2010 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.

Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kättesaadavaks tegemise kuupäev on 04.12.2009.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN 62267:2010 consists of the English text of the European standard EN 62267:2009.

This standard is ratified with the order of Estonian Centre for Standardisation dated 28.02.2010 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.

Date of Availability of the European standard text 04.12.2009.

The standard is available from Estonian standardisation organisation.

ICS 45.060

### Standardite reprodutseerimis- ja levitamiseõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:  
Aru 10 Tallinn 10317 Eesti; [www.evs.ee](http://www.evs.ee); Telefon: 605 5050; E-post: [info@evs.ee](mailto:info@evs.ee)

### Right to reproduce and distribute Estonian Standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact Estonian Centre for Standardisation:  
Aru str 10 Tallinn 10317 Estonia; [www.evs.ee](http://www.evs.ee); Phone: +372 605 5050; E-mail: [info@evs.ee](mailto:info@evs.ee)

**Railway applications -  
Automated urban guided transport (AUGT) -  
Safety requirements  
(IEC 62267:2009)**

Applications ferroviaires -  
Transports guidés  
urbains automatiques (AUGT) -  
Exigences de sécurité  
(CEI 62267:2009)

Bahnanwendungen - Automatischer  
städtischer schienengebundener  
Personennahverkehr (AUGT) -  
Sicherheitsanforderungen  
(IEC 62267:2009)

This European Standard was approved by CENELEC on 2009-10-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: Avenue Marnix 17, B - 1000 Brussels**

## Foreword

The text of document 9/1261/FDIS, future edition 1 of IEC 62267, prepared by IEC TC 9, Electrical equipment and systems for railways, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62267 on 2009-10-01.

The following dates were fixed:

- latest date by which the EN has to be implemented  
at national level by publication of an identical  
national standard or by endorsement (dop) 2010-07-01
- latest date by which the national standards conflicting  
with the EN have to be withdrawn (dow) 2012-10-01

Annex ZA has been added by CENELEC.

---

## Endorsement notice

The text of the International Standard IEC 62267:2009 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61508	NOTE Harmonized in EN 61508 series (not modified).
IEC 62128-1	NOTE Identical to EN 50122-1:1997.
IEC 62236	NOTE In Europe, the series EN 50121 applies.
IEC 62279	NOTE In Europe, EN 50128 applies.

---

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Where a standard cited below belongs to the EN 50000 series, this European Standard applies instead of the relevant International Standard.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 62278	2002	Railway applications - Specification and demonstration of reliability, availability, maintainability and safety (RAMS)	EN 50126-1 + corr. May	1999 2006
IEC 62290-1	- <sup>1)</sup>	Railway applications - Urban guided transport management and command/control systems - Part 1: System principles and fundamental concepts	EN 62290-1	2006 <sup>2)</sup>
IEC 62425	- <sup>1)</sup>	Railway applications - Communication, signalling and processing systems - Safety related electronic systems for signalling	EN 50129	2003 <sup>2)</sup>

---

<sup>1)</sup> Undated reference.

<sup>2)</sup> Valid edition at date of issue.

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	10
3 Terms, definitions and abbreviations .....	10
3.1 Terms and definitions .....	11
3.2 Abbreviations .....	13
4 Methodology.....	13
4.1 System definition and application conditions .....	14
4.2 Hazard analysis at top system level.....	14
4.3 Safety requirements .....	14
5 System description .....	14
5.1 Station .....	15
5.2 Train .....	15
5.3 Guideway between stations .....	16
5.4 System boundaries.....	17
6 Entities to be protected.....	18
6.1 Persons.....	18
6.1.1 Passengers .....	18
6.1.2 Staff .....	18
6.1.3 External emergency services.....	19
6.1.4 Public .....	19
6.2 Property .....	19
7 Identified hazardous situations and possible safeguards .....	19
7.1 Supervising guideway.....	20
7.1.1 Prevent collisions with obstacles .....	20
7.1.2 Prevent collisions with persons.....	21
7.2 Supervising passenger transfer .....	23
7.2.1 Control passenger doors .....	23
7.2.2 Prevent injuries to persons between cars or between platform and train.....	23
7.2.3 Ensure safe starting conditions .....	24
7.3 Operating a train .....	25
7.3.1 Put in or take out of operation.....	25
7.3.2 Supervise the status of the train .....	26
7.4 Ensuring detection and management of emergency situations .....	27
8 Safety requirements .....	30
8.1 General requirements.....	30
8.1.1 Public works regulations to protect the guideway.....	30
8.1.2 Fire protection .....	31
8.1.3 Systems and equipment .....	31
8.1.4 Rules for passenger behaviour .....	32
8.2 Monitoring the AUGT system.....	32
8.2.1 Monitoring by the OCC staff .....	32
8.2.2 Action of operational staff.....	33
8.2.3 Communication systems .....	33

8.3	Operational rules.....	34
8.3.1	Rules for rescue of passengers .....	34
8.3.2	Rules for fire emergency.....	34
8.3.3	Rules for foreseeable vandalism.....	35
8.3.4	Rules for checking guideway clearance .....	35
8.3.5	Rules for start-up and shut down of operations .....	35
8.3.6	Rules for train operations in the depot .....	36
8.3.7	Rules for trains to be put in or taken out of operation.....	36
8.3.8	Rules for stranded train removal.....	36
8.4	Safeguards on platforms .....	36
8.4.1	Common safeguards for enclosed and open platforms.....	37
8.4.2	Enclosed platforms .....	39
8.4.3	Open platforms with detection systems.....	41
8.5	Safeguards in trains .....	41
8.5.1	Door closed supervision .....	42
8.5.2	Door release for passenger transfer .....	42
8.5.3	Door release for emergency opening .....	43
8.5.4	Emergency exits .....	43
8.5.5	On board obstacle detection device .....	43
8.5.6	Derailment detection device .....	43
8.5.7	On board video surveillance .....	44
8.5.8	Public address system (train) .....	44
8.5.9	On board announcement for taking a train out of operation.....	44
8.5.10	Emergency stop demand on board .....	44
8.5.11	Emergency call device on board .....	45
8.5.12	Fire and smoke detection (train) .....	45
8.5.13	Train status supervision and testing.....	45
8.5.14	Manual operation.....	46
8.5.15	Safe speed during automatic coupling .....	46
8.5.16	Reaction to unexpected train movement .....	46
8.5.17	Warning means in the train for evacuation .....	46
8.6	Safeguards for passenger transfer area.....	46
8.6.1	Train immobilisation during passenger transfer.....	47
8.6.2	Safeguards related to the opening of the doors.....	47
8.6.3	Safeguards related to the closing of the doors .....	47
8.6.4	Marking of train door areas on the platform .....	48
8.6.5	Surveillance by operational staff.....	49
8.6.6	Safeguards related to gap between train and platform .....	49
8.6.7	Safeguards related to coupling area between cars.....	51
8.6.8	Safeguards related to space between train and platform screen .....	51
8.6.9	Safeguards to protect passengers from electrocution after falling into the gap .....	51
8.7	Safeguards for guideway .....	51
8.7.1	Segregated guideway .....	52
8.7.2	Warning means along the guideway .....	52
8.7.3	Physical barriers along the track.....	52
8.7.4	Physical barriers beside bridges .....	52
8.7.5	Intrusion detection device between platform track and guideway between stations .....	52

8.7.6	Guideway intrusion detection device .....	53
8.7.7	Wayside obstacle detection device .....	53
8.7.8	Platform end door with controlled access .....	53
8.7.9	Emergency exit from physically segregated guideway .....	53
8.7.10	Fire and smoke detection (guideway between stations) .....	53
8.7.11	Water flooding protection .....	54
8.7.12	Level crossing .....	54
8.7.13	Work zones .....	55
8.8	Safeguards for transfer areas and depots .....	55
9	Information for use .....	56
10	Specific safety requirements for upgrading existing lines to DTO or UTO .....	56
11	Verification of safety .....	57
11.1	Documentation and responsibilities .....	58
11.2	Verification process .....	58
Annex A (informative)	Role of the OCC .....	60
Bibliography	.....	61
Figure 1	– Life Cycle Phases covered by this standard (see Figure 10 of IEC 62278) .....	13
Figure 2	– Boundary of the station subsystem .....	15
Figure 3	– Boundary of the “guideway between stations” subsystem .....	16
Figure 4	– Boundary of the “guideway between stations” subsystem with level crossing .....	17
Figure 5	– Boundary of the “guideway between stations” subsystem with sidings .....	17
Figure 6	– Verification of safety .....	58
Figure A.1	– Role of the OCC in the safety of the system .....	60
Table 1	– Grades of automation .....	9
Table 2	– Prevent collisions with obstacles .....	20
Table 3	– Prevent collisions with persons .....	21
Table 4	– Prevent injuries to persons associated with opening and closing passenger transfer doors .....	23
Table 5	– Prevent injuries to persons between cars or between platform and train .....	24
Table 6	– Prevent passenger injury during train starting .....	25
Table 7	– Prevent harm to passengers in relation to taking the train out of operation or putting the train in operation .....	26
Table 8	– Prevent injury to person resulting from train failures .....	26
Table 9	– Prevent injury to persons related to emergency situations .....	27



## INTRODUCTION

This International Standard is a generic guideline providing recommendations to assist railway authorities and safety regulatory authorities to define safety requirements appropriate to AUGT systems. The generic requirements recommended in this standard are based on the experience gained from AUGT systems already in operation. Safety requirements for each specific application, however, can only be defined from the results of a risk analysis, taking into consideration the conditions in which the AUGT system is to be set up and based on the risk acceptance principles prevailing in the local environment. The standard applicable for conducting a mandatory and comprehensive risk analysis of an AUGT system is IEC 62278 (RAMS).

In view of the diversity of the technical solutions that may be adopted for new AUGT systems and the diversity of operational conditions, the list of generic hazardous situations considered in this standard should be regarded as a minimum list. The requirements for a safeguard as described in this standard are intended as minimum requirements in case a specific safeguard is applied to mitigate the related hazardous situation. However, the specific risk analysis may show that some requirements of a chosen safeguard should be modified to take into account some specific conditions. Each specific design of the new AUGT system and each aspect of the specific topographic, environmental, social or legal environment of the new AUGT system can also generate new hazards and therefore may require additional safety requirements. A specific hazard analysis to identify additional requirements or requirements to be modified is therefore always a necessity.

This standard, therefore, does not and could not prescribe any specific means that could, without a fail, mitigate risks arising from hazardous situations. Rather, it identifies a list of foreseeable hazardous situations, derived from the elementary consideration that functions assumed by the driver and staff in conventional systems are replaced in AUGT systems by automated functions or other safeguards. It is the purpose of this standard that this list of hazardous situations should be carefully considered during the risk analysis carried out for any new AUGT system.

In addition to generic hazardous situations, this standard also describes possible and widely implemented safeguards that the specific risk analysis may well show to be adapted to the specific application.

It should be noted that not all hazardous situations identified in the context of one or other of the large number of different AUGT systems already in operation in the world have necessarily been covered in this standard. Nor would it have been necessarily helpful. Neither could this standard describe all the possible safeguards demanded by each and every specific application.

This standard does not require that a safeguard be put in place for every generic hazardous situation identified. This is because often, the risk associated with a hazardous situation may be assessed as tolerable without the need for a safeguard. According to IEC 62278, it is the responsibility of the railway authority, in agreement with the Safety Regulatory Authority having jurisdiction, to decide on the tolerability of each risk and on the necessity of a specific safeguard, taking into account their specific risk acceptance criteria and legal requirements that are applicable for the specific AUGT application.

# RAILWAY APPLICATIONS – AUTOMATED URBAN GUIDED TRANSPORT (AUGT) – SAFETY REQUIREMENTS

## 1 Scope

This International Standard covers high-level safety requirements applicable to automated urban guided transport systems, with driverless or unattended self-propelled trains, operating on an exclusive guideway.

This standard only deals with the safety requirements needed to compensate for the absence of a driver or attendant staff who would otherwise be responsible for some or all of train operation functions (see Table 1), depending on the level of automation of the system (see shaded areas in Table 1 and see 3.1 for a definition of the different grades of automation).

The requirements of this standard are restricted to transports systems as defined in Clause 5 and to DTO and UTO as defined in 3.1.4 and 3.1.20, respectively (see the shaded areas in Table 1).

Table 1 – Grades of automation

Basic functions of train operation		On-sight train operation	Non- automated train operation	Semi- automated train operation	Driverless train operation	Unattended train operation
		TOS	NTO	STO	DTO	UTO
		GOA0	GOA1	GOA2	GOA3	GOA4
Ensuring safe movement of trains	Ensure safe route	X (points command/ control in system)	S	S	S	S
	Ensure safe separation of trains	X	S	S	S	S
	Ensure safe speed	X	X (partly supervised by system)	S	S	S
Driving	Control acceleration and braking	X	X	S	S	S
Supervising guideway	Prevent collision with obstacles	X	X	X	S	S
	Prevent collision with persons	X	X	X	S	S
Supervising passenger transfer	Control passengers doors	X	X	X	X or S	S
	Prevent injuries to persons between cars or between platform and train	X	X	X	X or S	S
	Ensure safe starting conditions	X	X	X	X or S	S
Operating a train	Put in or take out of operation	X	X	X	X	S
	Supervise the status of the train	X	X	X	X	S
Ensuring detection and management of emergency situations	Perform train diagnostic, detect fire/smoke and detect derailment, handle emergency situations (call/evacuation, supervision)	X	X	X	X	S and/or staff in OCC
NOTE						
X = responsibility of operations staff (may be realised by technical system).						
S = realised by technical system.						

This standard does not specifically look at security issues. However, aspects of safety requirements may apply to assuring security within the transport system.

NOTE The definitions of “security” and “safety” are given by IEC 62278.

Application of this standard is subsidiary to the responsibility of the transport authority and the safety regulatory authority (see IEC 62278) and to the specific laws and decrees applicable within the prevailing environment (economic, social, political, etc.) where the transport system is located, taking into account:

- social risk acceptance in different cultures or different national legal regulations (e.g. SHOREI, BOStrab) or principles (e.g. GAME, ALARP);
- laws and decrees in different states;
- special or different requirements specified by the safety regulatory authority or by an independent assessor in charge of the specific application;

- the responsibility for "safe operation" by the transport authority.

This standard does not apply to the following types of transport systems, unless specifically required by the Transport Authority:

- APMs (Automated People Movers) operating entirely inside a privileged environment such as an airport, a commercial centre or a leisure resort;
- amusement rides and roller-coasters, generally featuring a single station so that passengers board and alight the system at the same location;
- intercity and mainline train services, generally operating in a rural environment on part of their routes;
- cable-driven systems;
- systems featuring electronically guided vehicles with optical sensors, magnetic sensors, or similar devices/systems.

This standard is not concerned with risks arising during works for construction, installation, modification and dismantling of a system.

This standard is not concerned with pre-existing DTO or UTO systems (see definitions in 3.1) that were designed before this standard took effect.

In the case of upgrading an existing transport system to a DTO or UTO system, the risks associated with the existing system are outside the scope of this standard. However, this standard and the risk analysis process described are relevant for the additional subsystems and possibly for the transition process itself. Therefore, the application of the standard is at the discretion of the safety regulatory authority.

In the case of extending or modifying an existing DTO or UTO system in operation, this standard applies only if the change is significant as determined by the safety regulatory authority. However, the risks due to the relationship with the unchanged parts of existing systems (e.g. rolling stock, traction power supply, signalling and platforms) should be taken into account.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62278:2002, *Railway applications – Specification and demonstration of reliability, availability, maintainability and safety (RAMS)*

IEC 62290-1, *Railway applications – Urban guided transport management and command/control systems – Part 1: System principles and fundamental concepts*

IEC 62425, *Railway applications – Communication, signalling and processing systems – Safety related electronic systems for signalling*

## 3 Terms, definitions and abbreviations

For the purposes of this document, the following terms, definitions and abbreviations apply.