



Edition 3.0 2009-01

# INTERNATIONAL STANDARD

Radio frequency and coaxial cable assemblies –
Part 3-1: Blank detail specification for semi-flexible coaxial cable assemblies





### THIS PUBLICATION IS COPYRIGHT PROTECTED

### Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Email: inmail@iec.ch Web: www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub
- The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.
- IEC Just Published: www.iec.ch/online news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

■ Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Centre: <a href="www.iec.ch/webstore/custserv">www.iec.ch/webstore/custserv</a>
If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us: 

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 3.0 2009-01

## INTERNATIONAL STANDARD

Radio frequency and coaxial cable assemblies –
Part 3-1: Blank detail specification for semi-flexible coaxial cable assemblies

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

K

ICS 33.120.10

ISBN 2-8318-1021-3

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### RADIO FREQUENCY AND COAXIAL CABLE ASSEMBLIES –

### Part 3-1: Blank detail specification for semi-flexible coaxial cable assemblies

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60966-3-1 has been prepared by IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This third edition cancels and replaces the second edition published in 2003 and constitutes a technical revision.

The major change with respect to the first edition is the reference to the third edition of the sectional specification.

This blank detail specification is to be read in conjunction with the second edition of IEC 60966-1 (1999) and with the third edition of IEC 60966-3 (2008).

The text of this standard is based on the following documents:

FDIS	Report on voting
46/306/FDIS	46/318/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60966 series, under the general title: Radio frequency and coaxial cable assemblies, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- · withdrawn,
- · replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

### INTRODUCTION

This part of IEC 60966 is a blank detail specification that relates to semi-flexible coaxial cable assemblies operating in the transverse electromagnetic mode (TEM).

The creation of a uniform layout and style of a detail specification is determined by the use of a blank detail specification pro forma. The detail specification may be prepared by the insertion of data into the pro forma by a national standards organization, by an approved manufacturer or by a user (when prepared by a user, the detail specification shall be submitted to the national authorized institution by an approved manufacturer).

Instructions to complete a blank detail specification:

Detail specifications should, as far as possible, be written in accordance with the pro forma which has:

- a front page with a general description and a drawing or isometric sketch of the cable assembly and its possible variants;
- ratings, characteristics and inspection requirements (those which are not required or specified shall be omitted).

Under quality assessment, tests are divided into groups. Whenever possible, entire groups are either specified or omitted.

### These groups are:

Ва	(basic)	Visual and dimensional tests
Eb	(electrical basic)	Low-frequency operational tests
Eh	(electrical high frequency)	High-frequency tests
Ep	(electrical phase)	Electrical length tests
Ee	(electrical screening effectiveness)	Screening effectiveness tests
Ez	(electrical impedance Z)	Impedance uniformity tests
Et	(electrical transmission)	Power rating test
Mn	(mechanical)	Mechanical tests
Vc	(environmental climatic)	Climatic tests
Vv	(environmental vibration)	Vibration, bumps and shock tests
Vt	(environmental temperature)	Humidity, rapid change of temperature and chemical tests
Vf	(environmental flammability)	Flammability dust and water immersion tests

The numbers shown in brackets on this page correspond to the following items of required information, which should be entered in the spaces provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number, issue number and date of issue.
- [3] Address of the organization from which the document is available.
- [4] Related documents.
- [5] Any other reference to the cable assembly, national reference, trade name, etc.
- [6] A drawing of the cable assembly giving the outline and principal dimensions. The dimensions are considered to be in millimetres unless otherwise specified.
  NOTE The symbol "I" may be used to specify the cable length. In this case, the detail specification covers cable assemblies of any length and "I" should then be specified in the order.
- [7] Nominal characteristic impedance of the cable assembly.
- [8] Frequency range of use of the cable assembly (DC may be used as a lower limit of frequency, indicating that the cable assembly is capable of transmitting d.c., but at d.c. a number of characteristics may neither apply nor be verified by inspection.)
- [9] Weight, function of the length of the cable assembly.
- [10] Minimum static inside bending radius of the cable assembly. Also minimum dynamic inside bending radius of the cable assembly, i.e. the bending radius used for the insertion loss and stability of electrical length tests.
- [11] Climatic category of the cable assembly related to IEC 60068.
- [12] The applicable quality assessment test groups according to Table 1 of the sectional specification (for example, Ba, Eh, Eb).
- [13] Description, of the components used for the manufacture of the cable assembly. When the components do not conform with the relevant publication(s), their relevant materials requirements shall be listed.
- [14] Variants of the cable assembly may be listed in one detail specification. The variants may differ by colour, connector material, connector sex or type. (Inspection for quality conformance will be the same for all variants whereas the ratings and characteristics can change.)
- [15] Number of pages of the blank detail specification including the annexes.
- [16] Ratings and characteristics of the cable assembly. The properties not specified should be omitted.
- [17] Reference to the appropriate subclause in the sectional and generic specifications.
- [18] The value either guaranteed or used for the defined test.
- [19] All information required by the sectional specification and any remarks considered as important for understanding the test.
- [20] Test groups (corresponding to box [12] on page 1 of the blank detail specification).
- [21] Name of test and its subclause number in the sectional and generic specifications.
- [22] Periodicity of the test. The periodic tests apply only in the case of qualification approval.
- [23] Inspection level selected from IEC 60410.

- [24] Acceptable quality level selected from IEC 60410.
- [25] Sample size.
- [26] Acceptance criteria.
- [27] Test specimen length should be specified if the length is different from that given in box [6] on page 1 of the blank detail specification or if the length in box [6] is left free with the parameter "I".

### Reference documents

IEC 60068 (all parts), Environmental testing

Sometimen Seneral and Alleger Sometimes of the seneral and the IEC 60410, Sampling plans and procedures for inspection by attributes