

VERTIKAALSED LIIKLUSKORRALDUSVAHENDID.
MUUDETAVA TEABEGA LIIKLUSMÄRGID

Road vertical signs - Variable message traffic signs

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 12966:2014+A1:2018 sisaldab Euroopa standardi EN 12966:2014+A1:2018 ingliskeelset teksti.	This Estonian standard EVS-EN 12966:2014+A1:2018 consists of the English text of the European standard EN 12966:2014+A1:2018.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 12.12.2018.	Date of Availability of the European standard is 12.12.2018.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 93.080.30

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Road vertical signs - Variable message traffic signs

Signaux de signalisation routière verticale - Panneaux à messages variable

Vertikale Verkehrszeichen - Wechselverkehrszeichen

This European Standard was approved by CEN on 18 October 2014 and includes Amendment 1 approved by CEN on 10 October 2018.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.




EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	7
Introduction	9
1 Scope	10
2 Normative references	10
3 Terms and definitions	11
4 Product characteristics	15
4.1 Dimensions and tolerances requirements.....	15
4.2 General design requirement.....	15
4.3 Visual performance requirements of continuous VMS.....	15
4.4 Visual performance requirements of discontinuous VMS.....	16
4.5 Physical performance requirements	25
4.6 Dangerous substances.....	28
5 Testing, assessment and sampling methods	29
5.1 Test sequence	29
5.2 Durability	29
5.3 Test modules.....	29
5.4 Physical performance test methods.....	31
5.5 Visual performance test methods	37
6 Assessment and verification of constancy of performance (AVCP)	46
6.1 General.....	46
6.2 Type testing.....	46
6.3 Factory production control (FPC)	52
7 Classification and designation	59
7.1 General.....	59
7.2 Continuous retro-reflective VMS.....	59
7.3 Continuous, externally illuminated retro-reflective VMS.....	59
7.4 Discontinuous VMS.....	60
8 Marking, labelling and packaging	61
9 Product information	61
Annex A (normative) Equivalent area	63
A.1 General.....	63
A.2 Calculation of the luminance.....	63
A.3 Calculation of non-matrix equivalent areas.....	66
A.3.1 Equivalent area for a line of elements.....	66
A.3.2 Equivalent area for a symbol fully populated with elements	67
A.3.3 Equivalent area for a symbol partially populated with elements	67
Annex B (normative) VMS performance declaration codes for marking	69
B.1 General.....	69
B.2 Code for continuous retro-reflective VMS.....	69
B.3 Code for externally illuminated continuous retro-reflective VMS.....	69
B.4 Code for discontinuous VMS.....	70
Annex L (informative) Terminology used in this European Standard	71
Annex M (informative) Guidance on graphics for discontinuous light emitting signs	73
M.1 General.....	73
M.2 Apparent luminance of lines and letter strokes	73

M.2.1	General	73
M.2.2	Further technical explanation of Apparent luminance.....	74
M.3	VMS with colour inversion	75
M.4	VMS without colour inversion.....	81
Annex N	(informative) Guidance on dimensions , luminance, beam width, legibility and efficiency for discontinuous VMS.....	83
N.1	General	83
N.2	Dimensions	83
N.2.1	General	83
N.2.2	Text	84
N.2.3	Circles.....	84
N.2.4	Triangles	85
N.3	Luminance and beam width classes.....	85
N.4	Beam width and distances of legibility	90
N.4.1	Group of VMS, centred above the road.....	90
N.4.2	Group of VMS, not centred above the road	91
N.4.3	Curved road sections.....	92
N.4.4	Limits of legibility due to vertical beam	93
N.4.5	Calculation of recognition time	95
N.4.5.1	General	95
N.4.5.2	Distances in metres per second at various speeds.....	95
N.4.5.3	Example of calculation of the recognition time	95
N.4.5.3.1	General	95
N.4.5.3.2	Using beam width class B2.....	96
N.4.5.3.3	Using beam width class B4.....	97
N.4.5.3.4	Using beam width class B6.....	97
N.4.5.4	Conclusions after calculation of recognition time	98
N.4.6	Luminance and luminance ratio	98
N.4.7	Beam width	99
N.5	Energy efficiency.....	99
Annex O	(informative) Specific design issues.....	100
O.1	Finish.....	100
O.2	Front panels.....	100
O.3	Front screens.....	100
O.4	Appearance	100
O.5	Electrolytic compatibility	100
O.6	Protection against thermal overload	100
O.7	Physical security against unauthorized access.....	100
O.8	Interfaces between VMS, control, and higher order equipment.....	100
O.9	Diagnostic.....	101
Annex P	(informative) Guidance for design of VMS messages.....	102
P.1	Design of VMS messages.....	102
P.2	Specifying text dimensions	103
Annex Q	(informative) Technical documentation.....	106
Q.1	Sign enclosure.....	106
Q.2	Electrical equipment	106
Q.3	Mounting devices (if applicable).....	106
Q.4	Retro-reflective and non retro-reflective components	106
Annex R	(informative) Example of recommended summary of class combinations.....	108

Annex ZA (informative)  Relationship of this European Standard with Regulation (EU) No.305/2011	116
ZA.1 Scope and relevant characteristics.....	116
ZA.2 System of Assessment and Verification of Constancy of Performance (AVCP)	119
ZA.3 Assignment of AVCP tasks	119
ZA.4 The following clauses are not related to Regulation (EU) No 305/2011:	120
Bibliography	121

Figures	Page
Figure 1 — Chromaticity areas for the colour classes C1 and C2 plotted in the CIE 1931 chromaticity diagram	18
Figure 2 — Examples of passed and failed luminance distributions	23
Figure 3 — Examples of variable message traffic sign test modules in front view - a) and c) - and side view b)	31
Figure 4 — Side elevation of the set-up for the measurement of luminance and luminance ratio	38
Figure 5 — Layout examples for a test module and the positioning of the measuring area (circle) of the luminance meter	43
Figure A.1 — Merging of elements	63
Figure A.2 — Character with a regular orthogonal matrix of (5 × 8) elements	64
Figure A.3 — Open line	66
Figure A.4 — Closed line	66
Figure A.5 — Example of symbol with an area fully populated with elements	67
Figure A.6 — Example of symbol with an area partially populated with elements	68
Figure B.1 — Code of performance classes of continuous retro-reflective VMS	69
Figure B.2 — Code of performance classes of externally illuminated continuous retro-reflective VMS	70
Figure B.3 — Code of performance classes of discontinuous VMS	70
Figure L.1 — Parts of a VMS	71
Figure L.2 — Test configuration	72
Figure M.1 — A legend seen at short (left), longer (centre), and very long distance (right)	74
Figure M.2 — Example for calculation of dimensions of circular mandatory VMS	78
Figure M.3 — Example for calculation of dimensions of circular mandatory VMS	79
Figure M.4 — Example for calculation of dimensions of a triangular warning VMS	80
Figure M.5 — Example of VMS using (64 × 64) elements with colour inversion	81
Figure M.6 — Example of VMS using (48 × 48) elements with colour inversion	81
Figure M.7 — Example of VMS using (32 × 32) elements with colour inversion	81
Figure M.8 — Example of VMS using (64 × 64) elements, no colour inversion	82
Figure M.9 — Example of VMS using (48 × 48) elements, no colour inversion	82
Figure M.10 — Example of VMS using (32 × 32) elements, no colour inversion	82
Figure N.1 — Relation between classes	86
Figure N.2 — Example of coverage by beam width class B1	87
Figure N.3 — Example of coverage by beam width class B3	88
Figure N.4 — Example of coverage by beam width class B6	89
Figure N.5 — Legibility of group of VMS, centred on gantry above the road	90
Figure N.6 — Legibility of group of VMS, mounted on cantilever aside the road	91
Figure N.7 — Legibility of group of VMS, mounted on cantilever aside the road	93
Figure N.8 — Legibility of group of VMS, mounted on cantilever aside the road	94
Figure P.1 — Example of the design of the letter E in a regular orthogonal matrix	102
Figure P.2 — Equivalent text dimensions using uppercase characters	103

Figure P.3 — Equivalent text dimensions using upper- and lower-case characters	104
Figure P.4 — Equivalent text dimensions of full matrix display using proportional character spacing	105
Figure R.1 — Example of summary of the characteristics of products	109
Figure R.2 — Example 1 for visual performance class combination	111
Figure R.3 — Example 2 for visual performance class combination	112
Figure R.4 — Example 3 for visual performance class combination	114
Figure R.5 — Example 4 for visual performance class combination	115

Tables	Page
Table 1 — Class designation of the visual performance parameters of VMS	16
Table 2 — Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the colours of class C1	17
Table 3 — Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the colours of class C2	17
Table 4 — L_e and L_a luminance limits for white on reference axis	19
Table 5 — L_e and L_a luminance limits for yellow on reference axis	20
Table 6 — L_e and L_a luminance limits for orange on reference axis	20
Table 7 — L_e and L_a luminance limits for green on reference axis	20
Table 8 — L_e and L_a luminance limits for red on reference axis	21
Table 9 — L_e and L_a luminance limits for blue on reference axis	21
Table 10 — Minimum luminance ratio values (LR) for various colours and classes R1, R2 and R3, at test angles on the reference axis and off the reference axis	22
Table 11 — Beam width classes	24
Table 12 — Class designation	25
Table 13 — Temperature range classes	25
Table 14 — Ingress protection level classes	26
Table 15 — Effect of voltage interruption	28
Table 16 — Operating voltage range, power-up activation and temporary overvoltage tests	32
Table 17 — Frequency and voltage tests	32
Table 18 — Impact test	33
Table 19 — Vibration test	33
Table 20 — Corrosion test	34
Table 21 — Water ingress test - Severity	34
Table 22 — Dust ingress test - Severity	34
Table 23 — Temperature test	35
Table 24 — Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance under external illumination and luminance ratio	39
Table 25 — Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance without external illumination	39
Table 26 — Test angles (in degrees, with respect to the reference axis), used for the measurement of beam width, and for uniformity of luminous intensity and colour of monochromatic elements	40
Table 27 — Test angles (in degrees, with respect to the reference axis), used for the measurement of uniformity of luminous intensity and colour of elements formed by mixing colours	41
Table 28 — Characteristics of continuous VMS	47
Table 29 — Characteristics of discontinuous VMS	49
Table 30 — Identification label	52
Table 31 — Minimum frequency of testing continuous VMS for product testing and evaluation as part of FPC	55

Table 32 — Minimum frequency of testing discontinuous VMS for product testing and evaluation as part of FPC	56
Table M.1 — Parameters for mandatory signs using a red circle	76
Table M.2 — Parameters for mandatory signs using a red triangle	77
Table N.1 — Minimum dimensions of text (mm)	84
Table N.2 — Minimum dimensions of circles (mm)	85
Table N.3 — Minimum dimensions of triangles (mm)	85
Table N.4 — Examples for applications of beam width classes	86
Table N.5 — Examples for recognition time depending on character height, speed and vertical beam width	94
Table N.6 — Conversion from speed unit km/h to m/s	95
Table ZA.1 — Relevant clauses for continuous VMS	116
Table ZA.2 — Relevant clauses for discontinuous VMS	118
Table ZA.3 — Assignment of AVCP tasks for VMS under system 1	120

European foreword

This document (EN 12966:2014+A1:2018) has been prepared by Technical Committee CEN/TC 226 “Road equipment”, the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2019 and conflicting national standards shall be withdrawn at the latest by September 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 7 November 2018.

This document will supersede A1 EN 12966:2014 A1.

The start and finish of text introduced or altered by amendment is indicated in the text by tags A1 A1.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with Regulation (EU) No. 305/2011 [1], see informative Annex ZA, which is an integral part of this document.

EN 12966, *Road vertical sign – Variable message traffic signs*, covers the product standard, assessment and verification of constancy of performance (AVCP) including type testing and factory production control.

It derives from performance requirements and test methods published in CEN, CENELEC, CIE, IEC and ISO documents.

The main changes with respect to the previous edition are listed below:

- The new structure of the standard has been adapted to the structure proposed by CEN BT for harmonized standards
 - Consequently the contents of Clauses 4 to 8 of the previous edition have been moved to Clause 4, Product characteristics, in 4.1 to 4.6;
 - Contents of Clause 9 of the previous edition have been moved to Clause 5, Testing, assessment and sampling methods;
 - Contents of EN 12966-2:2005 and contents of EN 12966-3:2005 have been moved to Clause 6, Assessment and verification of constancy of performance (AVCP), and revised in accordance with requirements of CPR;
 - contents of Clause 10 of the previous edition have been moved to Clause 7, Classification and designation;
 - contents of Clause 11 of the previous edition have been moved to Clause 8, Marking, labelling and packaging;

- contents of Clause 12 of the previous edition are now included in Clause 6, Assessment and verification of constancy of performance (AVCP);
- contents of Clause 13 of the previous edition are now included in 4.6, Dangerous substances;
- informative Annex B of the previous edition has been renamed informative Annex L;
- informative Annex C of the previous edition has been renamed informative Annex M, information and guidance on graphics for discontinuous light emitting signs including figures has been added for better understanding;
- informative Annex D of the previous edition has been renamed informative Annex N, information and guidance on dimensions, luminance, beam width, legibility and efficiency for discontinuous VMS including figures has been added for better understanding;
- informative Annex E of the previous edition has been renamed informative Annex O;
- informative Annex F of the previous edition has been renamed informative Annex P ;
- new normative Annex B has been added to define declaration codes for marking;
- new informative Annex Q has been added to give guidance for technical documentation;
- new informative Annex R has been added showing templates for summary of test results;
- visual performance requirements of continuous VMS (4.3) and discontinuous VMS (4.4), have been updated, test methods have been simplified (5.5);
- physical performance requirements have been updated (4.5), test method have been adjusted accordingly (5.4);
- informative Annex ZA has been revised in accordance with requirements of the CPR.

NOTE The structure of the document follows the requirements requested by the CEN CPR Consultant at the time of drafting the document.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This European Standard is designed for use by manufacturers, who are placing their variable message traffic signs on the market, as well as by Road Authorities and private developers who wish to use variable message signs. It provides requirements for performance of characteristics of these signs, test and assessment methods and the means of assessment and verification of constancy of performance (AVCP).

This European Standard is a product standard covering the requirements for variable message traffic signs (VMS). A VMS is a sign where the information shown can be changed or switched on or off as required. The information can be text and/or symbols.

VMS fall into the two different types of continuous and discontinuous. Continuous VMS show sign faces of the types of fixed signs defined in EN 12899. Discontinuous VMS use luminous elements to show different messages on a single sign face.

There is diversity of VMS. Some have elements that are placed with a view of displaying a few predetermined messages, while other have elements placed in arrays. Some can show messages where all elements have approximately the same luminous intensity while other can vary the luminous intensity individually. Some can show certain predetermined colours, while other can show a range of colours. Some can show only character legends while other can show a wider range of legends.

This European Standard does not describe the detailed form and configuration of a VMS. Therefore, test modules representing the VMS are used to demonstrate compliance with the requirements of this European Standard because of the impracticality of testing some complete VMS.

Because of the major demands on a sign for good legibility and visibility throughout the required viewing range, the main properties of the sign are described. These properties can vary depending on the situation. For example, it will not be necessary to ask for a minimum temperature requirement of -40 °C in Greece, but this needs to be considered in Lapland. For visual performance there will be a difference between installation on highways - with good distance visibility and a narrow beam width - and installation in cities, where there is only short distance legibility and when a wide beam width may be required.

This European Standard uses requirements for performance of the characteristics, which are not dependent on technology. The visual and environmental performance is demonstrated on a test module representing the VMS. This European Standard contains a number of defined requirements on VMS, some of which have to be demonstrated on the test module, others that are to be verified by the manufacturer. It is the manufacturer's responsibility to ensure that the VMS is fully represented by the test module.

The performances of the main characteristics of discontinuous VMS are given by classes, which are designed to be selected by choosing a combination of classes dependent on the end-user's requirements. National annexes may define class combination applicable to the local needs. This combination covers not only the regulatory requirements of the destination country but also issues of lifetime, quality, maintenance and construction, all of which affect the ability of a sign in its particular application, to meet safety and fitness for purpose. The details in the informative annexes are provided as useful guidance on the additional aspects relating to VMS for those setting up purchasing contracts for signs or signing systems.

Installed discontinuous VMS should be regulated in view of the ambient light and the stroke width of legends to provide the intended apparent luminance and balance of colours. Symbols and fonts for character legends should be designed to provide best possible legibility.

The working environment for VMS can be relatively harsh and equipment that is deemed "fit for purpose" is expected to last in an exposed, corrosive environment for a minimum of 10 years. It is essential that all materials and manufacturing processes take this into account.

1 Scope

This European Standard provides specifications for two types of variable message signs (VMS); i.e. continuous (see 3.4) and discontinuous (see 3.7).

This European Standard covers mobile, temporary and permanently installed VMS used in circulation areas, on public and private land, including tunnels for the information, guidance, warning and/or direction of traffic. Test modules are used to demonstrate compliance with the requirements.

This European Standard specifies visual and physical characteristics of VMS as well as their durability aspects. It also provides relevant requirements and corresponding test methods, assessment and verification of constancy of performance (AVCP) and marking.

NOTE Provisions for the evaluation of conformity with regards to type testing are further specified in 6.2; provisions with regards to factory production control (FPC) are further specified in 6.3.

This European Standard does not cover

- a) sign gantries, cantilevers, posts (supports) and foundations,
- b) signal heads,
- c) sizes and shapes of VMS messages,
- d) control units and monitoring units unless inside the VMS,
- e) control of sign luminance.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12899-1:2007, *Fixed, vertical road traffic signs — Part 1: Fixed signs*

EN 12899-4:2007, *Fixed, vertical road traffic signs — Part 4: Factory production control*

EN 50293:2012, *Road traffic signal systems — Electromagnetic compatibility*

EN 50556:2011, *Road traffic signal systems*

EN 60068-2-1, *Environmental testing — Part 2-1: Tests — Tests A: Cold (IEC 60068-2-1)*

EN 60068-2-2, *Environmental testing — Part 2-2: Tests — Tests B: Dry heat (IEC 60068-2-2)*

EN 60068-2-5, *Environmental testing — Part 2-5: Tests — Test Sa: Simulated solar radiation at ground level and guidance for solar radiation testing (IEC 60068-2-5)*

EN 60068-2-14, *Environmental testing — Part 2-14: Tests — Test N: change of temperature (IEC 60068-2-14)*

EN 60068-2-30, *Environmental testing — Part 2-30: Tests — Test Db: Damp heat, cyclic (12 h + 12 h cycle) (IEC 60068-2-30)*

EN 60068-2-64, *Environmental testing — Part 2-64: Tests — Test Fh: Vibration, broadband random and guidance (IEC 60068-2-64)*

EN 60529, *Degrees of protection provided by enclosures (IP Code) (IEC 60529)*

EN 60598-1, *Luminaires — Part 1: General requirements and tests (IEC 60598-1)*

EN 60664-1, *Insulation coordination for equipment within low-voltage systems — Part 1: Principles, requirements and tests (IEC 60664-1)*

EN 60950-1:2006, *Information technology equipment — Safety - Part 1: General requirements (IEC 60950-1:2005, modified)*

EN 60950-22:2006, *Information technology equipment — Safety — Part 22: Equipment installed outdoors (IEC 60950-22:2005, modified)*

EN ISO 9227:2012, *Corrosion tests in artificial atmospheres — Salt spray tests (ISO 9227:2012)*

IEC 60417-1, *Graphical symbols for use on equipment — Part 1: Overview and application*

ISO 7000:2014, *Graphical symbols for use on equipment — Registered symbols*

CIE 015-2004, *Colorimetry*

CIE S 017:2011, *International lighting vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in CIE 015-2004 and CIE S 017:2011 and the following apply.

NOTE When reading this document for the first time, particular attention regarding terminology as given in Annex L helps for better understanding.

3.1

AVCP

assessment and verification of constancy of performance

3.2

backing board

surround to the VMS, used depending on local circumstances, providing improved visibility of the VMS by means of increasing its size and by providing suitable visible contrast with the VMS background

3.3

cantilever support

support system with a single post and a cantilever arm supporting VMS(s) mounted over the traffic lane(s)

3.4

continuous VMS

these are similar to fixed signs the only difference being that by some electro- and/or mechanical means they change between messages

EXAMPLE Rotating prism signs, roller blinds, etc.

Note 1 to entry: Fixed signs are specified in accordance with EN 12899-1:2007.