

Edition 1.0 2011-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE

High-voltage switchgear and controlgear -

Part 103: Switches for rated voltages above 1 kV up to and including 52 kV

Appareillage à haute tension -

Partie 103: Interrupteurs pour tensions assignées supérieures à 1 kV et inférieures ou égales à 52 kV





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: <u>www.iec.ch/online_news/justpub</u>

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

■ Catalogue des publications de la CEI: <u>www.iec.ch/searchpub/cur_fut-f.htm</u>

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

Just Published CEI: www.iec.ch/online news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

■ Electropedia: <u>www.electropedia.org</u>

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

■ Service Clients: <u>www.iec.ch/webstore/custserv/custserv_entry-f.htm</u>

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch Tél.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 1.0 2011-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE

High-voltage switchgear and controlgear –
Part 103: Switches for rated voltages above 1 kV up to and including 52 kV

Appareillage à haute tension – Partie 103: Interrupteurs pour tensions assignées supérieures à 1 kV et inférieures ou égales à 52 kV

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

PRICE CODE CODE PRIX

ICS 29.130.10 ISBN 978-2-88912-534-0

CONTENTS

FΟ	REWO	RD	6		
1	Gener	ral	8		
	1.1	Scope	8		
	1.2	Normative references	8		
2	Norma	al and special service conditions	9		
3	Terms and definitions				
		General terms			
		Assemblies of switchgear and controlgear			
		Parts of assemblies			
		Switching devices			
		Parts of switchgear and controlgear			
		Operation			
		Characteristic quantities			
		Index of definitions			
4		ys			
	4.1	Rated voltage ($U_{ m r}$)	14		
	4.2	Rated insulation level			
	4.3	Rated frequency (f _r)			
	4.4	Rated normal current and temperature rise			
	4.5	Rated short-time withstand current (I _k)			
	4.6	Rated peak withstand current (I _p)			
	4.7	Rated duration of short-circuit (t_k)	15		
	4.8	Rated supply voltage of closing and opening devices and of auxiliary and control circuits (U_a)			
	4.9	Rated supply frequency of closing and opening devices and of auxiliary circuits			
	4.10	Rated pressure of compressed gas supply for controlled pressure systems			
	4.11	Rated filling levels for insulation and/or operation			
	4.101	Rated mainly active load-breaking current (I_{load})			
	4.102	Rated closed-loop breaking current (I_{loop} and I_{pptr})			
	4.103	Rated cable-charging breaking current (/)	16		
	4.104	Rated line-charging breaking current (I_{lc})	16		
	4.105	Rated single capacitor bank breaking current for special purpose switches $(I_{\rm sb})$			
	4.106	Rated back-to-back capacitor bank breaking current for special purpose switches (I_{bb})	16		
	4.107	Rated back-to-back capacitor bank inrush making current for special purpose switches (I_{in})	16		
	4.108	Rated earth fault breaking current (I _{ef1})	16		
	4.109	Rated cable- and line-charging breaking current under earth fault conditions ($I_{ m ef2}$)			
	4.110	Rated motor breaking current for special purpose switches (I_{mot})			
	4.111	Rated short-circuit making current (I _{ma})	17		
	4.112	Rated breaking and making currents for a general purpose switch	17		
	4.113	Ratings for limited purpose switches	18		
	4.114	Ratings for special purpose switches	18		
	4.115	Ratings for switches backed by fuses	18		

	4.110	switches	18
5	Desig	n and construction	
	5.1	Requirements for liquids in switchgear and controlgear	19
	5.2	Requirements for gases in switchgear and controlgear	
	5.3	Earthing of switchgear and controlgear	19
	5.4	Auxiliary and control equipment	19
	5.5	Dependent power operation	19
	5.6	Stored energy operation	19
	5.7	Independent manual or power operation (independent unlatched operation)	19
	5.8	Operation of releases	19
	5.9	Low- and high-pressure interlocking and monitoring devices	19
	5.10	Nameplates	19
	5.11	Interlocking devices	21
	5.12	Position indication	21
	5.13	Degrees of protection provided by enclosures	21
	5.14	Creepage distances for outdoor insulators	21
	5.15	Gas and vacuum tightness	21
	5.16	Liquid tightness	21
	5.17	Fire hazard (flammability)	22
	5.18	Electromagnetic compatibility (EMC)	22
	5.19	X-ray emission	
	5.20	Corrosion	22
	5.101	Making and breaking operations	22
	5.102	Requirements for switch-disconnectors	22
	5.103	Mechanical strength	22
	5.104	Securing the position	22
	5.105	Auxiliary contacts for signalling	22
	5.106	No-load transformer breaking	23
6	Type	tests	23
	6.1	General	23
		6.1.1 Grouping of tests	23
		6.1.2 Information for identification of specimens	24
		6.1.3 Information to be included in the type-test reports	24
		6.1.101Reference no-load test	
	6.2	Dielectric tests	24
	6.3	Radio interference voltage (r.i.v.) test	24
	6.4	Measurement of the resistance of circuits	24
	6.5	Temperature-rise tests	24
	6.6	Short-time withstand current and peak withstand current tests	24
	6.7	Verification of the protection	25
		Tightness tests	
	6.9	Electromagnetic compatibility (EMC) tests	25
		Additional tests on auxiliary and control circuits	
		6.10.1 General	
		6.10.2 Functional tests	25
		6.10.3 Electrical continuity of earthed metallic parts test	25
		6.10.4 Verification of the operational characteristics of auxiliary contacts	25
		6.10.5 Environmental tests	. 25

			ielectric test	
			on test procedure for vacuum interrupters	
	6.101	ū	and breaking tests	
		6.101.1	Test duties for general purpose switches	
		6.101.2	Test duties for limited purpose switches	
		6.101.3	Test duties for special purpose switches	
		6.101.4	Arrangement of the switch for tests	
		6.101.5	Earthing of test circuit and switch	
		6.101.6	Test parameters	
		6.101.7		
		6.101.8	Behaviour of switch during breaking tests	46
		6.101.9	Condition of switch after breaking tests and short-circuit making tests	47
		6.101.10	Type-test reports	48
	6.102	2 Mechar	nical and environmental tests	49
		6.102.1	Miscellaneous provisions for mechanical and environmental tests.	49
		6.102.2	Mechanical operation test at ambient air temperature	51
		6.102.3	Low and high temperature tests	52
		6.102.4	Humidity test on auxiliary and control circuits	52
		6.102.5	Operation under severe ice conditions	58
		6.102.6	Tests to verify the proper functioning of the position indicating	
7	Pouti	ne tests	device	
'			nical operating tests	
8	7.101			
0			election of switchgear and controlgear	
	8.101			
	8.102		ons affecting application	
	8.103		on coordinationon of class of switch	
	8.104			
		8.104.1	General purpose switch	
		8.104.2	Special purpose switch	
	0.405	8.104.3	or special applications	
^	8.105			
9			be given with inquiries, tenders and orders	
	9.1		on to be given with inquiries and orders	
	9.2		on to be given with tenders	
10		•	age, installation, operation and maintenance	
11				
12	Influe	ence of the	e product on the environment	63
An	nex A	(normative	e) Tolerances on test quantities for type tests	64
Bib	liogra	phy		66
				-
			hase test circuit for mainly active load current switching for test	(0)
				34
Fig	ure 2	Single-p	hase test circuit for mainly active load current switching for test	9.5
				აე
			hase test circuit for distribution line closed-loop and parallel switching test for test duties TD _{loop} and TD _{pptr}	37
			שט ש	

Figure 4 – Single-phase test circuit for distribution line closed-loop and parallel transformer current switching test, for test duties TD _{loop} and TD _{potr}	37
Figure 5 – General test circuit for three- and single-phase capacitive switching tests	
Figure 6 – Prospective TRV parameter limits for capacitor bank current breaking tests	
Figure 7 – Three-phase test circuit for earth fault breaking current tests, for test duty	
TD _{ef1}	45
Figure 8 – Three-phase test circuit for cable-charging breaking current tests under earth fault conditions, for test duty TD _{ef2}	45
Figure 9 – Three-phase test circuit for short-circuit making current test for test duty TD _{ma}	46
Figure 10 – Single-phase test circuit for short-circuit making current test for test duty TD _{ma}	46
Figure 11 – Test sequences for low and high temperature tests	53
Figure 12 – Humidity test	57
Table 1 – Preferred values of rated line- and cable-charging breaking currents for general purpose switch	17
Table 2 – Product information	20
Table 3 – Test duties for general purpose switches – Test duties for three-phase tests on three-pole operated, switches	26
Table 4 – Test duties for general purpose switches – Single phase tests on three-pole switches operated pole-after-pole and single-pole switches applied on three-phase systems	27
Table 5 – Test duties for special purpose switches – Three-phase tests on three-pole operated, switches	
Table 6 – Test duties for special purpose switches – Single phase tests on three-pole switches operated pole-after-pole and single-pole switches applied on three-phase	
systems	
Table 7 – Supply circuit TRV parameters for mainly active load current breaking tests ^a	
Table 8 – TRV parameters for distribution line closed loop breaking tests	
Table 9 – TRV parameters for parallel power transformer current breaking tests	39
Table 10 – Prospective recovery voltage parameter limits for capacitor bank current breaking tests	43
Table A.1 – Tolerances on test quantities for type tests	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR -

Part 103: Switches for rated voltages above 1 kV up to and including 52 kV

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62271-103 has been prepared by subcommittee 17A: High-voltage switchgear and controlgear, of IEC technical committee 17: Switchgear and controlgear.

This standard cancels and replaces the third edition of IEC 60265-1, published in 1998. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 60265-1:1998:

- the rated voltage of 52 kV is now included;
- the document is aligned with IEC 62271-1 and IEC 62271-100;
- addition of a test procedure for short-circuit making tests;
- introduction of notion of NSDD (non-sustained disruptive discharge) as defined in IEC 62271-1 and restrikes;
- new classes C1 and C2 for capacitive switching;

new Annex A defining tolerances.

The text of this standard is based on the following documents:

FDIS	Report on voting
17A/961/FDIS	17A/966/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This standard is to be read in conjunction with IEC 62271-1:2007, to which it refers and which is applicable unless otherwise specified in this standard. In order to simplify the indication of corresponding requirements, the same numbering of clauses and subclauses is used as in IEC 62271-1. Amendments to these clauses and subclauses are given under the same references whilst additional subclauses are numbered from 101.

The list of all parts of the IEC 62271 series under the general title, *High-voltage switchgear* and controlgear, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed.
- withdrawn,
- · replaced by a revised edition, or
- amended.

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR -

Part 103: Switches for rated voltages above 1 kV up to and including 52 kV

1 General

1.1 Scope

This part of IEC 62271 is applicable to three-phase, alternating current switches and switch-disconnectors for their switching function, having making and breaking current ratings, for indoor and outdoor installations, for rated voltages above 1 kV up to and including 52 kV and for rated frequencies from $16^2/_3$ Hz up to and including 60 Hz. This standard is also applicable to single-pole switches used on three phase systems.

This standard is also applicable to the operating devices of these switches and to their auxiliary equipment.

Switch-disconnectors are also covered by IEC 62271-102 for their disconnecting function.

Devices that require a dependent manual operation are not covered by this standard.

General principles and provisions of this standard may also be applicable to single pole switches intended for application in single-phase systems. The requirements for dielectric tests and making and breaking tests should be in accordance with the requirements of the specific application.

This standard establishes requirements for general, limited and special purpose switches used in distribution systems.

It is assumed that opening and closing operations are performed according to the manufacturer's instructions. A making operation may immediately follow a breaking operation but a breaking operation should not immediately follow a making operation since the current to be broken may then exceed the rated breaking current of the switch.

NOTE 1 Except where special clarification is required, the term "switch" is used to refer to all kinds of switches and switch-disconnectors within the scope of this standard.

NOTE 2 Earthing switches are not covered by this standard. Earthing switches forming an integral part of a switch are covered by IEC 62271-102.

NOTE 3 This standard is not applicable to switching devices attached as an accessory to a high-voltage fuse assembly or its mounting and operated by opening and closing the fuse assembly.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-441:1984, International Electrotechnical Vocabulary (IEV) – Chapter 441: Switchgear, controlgear and fuses

IEC 60529:1989, Degrees of protection provided by enclosures (IP Code)

IEC 62271-1:2007, High-voltage switchgear and controlgear – Part 1: Common specifications

IEC 62271-100:2008, High-voltage switchgear and controlgear – Part 100: Alternating-current circuit-breakers

IEC 62271-102:2001, High-voltage switchgear and controlgear – Part 102: Alternating current disconnectors and earthing switches

IEC 62271-110:2009, High-voltage switchgear and controlgear – Part 110: Inductive load switching

2 Normal and special service conditions

Clause 2 of IEC 62271-1 is applicable.

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-441 and IEC 62271-1, as well as the following apply.

NOTE 1 Some terms and definitions are recalled hereunder for easier use or for the necessity of some precision or adaptation for the interpretation of this standard.

NOTE 2 The terms and definitions given below are classified in accordance with IEC 60050-441. The additional terms and definitions are classified so as to be aligned with the classification used in IEC 60050-441.

3.1 General terms

Subclause 3.1 of IEC 62271-1 is applicable with the following additions.

3.1.101

effectively earthed neutral system

system earthed through a sufficiently low impedance such that for all system conditions the ratio of the zero-sequence reactance to the positive-sequence reactance (X_0/X_1) is positive and less than 3, and the ratio of the zero-sequence resistance to the positive-sequence reactance (R_0/X_1) is positive and less than 1. Normally such systems are solidly earthed (neutral) systems or low impedance earthed (neutral) systems

NOTE For the correct assessment of the earthing conditions not only the physical earthing conditions around the relevant location but the total system is to be considered.

3.1.102

non-effectively earthed neutral system

system other than effectively earthed neutral system, not meeting the conditions given in 3.1.101. Normally such systems are isolated neutral systems, high impedance earthed (neutral) systems or resonant earthed (neutral) systems

NOTE For the correct assessment of the earthing conditions not only the physical earthing conditions around the relevant location but the total system is to be considered.

3.2 Assemblies of switchgear and controlgear

Subclause 3.2 of IEC 62271-1 applies.

3.3 Parts of assemblies

Subclause 3.3 of IEC 62271-1 applies.

3.4 Switching devices

Subclause 3.4 of IEC 62271-1 applies with the following addition.