

**Industrial communication networks - High availability
automation networks - Part 7: Ring-based Redundancy
Protocol (RRP)**

This document is a preview generated by EVS

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 62439-7:2012 sisaldab Euroopa standardi EN 62439-7:2012 ingliskeelset teksti.	This Estonian standard EVS-EN 62439-7:2012 consists of the English text of the European standard EN 62439-7:2012.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 16.03.2012.	Date of Availability of the European standard is 16.03.2012.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 25.040, 35.040

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

**Industrial communication networks -
High availability automation networks -
Part 7: Ring-based Redundancy Protocol (RRP)
(IEC 62439-7:2011)**

Réseaux de communication industriels -
Réseau de haute disponibilité pour
l'automation -
Partie 7: Protocole de redondance pour
réseau en anneau (RRP)
(CEI 62439-7:2011)

Industrielle Kommunikationsnetze -
Hochverfügbare Automatisierungsnetze -
Teil 7: Protokoll für ringbasierte
Redundanz (RRP)
(IEC 62439-7:2011)

This European Standard was approved by CENELEC on 2012-01-20. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 65C/668/FDIS, future edition 1 of IEC 62439-7, prepared by SC 65C, "Industrial networks", of IEC TC 65, "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62439-7:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2012-10-20
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-01-20

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62439-7:2011 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC 61158 series NOTE Harmonized in EN 61158 series.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60050-191	-	International Electrotechnical Vocabulary (IEV) - Chapter 191: Dependability and quality of service	-	-
IEC 62439-1	2010	Industrial communication networks - High availability automation networks - Part 1: General concepts and calculation methods	EN 62439-1	2010
ISO/IEC 8802-3	2000	Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications		-

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references.....	9
3 Terms, definitions, abbreviations, acronyms, and conventions.....	9
3.1 Terms and definitions.....	9
3.2 Abbreviations and acronyms.....	10
3.3 Conventions.....	10
4 RRP overview.....	11
4.1 General.....	11
4.2 Frame forwarding and receiving control.....	11
4.2.1 General.....	11
4.2.2 Normal Device (ND) and Gateway Device (GWD).....	11
4.2.3 Behaviours of the General Device (GD).....	12
4.2.4 Behaviours of the Line Network Manager (LNM).....	13
4.2.5 Behaviours of the Ring Network Managers (RNMs).....	13
4.3 Link status monitoring.....	14
4.4 Error detection.....	14
4.5 Plug and play.....	14
4.6 Network management information base (NMIB) management.....	14
4.7 Network recovery.....	15
4.8 Automatic network configuration.....	15
4.9 RRP basic operating principle.....	15
5 RRP redundancy behaviours.....	17
5.1 Network topology.....	17
5.2 Network recovery in ring network.....	18
5.2.1 General.....	18
5.2.2 Link fault between neighbouring devices.....	20
5.2.3 Link fault of remote device.....	21
5.2.4 Device fault on a RNM.....	22
5.3 Automatic Ring Network Manager (RNM) election procedure.....	23
5.3.1 General.....	23
5.3.2 Primary RNM (RNMP).....	23
5.3.3 Secondary RNM (RNMS).....	24
5.4 Path management.....	24
5.4.1 General.....	24
5.4.2 Path in a line topology network.....	24
5.4.3 Path in a ring topology network.....	25
5.5 Device address collision.....	26
6 RRP class specification.....	27
6.1 General.....	27
6.2 Template.....	27
6.3 Attributes.....	29
7 RRP services specification.....	34
7.1 Set device information.....	34
7.2 Get device information.....	36

7.3	Get network information	38
7.4	Get path table information	40
8	RRP protocol specification.....	42
8.1	General	42
8.2	Ethernet header	43
8.2.1	Preamble.....	43
8.2.2	Start frame delimiter	43
8.2.3	Destination MAC address	43
8.2.4	Source MAC address	43
8.2.5	Length/Type	43
8.3	Encoding of RRP_FrameHDR.....	43
8.3.1	Version and length	43
8.3.2	DST_addr.....	44
8.3.3	SRC_addr.....	45
8.3.4	Frame Control (FC)	45
8.4	Encoding of data and pad.....	47
8.4.1	General	47
8.4.2	Encoding of FamilyReq.....	47
8.4.3	Encoding of FamilyRes.....	48
8.4.4	Encoding of MediaLinked.....	48
8.4.5	Encoding of AdvThis.....	49
8.4.6	Encoding of LineStart	49
8.4.7	Encoding of RingStart.....	50
8.4.8	Encoding of AckRNMS	51
8.4.9	Encoding of CheckRNMS	52
8.5	Frame Check Sequence (FCS).....	52
9	RRP protocol machine.....	52
9.1	Protocol state machine description.....	52
9.2	Local parameters and variables for protocol state.....	54
9.2.1	General	54
9.2.2	Variables to support local device information management.....	54
9.2.3	Variables to support network information management.....	55
9.2.4	Variables to support device path information management	55
9.2.5	Variables of Received RRP Frame.....	55
9.2.6	Local variables for protocol state	56
9.2.7	Constants for protocol state.....	56
9.3	State transitions	57
9.4	Function descriptions	70
10	RRP Management Information Base (MIB)	75
	Bibliography.....	81
	Figure 1 – Forwarding and receiving Ethernet frames	11
	Figure 2 – Structures of ND and GWD	12
	Figure 3 – LNM forwarding control	13
	Figure 4 – RNM forwarding control.....	13
	Figure 5 – Link status information	14
	Figure 6 – A device operation in initialization phase.....	15

Figure 7 – Devices operation in line network establishing phase	16
Figure 8 – Extension of line network operation.....	16
Figure 9 – Ring network establishment operation.....	17
Figure 10 – Ring to line network change operation.....	17
Figure 11 – Ring topology.....	18
Figure 12 – Link fault between neighbouring devices	21
Figure 13 – Link fault of remote device	22
Figure 14 – Device fault on a RNM	22
Figure 15 – Path management in a line topology network.....	24
Figure 16 – Path management in a ring topology network	25
Figure 17 – RRP device address collision in a ring network	26
Figure 18 – Common MAC frame format for RRP DLPDU	43
Figure 19 – RRP protocol state machine	53
Table 1 – RRP network recovery parameter	19
Table 2 – Parameters for calculation.....	19
Table 3 – Path table of Device1 in a line topology network.....	24
Table 4 – Path table of Device4 in a line topology network.....	25
Table 5 – Path table of Device1 in a ring topology network	25
Table 6 – Path table of Device3 in a ring topology network	26
Table 7 – Device address collision information.....	27
Table 8 – Parameters of set device information service	34
Table 9 – Parameters of get device information service	36
Table 10 – Parameters of get network information service	38
Table 11 – Parameters of get path table information service.....	40
Table 12 – RRP Length/Type field	43
Table 13 – Version.....	44
Table 14 – DST_addr.....	44
Table 15 – SRC_addr	45
Table 16 – Network control message type.....	45
Table 17 – Type of service.....	45
Table 18 – Priority	46
Table 19 – Validation of extension code.....	46
Table 20 – Encoding of FamilyReq frame.....	47
Table 21 – Encoding of FamilyRes frame.....	48
Table 22 – Encoding of MediaLinked frame.....	48
Table 23 – Encoding of AdvThis frame.....	49
Table 24 – Encoding of LineStart frame	49
Table 25 – Encoding of RingStart frame.....	50
Table 26 – Encoding of AckRNMS frame	51
Table 27 – Encoding of CheckRNMS frame	52
Table 28 – Variables to support device information management.....	54
Table 29 – Variables to support managing network information.....	55

Table 30 – Variables to support device path information management	55
Table 31 – Variables of Received RRP Frame	55
Table 32 – Local variables for protocol state	56
Table 33 – Constants for protocol state	56
Table 34 – RRP State transitions	57
Table 35 – RRP Function descriptions	70

This document is a preview generated by EVS

INTRODUCTION

The IEC 62439 series specifies relevant principles for high availability networks that meet the requirements for industrial automation networks.

In the fault-free state of the network, the protocols of the IEC 62439 series provide ISO/IEC 8802-3:2000 (IEEE 802.3) with compatible, reliable data communications, and preserve determinism in real-time data communications. In cases of fault, removal, and insertion of a component, they provide deterministic recovery times.

These protocols retain fully the Ethernet communication capabilities typically used in the office world, to ensure that software that relies on these protocols will remain applicable.

The market is in need of several network solutions, each with different performance characteristics and functional capabilities, meeting diverse application requirements. These solutions support different redundancy topologies and mechanisms, which are introduced in IEC 62439-1 and specified in the companion International Standards. IEC 62439-1 also distinguishes between these different solutions, providing guidance for the user.

The IEC 62439 series follows the general structure and terms of IEC 61158 series.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning IEC 61158-4-21 given in Clause 4 and Clause 5.

Patent Number KR 0789444 "COMMUNICATION PACKET PROCESSING APPARATUS AND METHOD FOR RING TOPOLOGY ETHERNET NETWORK CAPABLE OF PREVENTING PERMANENT PACKET LOOPING," owned by LS INDUSTRIAL SYSTEMS CO., LTD., Anyang, Korea

Patent Number KR 0732510 "NETWORK SYSTEM" owned by LS INDUSTRIAL SYSTEMS CO., LTD., Anyang, Korea

Patent Number KR 0870670 "Method For Determining a Ring Manager Node", owned by LS INDUSTRIAL SYSTEMS CO., LTD., Anyang, Korea

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holder of these patent rights has assured the IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of these patent rights is registered with IEC. Information may be obtained from:

LSIS Co Ltd
LS Tower
1026-6, Hogye-Dong
Dongan-Gu
Anyang, Gyeonggi-Do, 431-848
South Korea
Phone +82 2 2034 4917
Fax +82 2 2034 4648

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (<http://patents.iec.ch>) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

INDUSTRIAL COMMUNICATION NETWORKS – HIGH AVAILABILITY AUTOMATION NETWORKS –

Part 7: Ring-based Redundancy Protocol (RRP)

1 Scope

The IEC 62439 series of standards is applicable to high-availability automation networks based on the ISO/IEC 8802-3:2000 (Ethernet) technology.

This part of the IEC 62439 series specifies a redundancy protocol that is based on a ring topology, in which the redundancy protocol is executed at the end nodes, as opposed to being built into the switches. Each node detects link failure and link establishment using media-sensing technologies, and shares the link information with the other nodes, to guarantee fast connectivity recovery times. The nodes have equal RRP network management functions.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-191, *International Electrotechnical Vocabulary – Chapter 191 : Dependability and quality of service*

IEC 62439-1:2010, *Industrial communication networks – High availability automation networks – Part 1: General concepts and calculation methods*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

3 Terms, definitions, abbreviations, acronyms, and conventions

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-191 as well as in IEC 62439-1, and the following apply.

3.1.1

R-port

port in a communication device that is part of a line or ring structure

3.1.2

device address

2 octet address that designates the device associated with a single device on a specific local link