

Edition 2.0 2009-07

STANDARD

tem (h. Leto 108,6) Specification of the Radio Data System (RDS) for VHF/FM sound broadcasting in the frequency range from 87,5 MHz to 108,0 MHz

IEC 62106:2009(E)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Email: inmail@ Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

■ Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00





Edition 2.0 2009-07

INTERNATIONAL

Specification of the Radio Data System (RDS) for VHF, the frequency range from 87,5 MHz to 108,0 MHz Specification of the Radio Data System (RDS) for VHF/FM sound broadcasting in

COMMISSION

ICS 33.060.20; 33.170; 35.240.99

ISBN 2-8318-1054-1

CONTENTS

FOI	REWC)RD	8
1	Scop	e	10
2	Norm	ative references	10
3	Abbre	eviations and conventions	10
4	Modu	lation characteristics of the data channel (physical layer)	11
	4.1	General	
	4.2	Subcarrier frequency	
	4.3	Subcarrier phase	
	4.4	Subcarrier level	
	4.5	Method of modulation	
	4.6	Clock-frequency and data-rate	13
	4.7	Differential coding	13
	4.8	Data-channel spectrum shaping	14
5	Base	band coding (data-link layer)	17
	5.1	Baseband coding structure	
	5.2	Order of bit transmission	
	5.3	Error protection	18
	5.4	Synchronisation of blocks and groups	
6	Mess	age format (session and presentation layers)	19
	6.1	Addressing	19
		6.1.1 Design principles	19
		6.1.2 Principal features	20
		6.1.2 Principal features	21
		6.1.4 Open data channel/Applications Identification	
		6.1.5 Coding of the Group types	25
	6.2	6.1.5 Coding of the Group types	41
		6.2.1 Coding of information for control	42
		6.2.2 Coding and use of information for display	50
		6.2.3 Coding of Clock Time and date (CT)	51
		6.2.4 Coding of information for Transparent Data Channels (TDC)	51
		6.2.5 Coding of information for In House applications (H)	51
		6.2.6 Coding of Radio Paging (RP)	
		6.2.7 Coding of Emergency Warning Systems (EWS)	52
7	Desc	ription of features	53
	7.1	Alternative Frequencies list (AF)	53
	7.2	Clock Time and date (CT)	53
	7.3	Decoder Identification (DI) and dynamic PTY Indicator (PTYI)	53
	7.4	Extended Country Code (ECC)	53
	7.5	Enhanced Other Networks information (EON)	53
	7.6	Emergency Warning System (EWS)	54
	7.7	In House application (IH)	54
	7.8	Music Speech switch (MS)	
	7.9	Open Data Applications (ODA)	
	7.10	Programme Identification (PI)	
	7.11	Programme Item Number (PIN)	
	7.12	Programme Service name (PS)	55

7.13 Programme TYpe (PTY)	55
7.14 Programme TYpe Name (PTYN)	55
7.15 Radio Paging (RP)	55
7.16 RadioText (RT)	
7.17 Enhanced RadioText (eRT)	
7.18 RadioText Plus (RT+)	
7.19 Traffic Announcement identification (TA)	
7.20 Transparent Data Channels (TDC)	
7.21 Traffic Message Channel (TMC)	
7.22 Traffic Programme identification (TP)	
8 Marking	
Annex A (normative) Offset words to be used for group and block synchronisation	58
Annex B (informative) Theory and implementation of the modified shortened cyclic code	59
Annex C (informative) Implementation of group and block synchronisation using the modified shortened cyclic code	65
Annex D (normative) Programme identification codes and Extended country codes	68
Annex E (normative) Basic and extended RDS character sets	72
Annex F (normative) Programme type codes	86
Annex G (informative) Conversion between time and date conventions	89
Annex H (informative) ARI (Autofahrer-Rundfunk-Information) system – Discontinuation	91
Annex J (normative) Language identification	
Annex K (informative) RDS logo	
Annex L (informative) Open data registration	
Annex M (normative) Coding of Radio Paging (RP)	
	90
Annex N (normative) Country codes and extended country codes for countries outside the European Broadcasting Area	
Annex P (normative) Coding of RadioText Plus information (RT+)	
Annex Q (normative) Coding of enhanced RadioText (eRT)	147
Annex R (informative) RBDS in the USA	152
Annex S (normative) List of RDS specific abbreviations	153
Bibliography	154
' O	
Figure 1 – Block diagram of radio-data equipment at the transmitter	12
Figure 2 – Block diagram of a typical radio-data receiver/decoder	12
Figure 3 – Amplitude response of the specified transmitter or receiver data-shaping filter	15
Figure 4 – Amplitude response of the combined transmitter and receiver data-shaping filters	15
Figure 5 – Spectrum of biphase coded radio-data signals	6
Figure 6 – Time-function of a single biphase symbol	16
Figure 7 – 57 kHz radio-data signals	
Figure 8 – Structure of the baseband coding	
Figure 9 – Message format and addressing	18
Figure 10 ODA version A groups	0.4

Figure 11 – ODA version B groups	25
Figure 12 – Basic tuning and switching information – Type 0A group	25
Figure 13 – Basic tuning and switching information – Type 0B group	26
Figure 14 – Programme Item Number and slow labelling codes – Type 1A group	27
Figure 15 – Programme Item Number – Type 1B group	28
Figure 16 - RadioText - Type 2A group	28
Figure 17 - RadioText - Type 2B group	29
Figure 18 – Application Identification for Open data – Type 3A group	30
Figure 19 – Open data – Type 3B group	31
Figure 20 - Clock time and date transmission - Type 4A group	32
Figure 21 – Open data – Type 4B group	32
Figure 22 – Transparent data channels – Type 5A group	33
Figure 23 – Transparent data channels – Type 5B group	33
Figure 24 – In-house applications – Type 6A and 6B group	34
Figure 25 – Radio Paging – Type 7A group	34
Figure 26 – Type 7B group	35
Figure 27 – Traffic Message Channel Type 8A group	35
Figure 28 – Open data – Type 8B group	35
Figure 29 – Allocation of EWS message bits – Type 9A group	36
Figure 30 – Open data – Type 9B group	36
Figure 31 – Programme Type Name PTYN – Type 10A group	37
Figure 32 – Open data – Type 10B group	37
Figure 33 – Open data – Type 11A and 11B groups	38
Figure 34 – Open data – Type 12A and 12B groups.	38
Figure 35 – Enhanced Paging information – Type 13A group	39
Figure 36 – Open data – Type 13B group	40
Figure 37 – Enhanced Other Networks information – Type 14A groups	40
Figure 38 – Enhanced Other Networks information – Type 14B groups	
Figure 39 – Open data – Type 15A group	41
Figure 40 – Fast basic tuning and switching information – Type 15B group	41
Figure 41 – Structure of Block 3 of Type 1A groups	48
Figure 42 – Structure of variant 12 of block 3 of type 14A groups (linkage information) – National link	
Figure 43 – Structure of variant 12 of block 3 of type 14A groups (linkage information) – International link	50
Figure 44 – Structure of Variant 7 of Block 3 of type 1A groups for Identification of a programme carrying EWS information	
Figure B.1 – Generator matrix of the basic shortened cyclic code in binary notation	60
Figure B.2 – Shift-register implementation of the encoder	
Figure B.3 – Parity-check matrix of the basic shortened cyclic code	62
Figure B.4 – Shift-register implementation of the decoder	63
Figure C.1 – Group and block synchronisation detection circuit	66
Figure D.1 – PI structure	68

Figure D.2 – Structure of Variant 0 of Block 3 of Type 1A groups (Extended Country Codes)	69
Figure D.3 – Correspondence between geographical locations and the symbols used for the various countries within the European Broadcasting Area as an example	69
Figure G.1 – Conversion routes between Modified Julian Date (MJD) and Coordinated Universal Time (UTC)	89
Figure U.1 – Language identification code allocation	
Figure M.1 – Group type 7A message format for Radio Paging	
Figure M.2 – Group type 7A paging without an additional message	
Figure M.3 – Group type 7A paging with an additional 10 digit message	103
Figure M.4 – Group type 7A paging with an additional 18 digit message	103
Figure M.5 – Group type 7A paging with an additional alphanumeric message	104
Figure M.6 – Group type 7A paging with an additional international 15 digit message	105
Figure M.7 – Functions message in international paging	106
Figure M.8 – Variant 0 of 1A group with PIN	108
Figure M.9 – Variant 2 of 1A group with PIN	109
Figure M.10 – Variants of 1A group without PIN	110
Figure M.11 – Group type 13A	116
Figure M.12 – Tone-only message	118
Figure M.13 – First 7A group of a variable-length message	118
Figure M.14 – Group type 7A national paging with additional alphanumeric message	120
Figure M.15 – Group type 7A national paging with additional variable-length numeric message	121
Figure M.16 – Group type 7A national paging with additional variable-length functions message	122
Figure M.17 – The two first 7A groups of an international alphanumeric message	124
Figure M.18 – The two first 7A groups of an international variable-length numeric message	124
Figure M.19 – The two first 7A groups of an international variable-length functions message	124
Figure M.20 – Traffic handling capacity, busy hour, call rate = 0,10 calls/pager/hour	128
Figure M.21 – Traffic handling capacity, busy hour, call rate = 0,067 calls/pager/hour	129
Figure M.22 – Traffic handling capacity, busy hour, call rate = 0,05 calls/pager/hour	129
Figure P.1 – RT+ information of the category 'Item' (see Table P.2) will be attached to the programme elements Item 1 and Item 2	140
Figure P.2 – RT+ information of the category 'Item' will be attached to the programme elements Item 1 and Item 2, but not to the programme element News	140
Figure P.3 – RT+ information of the category 'Item' will be attached only to the programme element Item 1, but not to the programme element Talk	140
Figure P.4 – Bit allocation for group 3A (message bits and AID)	141
Figure P.5 – Coding of the message bits of the application group	142
Figure Q.1 – eRT information elements	47
Figure Q.2 – Bit allocation for group 3A (message bits and AID)	148
Figure Q.3 – Coding of the message bits of the application group	149

Table 1 – Encoding rules	13
Table 2 – Decoding rules	14
Table 3 – Group types	21
Table 4 – Main feature repetition rates	22
Table 5 - Group repetition rates	23
Table 6 ODA group availability signalled in type 3A groups	24
Table 7 – STY codes	39
Table 8 – Codes for TP and TA	
Table 9 – Bit d ₀ to d ₃ meanings	42
Table 10 – VHF code table	43
Table 11 – Special meanings code table	43
Table 12 – Code tables according to ITU regions	43
Table A.1 – Offset word codes	58
Table B.1 – Offset word syndromes using matrix of Figure B.3	63
Table C.1 – Offset word syndromes for group and block synchronisation	67
Table D.1 – PI code structure	68
Table D.2 – Symbols used for ECC and PI country codes for the countries in the European Broadcasting Area	70
Table D.3 – Area coverage codes	71
Table D.4 – Programme reference number codes	71
Table D.5 – PI codes for short range transmitting devices	71
Table E.1 – Basic RDS character set	72
Table E.2 – Extended RDS character set, for eRT only	73
Table F.1 – Programme type codes and corresponding terms for display	86
Table G.1 – Symbols used	89
Table J.1 – Language identification codes	92
Table M.1 – Pager group codes	99
Table M.2 – Codes for additional message contents	102
Table M.3 – Paging segment address codes for 10 and 18 digit messages	104
Table M.4 – Paging segment address codes for alphanumeric messages	105
Table M.5 – Paging segment address codes for international 15 digit messages	106
Table M.6 – Paging segment address codes for functions message	107
	110
Table M.8 – Group designation codes	
Table M.9 – Cycle selection codes	115
Table M.10 – Message sorting codes	115
Table M.11 – Codes for message types	
Table M.12 – Description of the control byte	
Table M.13 – Use of paging call repetition flag	() 19
Table M.14 – Paging segment address codes for alphanumeric message	120
Table M.15 – Paging segment address codes for variable length numeric message	121
Table M.16 – Paging segment address codes for variable length functions message	123
Table M.17 – Address notification (50 bits)	126

127
127
135
144

Schment is a preview denerated by FLS

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SPECIFICATION OF THE RADIO DATA SYSTEM (RDS) FOR VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 87,5 MHz TO 108,0 MHz

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations flaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62106 has been prepared by technical area 1: Terminals for audio, video and data services and content, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition cancels and replaces the first edition, published in 2000 and constitutes a technical revision.

The main changes with respect to the previous edition are listed below.

- the list of RDS country codes, inclusive of the extended country codes, has been updated in Annexes D and N;
- Annex E, containing the character code tables to be used in RDS has been updated;
- RadioText Plus has been added as a new feature in Annex P;
- Enhanced RadioText has been added as a new feature in Annex Q.

NOTE 1 IEC 62106:2000 (first edition) and IEC 62106:2009 (second edition) have the same main text and annex structure. However, the main text of this edition is slightly restructured to more closely conform to ISO/IEC Directives, Part 2. Nevertheless, cross-referencing between this edition and the previous edition remains

possible. To find the corresponding subclause quickly, it is basically sufficient to subtract 3 clauses. Example: see 6.1.5.1 becomes, see 3.1.5.1 in the first edition.

The text of this standard is based on the following documents:

CDV	Report on voting
100/1454/CDV	100/1557/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

NOTE 2 For technical reasons equations and some figures had to be left unchanged and are not in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

Assued a. A bilingual version of the publication may be issued at a later date.

SPECIFICATION OF THE RADIO DATA SYSTEM (RDS) FOR VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 87,5 MHz TO 108,0 MHz

1 Scope

This International Standard describes the Radio Data System, RDS, intended for application to VHF/FM sound broadcasts in the range 87,5 MHz to 108,0 MHz which may carry either stereophonic (pilot tone system) or monophonic programmes (see clause 2 – Normative references ITU-R Recommendations BS 450-3 and BS 643-2). The main objectives of RDS are to enable improved functionality for FM receivers and to make them more user-friendly by using features such as Programme Identification, Programme Service name display and where applicable, automatic tuning for portable and car radios, in particular. The relevant basic tuning and switching information therefore has to be implemented by the type 0 group (see 6.1.5.1), and it is not optional unlike many of the other possible features in RDS.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10646, Information technology Universal Multiple-Octet Coded Character Set (UCS)

ISO 14819 (all parts), Traffic and Traveller Information (TTI) – TTI messages via traffic message Coding (TMC)

ITU-R Recommendation BS.450-3, Transmission standards for FM sound broadcasting at VHF

ITU-R Recommendation BS.643-2, System for automatic tuning and other applications in FM radio receivers for use with the pilot-tone system

ITU-T Recommendation E.212, For the three digit Mobile Country Codes used in Annex M of this RDS specification refer to Complement to ITU-T Rec. E.212 (05/2004) published by ITU Geneva as Annex to ITU Operational Bulletin 897, dated 2007-12-01

US NRSC-4-A, National Radio Systems Committee – NRSC-4-A: United States RBDS standard

ETSI EN 301 700, Digital Audio Broadcasting (DAB); VHF/FM broadcasting: cross referencing to simulcast DAB services by RDS-ODA 147

3 Abbreviations and conventions

For the purposes of this document, the following terms and definitions apply.

3.1

AM

amplitude modulation (broadcasting)