

Edition 4.0 2019-02

INTERNATIONAL STANDARD



Low-voltage electrical installations -

Part 5-53: Selection and erection of electrical equipment – Devices for protection for safety, isolation, switching, control and monitoring





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



Edition 4.0 2019-02

INTERNATIONAL STANDARD



Low-voltage electrical installations –
Part 5-53: Selection and erection of electrical equipment – Devices for protection for safety, isolation, switching, control and monitoring

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.130.01; 91.140.50 ISBN 978-2-8322-6509-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.		6
530.1 Scc	pe	8
530.2 Nor	mative references	8
530.3 Ter	ms and definitions	11
530.4 Ger	neral and common requirements	14
530.5 Ere	ction of equipment	14
531 Devices f	or protection against indirect contact by automatic disconnection of	4.4
	ercurrent protective devices	
531.1.1	TN systems	
531.1.2	TT systems	
531.1.3	IT systems	
	sidual current protective devices	
531.2.1	General conditions of installation	
531.2.2	Selection of devices according to their method of application	
531.2.3	TN systems	
531.2.4	TT systems	
531.2.5	IT systems	
	ulation monitoring devices	
	and precautions for protection against thermal effects	
	neral	
532.2 Loc	ations with a particular risk of fire	
532.2.1	General	
532.2.2	Locations with external influences BD2, BD3 or BD4	
532.2.3	Locations with external influences BE2	
	ection of arc fault detection devices (AFDD)	
	or protection against overcurrent	
533.1 Ger	neral requirements	18
533.1.1	General	18
533.1.2	Compliance with standards	18
533.1.3	Fuses	19
533.2 Sel	ection of devices for protection against overload current	
533.2.1	General	
533.2.2	Presence of harmonic currents	20
533.2.3	Unequal current sharing between parallel conductors	
533.3 Sel	ection of devices for protection against short-circuit current	
533.3.1	Thermal stresses	
533.3.2	Breaking capacity	21
533.4 Pos	itioning of overcurrent protection devices	21
533.4.1	General	
533.4.2	Positioning of devices for overload protection	
533.4.3	Positioning of devices for short-circuit protection	
533.5 Co-	ordination of overload and short-circuit protective functions	
533.5.1	Protective functions provided by one device	
533.5.2	Protective functions provided by separate devices	
	or protection against transient overvoltages	

534.1	General	. 23
534.2	Void	. 24
534.3	Void	. 24
534.4	Selection and erection of SPDs	. 24
534.4	4.1 SPD location and SPD test class	. 24
534.4	1.2 Transient overvoltage protection requirements	. 25
534.4	1.3 Connection types	. 25
534.4	1.4 Selection of SPDs	. 27
534.4	1.5 Protection of the SPD against overcurrent	.31
534.4	1.6 Fault protection	. 33
534.4	1.7 SPDs installation in conjunction with RCDs	. 34
534.4		
534.4		
534.4	1.10 Connecting conductors of SPDs	
	rdination of protective devices	
	Selectivity between overcurrent protective devices	
535.1		
535. ²		. 37
535. ²		
535. ²		
535. ²		
	Co-ordination between residual current protective devices and OCPDs	
	Selectivity between residual current protective devices and OCFDs	
	Selectivity of RCD and OCPD	
	·	
	Combined short-circuit protection of OCPDstion and switching	
	Isolation	
536.2		
536.2		
	Switching-off for mechanical maintenance	
536.3		
536.3		
	Emergency switching	
536.4		.43
536.4	5 , 5	.43
536.4	0 7 11 0	
536.5	Functional switching (control)	
536.5		
536.5		
	toring	
537.1	General	. 45
537.	1.1 Monitoring devices	.45
537.	1.2 Selection of insulation monitoring devices (IMDs)	. 45
537.	1.3 Selection of residual current monitoring devices (RCMs)	.45
537.2	IT systems for continuity of supply	.45
537.2	2.1 General	.45
537.2	2.2 Insulation monitoring devices (IMDs)	.46
537.2	2.3 Installation of IMDs	.46
527.2	IT public distribution system	.46

537.4 Off-line systems in TN, TT and IT systems	46
Annex A (informative) Position of devices for overload protection	48
A.1 General	48
A.2 Cases where overload protection need not be placed at the origin of the branch circuit	48
Annex B (informative) Position of devices for short-circuit protection	50
B.1 General	50
B.2 Cases where short-circuit protection need not be placed at the origin of branch circuit	50
Annex C (informative) SPD installation – Examples of installation diagrams according to system configurations	52
C.1 TT system – 3 phase supply plus neutral	52
C.2 TN-C and TN-C-S systems – 3 phase supply	56
C.3 TN-S system – 3 phase supply plus neutral	60
C.4 IT system – 3 phase supply with or without neutral	
Annex D (informative) Installation supplied by overhead lines	65
Annex E (normative) Reference standards for devices for isolation and switching	66
Annex F (informative) List of notes concerning certain countries	68
Bibliography	75
Figure 1 – Example of installation of class I, class II and class III tested SPDs	25
Figure 2 – Connection type CT1 (4+0-configuration) for a three-phase system with neutral	26
Figure 3 – Connection type CT1 (3+0-configuration) for a three-phase system	
Figure 4 – Connection type CT2 (e.g. 3+1-configuration) for a three-phase system with neutral	
Figure 5 – Connection points of an SPD assembly	
Figure 6 – Example of overcurrent protection in the SPD branch by using a dedicated	01
external overcurrent protective device	32
Figure 7 – Protective device, which is a part of the installation, also used to protect the SPD	33
Figure 8 – Connection of the SPD	35
Figure 9 – Example of installation of an SPD in order to decrease lead length of SPD supply conductors	36
Figure 10 – Example of selectivity	38
Figure 11 – Example of currents and their correlation to selectivity	
Figure 12 – Example of combined short-circuit protection of OCPDs	
Figure A.1 – Overload protective device (P ₂) not at the origin of branch circuit (B)	
Figure A.2 – Overload protective device (P ₂) installed within 3 m of the origin of the	
branch circuit (B)	49
	50
Figure B.2 – Short-circuit protective device P ₂ installed at a point on the supply side of the origin of a branch circuit	51
Figure C.1 – Example of SPDA installation with connexion type CT2 on the supply side (upstream) of the main RCD in TT system	52
Figure C.2 – Example of SPD installation with connexion type CT2 on the supply side (upstream) of the main RCD in TT system	53

Figure C.5 – Example of SPDA installation in TN-C system	RCD in TT system	54
Figure C.5 – Example of SPDA installation in TN-C system	Figure C.4 – Example of SPD installation on the load side (downstream) of the RCD in	5 5
Figure C.6 – Example of SPD installation with connexion type CT1 in TN-C system		
Figure C.7 – Example of SPD installation in TN-C-S system where the PEN is separated into PE and N at the origin of the installation (upstream of the SPD)		
separated into PE and N at the origin of the installation (upstream of the SPD)		57
Figure C.9 – Example of SPDA installation in TN-S system		58
Figure C.10 – Example of SPDs installation in TN-S	Figure C.8 – Example of SPDs installation in TN-C-S in different distribution boards	59
Figure C.11 – Example of SPDA installation in IT system with neutral	Figure C.9 – Example of SPDA installation in TN-S system	60
Figure C.12 – Example of SPD installation in IT system without neutral	Figure C.10 – Example of SPDs installation in TN-S	61
Figure C.13 – Example of SPD installation in IT system with neutral	Figure C.11 – Example of SPDA installation in IT system with neutral	62
Figure F.1 – Single user	Figure C.12 – Example of SPD installation in IT system without neutral	63
Figure F.2 – Several users	Figure C.13 – Example of SPD installation in IT system with neutral	64
Figure F.3 – Lamp control circuit with switching in the neutral conductor	Figure F.1 – Single user	71
Table 1 – Required rated impulse voltage of equipment	Figure F.2 – Several users	71
Table 2 – $U_{\rm C}$ of the SPD dependent on supply system configuration	Figure F.3 – Lamp control circuit with switching in the neutral conductor	73
Table 2 – $U_{\rm C}$ of the SPD dependent on supply system configuration	\sim	
Table 3 – Nominal discharge current $(I_{\rm I})$ in kA depending on supply system and connection type	Table 1 – Required rated impulse voltage of equipment	28
Table 4 – Selection of impulse discharge current (I_{imp}) where the building is protected against direct lightning strike	Table 2 – $U_{ m C}$ of the SPD dependent on supply system configuration	29
Table 4 – Selection of impulse discharge current (I_{imp}) where the building is protected against direct lightning strike	Table 3 – Nominal discharge current (<i>I</i> _n) in kA depending on supply system and connection type	30
Table D.1 – Selection of impulse discharge current (I _{imp})65 Table E.1 – Devices for isolation and switching66	Table 4 – Selection of impulse discharge current (I_{imp}) where the building is protected against direct lightning strike	30
Table E.1 – Devices for isolation and switching66	Table 5 – Connection of the SPD dependent on supply system	34
Table E.1 – Devices for isolation and switching66	Table D.1 – Selection of impulse discharge current ($I_{ m imp}$)	65
		Q,

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LOW-VOLTAGE ELECTRICAL INSTALLATIONS -

Part 5-53: Selection and erection of electrical equipment – Devices for protection for safety, isolation, switching, control and monitoring

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60364 has been prepared by IEC technical committee 64: Electrical installations and protection against electric shock.

This fourth edition cancels and replaces the third edition published in 2001, Amendment 1:2002 and Amendment 2:2015. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) revision of all clauses except 531 and 534;
- b) introduction of a new Clause 537 Monitoring;
- c) Clause 530 contains all normative references and all terms and definitions.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
64/2352/FDIS	64/2359/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The reader's attention is drawn to the fact that Annex F lists all of the "in-some-country" clauses on differing practices relating to the subject of this standard.

A list of all parts in the IEC 60364 series, published under the general title *Low-voltage* electrical installations, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- · replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

LOW-VOLTAGE ELECTRICAL INSTALLATIONS -

Part 5-53: Selection and erection of electrical equipment – Devices for protection for safety, isolation, switching, control and monitoring

530.1 Scope

This document provides requirements for:

- a) isolation, switching, control and monitoring, and
- b) selection and erection of:
 - 1) devices for isolation, switching, control and monitoring, and
 - 2) devices to achieve compliance with measures of protection for safety.

530.2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60204-1, Safety of machinery – Electrical equipment of machines – Part 1: General requirements

IEC 60269-2, Low-voltage fuses – Part 2: Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application) – Examples of standardized systems of fuses A to K

IEC 60269-3, Low-voltage fuses – Part 3: Supplementary requirements for fuses for use by unskilled persons (fuses mainly for household and similar applications) – Examples of standardized systems of fuses A to F

IEC 60269-4, Low-voltage fuses – Part 4: Supplementary requirements for use-links for the protection of semiconductor devices

IEC 60309 (all parts), Plugs, socket-outlets and couplers for industrial purposes

IEC 60364 (all parts), Low-voltage electrical installations

IEC 60364-4-41:2005, Low-voltage electrical installations – Part 4-41: Protection for safety – Protection against electric shock IEC 60364-4-41:2005/AMD1:2017

IEC 60364-4-42:2010, Low-voltage electrical installations – Part 4-42: Protection for safety – Protection against thermal effects IEC 60364-4-42:2010/AMD1:2014

IEC 60364-4-43:2008, Low-voltage electrical installations – Part 4-43: Protection for safety – Protection against overcurrent

IEC 60364-4-44:2007, Low-voltage electrical installations – Part 4-44: Protection for safety – Protection against voltage disturbances and electromagnetic disturbances IEC 60364-4-44:2007/AMD1:2015

IEC 60364-5-55, Electrical installations of buildings – Part 5-55: Selection and erection of electrical equipment – Other equipment

IEC 60364-6:2016, Low voltage electrical installations- Part 6: Verification

IEC 60417 (all parts), Graphical symbols for use on equipment

IEC 60664-1:2007, Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests

IEC 60669-1, Switches for household and similar fixed-electrical installations – Part 1: General requirements

IEC 60669-2-1, Switches for household and similar fixed electrical installations – Part 2-1: Particular requirements – Electronic switches

IEC 60669-2-2, Switches for household and similar fixed electrical installations – Part 2-2: Particular requirements – Electromagnetic remote-control switches (RCS)

IEC 60669-2-3, Switches for household and similar fixed electrical installations – Part 2-3: Particular requirements – Time-delay switches (TDS)

IEC 60669-2-4, Switches for household and similar fixed electrical installations – Part 2-4: Particular requirements – Isolating switches

IEC 60669-2-5, Switches for household and similar fixed electrical installations – Part 2-5: Particular requirements – Switches and related accessories for use in home and building electronic systems (HBES)

IEC 60669-2-6, Switches for household and similar fixed electrical installations – Part 2-6: Particular requirements – Fireman's switches for exterior and interior signs and luminaires

IEC 60670-24, Boxes and enclosures for electrical accessories for household and similar fixed electrical installations – Part 24: Particular requirements for enclosures for housing protective devices and other power dissipating electrical equipment

IEC 60884 (all parts), Plugs and socket-outlets for household and similar purposes

IEC 60898 (all parts), Electrical accessories – Circuit-breakers for overcurrent protection for household and similar installations

IEC 60906 (all parts), IEC system of plugs and socket-outlets for household and similar purposes

IEC 60947-2:2016, Low-voltage switchgear and controlgear – Part 2: Circuit-breakers

IEC 60947-3, Low-voltage switchgear and controlgear – Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units

IEC 60947-4-1, Low-voltage switchgear and controlgear – Part 4-1: Contactors and motor-starters – Electromechanical contactors and motor-starters

IEC 60947-4-2, Low-voltage switchgear and controlgear – Part 4-2: Contactors and motor-starters – AC semiconductor motor controllers and starters

IEC 60947-4-3, Low-voltage switchgear and controlgear – Part 4-3: Contactors and motor-starters – AC semiconductor controllers and contactors for non-motor loads

IEC 60947-5-1, Low-voltage switchgear and controlgear – Part 5-1: Control circuit devices and switching elements – Electromechanical control circuit devices

IEC 60947-6-1, Low-voltage switchgear and controlgear – Part 6-1: Multiple function equipment – Transfer switching equipment

IEC 60947-6-2, Low-voltage switchgear and controlgear – Part 6-2: Multiple function equipment – Control and protective switching devices (or equipment) (CPS)

IEC 61008 (all parts), Residual current operated circuit-breakers without integral overcurrent protection for household and similar uses (RCCBs)

IEC 61009 (all parts), Residual current operated circuit-breakers with integral overcurrent protection for household and similar uses (RCBOs)

IEC 61095, Electromechanical contactors for household and similar purposes

IEC 61439-2, Low-voltage switchgear and controlgear assemblies – Part 2: Power switchgear and controlgear assemblies

IEC 61439-3, Low-voltage switchgear and controlgear assemblies – Part 3: Distribution boards intended to be operated by ordinary persons (DBO)

IEC 61439-6, Low-voltage switchgear and controlgear assemblies – Part 6: Busbar trunking systems (busways)

IEC 61534 (all parts), Powertrack systems

IEC 61557-8, Electrical safety in low voltage distribution systems up to 1 000 V a.c. and 1 500 V d.c. – Equipment for testing, measuring or monitoring of protective measures – Part 8: Insulation monitoring devices for IT systems

IEC 61557-9, Electrical safety in low voltage distribution systems up to 1 000 V a.c. and 1 500 V d.c. – Equipment for testing, measuring or monitoring of protective measures – Part 9: Equipment for insulation fault location in IT systems

IEC 61643-11, Low-voltage surge protective devices – Part 11: Surge protective devices connected to low-voltage power systems – Requirements and test methods

IEC 61643-12, Low-voltage surge protective devices – Part 12: Surge protective devices connected to low-voltage power distribution systems – Selection and application principles

IEC 61984:2008, Connectors – Safety requirements and tests

IEC 61995 (all parts), Devices for the connection of luminaires for household and similar purposes

IEC 62020, Electrical accessories – Residual current monitors for household and similar uses (RCMs)

IEC 62208, Empty enclosures for low-voltage switchgear and controlgear assemblies – General requirements

IEC 62305 (all parts), Protection against lightning

IEC 62423, Type F and type B residual current operated circuit-breakers with and without integral overcurrent protection for household and similar uses

IEC 62606, General requirements for arc fault detection devices

IEC 62626-1, Low-voltage switchgear and controlgear enclosed equipment – Part 1: Enclosed switch-disconnectors outside the scope of IEC 60947-3 to provide isolation during repair and maintenance work

530.3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp.

530.3.1

disconnector

mechanical switching device which in the open position complies with the requirements specified for the isolating function

Note 1 to entry: A disconnector is capable of opening and closing a circuit when either negligible current is broken or made, or when no significant change in the voltage across the terminals of each of the poles of the disconnector occurs. It is also capable of carrying currents under normal circuit conditions and carrying for a specified time currents under abnormal conditions such as those of short-circuit.

[SOURCE: IEC 60050-441:2000, 441-14-05, modified – Referring to isolating function instead of isolating distance.]

530.3.2

switch disconnector

switch which, in the open position, satisfies the isolating requirements specified for a disconnector

[SOURCE: IEC 60050-441:1984, 441-14-12]

530.3.3

mechanical switch

device capable of making, carrying and breaking currents through contacts controlled by mechanical operation under normal circuit conditions which may include specified operating overload conditions and also carrying for specified time currents under specified abnormal circuit conditions such as those of short-circuit

Note 1 to entry: A switch can be capable of making but not breaking short-circuit currents.

[SOURCE: IEC 60050-441:2000, 441-14-10, modified – "through contacts controlled by mechanical operation" has been added.]

530.3.4

switching-off for mechanical maintenance

opening operation of a switching device intended to inactivate an item or items of electrically powered equipment for the purpose of preventing a hazard, other than due to electric shock or to arcing, during non-electrical work on the equipment