

# INTERNATIONAL STANDARD

**Electrical accessories – Circuit-breakers for overcurrent protection for  
household and similar installations –  
Part 3: Circuit-breakers for DC operation**



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

# INTERNATIONAL STANDARD

**Electrical accessories – Circuit-breakers for overcurrent protection for  
household and similar installations –  
Part 3: Circuit-breakers for DC operation**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 29.120.50

ISBN 978-2-8322-6676-2

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

|  |    |
|--|----|
| FOREWORD.....  | 9  |
| 1 Scope.....   | 11 |
| 2 Normative references .....   | 12 |
| 3 Terms and definitions .....  | 12 |
| 3.1 Devices.....   | 13 |
| 3.2 General terms .....  | 13 |
| 3.3 Constructional elements.....   | 15 |
| 3.4 Conditions of operation .....  | 18 |
| 3.5 Characteristic quantities .....  | 19 |
| 3.6 Definitions related to insulation co-ordination.....                           | 23 |
| 4 Classification.....  | 25 |
| 4.1 General.....   | 25 |
| 4.2 According to the number of poles.....  | 25 |
| 4.3 According to the current direction through the poles.....                      | 25 |
| 4.4 According to the protection against external influences .....                  | 26 |
| 4.5 According to the method of mounting .....                                      | 26 |
| 4.6 According to the methods of connection.....                                    | 26 |
| 4.6.1 According to the fixation system .....                                       | 26 |
| 4.6.2 According to the type of terminals.....                                      | 26 |
| 4.7 According to the instantaneous tripping current (see 3.5.18).....              | 26 |
| 5 Characteristics of circuit-breakers.....   | 26 |
| 5.1 List of characteristics .....  | 26 |
| 5.2 Rated quantities.....  | 27 |
| 5.2.1 Rated voltages .....   | 27 |
| 5.2.2 Rated direct current ( $I_n$ ) .....   | 27 |
| 5.2.3 Rated short-circuit capacity ( $I_{cn}$ ) .....                              | 27 |
| 5.2.4 Rated making and breaking capacity of an individual pole ( $I_{cn1}$ ) ..... | 27 |
| 5.3 Standard and preferred values .....  | 28 |
| 5.3.1 Preferred values of rated voltage .....                                      | 28 |
| 5.3.2 Preferred values of rated current .....                                      | 28 |
| 5.3.3 Values of rated short-circuit capacity .....                                 | 28 |
| 5.3.4 Standard ranges of instantaneous tripping.....                               | 28 |
| 5.3.5 Standard value of rated impulse withstand voltage ( $U_{imp}$ ).....         | 28 |
| 6 Marking and other product information.....                                       | 29 |
| 7 Standard conditions for operation in service .....                               | 30 |
| 7.1 General.....   | 30 |
| 7.2 Ambient air temperature range.....   | 30 |
| 7.3 Altitude .....   | 31 |
| 7.4 Atmospheric conditions .....   | 31 |
| 7.5 Conditions of installation .....   | 31 |
| 7.6 Pollution degree.....  | 31 |
| 8 Requirements for construction and operation.....                                 | 31 |
| 8.1 Mechanical design .....  | 31 |
| 8.1.1 General .....  | 31 |
| 8.1.2 Mechanism .....  | 31 |
| 8.1.3 Clearances and creepage distances (see Annex A) .....                        | 33 |

|       |  |    |
|-------|--|----|
| 8.1.4 | Screws, current-carrying parts and connections .....   | 35 |
| 8.1.5 | Terminals for external conductors .....  | 36 |
| 8.1.6 | Non-interchangeability .....   | 38 |
| 8.1.7 | Mechanical mounting of plug-in type circuit-breakers .....   | 39 |
| 8.2   | Protection against electric shock .....  | 39 |
| 8.3   | Dielectric properties and isolating capability .....   | 39 |
| 8.3.1 | General .....  | 39 |
| 8.3.2 | Dielectric properties .....  | 40 |
| 8.3.3 | Isolating capability .....   | 40 |
| 8.3.4 | Dielectric strength at rated impulse withstand voltage ( $U_{imp}$ ) .....   | 40 |
| 8.4   | Temperature rise .....   | 40 |
| 8.4.1 | Temperature rise limits .....  | 40 |
| 8.4.2 | Ambient air temperature .....  | 40 |
| 8.5   | Uninterrupted duty .....   | 41 |
| 8.6   | Automatic operation .....  | 41 |
| 8.6.1 | Standard time-current zone .....   | 41 |
| 8.6.2 | Conventional quantities .....  | 42 |
| 8.6.3 | Tripping characteristic .....  | 42 |
| 8.7   | Mechanical and electrical endurance .....  | 42 |
| 8.8   | Performance at short-circuit currents and at small DC currents .....   | 43 |
| 8.9   | Resistance to mechanical shock and impact .....  | 43 |
| 8.10  | Resistance to heat .....   | 43 |
| 8.11  | Resistance to abnormal heat and to fire .....  | 43 |
| 8.12  | Resistance to rusting .....  | 43 |
| 8.13  | Behaviour in case of making inrush current .....   | 43 |
| 8.14  | Power loss .....   | 43 |
| 8.15  | Requirement of small DC currents .....   | 44 |
| 9     | Tests .....  | 44 |
| 9.1   | Type tests and test sequences .....  | 44 |
| 9.2   | Test conditions .....  | 45 |
| 9.3   | Test of indelibility of marking .....  | 46 |
| 9.4   | Test of reliability of screws, current-carrying parts and connections .....  | 46 |
| 9.5   | Tests of reliability of screw-type terminals for external copper conductors .....  | 47 |
| 9.6   | Test of protection against electric shock .....  | 49 |
| 9.7   | Test of dielectric properties .....  | 49 |
| 9.7.1 | Resistance to humidity .....   | 49 |
| 9.7.2 | Insulation resistance of the main circuit .....  | 50 |
| 9.7.3 | Dielectric strength of the main circuit .....  | 51 |
| 9.7.4 | Insulation resistance and dielectric strength of auxiliary circuits .....  | 51 |
| 9.7.5 | Verification of impulse withstand voltages (across clearances and across solid insulation) and of leakage current across open contacts ..... | 52 |
| 9.8   | Test of temperature rise and measurement of power loss .....   | 55 |
| 9.8.1 | Ambient air temperature .....  | 55 |
| 9.8.2 | Test procedure .....   | 55 |
| 9.8.3 | Measurement of the temperature of parts .....  | 55 |
| 9.8.4 | Temperature rise of a part .....   | 55 |
| 9.8.5 | Measurement of power loss .....  | 55 |
| 9.9   | 28-day test .....  | 56 |
| 9.10  | Test of tripping characteristic .....  | 56 |

|         |   |    |
|---------|---|----|
| 9.10.1  | General .....   | 56 |
| 9.10.2  | Test of time-current characteristic.....  | 56 |
| 9.10.3  | Test of instantaneous tripping, of correct opening of the contacts and of the trip-free function .....  | 56 |
| 9.10.4  | Test of effect of single-pole loading on the tripping characteristic of multipole circuit-breakers..... | 57 |
| 9.10.5  | Test of effect of ambient temperature on the tripping characteristic .....                              | 58 |
| 9.11    | Verification of mechanical and electrical endurance .....   | 58 |
| 9.11.1  | General test conditions .....   | 58 |
| 9.11.2  | Test procedure .....  | 58 |
| 9.11.3  | Condition of the circuit-breaker after test .....   | 59 |
| 9.12    | Short-circuit tests.....  | 59 |
| 9.12.1  | General .....   | 59 |
| 9.12.2  | Values of test quantities .....   | 60 |
| 9.12.3  | Tolerances on test quantities .....   | 60 |
| 9.12.4  | Test circuit for short-circuit performance.....   | 60 |
| 9.12.5  | Time constant of the test circuits .....  | 61 |
| 9.12.6  | Measurement and verification of $I^2t$ and of the peak current ( $I_p$ ).....                           | 62 |
| 9.12.7  | Calibration of the test circuit .....   | 62 |
| 9.12.8  | Interpretation of records .....   | 62 |
| 9.12.9  | Condition of the circuit-breaker for test .....   | 62 |
| 9.12.10 | Behaviour of the circuit-breaker during short-circuit tests.....  | 64 |
| 9.12.11 | Test procedure .....  | 64 |
| 9.12.12 | Verification of the circuit breaker after short circuit tests .....                                     | 67 |
| 9.13    | Mechanical stresses .....   | 68 |
| 9.13.1  | Mechanical shock .....  | 68 |
| 9.13.2  | Resistance to mechanical stresses and impact .....  | 68 |
| 9.14    | Test of resistance to heat.....   | 71 |
| 9.15    | Resistance to abnormal heat and to fire .....   | 72 |
| 9.16    | Test of resistance to rusting.....  | 73 |
| 9.17    | Verification of the behaviour in case of making inrush current.....                                     | 73 |
| 9.17.1  | General .....   | 73 |
| 9.17.2  | Values of the test quantities.....  | 73 |
| 9.17.3  | Limit deviations of the test quantities .....   | 74 |
| 9.17.4  | Test circuit for the determination of the withstand capacity against making currents .....              | 74 |
| 9.17.5  | Testing for determination of the withstand capacity against making currents .....                       | 75 |
| Annex A | (normative) Determination of clearances and creepage distances .....                                    | 87 |
| A.1     | General.....  | 87 |
| A.2     | Orientation and location of a creepage distance.....  | 87 |
| A.3     | Creepage distances where more than one material is used.....  | 87 |
| A.4     | Creepage distances split by floating conductive part.....   | 87 |
| A.5     | Measurement of creepage distances and clearances .....  | 87 |
| Annex B | (normative) Test sequences and number of samples necessary to prove compliance with this document ..... | 92 |
| B.1     | Test sequences .....  | 92 |
| B.2     | Number of samples to be submitted for full test procedure and acceptance criteria .....                 | 93 |
| B.3     | Number of samples to be submitted for simplified test procedure .....                                   | 94 |

|   |     |
|---|-----|
| Annex C (informative) Co-ordination under short-circuit conditions between a circuit-breaker and another short-circuit protective device (SCPD) associated in the same circuit..... | 97  |
| C.1 General.....  | 97  |
| C.2 Purpose .....   | 97  |
| C.3 General requirements for the co-ordination of a circuit-breaker with another SCPD .....   | 98  |
| C.3.1 General consideration.....  | 98  |
| C.3.2 Take-over current .....   | 98  |
| C.3.3 Behaviour of $C_1$ in association with another SCPD .....   | 98  |
| C.4 Type and characteristics of the associated SCPD .....   | 98  |
| C.5 Verification of selectivity .....   | 99  |
| C.6 Verification of back-up protection.....   | 99  |
| C.6.1 Determination of the take-over current.....   | 99  |
| C.6.2 Verification of back-up protection.....   | 99  |
| C.6.3 Tests for verification of back-up protection .....  | 100 |
| C.6.4 Results to be obtained.....   | 101 |
| Annex D (informative) Examples of terminals.....  | 105 |
| Annex E (informative) Correspondence between IEC and AWG copper conductors.....   | 108 |
| Annex F (normative) Arrangement for short-circuit test .....  | 109 |
| Annex G (normative) Routine tests .....   | 112 |
| G.1 General.....  | 112 |
| G.2 Tripping tests.....   | 112 |
| G.3 Verification of clearances between open contacts .....  | 112 |
| Annex H (normative) Particular requirements for circuit-breakers with screwless type terminals for external copper conductors.....  | 113 |
| H.1 Scope .....   | 113 |
| H.2 Normative references.....   | 113 |
| H.3 Terms and definitions.....  | 113 |
| H.4 Classification .....  | 114 |
| H.5 Characteristics of circuit-breakers.....  | 114 |
| H.6 Marking and other product information .....   | 114 |
| H.7 Standard conditions for operation in service.....   | 114 |
| H.8 Requirements for construction and operation .....   | 115 |
| H.8.1 Connection or disconnection of conductors.....  | 115 |
| H.8.2 Dimensions of connectable conductors .....  | 115 |
| H.8.3 Connectable cross-sectional areas .....   | 116 |
| H.8.4 Insertion and disconnection of conductors .....   | 116 |
| H.8.5 Design and construction of terminals .....  | 116 |
| H.8.6 Resistance to ageing .....  | 116 |
| H.9 Tests .....   | 116 |
| H.9.1 Test of reliability of screwless terminals.....   | 116 |
| H.9.2 Tests of reliability of terminals for external conductors: mechanical strength .....  | 117 |
| H.9.3 Cycling test.....   | 118 |
| H.10 Reference documents .....  | 120 |
| Annex I (normative) Particular requirements for circuit-breakers with flat quick-connect terminations.....  | 121 |
| I.1 Scope .....   | 121 |

|   |   |     |
|---|---|-----|
| I.2   | Normative references.....                             | 121 |
| I.3   | Terms and definitions.....                            | 121 |
| I.4   | Classification .....                                  | 122 |
| I.5   | Characteristics of circuit-breakers.....              | 122 |
| I.6   | Marking and other product information .....           | 122 |
| I.7   | Standard conditions for operation in service.....     | 122 |
| I.8   | Requirements for construction and operation .....     | 122 |
| I.8.1   | Clearances and creepage distances (see Annex A) ..... | 122 |
| I.8.2   | Terminals for external conductors .....               | 123 |
| I.9   | Tests .....   | 123 |
| I.9.1   | Mechanical overload-force .....                       | 123 |
| Annex J (normative) Specific requirements for circuit-breakers with screw-type terminals for external untreated aluminium conductors and with aluminium screw-type terminals for use with copper or with aluminium conductors ..... |   | 128 |
| J.1   | Scope .....   | 128 |
| J.2   | Normative references.....                             | 128 |
| J.3   | Terms and definitions.....                            | 128 |
| J.4   | Classification .....                                  | 129 |
| J.5   | Characteristics of circuit-breakers.....              | 129 |
| J.6   | Marking and other product information .....           | 129 |
| J.7   | Standard conditions for operation in service.....     | 129 |
| J.8   | Constructional requirements .....                     | 130 |
| J.9   | Tests .....   | 130 |
| J.9.1   | Test conditions .....                                 | 132 |
| J.9.2   | Current cycling test.....                             | 132 |
| J.10  | Reference documents .....                             | 137 |
| Bibliography.....   |   | 138 |
| Figure 1 – Thread forming tapping screw .....   |   | 75  |
| Figure 2 – Thread cutting tapping screw .....   |   | 75  |
| Figure 3 – Single-pole circuit-breaker or pole of multiple circuit breaker.....   |   | 75  |
| Figure 4 – Two-pole circuit-breaker with two protected poles .....  |   | 76  |
| Figure 5 – Three-pole circuit-breaker with two protected poles and non-polarized protected M pole .....   |   | 76  |
| Figure 6 – Calibration of the test circuit in case of direct currents .....   |   | 77  |
| Figure 7 –Mechanical shock test apparatus (see 9.13.1).....   |   | 77  |
| Figure 8 – Standard test finger (see 9.6).....  |   | 78  |
| Figure 9 – Mechanical impact test apparatus (see 9.13.2).....   |   | 79  |
| Figure 10 – Striking element for pendulum for mechanical impact test apparatus (see 9.13.2) .....   |   | 80  |
| Figure 11 – Mounting support for mechanical impact test (see 9.13.2) .....  |   | 81  |
| Figure 12 – Example of mounting for a rear fixed circuit-breaker for mechanical impact test (see 9.13.2) .....  |   | 82  |
| Figure 13 – Example of mounting of a panel board type circuit-breaker for mechanical impact test (see 9.13.2) .....   |   | 83  |
| Figure 14 – Application of force for mechanical test on a rail-mounted circuit-breaker (see 9.13.2.4) .....   |   | 84  |
| Figure 15 – Ball-pressure test apparatus.....   |   | 84  |



|   |     |
|---|-----|
| Figure 16 – Example of application of force for mechanical test on two-pole plug-in circuit-breaker, the holding in position of which depends solely on the plug-in connections (see 9.13.2.5)..... | 85  |
| Figure 17 – Diagrammatic representation (see 9.15).....   | 86  |
| Figure 18 – Impedance $Z_1$ for test circuit in Figures 3, 4 and 5 for the simulation of making currents .....  | 86  |
| Figure A.1 – Examples of methods of measuring creepage distances and clearances.....  | 91  |
| Figure C.1 – Overcurrent co-ordination between a circuit-breaker and a fuse or back-up protection by a fuse – Operating characteristics .....   | 102 |
| Figure C.2 – Total selectivity between two circuit-breakers .....   | 103 |
| Figure C.3 – Back-up protection by a circuit-breaker – Operating characteristics .....  | 104 |
| Figure D.1 – Examples of pillar terminals .....   | 105 |
| Figure D.2 – Examples of screw terminals and stud terminals .....   | 106 |
| Figure D.3 – Examples of saddle terminals .....   | 107 |
| Figure D.4 – Examples of lug terminals.....   | 107 |
| Figure F.1 – Test arrangement.....  | 110 |
| Figure F.2 – Grid circuit .....   | 111 |
| Figure F.3 – Grid circuit .....   | 111 |
| Figure H.1 – Connecting samples .....   | 118 |
| Figure H.2 – Examples of screwless-type terminals .....   | 120 |
| Figure I.1 – Example of position of the thermocouple for measurement of the temperature rise .....  | 124 |
| Figure I.2 – Dimensions of male tabs .....  | 125 |
| Figure I.3 – Dimensions of round dimple detents (see Figure I.2).....   | 126 |
| Figure I.4 – Dimensions of rectangular dimple detents (see Figure I.2) .....  | 126 |
| Figure I.5 – Dimensions of hole detents .....   | 126 |
| Figure I.6 – Dimensions of female connectors.....   | 127 |
| Figure J.1 – General arrangement for the test.....  | 136 |
| Figure J.2 .....  | 136 |
| Figure J.3 .....  | 137 |
| Figure J.4 .....  | 137 |
| Figure J.5 .....  | 137 |
| Figure J.6 .....  | 137 |
| Table 1 – Preferred values of rated voltage and corresponding supply systems .....  | 28  |
| Table 2 – Ranges of instantaneous tripping .....  | 28  |
| Table 3 – Minimum clearances and creepage distances.....  | 34  |
| Table 4 – Connectable cross-sections of copper conductors for screw-type terminals.....   | 37  |
| Table 5 – Temperature rise values .....   | 40  |
| Table 6 – Time-current operating characteristics.....   | 41  |
| Table 7 – Maximum power loss per pole .....   | 44  |
| Table 8 – List of type tests .....  | 44  |
| Table 9 – Cross-sectional areas ( $S$ ) of test copper conductors corresponding to the rated currents .....   | 46  |
| Table 10 – Screw thread diameters and applied torques .....   | 47  |

|   |     |
|---|-----|
| Table 11 – Pulling forces .....   | 48  |
| Table 12 – Test voltage of auxiliary circuits .....   | 52  |
| Table 13 – Test voltage for verification of impulse withstand voltage .....   | 54  |
| Table 14 – Test voltage for verifying the suitability for isolation, referred to the rated impulse withstand voltage of the circuit breakers and the altitude where the test is carried out ..... | 54  |
| Table 15 – Applicability of tests .....   | 60  |
| Table 16 – Ratio $k$ between service short-circuit capacity ( $I_{CS}$ ) and rated short-circuit capacity ( $I_{CN}$ ) .....  | 66  |
| Table B.1 – Test sequences.....   | 92  |
| Table B.2 – Number of samples for full test procedure .....   | 94  |
| Table B.3 – Reduction of samples for series of circuit-breakers having different numbers of poles .....   | 95  |
| Table B.4 – Test sequences for a series of circuit-breakers being of different instantaneous tripping classifications .....   | 96  |
| Table H.1 – Connectable conductors .....  | 115 |
| Table H.2 – Cross-sections of copper conductors connectable to screwless-type terminals.....  | 116 |
| Table H.3 – Pull forces .....   | 117 |
| Table I.1 – Informative table on colour code of female connectors in relationship with the cross section of the conductor.....  | 122 |
| Table I.2 – Overload test forces .....  | 123 |
| Table I.3 – Dimensions of tabs.....   | 124 |
| Table I.4 – Dimensions of female connectors.....  | 127 |
| Table J.1 – Marking for terminals .....   | 129 |
| Table J.2 – Connectable cross-sections of aluminium conductors for screw-type terminals.....  | 130 |
| Table J.3 – List of tests according to the material of conductors and terminals.....  | 131 |
| Table J.4 – Connectable conductors and their theoretical diameters .....  | 131 |
| Table J.5 – Cross sections ( $S$ ) of aluminium test conductors corresponding to the rated currents .....   | 132 |
| Table J.6 – Test conductor length .....   | 133 |
| Table J.7 – Equalizer and busbar dimensions .....   | 133 |
| Table J.8 – Test current as a function of rated current .....   | 135 |
| Table J.9 – Example of calculation for determining the average temperature deviation $D$ ....   | 135 |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

# **ELECTRICAL ACCESSORIES – CIRCUIT-BREAKERS FOR OVERCURRENT PROTECTION FOR HOUSEHOLD AND SIMILAR INSTALLATIONS –**

## **Part 3: Circuit-breakers for DC operation**

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60898-3 has been prepared by sub-committee 23E: Circuit-breakers and similar equipment for household use, of IEC technical committee 23: Electrical accessories.

The text of this International Standard is based on the following documents:

|               |                  |
|---------------|------------------|
| FDIS          | Report on voting |
| 23E/1122/FDIS | 23E/1126/RVD     |

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60898 series, published under the general title *Electrical accessories – Circuit-breakers for overcurrent protection for household and similar installations*, can be found on the IEC website.

In this document, the following print types are used:

- Requirements proper: in roman type.
- *Test specifications: in italic type.*
- Explanatory matter: in smaller roman type.

The following differences exist in the countries indicated below.

- 4.7, Note 2: In China, other ranges of instantaneous tripping defined by the manufacturer are allowed.
- Clause 6, Notes 1 and 2: In the following countries: DK, FI, NO, SE and ZA the marking of the symbol on the circuit-breaker is mandatory to indicate that the device provides isolation for the installation downstream. In Australia this marking on the circuit-breaker is mandatory but is not required to be visible after installation.
- H.1, Note: In CZ, DK, NL, NO and CH, the upper limit of current for use of screwless terminals is 16 A.
- H.3.3, Note 1 to entry: In the following countries only universal screwless type terminals are accepted: AT, BE, CN, DK, DE, ES, FR, IT, PT and SE.
- Clause I.1, Note: The use of circuit-breakers with flat quick-connect terminations for rated currents up to and including 20 A is accepted in BE, FR, IT, ES, PT and US.
- I.8.2.2, Note 1: The use for rated currents up to and including 20 A is accepted in BE, FR, IT, PT, ES and US.
- Clause J.1, Note: In Austria, Australia and Germany, the use of aluminium screw-type terminals for use with copper conductors is not allowed.
- In Austria and Germany, terminals for aluminium conductors only are not allowed.
- In Spain, the use of aluminium conductors is not allowed for final circuits in household and similar installations e.g. offices, shops.
- In Denmark, the minimum cross-sectional area for aluminium conductors is 16 mm<sup>2</sup>.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

# **ELECTRICAL ACCESSORIES – CIRCUIT-BREAKERS FOR OVERCURRENT PROTECTION FOR HOUSEHOLD AND SIMILAR INSTALLATIONS –**

## **Part 3: Circuit-breakers for DC operation**

### **1 Scope**

This part of IEC 60898 applies to DC circuit-breakers, having a rated DC voltage not exceeding 440 V, a rated current not exceeding 125 A and a rated short-circuit capacity not exceeding 10 000 A.

These circuit-breakers are intended for the protection against overcurrents of wiring installations of buildings and similar applications; they are designed for use by uninstructed people and for not being maintained.

They are intended for use in an environment with pollution degree 2.

They are suitable for isolation.

Circuit-breakers in compliance with this document are suitable for use in TN, TT, and, under specific conditions, IT systems.

This document also applies to circuit-breakers having more than one rated current, provided that the means for changing from one discrete rating to another is not accessible in normal service and that the rating cannot be changed without the use of a tool.

This document does not apply to

- circuit-breakers intended to protect motors;
- circuit-breakers, the current setting of which is adjustable by means accessible to the user.

For circuit-breakers having a degree of protection higher than IP20 according to IEC 60529, for use in locations where arduous environmental conditions prevail (e.g. excessive humidity, heat or cold or deposition of dust) and in hazardous locations (e.g. where explosions are liable to occur), special constructions can be required.

For an environment with a higher pollution degree, enclosures giving the appropriate degree of protection are used.

This document does not apply to circuit-breakers for AC operation, which is covered by IEC 60898-1.

This document does not apply to circuit-breakers for AC and DC operation, which is covered by IEC 60898-2.

Circuit breakers according to this document have a high resistance against unwanted tripping, regardless whether caused by in-rush currents through loading of electronic loads or by switching operations in the circuit.

**NOTE** Circuit-breakers within the scope of this document can also be used for protection against electric shock in case of a fault, depending on their tripping characteristics and on the characteristics of the installation. The criterion of application for such purposes is dealt with by installation rules.

This document contains all requirements necessary to ensure compliance with the operational characteristics required for these devices by type tests.

It also contains the details relative to test requirements and methods of testing necessary to ensure reproducibility of test results.

Guidance on the coordination, under short-circuit conditions, between a circuit-breaker and another short-circuit protective device (SCPD) is given in Annex C.

Routine tests intended to reveal, as far as safety is concerned, unacceptable variations in material or manufacture are given in Annex G.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-441, *International Electrotechnical Vocabulary – Switchgear, controlgear and fuses* (available at <http://www.electropedia.org>)

IEC 60227 (all parts), *Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V*

IEC 60228:2004, *Conductors of insulated cables*

IEC 60269 (all parts), *Low-voltage fuses*

IEC 60417, *Graphical symbols for use on equipment* (available at <http://www.graphical-symbols.info/equipment>)

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

IEC 60664-1:2007, *Insulation co-ordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests*

IEC 60695-2-10, *Fire hazard testing – Part 2-10: Glowing/hot-wire based test methods – Glow-wire apparatus and common test procedure*

IEC 60695-2-11:2014, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products (GWEPT)*

IEC 60947-2:2016, *Low-voltage switchgear and controlgear – Part 2: Circuit-breakers*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-441, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>