

AKUSTIKA

Heli sumbumine välistingimustes leviku korral

Osa 1: Atmosfääris absorbeeruva heli arvutusmeetod

Acoustics

Attenuation of sound during propagation outdoors

Part 1: Calculation of the absorption of sound by the atmosphere

(ISO 9613-1:1993, identical)

EESTI STANDARDI EESSÕNA**NATIONAL FOREWORD**

See Eesti standard EVS-ISO 9613-1:2020 „Akustika. Heli sumbumine välistingimustes leviku korral. Osa 1: Atmosfääris absorbeeruva heli arvutusmeetod“ sisaldab rahvusvahelise standardi ISO 9613-1:1993 „Acoustics. Attenuation of sound during propagation outdoors. Part 1: Calculation of the absorption of sound by the atmosphere“ identset ingliskeelset teksti.	This Estonian Standard EVS-ISO 9613-1:2020 consists of the identical English text of the International Standard ISO 9613-1:1993 „Acoustics. Attenuation of sound during propagation outdoors. Part 1: Calculation of the absorption of sound by the atmosphere“.
Ettepaneku rahvusvahelise standardi ümbertrüki meetodil ülevõtuks on esitanud EVS/TK 61, standardi avaldamist on korraldanud Eesti Standardikeskus.	Proposal to adopt the International Standard by reprint method has been presented by EVS/TK 61, the Estonian Standard has been published by the Estonian Centre for Standardisation.
Standard EVS-ISO 9613-1:2020 on jõustunud sellekohase teate avaldamisega EVS Teataja 2020. aasta veebruarikuu numbris.	Standard EVS-ISO 9613-1:2020 has been endorsed with a notification published in the February 2020 issue of the official bulletin of the Estonian Centre for Standardisation.
Standard on kättesaadav Eesti Standardikeskusest.	This standard is available from the Estonian Centre for Standardisation.

Käsitlusala

Standardisarja ISO 9613 see osa määratleb analüütilise meetodi heli sumbumise arvutamiseks atmosfääris neeldumise tõttu mitmesugustes meteotingimustes mis tahes allikast pärineva heli kohta, mis levib vastuvõtjani välisõhus.

Puhta tooni helide puhul on sumbumine kindlaks määratud sumbumisteguriga, mis on nelja muutuja funktsioon: helisagedus, õhutemperatuur, -niiskus ja -rõhk. Arvutatud sumbumistegurid on esitatud tabelina järgmiste muutujate vahemike jaoks:

- sagedus 50 Hz kuni 10 kHz,
- temperatuur -20 °C kuni +50 °C,
- suhteline õhuniiskus 10 % kuni 100 % ja
- õhurõhk 101,325 kPa (üks atmosfäär).

Võrrandid on ette nähtud konkreetseks kasutamiseks ka laiematele vahemikele, näiteks ultraheli sagedustel akustilise skaala modelleerimiseks ja madalamatel õhurõhkudel levikul olenevalt maapinna reljeefist.

Lairiba helidele, mida analüüsitakse murdarvuliste oktaavriba filtritega (nt ühe kolmandiku oktaavriba filtrid), on ette nähtud meetod sumbumise arvutamiseks puhta tooniga helisignaali kaudu riba nominaalsagedustel. Alternatiivne spektri-integratsioonimeetod on kirjeldatud lisas D. Heli spekter võib olla lairiba, millel ei ole diskreetse sagedusega komponente, või see võib olla lairiba- ja diskreetse sagedusega helide kombinatsioon.

Standardisarja ISO 9613 see osa kehtib ühtlaste meteotingimustega atmosfääri tingimustel. Samuti võib seda kasutada mõõdetud helirõhutasemetele kohaldatavate kohanduste määramiseks, et võtta arvesse erinevusi atmosfääri neeldumiskadude vahel eri meteotingimustes. Meetodi laiendamist mittehomogeenses keskkonnas käsitletakse lisas C, eelkõige meteotingimustes, mis varieeruvad maapinnast kõrgemal.

Standardisarja ISO 9613 see osa eeldab, et atmosfäär ei sisalda oluliselt udu ega saasteaineid. Heli summutamise arvutamist muude mehhanismide kui atmosfääris neeldumise korral, näiteks refraktsiooni või peegeldumise korral, on kirjeldatud standardis ISO 9613-2.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 17.140.01

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact the Estonian Centre for Standardisation:
Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 9613-1 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Sub-Committee SC 1, *Noise*.

ISO 9613 consists of the following parts, under the general title *Acoustics — Attenuation of sound during propagation outdoors*:

- *Part 1: Calculation of the absorption of sound by the atmosphere*
- *Part 2: A general method of calculation*

Annexes A, B, C, D, E and F of this part of ISO 9613 are for information only.

© ISO 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Introduction

The aim of this International Standard is to specify methods of calculating the attenuation of sound propagating outdoors in order to predict the level of environmental noise at distant locations from various sound sources.

This document is a preview generated by EVS

Acoustics — Attenuation of sound during propagation outdoors —

Part 1:

Calculation of the absorption of sound by the atmosphere

1 Scope

This part of ISO 9613 specifies an analytical method of calculating the attenuation of sound as a result of atmospheric absorption for a variety of meteorological conditions when the sound from any source propagates through the atmosphere outdoors.

For pure-tone sounds, attenuation due to atmospheric absorption is specified in terms of an attenuation coefficient as a function of four variables: the frequency of the sound, and the temperature, humidity and pressure of the air. Computed attenuation coefficients are provided in tabular form for ranges of the variables commonly encountered in the prediction of outdoor sound propagation:

- frequency from 50 Hz to 10 kHz,
- temperature from $-20\text{ }^{\circ}\text{C}$ to $+50\text{ }^{\circ}\text{C}$,
- relative humidity from 10 % to 100 %, and
- pressure of 101,325 kPa (one atmosphere).

Formulae are also provided for wider ranges suitable for particular uses, for example, at ultrasonic frequencies for acoustical scale modelling, and at lower pressures for propagation from high altitudes to the ground.

For wideband sounds analysed by fractional-octave band filters (e.g. one-third-octave band filters), a method is specified for calculating the attenuation due to atmospheric absorption from that specified for pure-tone sounds at the midband frequencies. An alternative spectrum-integration method is described in annex D. The spectrum of the sound may be wide-

band with no significant discrete-frequency components or it may be a combination of wideband and discrete frequency sounds.

This part of ISO 9613 applies to an atmosphere with uniform meteorological conditions. It may also be used to determine adjustments to be applied to measured sound pressure levels to account for differences between atmospheric absorption losses under different meteorological conditions. Extension of the method to inhomogeneous atmospheres is considered in annex C, in particular to meteorological conditions that vary with height above the ground.

This part of ISO 9613 accounts for the principal absorption mechanisms present in an atmosphere devoid of significant fog or atmospheric pollutants. The calculation of sound attenuation by mechanisms other than atmospheric absorption, such as refraction or ground reflection, is described in ISO 9613-2.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 9613. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 9613 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 2533:1975, *Standard Atmosphere*.

ISO 266:1975, *Acoustics — Preferred frequencies for measurements*.

IEC 225:1966, *Octave, half-octave and third-octave band filters intended for the analysis of sounds and vibrations*.

3 Symbols

f	frequency of the sound, in hertz
f_m	midband frequency, in hertz
h	molar concentration of water vapour, as a percentage
p_r	reference ambient atmospheric pressure, in kilopascals
p_i	initial sound pressure amplitude, in pascals
p_t	sound pressure amplitude, in pascals
p_0	reference sound pressure amplitude (20 μ Pa)
p_a	ambient atmospheric pressure, in kilopascals
s	distance, in metres, through which the sound propagates
T	ambient atmospheric temperature, in kelvins
T_0	reference air temperature, in kelvins
α	pure-tone sound attenuation coefficient, in decibels per metre, for atmospheric absorption

NOTE 1 For convenience, in this part of ISO 9613, the shortened term "attenuation coefficient" will be used for α in place of the full description.

δL_t attenuation due to atmospheric absorption, in decibels

4 Reference atmospheric conditions

4.1 Composition

Atmospheric absorption is sensitive to the composition of the air, particularly to the widely varying concentration of water vapour. For clean, dry air at sea level, the standard molar concentrations, or fractional volumes of the three principal, normally fixed, constituents of nitrogen, oxygen and carbon dioxide are: 0,780 84; 0,209 476; and 0,000 314, respectively (taken from ISO 2533). For dry air, other minor trace constituents, which have no significant influence on atmospheric absorption, make up the remaining fraction of 0,009 37. For atmospheric absorption calculations, the standard molar concentrations of the three principal constituents of dry air may be assumed to hold for altitudes up to at least 50 km above mean sea level. However, the molar concentration of water vapour, which has a major influence on atmospheric absorption, varies widely near the ground and by over two orders of magnitude from sea level to 10 km.

4.2 Atmospheric pressure and temperature

For the purposes of this part of ISO 9613, the reference ambient atmospheric pressure, p_r , is that of the International Standard Atmosphere at mean sea level, namely 101,325 kPa. The reference air temperature, T_0 , is 293,15 K (20 °C), i.e. the temperature at which the most reliable data supporting this part of ISO 9613 were obtained.

5 Attenuation coefficients due to atmospheric absorption for pure-tone sounds

5.1 Basic expression for attenuation

As a pure-tone sound propagates through the atmosphere over a distance s , the sound pressure amplitude p_t decreases exponentially as a result of the atmospheric absorption effects covered by this part of ISO 9613 from its initial value p_i , in accordance with the decay formula for plane sound waves in free space

$$p_t = p_i \exp(-0,115 \, 1 \alpha s) \quad \dots (1)$$

NOTE 2 The term $\exp(-0,115 \, 1 \alpha s)$ represents the base e of Napierian logarithms raised to the exponent indicated by the argument in parentheses and the constant $0,115 \, 1 = 1/[10 \lg(e^2)]$.

5.2 Attenuation of sound pressure levels

The attenuation due to atmospheric absorption $\delta L_t(f)$, in decibels, in the sound pressure level of a pure tone with frequency f , from the initial level at $s = 0$ to the level at distance s , is given by

$$\delta L_t(f) = 10 \lg(p_i^2/p_t^2) \quad \text{dB} = \alpha s \quad \dots (2)$$

6 Calculation procedure for pure-tone attenuation coefficients

6.1 Variables

The acoustic and atmospheric variables, i.e. frequency of the sound, ambient atmospheric temperature, molar concentration of water vapour and ambient atmospheric pressure, are listed in clause 3, together with their symbols and units.

NOTES

3 For a specific sample of moist air, the molar concentration of water vapour is the ratio (expressed as a percentage) of the number of kilomoles (i.e. the number of kilogram molecular weights) of water vapour to the sum of the number of kilomoles of dry air and water vapour. By Avogadro's law, the molar concentration of water vapour is also the ratio of the partial pressure of water vapour to the atmospheric pressure.