
**Plastics — Determination of dynamic
mechanical properties —**

**Part 2:
Torsion-pendulum method**

*Plastiques — Détermination des propriétés mécaniques
dynamiques —*

Partie 2: Méthode au pendule de torsion



This document is a preview generated by EMS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Test apparatus	3
5.1 Pendulum	3
5.2 Inertial element	3
5.2.1 General	3
5.2.2 Method A (see Figure 1)	3
5.2.3 Method B (see Figure 2)	3
5.3 Clamps	3
5.4 Oscillation-inducing device	4
5.5 Oscillation-frequency and oscillation-amplitude recording equipment	4
5.6 Temperature-controlled chamber	4
5.7 Gas supply	4
5.8 Temperature-measurement device	4
5.9 Devices for measuring test-specimen dimensions	4
6 Test specimens	4
6.1 General	4
6.2 Shape and dimensions	4
6.3 Preparation	5
7 Number of specimens	5
8 Conditioning	5
9 Procedure	5
9.1 Test atmosphere	5
9.2 Measurement of specimen cross-section	5
9.3 Mounting the test specimens	5
9.4 Varying the temperature	5
9.5 Performing the test	5
10 Expression of results	6
10.1 Symbols and correction factors	6
10.2 Calculation of logarithmic decrement, Δ	7
10.3 Calculation of torsional storage modulus, G'_{to}	8
10.4 Calculation of torsional loss modulus, G''_{to}	8
11 Precision	9
12 Test report	9
Annex A (normative) Influence of longitudinal force, W	10
Annex B (informative) Damping correction factor, F_d	11
Annex C (informative) Dimensional correction factor, F_c	12
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 5, *Physical-chemical properties*.

This third edition cancels and replaces the second edition (ISO 6721-2:2008), which has been technically revised. The main changes compared to the previous edition are as follows:

- the document has been revised editorially;
- normative references have been changed to undated.

A list of all parts in the ISO 6721 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Plastics — Determination of dynamic mechanical properties —

Part 2: Torsion-pendulum method

1 Scope

This document specifies two methods (A and B) for determining the linear dynamic mechanical properties of plastics, i.e. the storage and loss components of the torsional modulus, as a function of temperature, for small deformations within the frequency range from 0,1 Hz to 10 Hz.

NOTE The temperature dependence of these properties, measured over a sufficiently broad range of temperatures (for example from $-50\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$ for most commercially available plastics), gives information on the transition regions (for example the glass transition and the melting transition) of the polymer. It also provides information concerning the onset of plastic flow.

The two methods described are not applicable to non-symmetrical laminates (see ISO 6721-3). The methods are not suitable for testing rubbers, for which the user is referred to ISO 4664-2.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6721-1, *Plastics — Determination of dynamic mechanical properties — Part 1: General principles*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 6721-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Principle

A test specimen of uniform cross-section is gripped by two clamps, one of them fixed and the other connected to a disc, which acts as an inertial element, by a rod. The end of the specimen connected to the disc is excited, together with the disc, to execute freely decaying torsional oscillations. The oscillation mode is that designated IV in ISO 6721-1, and the type of modulus is G_{t0} as defined in ISO 6721-1.

The inertial element is suspended either from the specimen (method A, see [Figure 1](#)) or from a wire (method B, see [Figure 2](#)). In the latter case, the wire is also part of the elastically oscillating system.