INTERNATIONAL STANDARD

ISO 16535

Second edition 2019-06

Thermal insulating products for building applications — Determination of long-term water absorption by immersion

Produits isolants thermiques destinés aux applications du bâtiment — Détermination de l'absorption d'eau à long terme par immersion



Reference number ISO 16535:2019(E)



© ISO 2019

Nementation, no parhanical, including requested for All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Con	ntents	Page
Fore	word	iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle 4.1 Method 1: Partial immersion 4.2 Method 2: Total immersion	1
5	Apparatus	2
6	Test specimens 6.1 Dimensions of test specimens 6.2 Number of test specimens 6.3 Preparation of test specimens 6.4 Conditioning of test specimens	4
7	Procedure 7.1 Test conditions 7.2 Test procedure 7.2.1 Long-term water absorption by partial immersion (method 7.2.2 Long-term water absorption by total immersion (method 2)	
8	Calculation and expression of results 8.1 General 8.2 Long-term water absorption by partial immersion 8.3 Long-term water absorption by total immersion	
9	Accuracy of measurement	9
10	Test report	9
Bibli	Test reportiography	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see: www.iso.org/iso/foreword.html.

This document was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 88, *Thermal insulating materials and products*, in collaboration with ISO Technical Committee TC 163, *Thermal performance and energy use in the built environment*, Subcommittee SC 1, *Test and measurement methods*, in accordance with the agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 16535:2012), which has been technically revised. The main changes compared to the previous edition are as follows:

— The content in 5.3, 6.4, 7.1 and 10 has been revised to reflect the conditions for tropical countries.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Thermal insulating products for building applications — Determination of long-term water absorption by immersion

1 Scope

This document specifies the equipment and procedures for determining the long-term water absorption of test specimens. It is applicable to thermal insulating products.

This document specifies two methods:

- Method 1: Partial immersion:
- Method 2: Total immersion.

The long-term water absorption by partial immersion is intended to simulate the water absorption caused by long-term water exposure.

The long-term water absorption by total immersion is not directly related to the conditions on site, but has been recognized as a relevant condition of test for some products in some applications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 29768, Thermal insulating products for building applications — Determination of linear dimensions of test specimens

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

4 Principle

4.1 Method 1: Partial immersion

The long-term water absorption by partial immersion is determined by measuring the change in mass of a test specimen, the lower part of which is in contact with water for a period of 28 days.

The excess water adhering to the surface, not absorbed by the test specimen, is removed by drainage in method 1A or taken into account by deduction of the initial water uptake in method 1B.