
**Diesel engines — NO_x reduction agent
AUS 32 —**

**Part 5:
Refilling interface for passenger cars**

Moteurs diesel — Agent AUS 32 de réduction des NO_x —

Partie 5: Interface de remplissage pour voitures particulières



This document is a preview generated by ERS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

| | |
|--|-----------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Requirements | 2 |
| 4.1 Functional requirements | 2 |
| 4.2 Filler neck | 4 |
| 4.3 Filler nozzle | 6 |
| 4.4 Clearance space | 7 |
| 4.4.1 General | 7 |
| 4.4.2 Minimum clearance "Class A" | 7 |
| 4.4.3 Minimum clearance "Class B" | 8 |
| 5 Testing | 10 |
| 5.1 General test requirements | 10 |
| 5.2 Determination of spillage from nozzle | 10 |
| 5.3 Determination of smell | 10 |
| 5.3.1 General | 10 |
| 5.3.2 Preconditioning the system to establish constant test conditions | 11 |
| 5.3.3 Test procedure | 11 |
| 5.4 Minimum strength of filler neck | 12 |
| 5.4.1 General | 12 |
| 5.4.2 Testing simulating misuse | 12 |
| 5.4.3 Testing in axial direction | 13 |
| Annex A (informative) Filler neck with ribs | 15 |
| Bibliography | 16 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 34, *Propulsion, powertrain and powertrain fluids*.

This second edition cancels and replaces the first edition (ISO 22241-5:2012) which has been technically revised.

The main changes compared to the previous edition are as follows:

- the definition of AUS 32 has been deleted as it is included in ISO 22241-1 and the document is cited normatively;
- new definitions have been added;
- new normative references have been added;
- [Table 1](#) has been editorially and technically revised.

A list of all parts in the ISO 22241 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The refilling system specified in this document has been developed in accordance with passenger vehicle manufacturer's specifications. The functional requirements include a filling system that has minimal obtrusive odours, has minimal spill risk, limits pressure build-up and includes mismatch prevention. The system should be designed to prevent the deleterious effects of AUS 32, including, but not limited to, uncontrolled flow into gaps in body work with the potential to cause corrosion, smell nuisance and crystal formation.

Diesel engines — NO_x reduction agent AUS 32 —

Part 5: Refilling interface for passenger cars

1 Scope

This document applies to diesel engine powered road vehicles using selective catalytic reduction (SCR) technology. It is primarily intended for use by passenger cars and light commercial vehicles including buses with a gross vehicle mass of not more than 3,5 t, but can also be used by vehicles with a gross vehicle mass of over 3,5 t.

This document specifies the refilling interface for the NO_x reduction agent AUS 32 in conformance with ISO 22241-1, which is needed to operate converters with selective catalytic reduction (SCR) exhaust treatment system. This document specifies the essential functional and geometric requirements of the refilling system in order to ensure compatibility between the on-board refilling system and the off-board refilling system.

For light commercial vehicles and buses having a gross vehicle mass of not more than 3,5 t, the open refilling system specified in ISO 22241-4 can be used.

NOTE Throughout this document, the term “NO_x reduction agent AUS 32” is abbreviated to “AUS 32”.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2575, *Road vehicles — Symbols for controls, indicators and tell-tales*

ISO 22241-1, *Diesel engines — NO_x reduction agent AUS 32 — Part 1: Quality requirements*

ISO 22241-3, *Diesel engines — NO_x reduction agent AUS 32 — Part 3: Handling, transportation, and storage*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 22241-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

refilling system

off-board system and on-board system including their refilling interface for dispensing AUS 32 into the on-board tank of the vehicles

3.2

canister bottle

container of size one to ten litres capacity, with spout, used to refill the on-board tank of the vehicle