Paints and varnishes - Wettability - Part 7: Measurement of the contact angle on a tilt stage (roll-off angle) (ISO 19403-7:2017)



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN ISO 19403-7:2020 sisaldab Euroopa standardi EN ISO 19403-7:2020 ingliskeelset teksti.	This Estonian standard EVS-EN ISO 19403-7:2020 consists of the English text of the European standard EN ISO 19403-7:2020.		
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.		
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 12.02.2020.	Date of Availability of the European standard is 12.02.2020.		
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.		

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile <u>standardiosakond@evs.ee</u>.

ICS 01.040.87

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega: Koduleht <u>www.evs.ee</u>; telefon 605 5050; e-post <u>info@evs.ee</u>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD NORME EUROPÉENNE

EN ISO 19403-7

EUROPÄISCHE NORM

February 2020

ICS 01.040.87

English Version

Paints and varnishes - Wettability - Part 7: Measurement of the contact angle on a tilt stage (roll-off angle) (ISO 19403-7:2017)

Peintures et vernis - Mouillabilité - Partie 7: Mesurage de l'angle de contact sur un plan incliné (angle d'écroulement) (ISO 19403-7:2017) Beschichtungsstoffe - Benetzbarkeit - Teil 7: Messung des Kontaktwinkels bei Neigetischexperimenten (Abrollwinkel) (ISO 19403-7:2017)

This European Standard was approved by CEN on 4 November 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of ISO 19403-7:2017 has been prepared by Technical Committee ISO/TC 35 "Paints and varnishes" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 19403-7:2020 by Technical Committee CEN/TC 139 "Paints and varnishes" the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2020, and conflicting national standards shall be withdrawn at the latest by August 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 19403-7:2017 has been approved by CEN as EN ISO 19403-7:2020 without any modification.

Co	ntents		Page
For	eword		iv
Inti	roduction		v
1	Scope		1
2	Normative	e references	1
3	Terms and	d definitions	1
4	Principle.		2
5	Apparatu	s and materials	2
6	Sampling		4
7	Procedure	e	4
	7.1 7.1 7.1	.2 Test conditions	
	7.2 Me 7.2	asurement	
	7.2		
		.3 Determination of the roll-off angle	
8	Precision		8
9		rt	
		ative) Notes on sampling and treatment of test specimens	
		ative) Factors influencing the roll-off angle	
Bib	liography		13
		2	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 9, *General test methods for paints and varnishes*.

A list of all parts in the ISO 19403 series can be found on the ISO website.

Introduction

Dynamic contact angles describe the processes on the interface liquid/solid during volume increase (advancing angle) or volume decrease (receding angle) of a drop in horizontal position. As an alternative d t wette tween a. e concluded. to the static method (see ISO 19403-2), for the advancing angle always a surface area is wetted, which was previously unwetted. For the receding angle, the contact angle during dewetting is observed. From the difference between advancing angle and receding angle, information on chemical homogeneity and roughness can be concluded. The receding angle is not suitable for the determination of the surface energy.

Paints and varnishes — Wettability —

Part 7:

Measurement of the contact angle on a tilt stage (roll-off angle)

1 Scope

This document specifies a method for the dynamic measurement of the roll-off angle of a liquid drop on a solid surface. From the dynamic measurement, the advancing and receding angles of the drop rolling off can also be determined. The roll-off angle plays a role when evaluating, for example, easy-to-clean or anti-adherent surfaces.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4618, Paints and varnishes — Terms and definitions

ISO 19403-1, Paints and varnishes — Wettability — Part 1: Terminology and general principles

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4618, ISO 19403-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1

roll-off angle

 $\alpha_{\rm S}$

tipping of the surface of the solid body, due to which a liquid drop put down onto this surface rolls off

3.2

advancing angle

 θ_{a}

contact angle, which is measured during advancing of the three-phase point

Note 1 to entry: Generally, the advancing angle is used for the determination of the interface energy, in which case the measurement should be carried out close to the thermodynamic equilibrium. This is approximately reached if there is no influence of, for example, the dosing speed on the contact angle.

[SOURCE: ISO 19403-6:2017, 3.2]