INTERNATIONAL STANDARD

Third edition 2019-08

h j Hydraulic fluid power — Code for identification of valve mounting surfaces and cartridge valve cavities

Transmissions hydrauliques — Code pour l'identification des plans de



Reference number ISO 5783:2019(E)



© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

Contents

Fore	word		iv
Intro	oduction	n	v
1	Scope	ie	
2	Norm	native references	
3	Term	Terms and definitions	
4	Ident	tification code	
5	Size o	code	2
6	Exam 6.1 6.2 6.3	nples for different codes Mounting surface Slip-in cartridge cavity Screw-in cartridge cavity	2 2 3 3 3
Bibli	iograph	ıy	4
		't's a broken was a strand was a	20

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see <u>www.iso</u> .org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 5, *Control products and components*.

This third edition cancels and replaces the second edition (ISO 5783:1995), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the third position of the identification code has been modified in order to allow changes in referenced standards for valve mounting surfaces and cartridge valve cavities.
- the size codes 15, 16 and 17 have been added to <u>Table 1</u>.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

0 02 17 . (

Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure ed. connec avities. within an enclosed circuit. The control and regulation of the fluid are accomplished by valves which can be directly connected to fluid conductors, mounted on sub-plates, or installed as screw-in or slip-in cartridges in cavities.

this document is a preview demendence of the document is a preview demendence of the document of the document

Hydraulic fluid power — Code for identification of valve mounting surfaces and cartridge valve cavities

1 Scope

This document defines an identification code for hydraulic valve mounting surfaces and for hydraulic cartridge valve cavities that are defined in other International Standards (see Bibliography).

This document is not applicable to mounting surfaces and cartridge valve cavities that do not conform to these International Standards.

This document does not require that the hardware be marked with the identification code.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

4 Identification code

The mounting surfaces or the cartridge cavities shall be designated by the five groups of numbers indicated below, written in the order given, and separated by spaced hyphens:

- a) the number of the International Standard in which the mounting surface or the cartridge cavity is described;
- b) two numerals representing
 - either the size of the valve mounting surface (see <u>Clause 5</u>),
 - or the size of the slip-in cartridge valve (see <u>Clause 5</u>),
 - or the cavity thread diameter of the screw-in cartridge valve;
- c) two numerals as an unequivocal numbering;

NOTE In previous editions of this document these numerals were based on the figure number in the International Standard according to a). This could lead to confusion if figures in new versions of these International Standards are deleted and thus the numeral of a certain mounting surface or cavity would change.

d) one sign, e.g. an asterisk (*) or a single number as defined in the International Standard according to a) indicating different options:

numeral 0 is used for the basic version,