TECHNICAL REPORT

ISO/IEC TR 23091-4

First edition 2019-08

Information technology — Codingindependent code points —

Part 4:

art Usage Usage of video signal type code points





© ISO/IEC 2019

Vementation, no part of hanical, including pirequested from All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents					
Fore	word			iv	
Intro	ductio	n		v	
1	Scop	e		1	
2	<.O.	Normative references			
3		Terms and definitions			
4		Abbreviated terms			
5			3		
6			domains		
7	Common video signal type combinations				
	7.1		al		
	7.2		metry and colour range descriptions	7	
		7.2.1	General		
		7.2.2	Colour properties	7	
		7.2.3	Common descriptions and carriage – standard dynamic range video with		
		7.2.4	narrow colour gamut	9	
		7.2.4	Common descriptions and carriage – standard dynamic range video with wide colour gamut	10	
		7.2.5	Common descriptions and carriage – high dynamic range video with wide	10	
			colour gamut		
	7.3		ring display colour volume descriptions	12	
		7.3.1 7.3.2	Mastering display colour volume properties	12	
		7.3.4	descriptionsdescriptions and carriage – mastering display colour volume	13	
D:L1:					
PIDII	ograpn	ı y		15	
			⊘ ,,		
			O_{λ}		

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see http://patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information* in collaboration with ITU-T. The technically identical text is published as ITU-T Series H Supplement 19 (03/2019).

A list of all parts in the ISO/IEC 23091 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document discusses video signal property description code points and their combinations that are widely used in production and video content workflows. Video properties and values are usually expressed in "metadata" that can exist across production and distribution workflows. Knowledge of these properties and their combinations has value as content is processed in the end-to-end production-to-distribution workflow chain.

The combinations of all possible expressible video properties as code point values could hypothetically result in hundreds or thousands of permutations; but many of those combinations are rarely or never used in practice. For example, it is highly unlikely that perceptual quantization (PQ) transfer characteristics function specified in Rec. ITU-R BT.2100 would be combined with the colour primaries specified in Rec. ITU-R BT.601. Only a small subset of the possible combinations is used in practice.

This document is intended to help the producers of various content processing tools to avoid processing mistakes that can cause video quality degradation due to having incorrect assumptions made about video property combinations. There are only a few limited sets of video property combinations that are widely used in present-day video production and distribution equipment chains. This document describes these limited sets of combinations that are currently widely used and describes how the associated signal type metadata is carried to aid in the automation of content workflows across various domains of capture, production and distribution. Lastly, this document aims to help its readers, especially toolset developers, to repurpose tools to work properly across several domains (e.g., capture, vice convers production, production distribution, and service distribution) where similar video conversion functions (e.g., chroma sub-sampling or colour space conversions) may be performed.

This document is a preview general ded by tills

Information technology — Coding-independent code points —

Part 4:

Usage of video signal type code points

1 Scope

This document describes common industry representation practices for the usage of video signal type code points, as these properties are conveyed across video content production and distribution carriage systems.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Rec. ITU-T H.264 | ISO/IEC 14496-10, Information technology — Coding of audio-visual objects — Part 10: Advanced video coding

Rec. ITU-T H.265 | ISO/IEC 23008-2, Information technology — High efficiency coding and media delivery in heterogeneous environments — High efficiency video coding

Rec. ITU-T H.273 | ISO/IEC 23091-2, Information technology — Coding-independent code points — Part 2: Video

3 Terms and definitions

For the purposes of this document, the terms and definitions in Rec. ITU-T H.265 | ISO/IEC 23008-2, Rec. ITU-T H.264 | ISO/IEC 14496-10 and Rec. ITU-T H.273 | ISO/IEC 23091-2 and the following apply.

ISO ad IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at http://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org

3.1

colour volume

space of all colours and intensities that a device or signal can reproduce or convey

3.2

creative intent

desired vision of the content creator who adjusts and approves the appearance of rendered content in the production process

Note 1 to entry: Examples of a content creator are a director, cinematographer, videographer, editor or colourist.

3.3

electro-optical transfer function EOTF

function to map a non-linear video signal to display linear light