
**Heavy commercial vehicles
and buses — Centre of gravity
measurements — Axle lift, tilt-table
and stable pendulum test methods**

*Véhicules utilitaires lourds et autobus — Mesure du centre de gravité —
Méthode d'essais du plateau incliné, levage d'un essieu et pendule stable*



This document is a preview generated by ERS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principles	3
5 Variables	3
5.1 Reference system	3
5.2 Variables to be measured	3
5.2.1 Variables to be measured for location of x_{CG} and y_{CG} coordinates of centre of gravity in horizontal plane	3
5.2.2 Variables to be measured using the axle lift method for location of z_{CG} coordinates	4
5.2.3 Variables to be measured using the tilt-table method for location of z_{CG} coordinates	4
5.2.4 Variables to be measured using the stable pendulum method for location of z_{CG} coordinates	4
6 Measuring equipment	5
7 Test conditions	6
7.1 General	6
7.2 Ambient conditions	6
7.3 Test surface	6
7.4 Test vehicle	6
7.5 Operating and other liquids	6
7.6 Loading conditions, suspension and mechanical parts	6
8 Determination of the centre of gravity in the horizontal plane	7
8.1 General	7
8.2 x_{CG} position of the centre of gravity in the horizontal plane	7
8.2.1 Two axle vehicles	7
8.2.2 More than two axles	7
8.3 y_{CG} position of the centre of gravity in the horizontal plane	8
8.3.1 Two axle vehicles	8
8.3.2 More than two axles	8
9 Determination of the centre of gravity height	8
9.1 General	8
9.2 Axle lift method	8
9.2.1 General guidance	8
9.2.2 Procedure	10
9.2.3 Determination of the axle load and inclination angle	11
9.2.4 Location of the centre of gravity above the ground plane with loaded tyre radius	11
9.3 Tilt-table method	12
9.3.1 General guidance	12
9.3.2 Tilt-table procedures	14
9.3.3 Determination of the centre of gravity height z_{CG}	15
9.3.4 Data presentation	15
9.4 Stable pendulum method	15
9.4.1 General guidance	15
9.4.2 Stable pendulum procedure	17
9.4.3 Determination of platform properties	17
9.4.4 Determination of the applied torque	17

9.4.5	Consideration of platform deflection	18
9.4.6	Determination of the centre of gravity height, z_{CG}	18
9.4.7	Data Presentation	18
Annex A (informative)	Determination of static loaded radius, r_{stat}	19
Annex B (informative)	Test report — Axle lift method	20
Annex C (informative)	Test report — Tilt method (up to 3 axles)	23
Annex D (informative)	Test report — Stable pendulum method	26
Bibliography	29

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 33, *Vehicle dynamics and chassis components*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Methods are presented for measuring the location of the centre of gravity of an individual vehicle unit in the horizontal, lateral and vertical planes. Location of the longitudinal and lateral centre of gravity positions are obtained through successive use of wheel or platform scales. Three different methods are described for measurement of the vertical centre of gravity – the axle lift method, the tilt-table method, and the stable pendulum method. The selection of the method to use depends on the facility and resource availability, as well as constraints imposed by the vehicle design. Knowledge of a vehicle unit's centre of gravity supports vehicle modelling work, design validation and planning for other dynamic tests yet to be performed.

Heavy commercial vehicles and buses — Centre of gravity measurements — Axle lift, tilt-table and stable pendulum test methods

1 Scope

This document describes a standard method for measuring a vehicle's longitudinal and lateral (horizontal plane) centre of gravity (CG) positions and three methods for estimating a vehicle's vertical CG position, the axle lift, tilt-table, and stable pendulum methods. It applies to heavy vehicles, that is commercial vehicles and buses as defined in ISO 3833 (trucks and trailers with maximum weight above 3,5 tonnes and buses and articulated buses with maximum weight above 5 tonnes, according to ECE and EC vehicle classification, categories M3, N2, N3, O3 and O4). CG measurements are performed separately for each single unit.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 612, *Road vehicles — Dimensions of motor vehicles and towed vehicles — Terms and definitions*

ISO 8855, *Road vehicles — Vehicle dynamics and road-holding ability — Vocabulary*

ISO 15037-2, *Road vehicles — Vehicle dynamics test methods — Part 2: General conditions for heavy vehicles and buses*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8855, ISO 15037-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 scale

instrument or device used to measure total vehicle, axle, track or individual wheel weights

3.2 crane

device used to lift one end of the test vehicle, with sufficient lift capacity

3.3 load cell

device for measuring force along a single axis

3.4 axle hoist

device used to lift an individual axle with the *crane* (3.2) and safety provisions to prevent the axle from leaving the hoist once lifted