

---

---

## Hard coal — Determination of caking index

*Houille — Détermination de l'indice d'agglutination*



This document is a preview generated by ERS



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Principle.....	1
5 Reagent and materials.....	1
6 Apparatus.....	1
7 Preparation of test sample.....	5
8 Procedure.....	6
9 Expression of results.....	6
10 Precision.....	7
10.1 Repeatability limit.....	7
10.2 Reproducibility limit.....	7
11 Test report.....	7
Annex A (informative) Extraction and preparation of standard anthracite for caking index determination.....	8
Annex B (informative) Quality test for standard anthracite used for caking index determination ...	9
Bibliography.....	12

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 27, *Solid mineral fuels*, Subcommittee SC 5, *Methods of analysis*.

This second edition cancels and replaces the first edition (ISO 15585:2006), which has been technically revised. The main changes compared to the previous edition are as follows:

- Change to test precision (both for repeatability,  $r$ , and reproducibility,  $R$ ) resulting from ILS conducted in 2016 and 2017.
- Additional information provided on anthracite sample packing and homogeneity test in [Annex A](#) and standard deviation formula and flowchart for standard anthracite sample taking in [Annex B](#).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

Caking index is a key parameter to identify the caking power of hard coal, which is a measurement of the agglutinating strength between the coal particles and inert constituents after heating without the contact of air. Coal caking characteristic is important and widely used in coking, gasification, liquefaction and combustion industries.



# Hard coal — Determination of caking index

## 1 Scope

This document specifies a method of determination of caking index of hard coal. It is applicable to the evaluation of caking power of bituminous coal with random reflectance of vitrinite,  $R_v$ , greater than 0,6 % and less than or equal to 1,8 % ( $>0,6$  % and  $\leq 1,8$  %).

## 2 Normative references

There are no normative references in this document.

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

### 3.1

#### caking index

measure of the magnitude of the binding strength between coal particles or between coal particles and inert particles after coal is heated at 850 °C

## 4 Principle

A portion of prepared sample of coal of limited size range and the standard anthracite are mixed under defined conditions, and the mixture is carbonized rapidly. The crucible coke thus obtained is tested for strength in a drum conforming to certain specifications. The caking power of the test sample is expressed by the abrasive strength, i.e. resistance to breakage of the crucible coke.

## 5 Reagent and materials

**5.1 Standard anthracite**, having a moisture of less than 2,5 % in mass fraction, air-dried basis, an ash of less than 4 % in mass fraction, dry basis and a volatile matter of less than 8 % in mass fraction, dry, ash free basis. The size limits are 0,1 mm to 0,2 mm. The undersize content of 0,1 mm should not be more than 6 % in mass fraction, and the oversize content of 0,2 mm should not be more than 4 % in mass fraction.

NOTE [Annexes A](#) and [B](#) provide information on the extraction, preparation and testing of standard anthracite.

## 6 Apparatus

**6.1 Balance**, analytical balance with a resolution of at least 0,1 % relative of the test portion mass.