

# **PUBLICLY AVAILABLE SPECIFICATION**

## **PRE-STANDARD**

---

**Industrial communication networks – Broadband fieldbus specification – Autbus**



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

# PUBLICLY AVAILABLE SPECIFICATION

## PRE-STANDARD

---

**Industrial communication networks – Broadband fieldbus specification – Autbus**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 00.000

ISBN 978-2-8322-7749-2

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

|                                                              |    |
|--------------------------------------------------------------|----|
| FOREWORD.....                                                | 11 |
| 1 Scope.....                                                 | 12 |
| 2 Normative references .....                                 | 12 |
| 3 Terms and definitions, abbreviated terms and symbols ..... | 12 |
| 3.1 Terms and definitions.....                               | 12 |
| 3.2 Abbreviated terms.....                                   | 14 |
| 3.3 Symbols.....                                             | 16 |
| 4 Data type.....                                             | 16 |
| 4.1 Overview.....                                            | 16 |
| 4.2 Basic data type .....                                    | 16 |
| 4.2.1 Unsigned type coding (UINT).....                       | 16 |
| 4.2.2 Time type coding (TIMEV) .....                         | 17 |
| 4.2.3 Date type coding (DATE2000) .....                      | 17 |
| 4.2.4 Time of day type coding (TIMEOFDAY) .....              | 18 |
| 4.2.5 Time difference type coding (TIMEDIFFER).....          | 18 |
| 4.2.6 String type coding (STRING) .....                      | 18 |
| 4.2.7 Bitmap type coding (BITMAP).....                       | 19 |
| 4.3 Complex type.....                                        | 19 |
| 4.3.1 Struct type coding (STRUCT).....                       | 19 |
| 4.3.2 Array type coding (ARRAY) .....                        | 19 |
| 5 AUTOBUS overview .....                                     | 19 |
| 5.1 Overview.....                                            | 19 |
| 5.2 AUTOBUS protocol stack architecture .....                | 20 |
| 5.3 Device type.....                                         | 22 |
| 5.3.1 Overview .....                                         | 22 |
| 5.3.2 Control Device.....                                    | 22 |
| 5.3.3 Field Device .....                                     | 22 |
| 5.3.4 Management Node .....                                  | 22 |
| 5.3.5 Terminal Node.....                                     | 22 |
| 5.4 Network topology .....                                   | 22 |
| 6 System management.....                                     | 23 |
| 6.1 Overview.....                                            | 23 |
| 6.2 System management process .....                          | 23 |
| 6.3 System management information table.....                 | 24 |
| 6.3.1 PhL related management information table.....          | 24 |
| 6.3.2 DLL related management information table.....          | 31 |
| 6.3.3 AL related management information table.....           | 34 |
| 7 Physical layer .....                                       | 36 |
| 7.1 Physical Layer overview.....                             | 36 |
| 7.2 PhL resource .....                                       | 37 |
| 7.2.1 Signal frame .....                                     | 37 |
| 7.2.2 Data subframe .....                                    | 39 |
| 7.2.3 OFDM symbol.....                                       | 40 |
| 7.2.4 Code Block.....                                        | 41 |
| 7.2.5 Resource element.....                                  | 41 |
| 7.2.6 Working mode .....                                     | 42 |

|       |                                                |     |
|-------|------------------------------------------------|-----|
| 7.3   | DLL–PhL interface .....                        | 44  |
| 7.3.1 | General .....                                  | 44  |
| 7.3.2 | Service primitive .....                        | 45  |
| 7.3.3 | Primitive process .....                        | 47  |
| 7.4   | System management-PhL interface.....           | 47  |
| 7.4.1 | General .....                                  | 47  |
| 7.4.2 | Service primitive .....                        | 47  |
| 7.4.3 | Primitive process .....                        | 49  |
| 7.5   | DCE Independent Sublayer (DIS).....            | 50  |
| 7.5.1 | General .....                                  | 50  |
| 7.5.2 | Data sequence .....                            | 50  |
| 7.6   | DTE-DCE interface .....                        | 51  |
| 7.6.1 | General .....                                  | 51  |
| 7.6.2 | Interface signal.....                          | 51  |
| 7.6.3 | Signal process .....                           | 52  |
| 7.7   | Medium Dependent Sublayer (MDS) .....          | 52  |
| 7.7.1 | General .....                                  | 52  |
| 7.7.2 | MDS specification.....                         | 52  |
| 7.8   | MDS-MAU interface .....                        | 59  |
| 7.8.1 | General .....                                  | 59  |
| 7.8.2 | MDS-MAU interface .....                        | 59  |
| 7.9   | Medium Attachment Unit (MAU).....              | 62  |
| 7.9.1 | Overview .....                                 | 62  |
| 7.9.2 | Electrical specifications .....                | 62  |
| 7.9.3 | Transmission Medium Interface .....            | 62  |
| 7.9.4 | Medium .....                                   | 63  |
| 8     | Data-link layer .....                          | 65  |
| 8.1   | General.....                                   | 65  |
| 8.1.1 | DLL protocol architecture.....                 | 65  |
| 8.1.2 | DLL working mechanism.....                     | 67  |
| 8.2   | DLL services .....                             | 70  |
| 8.2.1 | General .....                                  | 70  |
| 8.2.2 | Data-link service model .....                  | 71  |
| 8.2.3 | Data-link service description.....             | 72  |
| 8.2.4 | Data-link management service description.....  | 85  |
| 8.2.5 | Clock synchronization service description..... | 101 |
| 8.3   | DLL protocol .....                             | 107 |
| 8.3.1 | Working procedure .....                        | 107 |
| 8.3.2 | DLPDU structure .....                          | 116 |
| 8.3.3 | State machine .....                            | 129 |
| 8.3.4 | Error handling.....                            | 134 |
| 9     | Application Layer.....                         | 136 |
| 9.1   | Overview.....                                  | 136 |
| 9.1.1 | Protocol architecture.....                     | 136 |
| 9.1.2 | Data type of AL.....                           | 137 |
| 9.1.3 | Data mapping modeling .....                    | 140 |
| 9.1.4 | Communication model .....                      | 143 |
| 9.2   | AL Service .....                               | 144 |
| 9.2.1 | Overview .....                                 | 144 |

|                                                                                                   |                                                                  |     |
|---------------------------------------------------------------------------------------------------|------------------------------------------------------------------|-----|
| 9.2.2                                                                                             | Application Service Elements.....                                | 145 |
| 9.2.3                                                                                             | Application service .....                                        | 169 |
| 9.3                                                                                               | Specification for AL protocol .....                              | 171 |
| 9.3.1                                                                                             | Overview .....                                                   | 171 |
| 9.3.2                                                                                             | Message format.....                                              | 171 |
| 9.3.3                                                                                             | State machine .....                                              | 176 |
| Annex A (informative)                                                                             | Example of data subframe allocation .....                        | 184 |
| A.1                                                                                               | Example A .....                                                  | 184 |
| A.2                                                                                               | Example B .....                                                  | 185 |
| A.3                                                                                               | Example C .....                                                  | 186 |
| Annex B (normative)                                                                               | RS code generating polynomial .....                              | 187 |
| Annex C (informative)                                                                             | Example for NodeID and MAC address mapping .....                 | 188 |
| Annex D (informative)                                                                             | Example for multicast group working mechanism .....              | 189 |
| Annex E (informative)                                                                             | Example of service data mapping DTU message .....                | 190 |
| Annex F (informative)                                                                             | Example of OPC UA data model and AUTOBUS data model mapping..... | 191 |
| Annex G (informative)                                                                             | Example of RTA service processing .....                          | 192 |
| Annex H (informative)                                                                             | AUTOBUS virtualization solution example.....                     | 193 |
| Bibliography                                                                                      | .....                                                            | 196 |
| Figure 1 – BITMAP data type .....                                                                 |                                                                  | 19  |
| Figure 2 – Corresponding relationship between AUTOBUS protocol stack and OSI reference model..... |                                                                  | 20  |
| Figure 3 – AUTOBUS protocol stack architecture .....                                              |                                                                  | 21  |
| Figure 4 – AUTOBUS network topology .....                                                         |                                                                  | 23  |
| Figure 5 – AUTOBUS system management process .....                                                |                                                                  | 24  |
| Figure 6 – Resource block information structure .....                                             |                                                                  | 31  |
| Figure 7 – AUTOBUS Physical Layer model .....                                                     |                                                                  | 37  |
| Figure 8 – AUTOBUS SF and OFDM symbol .....                                                       |                                                                  | 38  |
| Figure 9 – SF structure .....                                                                     |                                                                  | 39  |
| Figure 10 – Carrier mode A and carrier mode B of data subframe .....                              |                                                                  | 40  |
| Figure 11 – OFDM symbol structure of PhL.....                                                     |                                                                  | 40  |
| Figure 12 – OFDM timing structure .....                                                           |                                                                  | 41  |
| Figure 13 – DLPDU and CB .....                                                                    |                                                                  | 41  |
| Figure 14 – Resource element schematic diagram .....                                              |                                                                  | 42  |
| Figure 15 – Mapping between data units across the DLL-PhL interface.....                          |                                                                  | 44  |
| Figure 16 – DLL-PhL interface service primitive process .....                                     |                                                                  | 47  |
| Figure 17 – System management-PhL interface primitive process.....                                |                                                                  | 50  |
| Figure 18 – DTE-DCE interface signal process .....                                                |                                                                  | 52  |
| Figure 19 – PhL channel process.....                                                              |                                                                  | 53  |
| Figure 20 – Scrambling sequence generation .....                                                  |                                                                  | 53  |
| Figure 21 – Convolutional encoder with a code rate of 1/2 .....                                   |                                                                  | 55  |
| Figure 22 – Bit deletion process with code rates 2/3 and 3/4.....                                 |                                                                  | 55  |
| Figure 23 – Generation of m sequence .....                                                        |                                                                  | 57  |
| Figure 24 – OFDM symbol structure diagram .....                                                   |                                                                  | 58  |

|                                                                                                     |     |
|-----------------------------------------------------------------------------------------------------|-----|
| Figure 25 – MDS-MAU interface service process diagram .....                                         | 60  |
| Figure 26 – Signal spectrum template .....                                                          | 61  |
| Figure 27 – Connector of the shielded twisted pair .....                                            | 64  |
| Figure 28 – Terminal resistor .....                                                                 | 64  |
| Figure 29 – DLL in AUTBUS protocol stack architecture .....                                         | 65  |
| Figure 30 – Relationship of AUTBUS DLL to other filedbus layers and to users of<br>AUTBUS DLS ..... | 66  |
| Figure 31 – AUTBUS DLL protocol architecture diagram .....                                          | 66  |
| Figure 32 – Resource mapping between DLL and PhL .....                                              | 69  |
| Figure 33 – DLL resource mapping message queue scheduling diagram .....                             | 70  |
| Figure 34 – Primitive process of CLMDTA .....                                                       | 73  |
| Figure 35 – Primitive process of CLMDTNA .....                                                      | 75  |
| Figure 36 – Primitive process of CLMDTRA .....                                                      | 77  |
| Figure 37 – Primitive process of CLMDTRRNA .....                                                    | 79  |
| Figure 38 – Primitive process of CMDTA .....                                                        | 81  |
| Figure 39 – Primitive process of CMDTNA .....                                                       | 83  |
| Figure 40 – Data-link config management service primitive process .....                             | 86  |
| Figure 41 – TN active logout discovery service primitive process .....                              | 90  |
| Figure 42 – Data-link discovery management service primitive sequence diagram .....                 | 90  |
| Figure 43 – Local data-link maintenance service primitive process diagram .....                     | 93  |
| Figure 44 – Remote data-link maintenance service primitive process diagram .....                    | 93  |
| Figure 45 – Data-link establish management service primitive process .....                          | 96  |
| Figure 46 – Data-link release management service primitive sequence diagram .....                   | 98  |
| Figure 47 – Data-link update management service primitive sequence diagram .....                    | 100 |
| Figure 48 – Delay measurement service primitive process .....                                       | 102 |
| Figure 49 – Clock synchronization service primitive process .....                                   | 104 |
| Figure 50 – Clock interrupt service primitive process .....                                         | 106 |
| Figure 51 – Resource mapping configuration diagram .....                                            | 108 |
| Figure 52 – Initial access configuration procedure diagram .....                                    | 109 |
| Figure 53 – The random access configuration procedure diagram .....                                 | 110 |
| Figure 54 – Node leave procedure diagram .....                                                      | 112 |
| Figure 55 – DLS data sending procedure diagram .....                                                | 113 |
| Figure 56 – DLS data receiving procedure diagram .....                                              | 114 |
| Figure 57 – Clock synchronization delay measurement procedure diagram .....                         | 115 |
| Figure 58 – Clock register structure diagram .....                                                  | 115 |
| Figure 59 – Clock synchronization procedure .....                                                   | 116 |
| Figure 60 – Universal DLPDU structure .....                                                         | 116 |
| Figure 61 – Basic configuration DLPDU structure .....                                               | 117 |
| Figure 62 – General configuration block structure .....                                             | 118 |
| Figure 63 – Address assignment DLPDU structure .....                                                | 119 |
| Figure 64 – Multicast assignment DLPDU structure .....                                              | 120 |
| Figure 65 – Resource allocation DLPDU structure .....                                               | 121 |
| Figure 66 – Access notification DLPDU structure .....                                               | 122 |

|                                                                                                                    |     |
|--------------------------------------------------------------------------------------------------------------------|-----|
| Figure 67 – Resource application DLPDU structure.....                                                              | 123 |
| Figure 68 – Resource release DLPDU structure.....                                                                  | 124 |
| Figure 69 – Status query DLPDU structure .....                                                                     | 125 |
| Figure 70 – Status response DLPDU.....                                                                             | 125 |
| Figure 71 – Announcement DLPDU structure.....                                                                      | 126 |
| Figure 72 – Clock synchronization DLPDU structure .....                                                            | 128 |
| Figure 73 – Common DLPDU structure .....                                                                           | 129 |
| Figure 74 – DLDE state machine .....                                                                               | 130 |
| Figure 75 – DLME state machine .....                                                                               | 132 |
| Figure 76 – DLCE state machine .....                                                                               | 133 |
| Figure 77 – AL in AUTBUS protocol stack architecture.....                                                          | 136 |
| Figure 78 – Relationship of AUTBUS AL to other fieldbus layers and to users of<br>AUTBUS application service ..... | 136 |
| Figure 79 – Diagram of AUTBUS AL protocol architecture .....                                                       | 137 |
| Figure 80 – Data mapping modeling object structure.....                                                            | 141 |
| Figure 81 – Diagram of mapping data buffers and service data variables .....                                       | 142 |
| Figure 82 – Diagram of P/S model .....                                                                             | 143 |
| Figure 83 – P/S model of PUSH mode .....                                                                           | 143 |
| Figure 84 – P/S model of PULL mode .....                                                                           | 144 |
| Figure 85 – Diagram of C/S communication model.....                                                                | 144 |
| Figure 86 – RT data transmission model.....                                                                        | 147 |
| Figure 87 – Diagram of nRT data request response model .....                                                       | 149 |
| Figure 88 – Diagram of nRT data AP interaction based on C/S communication model.....                               | 149 |
| Figure 89 – Diagram of nRT data AP interaction based on P/S communication model.....                               | 150 |
| Figure 90 – Time synchronization application interaction pocess .....                                              | 152 |
| Figure 91 – Time query fow .....                                                                                   | 153 |
| Figure 92 – Resource AP interaction based on C/S communication model .....                                         | 155 |
| Figure 93 – Resource ASE local service function Diagram .....                                                      | 155 |
| Figure 94 – NETWORKID identification field structure.....                                                          | 156 |
| Figure 95 – NETWORKID interaction process diagram.....                                                             | 158 |
| Figure 96 – Diagram of MAC mapping table service function.....                                                     | 158 |
| Figure 97 – IP mapping table service function diagram .....                                                        | 159 |
| Figure 98 – AUTBUS AL data message is mapped to IP payload data payload .....                                      | 159 |
| Figure 99 – AUTBUS AL protocol header and IP protocol header mapping.....                                          | 160 |
| Figure 100 – IP data message is mapped to valid data of AUTBUS AL data message.....                                | 160 |
| Figure 101 – Static configuration initialization process .....                                                     | 163 |
| Figure 102 – Join the network interaction process.....                                                             | 163 |
| Figure 103 – Passively exit the network interaction process.....                                                   | 165 |
| Figure 104 – Actively exit network interaction process .....                                                       | 165 |
| Figure 105 – Diagram of diagnostic object mapping .....                                                            | 166 |
| Figure 106 – Diagram of the logging process .....                                                                  | 167 |
| Figure 107 – A physical bus divided into two virtual bus domain diagrams .....                                     | 167 |
| Figure 108 – Diagram of virtualized AP interaction based on C/S communication model .....                          | 169 |



|                                                                                    |     |
|------------------------------------------------------------------------------------|-----|
| Figure 109 – Virtualization ASE local implementation diagram .....                 | 169 |
| Figure 110 – AL protocol message header structure .....                            | 171 |
| Figure 111 – Message structure of multiple DTUs .....                              | 173 |
| Figure 112 – Transmission unit message format .....                                | 174 |
| Figure 113 – Time service notification message structure .....                     | 174 |
| Figure 114 – System management data message format .....                           | 176 |
| Figure 115 – Diagram of state transition of publisher state machine .....          | 177 |
| Figure 116 – Diagram of state transition of subscriber state machine .....         | 179 |
| Figure 117 – Diagram of state transition of client state machine .....             | 180 |
| Figure 118 – Diagram of transition state of server state machine .....             | 180 |
| Figure 119 – Diagram of transition state of ALCE state machine .....               | 181 |
| Figure 120 – Diagram of transition state of ALDE state machine .....               | 182 |
| Figure 121 – Diagram of state transition for ALME state machine .....              | 183 |
| Figure A.1 – Resource allocation example A .....                                   | 184 |
| Figure A.2 – Resource allocation example B .....                                   | 185 |
| Figure A.3 – Resource allocation example C .....                                   | 186 |
| Figure D.1 – Multicast working mechanism diagram .....                             | 189 |
| Figure E.1 – Data transmission unit message content example .....                  | 190 |
| Figure F.1 – OPC UA data model and mapping of AUTOBUS data model .....             | 191 |
| Figure G.1 – Example of RTA service processing .....                               | 192 |
| Figure H.1 – Diagram of AUTOBUS industrial bus service deployment .....            | 193 |
| Figure H.2 – Diagram of networking topology based on the virtualized bus .....     | 193 |
| Figure H.3 – Virtual network topology based on logical business function RT1 ..... | 194 |
| Table 1 – Unsigned type data coding .....                                          | 16  |
| Table 2 – UINT16 type data coding .....                                            | 17  |
| Table 3 – TIMEV type data coding .....                                             | 17  |
| Table 4 – DATE2000 type coding .....                                               | 17  |
| Table 5 – TIMEOFDAY type coding .....                                              | 18  |
| Table 6 – TIMEDIFFER type coding .....                                             | 18  |
| Table 7 – STRING type data coding .....                                            | 18  |
| Table 8 – Physical device configuration information table .....                    | 25  |
| Table 9 – System configuration related information table .....                     | 26  |
| Table 10 – PhL synchronization management information table .....                  | 27  |
| Table 11 – System diagnosis and maintenance related information table .....        | 28  |
| Table 12 – Physical communication resource management information table .....      | 29  |
| Table 13 – Protocol stack version management information table .....               | 31  |
| Table 14 – Link node management information table .....                            | 32  |
| Table 15 – Link timeout management information table .....                         | 33  |
| Table 16 – Time management information table .....                                 | 34  |
| Table 17 – Network management information table .....                              | 35  |
| Table 18 – AUTOBUS TMs and corresponding parameters .....                          | 42  |
| Table 19 – Working mode under carrier mode A .....                                 | 43  |

|                                                                                       |    |
|---------------------------------------------------------------------------------------|----|
| Table 20 – Working mode under carrier mode B .....                                    | 44 |
| Table 21 – Ph-Param service primitives and parameters .....                           | 45 |
| Table 22 – Ph-Param service primitive parameter description .....                     | 45 |
| Table 23 – Ph-Data service primitives and parameters .....                            | 45 |
| Table 24 – Ph-Data service primitive parameter description .....                      | 46 |
| Table 25 – Ph-Clock-Sync service primitives and parameters .....                      | 46 |
| Table 26 – Ph-Clock-Sync service primitive parameter description .....                | 46 |
| Table 27 – Ph-RESET primitives and parameters .....                                   | 48 |
| Table 28 – Ph-RESET service primitive parameter description .....                     | 48 |
| Table 29 – Ph-SET-VALUE primitives and parameters .....                               | 48 |
| Table 30 – Ph-SET-VALUE primitive parameter status description .....                  | 48 |
| Table 31 – Ph-GET-VALUE service primitives and parameters .....                       | 48 |
| Table 32 – Ph-EVENT service primitive and parameters .....                            | 49 |
| Table 33 – Ph-SYNC service primitives and parameters .....                            | 49 |
| Table 34 – RS code mode .....                                                         | 54 |
| Table 35 – Convolutional code mode .....                                              | 55 |
| Table 36 – Bit interleaving parameters .....                                          | 56 |
| Table 37 – OFDM configuration parameters .....                                        | 57 |
| Table 38 – Modulation Coding Scheme in carrier mode A .....                           | 58 |
| Table 39 – Modulation Coding Scheme in carrier mode B .....                           | 58 |
| Table 40 – Minimum services at MDS-MAU interface .....                                | 59 |
| Table 41 – Allowable constellation diagram errors in different modulation modes ..... | 61 |
| Table 42 – System transmission parameters .....                                       | 62 |
| Table 43 – Transmission medium interface .....                                        | 62 |
| Table 44 – NodeID address assignment of AUTOBUS DLL .....                             | 67 |
| Table 45 – NodeID and MAC address mapping .....                                       | 68 |
| Table 46 – Members of Multicast Group Mapping Table Description .....                 | 68 |
| Table 47 – CLMDTA service primitives and parameters .....                             | 74 |
| Table 48 – CLMDTA service primitive parameter description .....                       | 74 |
| Table 49 – CLMDTNA service primitives and parameters .....                            | 76 |
| Table 50 – CLMDTNA service primitive parameter description .....                      | 76 |
| Table 51 – CLMDTRA service primitives and parameters .....                            | 78 |
| Table 52 – CLMDTRA service primitive parameter description .....                      | 78 |
| Table 53 – CLMDTRRNA service primitives and parameters .....                          | 80 |
| Table 54 – CLMDTRRNA service primitive parameter description .....                    | 80 |
| Table 55 – CMDTA service primitives and parameters .....                              | 82 |
| Table 56 – CMDTA service primitive parameter description .....                        | 82 |
| Table 57 – CMDTNA service primitives and parameters .....                             | 84 |
| Table 58 – CMDTNA service primitive parameter description .....                       | 84 |
| Table 59 – DLS status output value description .....                                  | 85 |
| Table 60 – Data-link config management service .....                                  | 86 |
| Table 61 – Data-link config management service primitive parameter description .....  | 86 |
| Table 62 – CFG_PARAM_INFO structure description .....                                 | 87 |

|                                                                                                 |     |
|-------------------------------------------------------------------------------------------------|-----|
| Table 63 – TIMEOUT_CFG structure description .....                                              | 88  |
| Table 64 – GROUP_IDMAP_S structure description.....                                             | 88  |
| Table 65 – NODEID_MAC_S structure description .....                                             | 88  |
| Table 66 – COMM_RES_CFG structure description .....                                             | 89  |
| Table 67 – Data-link discovery service primitives and parameters.....                           | 91  |
| Table 68 – Data-link discovery management service primitive parameter description .....         | 91  |
| Table 69 – NODE_MGT_INFO_S structure description .....                                          | 92  |
| Table 70 – Data-link maintenance service primitives and parameters.....                         | 94  |
| Table 71 – Data-link maintenance service primitive parameter description .....                  | 94  |
| Table 72 – DIAG_INFO_S structure member parameter description .....                             | 94  |
| Table 73 – Data-link establish management service primitives and parameters.....                | 96  |
| Table 74 – Data-link establish management service parameter description .....                   | 96  |
| Table 75 – CH_RES_INFO_S structure member description .....                                     | 97  |
| Table 76 – Data-link release management service primitives and parameters .....                 | 98  |
| Table 77 – Data-link release management service primitive parameter description .....           | 99  |
| Table 78 – Data-link update management service primitives and parameters .....                  | 100 |
| Table 79 – Data-link update management service primitive parameter description .....            | 100 |
| Table 80 – DLMS status return value description .....                                           | 101 |
| Table 81 – Delay measurement service primitives and parameters .....                            | 102 |
| Table 82 – Delay measurement service primitive parameter description.....                       | 103 |
| Table 83 – Clock synchronization service primitives and parameters .....                        | 104 |
| Table 84 – Clock synchronization service primitive parameter description.....                   | 105 |
| Table 85 – Clock interrupt service primitives and parameters.....                               | 106 |
| Table 86 – Clock interrupt service primitive parameter description .....                        | 106 |
| Table 87 – DLCSS status return value description .....                                          | 107 |
| Table 88 – DLDE state transition description .....                                              | 131 |
| Table 89 – DLME state machine state transition description .....                                | 133 |
| Table 90 – DLCE state machine state transition description .....                                | 134 |
| Table 91 – Description of time information structure TIMEINFO_S .....                           | 138 |
| Table 92 – Description of clock option information structure CLOCK_OPTION_INFO_S.....           | 138 |
| Table 93 – Description of network configuration parameter structure<br>NETWORK_CFG_PARA_S ..... | 139 |
| Table 94 – Description of MAC mapping table NETWORKID_MAC_MAP_TABLE_S .....                     | 139 |
| Table 95 – Description of IP mapping table structure IP_MAP_TABLE_S.....                        | 140 |
| Table 96 – Service data mapping table parameter list .....                                      | 142 |
| Table 97 – Communication models supported by AUTOBUS AL ASEs.....                               | 145 |
| Table 98 – Application service interface return value list.....                                 | 145 |
| Table 99 – RT Data service interface parameters.....                                            | 146 |
| Table 100 – nRT data service interface parameters .....                                         | 148 |
| Table 101 – Timing service interface parameters .....                                           | 151 |
| Table 102 – Resource service interface parameters.....                                          | 154 |
| Table 103 – Addressing service interface parameters .....                                       | 157 |
| Table 104 – Management service interface parameters .....                                       | 161 |

|                                                                              |     |
|------------------------------------------------------------------------------|-----|
| Table 105 – Virtual service interface parameters .....                       | 168 |
| Table 106 – Read service parameters.....                                     | 170 |
| Table 107 – Write service parameters.....                                    | 170 |
| Table 108 – Application service errcode description.....                     | 171 |
| Table 109 – AL service type flag encoding.....                               | 172 |
| Table 110 – State transition table of publisher state machine.....           | 177 |
| Table 111 – State transition table of subscriber state machine.....          | 178 |
| Table 112 – State transition table of client state machine.....              | 179 |
| Table 113 – State transition table of server state machine .....             | 180 |
| Table 114 – State transition table of ALCE state machine .....               | 181 |
| Table 115 – State transition table of ALDE state machine .....               | 182 |
| Table 116 – State transition table of ALME state machine.....                | 183 |
| Table B.1 – RS code (255,247) generating polynomial.....                     | 187 |
| Table B.2 – RS code (255,239) generating polynomial.....                     | 187 |
| Table B.3 – RS code (255,223) generating polynomial.....                     | 187 |
| Table C.1 – Example of NodeID and MAC address mapping table saved on TN..... | 188 |
| Table H.1 – Virtual bus environment node NETWORKID list .....                | 195 |

preview generated by EVS

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

# INDUSTRIAL COMMUNICATION NETWORKS – BROADBAND FIELDBUS SPECIFICATION – AUTBUS

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is an intermediate specification made available to the public and needing a lower level of consensus than an International Standard to be approved by vote (simple majority).

IEC PAS 62356 has been processed by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

| Draft PAS    | Report on voting |
|--------------|------------------|
| 65C/973/DPAS | 65C/983/RVDPAS   |

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 2 years starting from the publication date. The validity may be extended for a single period up to a maximum of 2 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

# INDUSTRIAL COMMUNICATION NETWORKS – BROADBAND FIELDBUS SPECIFICATION – AUTBUS

## 1 Scope

This document defines the broadband fieldbus specification AUTBUS. AUTBUS implements real-time, high reliability and deterministic transmission and application for both industrial fieldbus data and ISO/IEC/IEEE 8802-3 Ethernet data by shared medium bus.

This document explains the structure and content of AUTBUS, and describes the definition and specification of Physical Layer (PhL) protocol / service, Data-link Layer (DLL) protocol / service and Application Layer (AL) protocol / service of AUTBUS.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3:1997, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC/IEEE 8802-3:2017, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Standard for Ethernet*

## 3 Terms and definitions, abbreviated terms and symbols

### 3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1.1 cyclic

a term used to describe recurring events in a regular manner

#### 3.1.2 control device

refers to the physical entity with logical operation, timing, calculation and other functions to control all kinds of field device