

This document is a preview generated by EVS

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 61158-5-10:2012 sisaldb Euroopa standardi EN 61158-5-10:2012 ingliskeelset teksti.	This Estonian standard EVS-EN 61158-5-10:2012 consists of the English text of the European standard EN 61158-5-10:2012.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kätesaadavaks 08.06.2012.	Date of Availability of the European standard is 08.06.2012.
Standard on kätesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 25.040.40, 35.100.70, 35.110

Standardite reproduutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

English version

**Industrial communication networks -
Fieldbus specifications -
Part 5-10: Application layer service definition -
Type 10 elements
(IEC 61158-5-10:2010)**

Réseaux de communication industriels -
Spécifications des bus de terrain -
Partie 5-10: Définition des services des
couches d'application -
Eléments de type 10
(CEI 61158-5-10:2010)

Industrielle Kommunikationsnetze -
Feldbusse -
Teil 5-10: Dienstfestlegungen des
Application Layer (Anwendungsschicht) -
Typ 10-Elemente
(IEC 61158-5-10:2010)

This European Standard was approved by CENELEC on 2012-03-28. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 65C/606/FDIS, future edition 2 of IEC 61158-5-10, prepared by SC 65C, "Industrial networks", of IEC/TC 65, "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61158-5-10:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2012-12-28
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-03-28

This document supersedes EN 61158-5-10:2008.

EN 61158-5-10:2012 includes the following significant technical change with respect to EN 61158-5-10:2008:

- corrections;
- improvements;
- optimization of the synchronization;
- optimization of the startup time from power down.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61158-5-10:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC/TR 61158-1:2010 NOTE Harmonized as CLC/TR 61158-1:2010 (not modified).

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60559	-	Binary floating-point arithmetic for microprocessor systems	HD 592 S1	-
IEC 61131-1	-	Programmable controllers - Part 1: General information	EN 61131-1	-
IEC 61131-3	-	Programmable controllers - Part 3: Programming languages	EN 61131-3	-
IEC 61158-5-3	2010	Industrial communication networks - Fieldbus specifications - Part 5-3: Application layer service definition - Type 3 elements	EN 61158-5-3	2012
IEC 61158-6-3	2010	Industrial communication networks - Fieldbus specifications - Part 6-3: Application layer protocol specification - Type 3 elements	EN 61158-6-3	2012
IEC 61158-6-10	2010	Industrial communication networks - Fieldbus specifications - Part 6-10: Application layer protocol specification - Type 10 elements	EN 61158-6-10	2012
IEC 61375-1	-	Electric railway equipment - Train bus - Part 1: Train communication network	-	-
ISO/IEC 646	-	Information technology - ISO 7-bit coded character set for information interchange	-	-
ISO/IEC 7498-1	-	Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model	-	-
ISO/IEC 7498-3	-	Information technology - Open Systems Interconnection - Basic Reference Model: Naming and addressing	-	-
ISO/IEC 8822	-	Information technology - Open Systems Interconnection - Presentation service definition	-	-
ISO/IEC 8824-1	-	Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation	-	-
ISO/IEC 8859-1	-	Information technology - 8-bit single-byte coded graphic character sets - Part 1: Latin alphabet No.1	-	-
ISO/IEC 9545	-	Information technology - Open Systems Interconnection - Application Layer structure	-	-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ISO/IEC 10646-1	-	Information technology - Universal Multiple-Octet Coded Character Set (UCS) - Part 1: Architecture and Basic Multilingual Plane	-	-
ISO/IEC 10731	-	Information technology - Open Systems Interconnection - Basic reference model - Conventions for the definition of OSI services	-	-
ISO 8601	-	Data elements and interchange formats - Information interchange - Representation of dates and times	-	-
IEEE 802	2001	IEEE standard for local and metropolitan area networks: overview and architecture	-	-
IEEE 802.1AB	2005	IEEE Standard for Local and metropolitan area networks Station and Media Access Control Connectivity Discovery	-	-
IEEE 802.1D	2004	IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges	-	-
IEEE 802.1Q	2005	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-
IEEE 802.3	2005	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications	-	-
IETF RFC 1305	-	Network Time Protocol, Version 3 - Specification and Implementation	-	-
IETF RFC 768	-	User Datagram Protocol	-	-
IETF RFC 3636	-	Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)	-	-
IETF RFC 3621	-	Power Ethernet MIB	-	-
IETF RFC 3490	-	Internationalizing Domain Names in Applications (IDNA)	-	-
IETF RFC 3418	-	Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)	-	-
IETF RFC 791	-	Internet Protocol - DARPA Internet Program Protocol Specification	-	-
IETF RFC 2863	-	The Interfaces Group MIB	-	-
IETF RFC 826	-	Ethernet Address Resolution Protocol	-	-
IETF RFC 1034	-	Domain names - concepts and facilities	-	-
IETF RFC 2737	-	Entity MIB (Version 2)	-	-
IETF RFC 2674	-	Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering and Virtual LAN Extensions	-	-
IETF RFC 792	-	Internet Control Message Protocol	-	-
IETF RFC 1112	-	Host Extensions for IP Multicasting	-	-
IETF RFC 1952	-	GZIP file format specification version 4.3	-	-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IETF RFC 2131	-	Dynamic Host Configuration Protocol	-	-
IETF RFC 2365	-	Administratively Scoped IP Multicast	-	-
IETF RFC 3330	-	Special-Use IPv4 Addresses	-	-
The Open Group C706	-	CAE Specification DCE11: Remote Procedure Call	-	-

CONTENTS

FOREWORD	14
INTRODUCTION	16
1 Scope	17
1.1 Overview	17
1.2 Specifications	18
1.3 Conformance	18
2 Normative references	18
3 Terms, definitions, abbreviations, symbols and conventions	20
3.1 Referenced terms and definitions	20
3.2 Additional terms and definitions for distributed automation	21
3.3 Additional terms and definitions for decentralized periphery	23
3.4 Additional terms and definitions for media redundancy	31
3.5 Abbreviations and symbols	32
3.6 Additional abbreviations and symbols for distributed automation	33
3.7 Additional abbreviations and symbols for decentralized periphery	33
3.8 Additional abbreviations and symbols for media redundancy	34
3.9 Conventions	34
4 Concepts	37
5 Data type ASE	37
5.1 General	37
5.2 Formal definition of data type objects	40
5.3 FAL defined data types	41
5.4 Data type ASE service specification	84
6 Communication model for common services	84
6.1 Concepts	84
6.2 ASE data types	84
6.3 ASEs	85
7 Communication model for distributed automation	185
7.1 Concepts	185
7.2 ASE data types	191
7.3 ASEs	195
7.4 ARs	412
7.5 Summary of FAL classes	416
7.6 Summary of FAL services	417
8 Communication model for decentralized periphery	419
8.1 Concepts	419
8.2 ASE data types	436
8.3 ASEs	436
8.4 Behavior of an IO device	709
8.5 Behavior of an IO controller	753
8.6 Application characteristics	756
Annex A (informative) Device instances	759
Annex B (informative) Components of an Ethernet interface	761
Annex C (informative) Scheme of MAC address assignment	765
Annex D (informative) Collection of objects	766
Annex E (informative) Measurement of the fast startup time	767
Bibliography	768

Figure 1 – Data type class hierarchy example	38
Figure 2 – NetworkTime date relation	63
Figure 3 – PTCP applications.....	98
Figure 4 – Clock drift measurement	109
Figure 5 – Multiple synchronization.....	110
Figure 6 – MRP stack	112
Figure 7 – Ring topology with one manager and clients.....	123
Figure 8 – MRM in an open ring	123
Figure 9 – More than one MRM in the ring	124
Figure 10 – Media redundancy diagnosis dependencies	125
Figure 11 – Locating the destination for redundant RT frames	165
Figure 12 – Example of periods at a local port	172
Figure 13 – FAL ASEs communication architecture	187
Figure 14 – Runtime object model.....	188
Figure 15 – Relationship between engineering and runtime	189
Figure 16 – Navigation in the runtime object model.....	190
Figure 17 – Operating state block diagram.....	229
Figure 18 – Device status model for the common diagnosis	230
Figure 19 – ACCO ASE structure	261
Figure 20 – Productive operation of data connections	262
Figure 21 – Quality code transfer – standard behavior	274
Figure 22 – Startup of a connection	275
Figure 23 – Quality code with communication fault.....	275
Figure 24 – Quality code when a connection is cleared	276
Figure 25 – Quality code when a connection is deactivated	276
Figure 26 – Quality code during the transfer of "incorrect" connection data	277
Figure 27 – Quality code for provider in "CBAReady" state	278
Figure 28 – Quality code when clearing an object from the provider.....	278
Figure 29 – Quality code when a connection is forced.....	279
Figure 30 – Quality code at QoS violation	279
Figure 31 – Push mode	286
Figure 32 – Pull mode overview	287
Figure 33 – Detailed sequence chart of the pull mode.....	288
Figure 34 – QoS and ORPC communication channel	289
Figure 35 – QoS Violation within Pull Mode	290
Figure 36 – Monitoring the providers heartbeat	291
Figure 37 – State machine RemoteACCO	293
Figure 38 – State machine RemoteACCOProvider	293
Figure 39 – State machine RemoteACCOProvider _{ORPC}	294
Figure 40 – State machine AR _{ORPC} – Provider	294
Figure 41 – State machine GetConnectionData – Provider	295
Figure 42 – State machine ProviderConnection.....	295
Figure 43 – State machine ProvConnActivation.....	296
Figure 44 – State machine WorkerORPC	296
Figure 45 – Communication stack of distributed automation devices	297
Figure 46 – Application relations between devices	298
Figure 47 – Communication relations	298
Figure 48 – RT communication channel	300

Figure 49 – Interaction between provider and consumer	302
Figure 50 – State machine AR _{SRT} – Consumer	304
Figure 51 – State machine AR _{SRT} – Provider	305
Figure 52 – State machine AccoDataCR – Consumer	306
Figure 53 – State machine AccoDataCR – Provider	306
Figure 54 – RT frame layout	307
Figure 55 – Establishing an AccoDataCR	308
Figure 56 – Flowchart of the copy cycle for local connections	309
Figure 57 – State machine connect attempt	313
Figure 58 – Productive operation of data connections (ORPC channel)	320
Figure 59 – Productive operation of data connections (RT channel)	321
Figure 60 – Productive operation of data connections (Local channel)	321
Figure 61 – Data flow for cyclic RT	322
Figure 62 – Failure of the provider in productive operation (ORPC push mode)	324
Figure 63 – Failure of the provider in productive operation (ORPC pull mode)	325
Figure 64 – Scenario 1: Provider failure in productive operation (RT)	326
Figure 65 – Scenario 2: Recovery from provider failure in productive operation (RT)	327
Figure 66 – Failure of the consumer (push mode)	327
Figure 67 – Failure of the consumer (pull mode)	328
Figure 68 – Failure of the consumer	329
Figure 69 – Failure of the provider when setting up connections	331
Figure 70 – Information levels	332
Figure 71 – ACCO ASE status model for the common diagnosis	332
Figure 72 – ACCO ASE status model for the detailed diagnosis	333
Figure 73 – Structure of the transmitted connection data	375
Figure 74 – Example of communication between controlling devices and field devices	421
Figure 75 – Example of communication between an engineering station and several controlling and field devices	421
Figure 76 – Example of communication between field devices and a server station	422
Figure 77 – Example of communication between field devices	422
Figure 78 – Structural units of one arbitrary API of an IO device (general)	424
Figure 79 – Example 1 structural units for interfaces and ports within API 0	425
Figure 80 – Example 2 structural units for interfaces and ports within API 0	426
Figure 81 – Overview of application processes	428
Figure 82 – IO device with APs, slots and subslots	429
Figure 83 – Application Process with application process objects (APOs)	432
Figure 84 – Access to a remote APO	433
Figure 85 – Access to a remote APO for provider/consumer association	434
Figure 86 – Example of one AR with two AREPs	435
Figure 87 – Relation of a record data object to one real object	437
Figure 88 – Relation of a record data object to two real objects	438
Figure 89 – Overview IO ASE service interactions	448
Figure 90 – Example of a resource model at the alarm source	524
Figure 91 – General isochronous application model (example)	588
Figure 92 – ASE relations in an IO device operating in isochronous mode	594
Figure 93 – State machine relations in an IO device operating in isochronous mode	594
Figure 94 – SyncCtrl state diagram	598
Figure 95 – Output state diagram	600
Figure 96 – Input state diagram	605

Figure 97 – Assignment of communication relationship to application relationship	687
Figure 98 – Implicit application relationship	691
Figure 99 – Example IO application relationship (one-to-one)	692
Figure 100 – Example IO application relationship one-to-many	693
Figure 101 – Overview ASE state machines for IO device	709
Figure 102 – State diagram application startup IO device	711
Figure 103 – State diagram neighborhood check	719
Figure 104 – State diagram PD parameter check IO device	728
Figure 105 – State diagram for a submodule.....	738
Figure 106 – State diagram IO controller during startup	754
Figure 107 – Example of network topology including slower wireless segments	757
Figure 108 – Example of media redundancy including wireless segments	758
Figure A.1 – Instance model	759
Figure B.1 – Scheme of an Ethernet interface	761
Figure B.2 – Scheme of an Ethernet interface with bridging ability	762
Figure B.3 – Scheme of an Ethernet interface with optical ports.....	763
Figure B.4 – Scheme of an Ethernet interface with bridging ability using radio communication.....	764
Figure B.5 – Scheme of an Ethernet interface with radio communication.....	764
Figure C.1 – Scheme of MAC address assignment.....	765
Figure D.1 – Example for an intersection of IO device, slot, and AR.....	766
Figure E.1 – Measurement of the fast startup time	767
 Table 1 – V2 octets	42
Table 2 – L2 octets	42
Table 3 – PERSISTDEF	45
Table 4 – VARTYPE	45
Table 5 – ITEMQUALITYDEF	46
Table 6 – STATEDEF	49
Table 7 – GROUPERRORDEF	49
Table 8 – ACCESSRIGHTSDEF.....	50
Table 9 – HRESULT	50
Table 10 – E2 octets	52
Table 11 – E2 value range	53
Table 12 – Unipolar2.16 octets	53
Table 13 – Unipolar2.16 value range	53
Table 14 – N2 value range.....	55
Table 15 – N4 value range	55
Table 16 – X2 value range	56
Table 17 – X4 value range	57
Table 18 – C4 value range	57
Table 19 – T2 value range	59
Table 20 – T2 value range	59
Table 21 – D2 value range	60
Table 22 – R2 value range	60
Table 23 – UUID for decentralized peripherals	61
Table 24 – UUID for distributed automation	62
Table 25 – NetworkTime values	63
Table 26 – NetworkTime octets.....	63

Table 27 – UNICODEString values	65
Table 28 – UTF-8 character encoding scheme	65
Table 29 – OctetString2+Unsigned8 octets	76
Table 30 – Float32+Unsigned8 octets	77
Table 31 – Unsigned8+Unsigned8 octets	77
Table 32 – Data Types for Value in a VARIANT	80
Table 33 – Unsigned16_S octets	81
Table 34 – Unsigned16_S meaning	81
Table 35 – Integer16_S octets	81
Table 36 – Integer16_S meaning	82
Table 37 – Unsigned8_S octets	82
Table 38 – Unsigned8_S meaning	82
Table 39 – OctetString_S octets	83
Table 40 – OctetString_S status bits	83
Table 41 – F message trailer with 4 octets	83
Table 42 – F message trailer with 5 octets	84
Table 43 – Get	90
Table 44 – Set	92
Table 45 – Identify	95
Table 46 – Hello	96
Table 47 – Start bridge	103
Table 48 – Start slave	104
Table 49 – Start master	105
Table 50 – Stop bridge	106
Table 51 – Stop slave	107
Table 52 – Stop master	107
Table 53 – Sync state change	108
Table 54 – Start MRM	117
Table 55 – Stop MRM	118
Table 56 – Redundancy state change	119
Table 57 – Start MRC	120
Table 58 – Stop MRC	121
Table 59 – Neighborhood changed	121
Table 60 – MRP network/connection parameters	126
Table 61 – MRM parameters	127
Table 62 – MRC parameters	127
Table 63 – Set Prov Data	128
Table 64 – Set Prov Status	129
Table 65 – PPM Activate	130
Table 66 – Close	131
Table 67 – Start	131
Table 68 – Error	132
Table 69 – Get Cons Data	132
Table 70 – Get cons status	133
Table 71 – Set RedRole	133
Table 72 – CPM activate	134
Table 73 – APMS Activate	138
Table 74 – APMR Activate	139
Table 75 – APMS A Data	140

Table 76 – APMR A Data	141
Table 77 – APMR Ack	141
Table 78 – APMS Error	142
Table 79 – APMS Error ERRCLS/ERRCODE	142
Table 80 – APMR Error	143
Table 81 – APMR Error ERRCLS/ERRCODE	143
Table 82 – APMS_Close	143
Table 83 – APMR_Close	144
Table 84 – Connect	145
Table 85 – Release	146
Table 86 – Read	147
Table 87 – Write	148
Table 88 – Control	149
Table 89 – System capabilities	154
Table 90 – Auto negotiation support and status	155
Table 91 – MDI Power Support	155
Table 92 – Link aggregation status	156
Table 93 – Remote systems data change	159
Table 94 – Allowed values of ReductionRatio	162
Table 95 – Frame IDs for RT_CLASS_3	163
Table 96 – Sync Frame	163
Table 97 – FrameSendOffset	163
Table 98 – Tx Port Entry	164
Table 99 – Port state change	167
Table 100 – Set port state	167
Table 101 – Flush filtering data base	168
Table 102 – IFW IRT Schedule Add	168
Table 103 – IFW IRT Schedule Remove	169
Table 104 – IFW Schedule	169
Table 105 – MAU type change	174
Table 106 – Set MAU type	174
Table 107 – IP Multicast address	177
Table 108 – Set ARP Cache	177
Table 109 – Enterprise number	179
Table 110 – Vendor OUI	180
Table 111 – IRT Schedule Add	181
Table 112 – IRT Schedule Remove	181
Table 113 – Schedule	182
Table 114 – N Data	182
Table 115 – A Data	183
Table 116 – C Data	184
Table 117 – Connectable data types	192
Table 118 – Supported data types according to the Base Object Version	193
Table 119 – Usage of character sets	195
Table 120 – QueryInterface (Unknown interface)	197
Table 121 – AddRef (Unknown interface)	198
Table 122 – Release (Unknown interface)	199
Table 123 – GetTypeInfoCount (Dispatch interface)	200
Table 124 – GetTypeInfo (Dispatch interface)	201

Table 125 – GetIDsOfNames (Dispatch interface)	202
Table 126 – Invoke (Dispatch interface)	203
Table 127 – CRC table for the PDev stamp calculation (hexadecimal values)	208
Table 128 – get_Producer (Physical device interface)	209
Table 129 – get_Product (Physical device interface)	210
Table 130 – get_SerialNo (Physical device interface)	211
Table 131 – get_ProductionDate (Physical device interface)	212
Table 132 – Revision (Physical device interface)	213
Table 133 – get_LogicalDevice (Physical device interface)	214
Table 134 – Type (Physical device interface)	215
Table 135 – PROFINetRevision (Physical device interface)	216
Table 136 – get_PDevStamp (Physical device interface)	217
Table 137 – get_Count (Browse interface)	218
Table 138 – BrowseItems (Browse interface)	219
Table 139 – get_Count2 (Browse interface)	220
Table 140 – BrowseItems2 (Browse interface)	222
Table 141 – Save (Persist interface)	223
Table 142 – Save2 (Persist interface)	224
Table 143 – get_Name (Logical Device interface)	230
Table 144 – get_Producer (Logical Device interface)	231
Table 145 – get_Product (Logical Device interface)	232
Table 146 – get_SerialNo (Logical Device interface)	233
Table 147 – get_ProductionDate (Logical Device interface)	234
Table 148 – Revision (Logical Device interface)	235
Table 149 – get_ACCO (Logical Device interface)	236
Table 150 – get_RTAuto (Logical Device interface)	237
Table 151 – PROFINetRevision (Logical Device interface)	238
Table 152 – ComponentInfo (Logical Device interface)	239
Table 153 – get_State (State interface)	240
Table 154 – Activate (State interface)	242
Table 155 – Deactivate (State interface)	243
Table 156 – Reset (State interface)	244
Table 157 – AdviseState (State interface)	245
Table 158 – UnadviseState (State interface)	246
Table 159 – get_Time (Time interface)	247
Table 160 – put_Time (Time interface)	248
Table 161 – get_Count (Browse interface)	249
Table 162 – BrowseItems (Browse interface)	250
Table 163 – get_Count2 (Browse interface)	251
Table 164 – BrowseItems2 (Browse interface)	253
Table 165 – GroupError (Group error interface)	254
Table 166 – AdviseGroupError (Group Error interface)	256
Table 167 – UnadviseGroupError (Group Error interface)	257
Table 168 – PingFactor values	259
Table 169 – QoS subtypes in the ORPC communication channel	268
Table 170 – QoS subtypes in the RT communication channel	269
Table 171 – QoS Types and Values	269
Table 172 – Epsilon value for connectable data types	271
Table 173 – Quality Codes	273

Table 174 – Quality code priority table	281
Table 175 – Maximum ORPC substitute value apply time	291
Table 176 – Maximum GetConnectionData hold time	292
Table 177 – Usage of RT Variants	299
Table 178 – Mapping QoS Value to RT cycle time	300
Table 179 – Maximum RT Substitute Value Apply Time	301
Table 180 – Time Intervals and Timeouts	323
Table 181 – Error codes for the ACCO ASE detailed diagnosis	334
Table 182 – AddConnections (ACCO Management interface)	336
Table 183 – RemoveConnections (ACCO Management interface)	337
Table 184 – ClearConnections (ACCO Management interface)	339
Table 185 – SetActivationState (ACCO Management interface)	340
Table 186 – GetInfo (ACCO Management interface)	341
Table 187 – GetIDs (ACCO Management interface)	342
Table 188 – GetConnections (ACCO Management interface)	343
Table 189 – ReviseQoS (ACCO Management interface)	345
Table 190 – get_PingFactor (ACCO Management interface)	346
Table 191 – put_PingFactor (ACCO Management interface)	347
Table 192 – get_CDBCookie (ACCO Management interface)	348
Table 193 – GetConsIDs (ACCO Management interface)	349
Table 194 – GetConsConnections (ACCO Management interface)	350
Table 195 – DiagConsConnections (ACCO Management interface)	351
Table 196 – GetProvIDs (ACCO Management interface)	352
Table 197 – GetProvConnections (ACCO Management interface)	354
Table 198 – GetDiagnosis (ACCO Management interface)	356
Table 199 – Request	358
Table 200 – Connect (ACCO Server interface)	365
Table 201 – Disconnect (ACCO Server interface)	367
Table 202 – DisconnectMe (ACCO Server interface)	368
Table 203 – SetActivation (ACCO Server interface)	369
Table 204 – Ping (ACCO Server interface)	370
Table 205 – Connect2 (ACCO Server interface)	371
Table 206 – GetConnectionData (ACCO Server interface)	373
Table 207 – OnDataChanged (ACCO Callback interface)	376
Table 208 – Version	376
Table 209 – Flags	377
Table 210 – Gnip (ACCO Callback interface)	378
Table 211 – ReadItems (ACCO Sync interface)	379
Table 212 – WriteItems (ACCO Sync interface)	381
Table 213 – WriteItemsQCD (ACCO Sync interface)	383
Table 214 – GroupError (Group Error interface)	384
Table 215 – AdviseGroupError (Group Error interface)	385
Table 216 – UnadviseGroupError (Group Error interface)	386
Table 217 – ConnectCR (ACCO Server SRT interface)	388
Table 218 – DisconnectCR (ACCO Server SRT interface)	390
Table 219 – Connect (ACCO Server SRT interface)	391
Table 220 – Disconnect (ACCO Server SRT interface)	392
Table 221 – DisconnectMe (ACCO Server SRT interface)	394
Table 222 – SetActivation (ACCO Server SRT interface)	395

Table 223 – Hresult values for access to properties of Custom RT-Auto objects	400
Table 224 – Hresult values for access to properties of the System RT-Auto object	401
Table 225 – Common hresult values on access to properties of RT-Auto objects	401
Table 226 – Quality code for access to properties of Custom RT-Auto objects	401
Table 227 – Quality code for access to properties of the System RT-Auto object	402
Table 228 – get_Name (RT-Auto interface)	402
Table 229 – Revision (RT-Auto interface)	403
Table 230 – ComponentInfo (RT-Auto interface)	404
Table 231 – get_Count (Browse interface)	405
Table 232 – BrowseItems (Browse interface)	406
Table 233 – get_Count2 (Browse interface)	408
Table 234 – BrowseItems2 (Browse interface)	409
Table 235 – get_StateCollection (System properties interface)	411
Table 236 – get_StampCollection (System Properties interface)	412
Table 237 – CoCreateInstance	414
Table 238 – CoDisconnectObject	415
Table 239 – Call	415
Table 240 – Distributed automation FAL class summary	416
Table 241 – Assignment of the services to client and server	417
Table 242 – Requirements and features	420
Table 243 – Persistence behavior for record data objects	440
Table 244 – Read	441
Table 245 – Read Query	443
Table 246 – Write	445
Table 247 – Set input	455
Table 248 – Set Input IOCS	456
Table 249 – Get Input	457
Table 250 – Get Input IOCS	458
Table 251 – New Input	459
Table 252 – Set input APDU data status	460
Table 253 – New Input APDU Data Status	461
Table 254 – Read Input Data	462
Table 255 – Set Output	464
Table 256 – Set Output IOCS	465
Table 257 – Get Output	466
Table 258 – Get Output IOCS	467
Table 259 – New Output	468
Table 260 – Set Output APDU Data Status	469
Table 261 – New Output APDU Data Status	470
Table 262 – Read Output Data	471
Table 263 – Read Output Substitute Data	474
Table 264 – Write Output Substitute Data	476
Table 265 – Read Logbook	480
Table 266 – Logbook Event	481
Table 267 – Dependencies within channel properties	485
Table 268 – Ext Channel Error type	488
Table 269 – Ext Channel Add Value for Accumulative Info	489
Table 270 – Dependencies within Channel Properties for manufacturer specific diagnosis	490

Table 271 – Read Device Diagnosis	491
Table 272 – Diagnosis Item	493
Table 273 – Diagnosis Event	499
Table 274 – State table Diagnosis entry.....	502
Table 275 – Functions used in state tables	503
Table 276 – State table maintenance required entry	504
Table 277 – State table maintenance demanded entry.....	505
Table 278 – State table qualified entry.....	506
Table 279 – Alarm type	511
Table 280 – Channel Diagnosis	512
Table 281 – Manufacturer Specific Diagnosis.....	512
Table 282 – Submodule Diagnosis State.....	512
Table 283 – AR Diagnosis State	513
Table 284 – User Structure Identifier	514
Table 285 – Semantics of Specifier.....	515
Table 286 – Alarm Notification	519
Table 287 – Alarm Ack.....	523
Table 288 – Module State	529
Table 289 – Usage with respect to CR type	531
Table 290 – Detail	532
Table 291 – ARInfo.....	533
Table 292 – Ident Info	533
Table 293 – Connect.....	539
Table 294 – Connect Device Access	547
Table 295 – Release	549
Table 296 – Abort	550
Table 297 – End Of Parameter.....	550
Table 298 – Application Ready	551
Table 299 – Ready For Companion.....	553
Table 300 – Read Expected Identification	554
Table 301 – Read Real Identification	557
Table 302 – Read Identification Difference.....	560
Table 303 – Read AP Data	562
Table 304 – Read I&M0 Filter Data	563
Table 305 – Read I&M0 Data	567
Table 306 – Write I&M1 Data	569
Table 307 – Read I&M1 Data	571
Table 308 – Write I&M2 Data	573
Table 309 – Read I&M2 Data	575
Table 310 – Write I&M3 Data	577
Table 311 – Read I&M3 Data	579
Table 312 – Write I&M4 Data	581
Table 313 – Read I&M4 Data	583
Table 314 – Write IsoM Data.....	589
Table 315 – Read IsoM Data	591
Table 316 – SYNCH Event.....	593
Table 317 – Primitives issued by the AL to the SyncCtl state machine	596
Table 318 – Primitive issued by the SyncCtl state machine to the user	596
Table 319 – Primitives issued by the Input state machine to the user.....	596

Table 320 – Primitive issued by the Output state machine to the user	596
Table 321 – Primitives issued by the SyncCtl to the output state machine.....	596
Table 322 – Primitives issued by the output to the SyncCtl state machine.....	597
Table 323 – Primitives issued by the SyncCtl to the input state machine.....	597
Table 324 – Primitives issued by the output state machine to the AL	597
Table 325 – Primitives issued by the AL to the output state machine	597
Table 326 – Primitives issued by the input state machine to the AL	598
Table 327 – Primitives issued by the AL to the input state machine	598
Table 328 – SyncCtl state table	599
Table 329 – Output state table	601
Table 330 – Input state table	606
Table 331 – Subslot number for interface submodules	611
Table 332 – Subslot number for port submodules	612
Table 333 – Subslot Number for Interface Submodules	614
Table 334 – Subslot Number for Sync Interface Submodules	614
Table 335 – Sync Properties Role	615
Table 336 – Sync Class	616
Table 337 – Fiber Optic Types	616
Table 338 – Fiber Optic Cable Types	617
Table 339 – Write Expected Port Data	621
Table 340 – Write Adjusted Port Data	624
Table 341 – Read real port data.....	626
Table 342 – Read Expected Port Data	629
Table 343 – Read Adjusted Port Data	631
Table 344 – Write IR Data.....	634
Table 345 – Read IR Data	638
Table 346 – Write Sync Data	642
Table 347 – Read Real Sync Data	645
Table 348 – Read Expected Sync Data	648
Table 349 – Read PDev Data.....	651
Table 350 – Sync State Info.....	656
Table 351 – Write Fiber Optic Data	658
Table 352 – Read Real Fiber Optic Data	661
Table 353 – Write MRP Interface Data	663
Table 354 – Read MRP Interface Data	666
Table 355 – Write MRP Port Data	668
Table 356 – Read MRP Port Data	670
Table 357 – Write FSU Data	672
Table 358 – Read FSU Data	674
Table 359 – Write Network Component Data.....	676
Table 360 – Read Network Component Data.....	679
Table 361 – Read Real Interface Data	681
Table 362 – Set Time.....	685
Table 363 – Device Access	696
Table 364 – Companion AR	696
Table 365 – Media Redundancy.....	700
Table 366 – Frame ID	701
Table 367 – Read AR Data	706
Table 368 – State table application startup IO device	712

Table 369 – State table functions for startup IO device	718
Table 370 – State table neighborhood check	720
Table 371 – State table functions for neighborhood check	727
Table 372 – State table PD parameter check IO device	728
Table 373 – State table functions PD parameter check IO device	733
Table 374 – State table fiber optic maintenance required.....	734
Table 375 – State table fiber optic maintenance demanded	735
Table 376 – State table fiber optic diagnosis.....	736
Table 377 – State table for a submodule	738
Table 378 – State table for plug	748
Table 379 – State table for pull	750
Table 380 – State table of PTCP behavior	751
Table 381 – Functions used by PTCP behavior.....	752
Table 382 – State table IO controller during startup	755
Table 383 – Functions used by state table IO controller	756

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The application service is provided by the application protocol making use of the services available from the data-link or other immediately lower layer. This standard defines the application service characteristics that fieldbus applications and/or system management may exploit.

Throughout the set of fieldbus standards, the term “service” refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the application layer service defined in this standard is a conceptual architectural service, independent of administrative and implementation divisions.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 5-10: Application layer service definition – Type 10 elements

1 Scope

1.1 Overview

The fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a “window between corresponding application programs”.

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to type 10 fieldbus. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible service provided by the type 10 fieldbus Application Layer in terms of

- a) an abstract model for defining application resources (objects) capable of being manipulated by users via the use of the FAL service,
- b) the primitive actions and events of the service;
- c) the parameters associated with each primitive action and event, and the form which they take; and
- d) the interrelationship between these actions and events, and their valid sequences.

The purpose of this standard is to define the services provided to

- a) the FAL user at the boundary between the user and the Application Layer of the Fieldbus Reference Model, and
- b) Systems Management at the boundary between the Application Layer and Systems Management of the Fieldbus Reference Model.

This standard specifies the structure and services of the type 10 IEC fieldbus Application Layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI Application Layer Structure (ISO/IEC 9545).

FAL services and protocols are provided by FAL application-entities (AE) contained within the application processes. The FAL AE is composed of a set of object-oriented Application Service Elements (ASEs) and a Layer Management Entity (LME) that manages the AE. The ASEs provide communication services that operate on a set of related application process object (APO) classes. One of the FAL ASEs is a management ASE that provides a common set of services for the management of the instances of FAL classes.

Although these services specify, from the perspective of applications, how request and responses are issued and delivered, they do not include a specification of what the requesting and responding applications are to do with them. That is, the behavioral aspects of the applications are not specified; only a definition of what requests and responses they can

send/receive is specified. This permits greater flexibility to the FAL users in standardizing such object behavior. In addition to these services, some supporting services are also defined in this standard to provide access to the FAL to control certain aspects of its operation.

1.2 Specifications

The principal objective of this standard is to specify the characteristics of conceptual application layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of application layer protocols for time-critical communications.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of services standardized as the various Types of IEC 61158, and the corresponding protocols standardized in subparts of IEC 61158-6.

This specification may be used as the basis for formal Application Programming-Interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

- a) the sizes and octet ordering of various multi-octet service parameters, and
- b) the correlation of paired request and confirm, or indication and response, primitives.

1.3 Conformance

This standard does not specify individual implementations or products, nor do they constrain the implementations of application layer entities within industrial automation systems.

There is conformance of equipment to this application layer service definition standard mainly achieved through implementation of the modeled behavior of an application layer user (e.g. see user state machines) accompanied by implementation of conforming application layer protocols that fulfill the application layer services as defined in this standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60559, *Binary floating-point arithmetic for microprocessor systems*

IEC 61131-1, *Programmable controllers – Part 1: General information*

IEC 61131-3, *Programmable controllers – Part 3: Programming languages*

IEC 61158-5-3:2010¹, *Industrial communication networks – Fieldbus specifications – Part 5-3: Application layer service definitions – Type 3 elements*

IEC 61158-6-3:2010¹, *Industrial communication networks – Fieldbus specifications – Part 6-3: Application layer protocol specification – Type 3 elements*

IEC 61158-6-10:2010¹, *Industrial communication networks – Fieldbus specifications – Part 6-10: Application layer protocol specification – Type 10 elements*

IEC 61375-1, *Electric railway equipment – Train bus – Part 1: Train communication network*

¹ To be published.

ISO/IEC 646, *Information technology – ISO 7-bit coded character set for information interchange*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO 8601, *Data elements and interchange formats – Information interchange – Representation of dates and times*

ISO/IEC 8822, *Information technology – Open Systems Interconnection – Presentation service definition*

ISO/IEC 8824-1, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation*

ISO/IEC 8859-1, *Information technology – 8-bit single-byte coded graphic character sets – Part 1: Latin alphabet No. 1*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*

ISO/IEC 10646-1, *Information technology – Universal Multiple-Octet Coded Character Set (UCS) – Part 1: Architecture and Basic Multilingual Plane*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

IEEE 802-2001, *IEEE Standard for Local and metropolitan area networks: Overview and architecture*, available at <<http://www.ieee.org>>

IEEE 802.1AB-2005, *IEEE Standard for Local and metropolitan area networks: Station and media access control connectivity discovery*, available at <<http://www.ieee.org>>

IEEE 802.1D-2004, *IEEE Standard for Local and Metropolitan Area Networks – Media Access Control (MAC) Bridges*, available at <<http://www.ieee.org>>

IEEE 802.1Q-2005, *IEEE Standard for Local and metropolitan area networks – Virtual bridged local area networks*, available at <<http://www.ieee.org>>

IEEE 802.3-2005, *IEEE Standard for Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer*, available at <<http://www.ieee.org>>

IETF RFC 768, *User Datagram Protocol*, available at <<http://www.ietf.org>>

IETF RFC 791, *Internet Protocol*, available at <<http://www.ietf.org>>

IETF RFC 792, *Internet Control Message Protocol*, available at <<http://www.ietf.org>>

IETF RFC 826, *An Ethernet Address Resolution Protocol or Converting Network Protocol Addresses to 48.bit Ethernet Address for Transmission on Ethernet Hardware*, available at <<http://www.ietf.org>>

IETF RFC 1034, *Domain names – concepts and facilities*, available at <<http://www.ietf.org>>

IETF RFC 1112, *Host Extensions for IP Multicasting*, available at <<http://www.ietf.org>>

IETF RFC 1305, *Network Time Protocol (Version 3) – Specification, Implementation and Analysis*, available at <<http://www.ietf.org>>

IETF RFC 1952, *GZIP file format specification version 4.3*, available at <<http://www.ietf.org>>

IETF RFC 2131, *Dynamic Host Configuration Protocol*; available at <<http://www.ietf.org>>

IETF RFC 2365, *Administratively Scoped IP Multicast*, available at <<http://www.ietf.org>>

IETF RFC 2674, *Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering and Virtual LAN Extensions*, available at <<http://www.ietf.org>>

IETF RFC 2737, *Entity MIB (Version 2)*, available at <<http://www.ietf.org>>

IETF RFC 2863, *The Interfaces Group MIB*, available at <<http://www.ietf.org>>

IETF RFC 3330, *Special-Use IPv4 Addresses*, available at <<http://www.ietf.org>>

IETF RFC 3418, *Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)*, available at <<http://www.ietf.org>>

IETF RFC 3490, *Internationalizing Domain Names in Applications (IDNA)*, available at <<http://www.ietf.org>>

IETF RFC 3621, *Power Ethernet MIB*, available at <<http://www.ietf.org>>

IETF RFC 3636, *Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)*, available at <<http://www.ietf.org>>

The Open Group – Publication C706, *Technical standard DCE1.1: Remote Procedure Call*, available at <<http://www.opengroup.org/onlinepubs/9629399/toc.htm>>

3 Terms, definitions, abbreviations, symbols and conventions

3.1 Referenced terms and definitions

3.1.1 ISO/IEC 7498-1 terms

For the purposes of this document, the following terms as defined in ISO/IEC 7498-1 apply:

- a) application entity
- b) application process
- c) application protocol data unit
- d) application service element
- e) application entity invocation
- f) application process invocation
- g) application transaction
- h) real open system
- i) transfer syntax