



Edition 1.0 2020-04

# TECHNICAL SPECIFICATION



Nanomanufacturing – Key control characteristics – Part 5-3: Thin-film organic/nano electronic devices – Measurements of charge carrier concentration





### THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



## IEC TS 62607-5-3

Edition 1.0 2020-04

# TECHNICAL SPECIFICATION



Nanomanufacturing – Key control characteristics –
Part 5-3: Thin-film organic/nano electronic devices – Measurements of charge carrier concentration

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 07.030; 07.120 ISBN 978-2-8322-8073-7

Warning! Make sure that you obtained this publication from an authorized distributor.

### CONTENTS

<b>FOREW</b>	ORD	3
INTROD	UCTION	5
1 Scc	pe	6
2 Nor	mative references	6
3 Ter	ms and definitions	6
4 Sar	mple structures	6
4.1	Metal/insulator/semiconductor (MIS) structure	6
4.2	Thin-film specimens with the van der Pauw configuration	7
	eria for choosing a method for measuring carrier concentration in organic	ρ
	propriate data formats	
	(informative) Case study of carrier concentration measurements of organic	
	terials	10
A.1	Procedure of capacitance-voltage (C-V) measurement	10
A.2	Capacitance-voltage measurement for unoptimized pentacene MIS structures	11
A.3	Influences of semiconductor layer thickness and electrode contact conditions on C-V measurements	13
A.4	Capacitance-voltage measurement for a pentacene MIS structure with an ultrathin insulator	14
A.5	Procedure of Hall-effect measurement	17
A.6	Hall-effect measurement for organic semiconductor single-crystalline layers	
Bibliogra	aphy	20
	- Typical metal/insulator/semiconductor (MIS) structures	
•	<ul> <li>An organic MIS structure favourable for capacitance-voltage measurements</li> </ul>	7
	Sample structures for Hall-effect measurement with the van der Pauw ation	8
Figure A	x.1 – Equivalent circuit model for capacitance-voltage measurement with MIS	
Figure A organic	x.2 – Typical capacitance-voltage curves observed for MIS structures with semiconductor films	11
	n.3 – Capacitance-voltage curves obtained for the MIS structure with 70-nm- ntacene film	12
	A.5 – Capacitance-voltage curves obtained for a pentacene MIS structure with shin SAM-modified AlOx insulator	16
	a.6 – Hall-effect measurement results for rubrene single-crystalline layer doped ic chloride	19
Tahle 1	<ul> <li>Possible data format to be given together with carrier concentrations</li> </ul>	
	d with capacitance-voltage measurements	9
	<ul> <li>Possible data format to be given together with carrier concentrations</li> <li>with the Hall-effect measurements</li> </ul>	9

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

#### NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

## Part 5-3: Thin-film organic/nano electronic devices – Measurements of charge carrier concentration

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a Technical Specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical Specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62607-5-3, which is a Technical Specification, has been prepared by IEC technical committee 113: Nanotechnology for electrotechnical products and systems.

– 4 –

The text of this Technical Specification is based on the following documents:

Draft TS	Report on voting
113/477/DTS	113/523/RVDTS

Full information on the voting for the approval of this Technical Specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC TS 62607 series, published under the general title Nanomanufacturing – Key control characteristics, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · transformed into an International Standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

#### INTRODUCTION

Organic/nano thin-film devices are attracting much attention as promising candidates for light, low cost, flexible, and printable devices in large-area electronics applications. Recently, charge carrier doping techniques have been intensely studied and developed, in the same way as the mature silicon technologies. In organic light-emitting diodes (OLEDs) and organic thin-film transistors (OTFTs), which are typical organic/nano thin-film devices, carrier doping around contact electrode regions with molecular donor/acceptor dopants are often utilized to make ohmic-like contacts for the purpose of increasing electric current in the devices. While the great importance of carrier doping in organic/nano layers is well recognized, the carrier doping mechanisms have not been fully understood yet, and the evaluation method of charge carrier concentration in these materials has not been established.

Conventional representative methods for evaluating charge carrier concentrations (or dopant concentrations) and the type of charge carrier (electron or hole) in inorganic semiconductor materials are Hall-effect measurements and capacitance-voltage measurements. For example, the Hall-effect measurement based on the van der Pauw configuration enables one to get the above-mentioned physical parameters of the charge carrier in specimens with arbitrary shapes including thin-film structures. However, this versatile method cannot be utilized for higher resistance materials such as low-mobility organic semiconductors because of lower currents and sensitivities in the Hall effect. At the present time, the capacitance-voltage measurement based on metal/insulator/semiconductor structures is not applicable to highly-doped organic nets oncem. semiconductors that show some level of metallic behaviour. Therefore, standard methods and guidelines for measuring charge carrier concentration in organic semiconductor layers need to be developed.

#### NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

## Part 5-3: Thin-film organic/nano electronic devices – Measurements of charge carrier concentration

#### 1 Scope

This part of IEC TS 62607, which is a Technical Specification, specifies sample structures for evaluating a wide range of charge carrier concentration in organic/nano materials. This specification is provided for both capacitance-voltage (C-V) measurements in metal/insulator/semiconductor stacking structures and Hall-effect measurements with the van der Pauw configuration. Criteria for choosing measurement methods of charge carrier concentration in organic semiconductor layers are also given in this document.

#### 2 Normative references

There are no normative references in this document.

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

#### 3.1

#### doping

addition of impurities to a semiconductor to control hole or electron concentrations

Note 1 to entry: For organic semiconductors, not only atomic, but also molecular impurities are utilized.

Note 2 to entry: The added impurities are called "dopants".

#### 3.2

#### bottom-contact electrode

contact electrode located underneath the semiconductor layer to be tested

#### 3.3

#### top-contact electrode

contact electrode located on top of the semiconductor layer to be tested

#### 4 Sample structures

#### 4.1 Metal/insulator/semiconductor (MIS) structure

Fabrication of a metal/insulator/semiconductor (MIS) structure as shown in Figure 1 is necessary for measuring a capacitance-voltage (C-V) curve in organic/nano semiconductor layers. This structure consists of a series capacitor of the insulator and a depletion region in the semiconductor layer.