
**Energy efficiency of industrial
trucks — Test methods —**

Part 3:
Container handling lift trucks

*Efficacité énergétique des chariots de manutention — Méthodes
d'essai —*

Partie 3: Chariots élévateurs porte-conteneur



This document is a preview generated by ERS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions	1
4.1 General.....	1
4.2 Laden container handler.....	1
4.3 Empty container handler.....	2
5 Measurement procedure	2
5.1 General.....	2
5.2 Test set up.....	2
5.3 Operating sequence.....	2
Bibliography	4

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 110, *Industrial trucks*, Subcommittee SC 5, *Sustainability*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This document is intended to be used in conjunction with ISO 23308-1.

A list of all parts in the ISO 23308 series can be found on the ISO website.

Introduction

The ISO 23308 series deals with the energy efficiency of industrial trucks including batteries and battery chargers.

ISO 23308-1 contains the procedures to determine the efficiency of trucks, traction batteries and battery chargers. The other parts provide a specific test cycle for different truck types.

NOTE The test cycles are based on the VDI 2198 guideline. This guideline is widely accepted by industry and is used to measure the energy consumption of electric industrial trucks and internal combustion (IC) industrial trucks. The guideline has been in place since 1996 and it is used broadly. This approach allows the evaluation of the energy efficiency of trucks by comparison.

The content of this document is of relevance for the following stakeholder groups:

- machine manufacturers (small, medium and large enterprises);
- market surveillance authorities;
- machine users (small, medium and large enterprises);
- service providers, e.g. for consulting activities.

The stakeholder groups above have been given the opportunity to participate at the drafting process of this document. The machines concerned are indicated in the scope of this document.

Energy efficiency of industrial trucks — Test methods —

Part 3: Container handling lift trucks

1 Scope

This document specifies the method of energy consumption measurement for container handling lift trucks, as defined in ISO 5053-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 668, *Series 1 freight containers — Classification, dimensions and ratings*

ISO 5053-1, *Industrial trucks — Terminology and classification — Part 1: Types of industrial trucks*

ISO 23308-1:2020, *Energy efficiency of industrial trucks — Test methods — Part 1: General*

ISO 22915-9:2014, *Industrial trucks — Verification of stability — Part 9: Counterbalanced trucks with mast handling freight containers of 6 m (20 ft) length and longer*

ISO 22915-12:2015, *Industrial trucks — Verification of stability — Part 12: Industrial variable-reach trucks handling freight containers of 6 m (20 ft) length and longer*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5053-1 and ISO 23308-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Test conditions

4.1 General

The travelling position shall be in accordance with ISO 22915-9:2014, 4.2, and ISO 22915-12:2015, 4.2, such that the bottom of the container is no higher than 0,9 m above the seat index point (SIP) as defined in ISO 5353, and at a height ensuring that the operator has sufficient forward visibility.

For variable reach trucks in the travelling position the boom shall be fully retracted.

Additional requirements for test conditions are given in ISO 23308-1.

4.2 Laden container handler

A laden container handler shall be tested with a test load of 70 % of the rated load.