

# INTERNATIONAL STANDARD



**Ultrasonics – Non-focusing short pressure pulse sources including ballistic  
pressure pulse sources – Characteristics of fields**



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

# INTERNATIONAL STANDARD



**Ultrasonics – Non-focusing short pressure pulse sources including ballistic pressure pulse sources – Characteristics of fields**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 17.140.50

ISBN 978-2-8322-8340-0

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms and definitions .....	9
4 List of symbols .....	20
5 Conditions of measurement .....	22
5.1 General.....	22
5.2 Measurements in the water test chamber .....	22
5.3 Measurements in the dry test bench.....	22
6 Test equipment.....	22
6.1 Water test chamber .....	22
6.1.1 Coordinate system.....	23
6.1.2 Hydrophone for water test chamber measurements .....	23
6.1.3 Hydrophone for pressure pulse measurements .....	23
6.2 Dry test bench .....	24
6.3 Voltage measurement .....	24
6.3.1 Oscilloscope or transient recorder .....	24
6.3.2 Pressure pulse waveform recording .....	25
7 Measurement procedure .....	25
7.1 Measurement procedure in the water test chamber .....	26
7.1.1 General .....	26
7.1.2 Spatial measurements .....	26
7.1.3 Non-focusing source .....	28
7.1.4 Weakly focusing source .....	29
7.1.5 Beam plots of peak-positive acoustic pressure .....	29
7.1.6 Beam plots of peak-negative acoustic pressure .....	29
7.1.7 Measurement centre point and beam axis.....	30
7.1.8 Beam width measurements.....	30
7.1.9 Beam pressure maximum extent measurements .....	31
7.1.10 Beam cross-sectional area and beam pressure maximum cross-sectional area.....	31
7.1.11 Beam pressure maximum volume measurements.....	31
7.1.12 Beam volume.....	31
7.2 Temporal measurements.....	31
7.3 Acoustic energy measurements .....	32
7.3.1 General .....	32
7.3.2 Pulse-pressure-squared integral .....	32
7.3.3 Derived pulse-intensity integral.....	32
7.3.4 Derived beam $-n$ dB pressure maximum acoustic pulse energy .....	32
7.3.5 Derived acoustic pulse energy .....	33
7.4 Dry test bench measurements.....	33
Annex A (informative) Acoustic pressure pulse therapy.....	34
A.1 Background.....	34
A.1.1 General .....	34
A.1.2 Development of relevant measurement standard .....	34

A.1.3	Current knowledge on biomedical effects .....	34
A.1.4	Availability of clinical and technical data .....	34
A.2	Other treatment devices and methods not subject to this document .....	35
A.2.1	Percutaneous continuous and modulated wave systems .....	35
A.2.2	Extracorporeal shock wave lithotripsy .....	35
A.2.3	Further exclusions .....	35
Annex B (informative)	Types of pressure pulse transducers .....	36
B.1	Overview .....	36
B.1.1	General .....	36
B.1.2	Principle of ballistic pressure pulse sources .....	36
B.1.3	Rail gun principle .....	36
B.1.4	Further generation principles .....	37
B.2	Non-focusing and focusing transducers .....	37
B.3	Examples of pressure pulse sources and their parameter sets .....	38
B.4	Positioning and targeting methods .....	43
Annex C (informative)	Field measurement .....	44
C.1	Measurement probes and hydrophones .....	44
C.2	Water test chamber .....	46
C.2.1	General .....	46
C.2.2	Degassing procedures .....	46
C.3	Dry test bench .....	46
C.3.1	General .....	46
C.3.2	Selection and attachment of the hydrophone .....	48
C.3.3	Attachment of the hand piece .....	49
C.3.4	Proof of the similarity of measurements in water and the dry test bench .....	49
C.3.5	Special measurements with the dry test bench .....	49
C.4	Acoustic pulse energy .....	50
C.4.1	General .....	50
C.4.2	Extrapolation of the applicator surface pressure value .....	51
Annex D (informative)	Lists of parameters .....	52
Bibliography	.....	59
Figure 1	– Typical pressure pulse waveform at 2 mm distance from a ballistic pressure pulse source .....	25
Figure 2	– Typical pressure distribution along the beam axis of a non-focusing pressure pulse source .....	27
Figure 3	– Typical pressure distribution along the beam axis of a weakly focusing pressure pulse source .....	28
Figure 4	– Typical lateral pressure distributions of $p_C$ at the beam pressure maximum of two ballistic pressure pulse sources .....	30
Figure B.1	– Applicator directly coupled to the patient .....	39
Figure B.2	– Pressure pulse source, non-symmetric (linear), directly coupled to the patient .....	39
Figure B.3	– Pressure pulse source, symmetric, distant from the patient .....	40
Figure B.4	– Applicator coupled to patient .....	40
Figure B.5	– Non-focused pressure pulse field .....	40
Figure B.6	– Non-focused pressure pulse field - $n$ dB parameters (example: $n = 6$ ) .....	41
Figure B.7	– Non-focused pressure pulse field isobars .....	41

Figure B.8 – Weakly-focused pressure pulse field –6 dB contour and parameters .....	42
Figure B.9 – Weakly-focused pressure pulse field volume and isobar parameters .....	42
Figure B.10 – Weakly-focused pressure pulse field parameters .....	43
Figure C.1 – Design example of a dry test bench in two views .....	47
Figure C.2 – Detail of the measurement chamber item of the dry test bench .....	48
Table C.1 – Hydrophone types for pressure pulse measurements .....	45
Table C.2 – Measurement techniques and probes for quality assurance purposes .....	46
Table D.1 – List of device parameters .....	52
Table D.2 – Pressure pulse parameters .....	53
Table D.3 – Additional parameters useful for the correlation with biological effects .....	55
Table D.4 – Graphical representations of pressure pulse data .....	56
Table D.5 – Data of hydrophones and measurement conditions .....	57

This document is a preview generated by EVS

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ULTRASONICS – NON-FOCUSING SHORT PRESSURE  
PULSE SOURCES INCLUDING BALLISTIC  
PRESSURE PULSE SOURCES – CHARACTERISTICS OF FIELDS**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 63045 has been prepared by IEC technical committee 87: Ultrasonics.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
87/741/FDIS	87/743/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

Words in **bold** in the text are defined in Clause 3.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT** – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.



## INTRODUCTION

In this document, **pressure pulses** are single pulses of ultrasonic energy of up to 25  $\mu$ s duration which have only one significant positive and one negative peak carrying more than 95 % of the energy (see definitions). Focused **pressure pulses** (sometimes called "strongly focused") are characterized by a peak acoustic pressure in a point in the sound field distant from the **source aperture**. Parameters and measurement methods for focusing **pressure pulse** sources are described in IEC 61846. The parameters and measurement methods of any other types of **pressure pulses**, i.e. weakly focused and non-focused **pressure pulses**, are described in this document.

Devices with non-focusing/weakly focusing **pressure pulse** sources are used for the extracorporeal treatment of soft tissue pain situations in, for example, the shoulder, the heel spur or the tennis elbow and for trigger point therapy. Further, still under research are applications in orthopaedics, pain therapy, treatment of angina pectoris, stem cell therapy of infarcted cardiac areas, treatment of erectile dysfunction, of cellulitis, and wound repair.

The patients receive between 3 to 5 treatments of 10 min to 20 min duration with approximately or on average 1 000 pulses. Each **pressure pulse** consists of one significant compressional part and a trailing negative part and has an overall duration of less than 25  $\mu$ s. In present devices, 1 to 35 pulses per second are released to the target tissue. The pulses are usually applied to the patient by a manually guided hand piece. Targeting is commonly done by asking the patient to direct the pulses to the point of maximum pain.

The first use of non-focused/weakly focused **pressure pulses** to treat soft tissue pain situations was described in 1999. The first devices used the ballistic principle for the generation of the **pressure pulses**, which is based on an "air-gun" like acceleration of a projectile by pressurized air. The projectile impinges on the rear side of a larger metal **applicator**, the front side of which instantly releases one fast **pressure pulse** to the patient. Today, most of the devices on the market use this design and often are called "radial shock wave devices" or "ballistic sources" although a true shock wave is not created. Also, other pulse generating principles are being applied including variations of common lithotripter sources (electromagnetic, piezoelectric, electrohydraulic).

Before this first occurrence, focused **pressure pulses** were used clinically beginning in 1993 for the treatment of shoulder calcifications, tennis elbow pain and heel spur pain, initially using lithotripter-like electrohydraulic, electromagnetic or piezoelectric sources. These focused **pressure pulses** can be characterized by IEC 61846, but the parameters described therein are not sufficiently applicable to characterize the parameters and fields of weakly focused and non-focused **pressure pulses** and their propagation characteristics.

This document specifies methods of measuring and characterizing the acoustic **pressure pulses** generated by non-focusing/weakly focusing **pressure pulse equipment** and their propagation characteristics.

# ULTRASONICS – NON-FOCUSING SHORT PRESSURE PULSE SOURCES INCLUDING BALLISTIC PRESSURE PULSE SOURCES – CHARACTERISTICS OF FIELDS

## 1 Scope

This document is applicable to

- therapy equipment using extracorporeally induced non-focused or weakly focused **pressure pulses**;
- therapy equipment producing extracorporeally induced non-focused or weakly focused mechanical energy,

where the **pressure pulses** are released as single events of duration up to 25  $\mu\text{s}$ .

This document does not apply to

- therapy equipment using focusing **pressure pulse** sources such as extracorporeal lithotripsy equipment;
- therapy equipment using other acoustic waveforms like physiotherapy equipment, low intensity ultrasound equipment and HIFU/HITU equipment.

This document specifies

- measurable parameters which are used in the declaration of the acoustic output of extracorporeal equipment producing a **non-focused** or **weakly focused pressure pulse field**,
- methods of measurement and characterization of **non-focused** or **weakly focused pressure pulse fields**.

NOTE 1 The parameters defined in this document do not – at the time of publication – allow quantitative statements to be made about clinical efficacy and possible hazard. In particular, it is not possible to make a statement about the limits for these effects.

NOTE 2 Figure B.1 to Figure B.10 and Figure 2 to Figure 4 are useful to understand the geometry of the field applied in this document.

This document has been developed for equipment intended for use in **pressure pulse** therapy, for example therapy of orthopaedic pain like shoulder pain, tennis elbow pain, heel spur pain, muscular trigger point therapy, lower back pain, etc. It is not intended to be used for extracorporeal lithotripsy equipment (as described in IEC 61846), physiotherapy equipment using other waveforms (as described in IEC 61689) and HIFU/HITU equipment (see IEC 60601-2-62 and IEC TR 62649).

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60565-1, *Underwater acoustics – Hydrophones – Calibration of hydrophones – Part 1: Procedures for free-field calibration of hydrophones*

IEC 60565-2, *Underwater acoustics – Hydrophones – Calibration of hydrophones – Part 2: Procedures for low frequency pressure calibration*

IEC 62127-1:2007, *Ultrasonics – Hydrophones – Part 1: Measurement and characterization of medical ultrasonic fields up to 40 MHz*

IEC 62127-1:2007/AMD1:2013

IEC 62127-2:2007, *Ultrasonics – Hydrophones – Part 2: Calibration for ultrasonic fields up to 40 MHz*

IEC 62127-3, *Ultrasonics – Hydrophones – Part 3: Properties of hydrophones for ultrasonic fields up to 40 MHz*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1

##### **applicator**

part of the ballistic **pressure pulse** source which emits the **pressure pulses** to the patient

Note 1 to entry: In the case of a ballistic **pressure pulse** source, the front side of the **applicator** is often coupled to the skin of the patient using an ultrasound coupling gel or other agent and releasing the **pressure pulses** to the patient. In this case, the front of the **applicator** is equal to the **source aperture**.

Note 2 to entry: Depending on the design of the source, there may be a space between the source emitting the **pressure pulses** (e.g. membrane, surface of piezoelectric crystals, spark gap etc.) and the **source aperture**. Usually, this space is composed of an acoustically conducting pad coupling material or a fluid, which transmits the **pressure pulses** from the source to the **source aperture** (see 3.48).

#### 3.2

##### **beam $-n$ dB cross-sectional area**

$A_{z,n\text{dB}}$

area enclosed by the **peak-positive acoustic pressure** contour in any plane perpendicular to the **beam axis**, where all points on the contour have a pressure of  $-n$  dB relative to the value at the **beam axis** in this plane

Note 1 to entry: The value of  $n$  and the axial distance  $z$  from the measurement centre point shall be stated as subscript.

Note 2 to entry: Typical values of  $-n$  dB are:  $-3$  dB,  $-6$  dB,  $-10$  dB,  $-12$  dB,  $-20$  dB. Reasonable values of  $n$  for clinical approval and communication to the users can be identified by a risk analysis process, by applicable safety standards, by consulting notified bodies, expert communities (e.g. ISMST – International Society for Medical Shockwave Treatment) or through literature.

Note 3 to entry: The **beam  $-n$  dB cross-sectional area** is expressed in units of metre squared ( $\text{m}^2$ ).

#### 3.3

##### **beam $-n$ dB extent**

$z_{b,n\text{dB}}$

distance along the **beam axis** from the **source aperture** to the point where the **peak-positive acoustic pressure** has dropped farthest by  $-n$  dB relative to the acoustic pressure at the **source aperture**

Note 1 to entry: The value of  $n$  shall be stated as subscript.

Note 2 to entry: Typical values of  $-n$  dB are:  $-3$  dB,  $-6$  dB,  $-10$  dB,  $-12$  dB,  $-20$  dB. Reasonable values of  $n$  for clinical approval and communication to the users can be identified by a risk analysis process, by applicable safety standards, by consulting notified bodies, expert communities (e.g. ISMST – International Society for Medical Shockwave Treatment) or through literature.

Note 3 to entry: The **beam  $-n$  dB extent** is expressed in metres (m).