

---

---

**Paints and varnishes — Electro-  
deposition coatings —**

Part 8:  
**Electric charge density**



This document is a preview generated by ERS



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Principle.....</b>	<b>2</b>
<b>5 Apparatus and materials.....</b>	<b>2</b>
<b>6 Test panels.....</b>	<b>3</b>
<b>7 Number of determinations.....</b>	<b>3</b>
<b>8 Sample preparation.....</b>	<b>3</b>
<b>9 Procedure.....</b>	<b>4</b>
<b>10 Evaluation.....</b>	<b>5</b>
10.1 Electric charge density per unit mass.....	5
10.2 Electric charge density per unit volume.....	5
<b>11 Precision.....</b>	<b>6</b>
<b>12 Test report.....</b>	<b>6</b>
<b>Annex A (informative) Calculation of the electric charge density per unit mass using the practical or theoretical dry-film thickness in accordance with ISO 3233-2 or ISO 3233-3.....</b>	<b>8</b>
<b>Bibliography.....</b>	<b>10</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 9, *General test methods for paints and varnishes*.

A list of all parts in the ISO 22553 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

The electric charge density provides information about the efficiency of the deposition process during electro-deposition coating.

If measurement of the electrical wet-film resistance in accordance with ISO 22553-7 is necessary, this can be specified in the test assembly provided.



# Paints and varnishes — Electro-deposition coatings —

## Part 8: Electric charge density

### 1 Scope

This document specifies a method for determining the electric charge density of an electro-deposition coating (e-coat) for automotive industries and other general industrial applications, e.g. chiller units, consumer products, radiators, aerospace, agriculture.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1514, *Paints and varnishes — Standard panels for testing*

ISO 2808, *Paints and varnishes — Determination of film thickness*

ISO 4618, *Paints and varnishes — Terms and definitions*

ISO 22553-1, *Paints and varnishes — Electro-deposition coatings — Part 1: Vocabulary*

ISO 23321, *Solvents for paints and varnishes — Demineralized water for industrial applications — Specification and test methods*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4618, ISO 22553-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <http://www.electropedia.org/>

#### 3.1

##### electric charge density

volume electric charge

$\rho_A$

quotient of electrical charge  $Q$  and volume  $V$ :

$$\rho_A = \frac{Q}{V}$$

Note 1 to entry: The electric charge density is expressed in coulombs per cubic metre ( $\text{C}\cdot\text{m}^{-3}$ ).

Note 2 to entry:  $1 \text{ C}\cdot\text{m}^{-3} = 1 \text{ A}\cdot\text{s}\cdot\text{m}^{-3}$ .